Received by QCD: ASS 0/2923:12:01:35 PM Office State of New Mexico	Form CPugg 1 of 9
<u>District I</u> – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240	Revised July 18, 2013 WELL API NO.
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 District II - (575) 748-1283 OIL CONSERVATION DIVISION	30-025-28805 5. Indicate Type of Lease
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV - (505) 476-3460 1220 South St. Francis Dr. Santa Fe, NM 87505	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	B M JUSTIS
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number #12
2. Name of Operator	9. OGRID Number 326920
FAE II Operating LLC 3. Address of Operator	10. Pool name or Wildcat
11757 Katy Fwy #725, Houston, TX 77079	[33820] JALMAT; TAN-YATES-7 RVRS
4. Well Location (SHL) Unit Letter <u>E</u> : <u>1450</u> feet from the <u>NORTH</u> line and	120 feet from the <u>WEST</u> line
Section 20 Township 25S Range 37E NMP	
(BHL) Unit Letter A : 920 feet from the NORTH line and	403feet from theEASTline
Section 19 Township 25S Range 37E NMP: 11. Elevation (Show whether DR, RKB, RT, GR, etc.,	
3074	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR COMMENCE DRIVER OF TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRIVER OF TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRIVER OF TEMPORARILY ABANDON COMENCE DRIVER OF TEMPORARILY ABANDON COMMENCE DRIVER OF TEMPORARILY ABANDON COMME	SEQUENT REPORT OF: K
13. Describe proposed or completed operations. (Clearly state all pertinent details, an of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Con	d give pertinent dates, including estimated date
proposed completion or recompletion.	
*Note: Amendment of original approved C-103 application to P&A well on 5/24/23	
 MIRU. RIH W/TBG, TAG CMT @ 2,802' TO VERIFY. RIH, SPOT 30SX CLASS C CMT FROM 2,802'-2,602'. WOC & TAG. CIRC WELL W/ MLF; SPOT 30SX CLASS C CMT FROM 1,350' – 1150' WOC & PERF @ 485' – SQZ 100SX CLASS C CMT FROM 485' TO SURFACE/VERIFY. DIG OUT & CUT OFF WH 3' B.G.L.; WELD ON STEEL PLATE TO CSG & INSTAHOLE MARKER. 	
Spud Date: 9/6/1984 Rig Release Date:	
CEL MI MONED COM	.UGGED BY 3/14/24
I hereby certify that the information above is true and complete to the best of my knowledg	e and belief.
SIGNATURE Down How TITLE Production Engineer	DATE7/11/2023
Type or print name _Tyler Van Howe E-mail address: _tyler@faenergy For State Use Only	yus.com PHONE: (281) 798-4516
APPROVED BY:	nager DATE 9/14/23

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD at 575-626-0830 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

- 1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
- 2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
- 3. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
- 4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
- 5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
- 6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
- 7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
- 8. Produced water will not be used during any part of the plugging operation.
- 9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
- 10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
- 11. Class 'C' cement will be used above 7500 feet.
- 12. Class 'H' cement will be used below 7500 feet.
- 13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
- 14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

- 16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
- 17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
- 18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
- 19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
- 20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - 1) Glorieta
 - J) Yates.
 - K) Cherry Canyon Eddy County
 - L) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
- 21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIRMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)------AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S - R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S - R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A-F. Sec 27 Unit A,B,C,F,G,H.

T 19S - R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S - R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S - R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S - R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S - R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S - R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S - R 30E

Sec 1 – Sec 36

T 21S - R 31E

Sec 1 – Sec 36

T 22S - R 28E

Sec 36 Unit A,H,I,P.

T 22S - R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S - R 30E

Sec 1 – Sec 36

T 22S - R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S - R 28E

Sec 1 Unit A

T 23S - R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S - R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S - R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S - R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S - R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S - R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

Well Name: BM Jus	stis #12	API: 3	0-025-28805	Lease Type:	FEE
Surf. Location: 1450' FNL & 120' F\	VLT-R-Sec-S	pot-Lot: 2	5S-37E-20-E	Lease No:	
BHL Location: 928' FNL & 403' FE	<u>L</u>	2	5S-37E-19-A		
Formation(s): Jalmat [Tan-Yates-7 RVRs]				ounty/State:	Lea, NM
Surface Csg	CURRENT		,	KB : 3086'	
Size: 9 5/8'				DF: 3085'	
Wt.&Thrd: 36#				GL: 3074'	
Grade: J-55			Spud Da		
Set @: 430' Sxs cmt: 300 sxs			Compl. Da	ate: 9/23/1984	
Circ: Yes, 25 sxs					
TOC: Surface			<u> History - Hig</u>	ıhlights	
Hole Size: 12 1/4"			09/6/1984 : S	nud Well	
				pud vveii. Perf & Acidize Yates @	3382 -3417'
			10/10/1984:	Frac perfs w/12,000 20	0/40 + 34,400 10/20 +
				Well cleaned out to 358 and put well on product	35' PBTD, RIH w/ 2-3/8" ion.
	<u> </u>	SALT (Top @ 1268')	12/31/1993: \		
					perfs 3382'-3417' w/ 200
			sxs cmt. Pres	ssure tested 7" csg and	found leak above 128'.
			(0 - 3350'). N	•	d 7" casing to 1000 psi.
			l ,		
					Perfed Yates formation
				160' w/30 holes. Acidiz 60 ball sealers. Fraced	
			Water Frac G	G-R (33)/N-2 Foam 65/4	18% quality carring
				20/40, 38,640 lb of 12/2 leaned out to PBTD of	20, and 186,420 lb of 3351'. RIH w/ 99 jts 2-
					uction Yates formation.
					g. RUWL, Set 7" CIBP
				np ball 40' cmt on top on soure test held. Well T	of plug. Load casing with A'd.
				IIT performed, TA exter	
			5/15/2020: M	IIT performaed, TA exte	ension granted.
			<u> </u>		
	<u>s</u>	ALT (Bot @ 2734')			
CIBP set @ 2842' w/ 40' cmt on top		YATES (Top @ 28	88') IISOI ATEDI		
cint on top			00 <u>/ [100EATED]</u> 30 holes) - June 2006	[TA'd 6/2015]	
CICR set @ 3350'			1000 gal 15% MDA	-	
	-	Frac'd w/ 12	23,434 gal & 65/35 2	50060 # of sand.	
	1				
Production Csg		7 RVRS (Top @ 3	118') [ISOLATED]		
Size: <u>7"</u>				6', 3388', 3403', 3405',	3406', 3407', 3409',
Wt.&Thrd: 23#, ST&C	Z		', 3415', 3417' - Sqz'	d 2005	
Grade: <u>J-55</u> Set @: 3679'			1150 50% MCA v/ 12.000 20/40 + 34	,400 10/20 + 42,780 B	W
Sxs Cmt: 850 sxs			, 20, 10 - 04	,	
Circ: Yes; 318 sxs					
TOC: Surface Hole Size: 8 3/4"		QUEEN (Top @ 3	<u>570')</u>		
0 3/4	PBTD 2802'				
	TD 3680'				

<u>Tubu</u>	lars - Capacities and Performance	<u>9</u>		

Well Name:	BM Justi:	s #12	API:	30-025-28805	Lease Type:	FEE
Surf. Location:	1450' FNL & 120' FWL	T-R-Sec		25S-37E-20-E	Lease No:	
BHL Location:	928' FNL & 403' FEL			25S-37E-19-A		
Formation(s):	Jalmat [Tan-Yates-7 RVRs]				ounty/State:	Lea, NM
		PROPOSED				
Surface Csg		I I I	_		KB : 3086'	
Size:	9 5/8'				DF : 3085'	
Wt.&Thrd:	36#				GL : 3074'	
Grade:	J-55			-	ud Date: 9/6/1984	
Set @: Sxs cmt:	430' 300 sxs			Comp	ol. Date: 9/23/1984	
Circ:	Yes, 25 sxs					
TOC:	Surface			History	- Highlights	
Hole Size:	12 1/4"					
		Z			34: Spud Well.	
Perf @ 485'					34: Perf & Acidize Yates @ 984: Frac perfs w/12,000 2	
					BW. Well cleaned out to 35	
Cmt plug (30	sxs) 1150'-1350'		SALT (Top @ 1	tbg to 33	341' and put well on produc	tion.
			_	12/31/19	993: Well TA'd.	
)5: Set CICR @ 3350'. Sqz	
					Pressure tested 7" csg and casing leak, presure teste	
					D'). No leaks.	sa / Gaoing to 1000 poi.
					6: Tagged PBTD @ 3351'.	
					92-3060' w/30 holes. Acidi: 9A w/60 ball sealers. Frace	
				Water F	rac G-R (33)/N-2 Foam 65/	48% quality carring
				■ ·	b of 20/40, 38,640 lb of 12/ nd. Cleaned out to PBTD of	
				3/8" tbg.	EOT @ 3124'. Put on prod	duction Yates formation.
				@ 2842	POOH w/ all rods and tubir . Dump bail 40' cmt on top . Pressure test held. Well 1	of plug. Load casing with
					18: MIT performed, TA exte	
				5/15/202	20: MIT performaed, TA ext	tension granted.
				Propose	ed: P&A Well	
Cmt (30 sxs)	2602'-2802'					
CIBP set @ 2	2842' w/ 40'		SALT (Bot @ 2	(/34 ⁻)		
cmt on top	2042 W/ 40		YATES (To	o @ 2888') [ISOLATEI	<u> </u>	
-			Perf 2892'-3	060' (30 holes) - June	2006 [TA'd 6/2015]	
CICR set @	3350'			ze w/ 4000 gal 15% M		
		==	Frac'	d w/ 123,434 gal & 65/	/35 250060 # of sand.	
		_				
Production (Csg		7 RVRS (To	p @ 3118') [ISOLATE	<u>D]</u>	
Size:	7"				, 3386', 3388', 3403', 3405'	', 3406', 3407', 3409',
Wt.&Thrd:	23#, ST&C			', 3414', 3415', 3417' -	Sqz'd 2005	
Grade:	J-55 3670'			ze w/ 4150 50% MCA	± 3/1 //00 10/20 ± //2 700 B	21/1/
Set @: Sxs Cmt:	3679' 850 sxs		Frac	pens w/ 12,000 20/40	+ 34,400 10/20 + 42,780 B) V V
Circ:	Yes; 318 sxs					
TOC:	Surface		QUEEN (To	p @ 3570')		
Hole Size:	8 3/4"					
		PBTD 2802'				

Tubulars - Capacities and Performance		

TD 3680'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 259603

COMMENTS

Operator:	OGRID:
FAE II Operating LLC	329326
11757 Katy Freeway, Suite 725	Action Number:
Houston, TX 77079	259603
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM.	9/14/2023

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 259603

CONDITIONS

Operator:	OGRID:
FAE II Operating LLC	329326
11757 Katy Freeway, Suite 725	Action Number:
Houston, TX 77079	259603
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By		Condition Date
gcordero	None	9/14/2023