

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
August 1, 2011

Permit 352699

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

1. Operator Name and Address AMEREDEV OPERATING, LLC 2901 Via Fortuna Austin, TX 78746		2. OGRID Number 372224
		3. API Number 30-025-52130
4. Property Code 320055	5. Property Name AMEN CORNER 26 36 27 STATE COM	6. Well No. 183H

**7. Surface Location**

UL - Lot P	Section 22	Township 26S	Range 36E	Lot Idn P	Feet From 230	N/S Line S	Feet From 1075	E/W Line E	County Lea
---------------	---------------	-----------------	--------------	--------------	------------------	---------------	-------------------	---------------	---------------

**8. Proposed Bottom Hole Location**

UL - Lot G	Section 34	Township 26S	Range 36E	Lot Idn 2	Feet From 50	N/S Line S	Feet From 1650	E/W Line E	County Lea
---------------	---------------	-----------------	--------------	--------------	-----------------	---------------	-------------------	---------------	---------------

**9. Pool Information**

WC-025 G-08 S263620C;LWR BONE SPRIN	98150
-------------------------------------	-------

**Additional Well Information**

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 2907
16. Multiple N	17. Proposed Depth 17697	18. Formation 2nd Bone Spring Carbonate	19. Contractor	20. Spud Date 1/15/2024
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1745	1373	0
Int1	12.25	10.75	45.5	5106	1352	0
Prod	8.75	5.5	17	17697	5769	0

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	5000	5000	TBD

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC <input checked="" type="checkbox"/> and/or 19.15.14.9 (B) NMAC <input checked="" type="checkbox"/> if applicable.  Signature:	<b>OIL CONSERVATION DIVISION</b>	
Printed Name: Electronically filed by Christie Hanna	Approved By: Paul F Kautz	
Title: Regulatory	Title: Geologist	
Email Address: channa@ameredev.com	Approved Date: 10/19/2023	Expiration Date: 10/19/2025
Date: 10/18/2023	Phone: 737-300-4723	Conditions of Approval Attached

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720

**District II**  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720

**District III**  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170

**District IV**  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources  
Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

**FORM C-102**

Revised August 1, 2011

**Submit one copy to appropriate**

## District Office

☐ **AMENDED REPORT**

# WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-025-	<sup>2</sup> Pool Code 98150	<sup>3</sup> Pool Name WC-025 G-08 S263620C; LWR BONE SPRING
<sup>4</sup> Property Code 320055	<sup>5</sup> Property Name AMEN CORNER 26 36 27 STATE COM	
<sup>7</sup> OGRID No. 372224	<sup>8</sup> Operator Name AMEREDEV OPERATING, LLC.	<sup>6</sup> Well Number 183H  <sup>9</sup> Elevation 2907'

## <sup>10</sup>Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	22	26-S	36-E	—	230'	SOUTH	1075'	EAST	LEA

<sup>11</sup>Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
2	34	26-S	36-E	-	50'	SOUTH	1650'	EAST	LEA

<sup>12</sup> Dedicated Acres <b>233.64</b>	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code <b>C</b>	<sup>15</sup> Order No.
--	-------------------------------	--	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

NEW MEXICO EAST  
NAD 1983

## SURFACE LOCATION (SHL)

230' FSL - SEC. 22  
1075' FEL - SEC. 22  
X=877704 Y=373486  
LAT.: N 32.0221482  
LONG.: W 103.2480049

KICK OFF POINT (KOP)  
FIRST TAKE POINT (FTP)

100' FNL - SEC. 27  
1650' FEL - SEC. 27  
X=877133 Y=373151  
LAT.: N 32.0212448  
LONG.: W 103.2498605

LAST TAKE POINT (LTP)

100' FSL - SEC. 34  
1650' FEL - SEC. 34  
X=877203 Y=365639  
LAT.: N 32.0005942  
LONG.: W 103.2498752

BOTTOM HOLE LOCATION (BHL)

50' FSL - SEC. 34  
1650' FEL - SEC. 34  
X=877204 Y=365589  
LAT.: N 32.0004567  
LONG.: W 103.2498753

## 17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

De Hammond 10/18/2023  
Signature Date

**Floyd Hammond**  
Printed Name

**fhammond@ameredev.com**  
E-mail Address

## 18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true to the best of my belief.

06/03/2023

Date of Survey  
Signature and Seal of Professional Surveyor



**Certificate Number**

**District I**

1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Conditions

Permit 352699

**PERMIT CONDITIONS OF APPROVAL**

Operator Name and Address: AMEREDEV OPERATING, LLC [372224] 2901 Via Fortuna Austin, TX 78746	API Number: 30-025-52130
	Well: AMEN CORNER 26 36 27 STATE COM #183H

OCD Reviewer	Condition
pkautz	Notify OCD 24 hours prior to casing & cement
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing
pkautz	If cement does not circulate on any string , a CBL is required for that string of casing.
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud

Released to Imaging: 10/19/2023 10:47:16 AM



## **Ameredev Operating**

**Lea County, NM (N83-NME)**

**AMEN CORNER ST COM PROJECT**

**AMEN CORNER 26 36 27 ST COM 183H**

**OWB**

**Plan: PWP**

## **Standard Planning Report - Geographic**

**24 August, 2023**



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredev Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

<b>Project</b>	Lea County, NM (N83-NME)		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

Site	AMEN CORNER ST COM PROJECT				
Site Position:		Northing:	373,452.33 usft	Latitude:	32.0221652
From:	Lat/Long	Easting:	873,738.68 usft	Longitude:	-103.2607997
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "		

Well	AMEN CORNER ST COM 26 36 27 #183H					
Well Position	+N/-S	0.0 usft	Northing:	373,485.75 usft	Latitude:	32.0221482
	+E/-W	0.0 usft	Easting:	877,704.34 usft	Longitude:	-103.2480049
Position Uncertainty		3.0 usft	Wellhead Elevation:	usft	Ground Level:	2,907.0 usft
Grid Convergence:		0.58 °				

<b>Wellbore</b>	OWB				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2020	6/29/2023	6.14	59.69	47,197.44387666

<b>Design</b>	PWP			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	179.46

<b>Plan Survey Tool Program</b>	<b>Date</b>	8/24/2023		
<b>Depth From (usft)</b>	<b>Depth To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>
1	0.0	17,696.5 PWP (OWB)	MWD	
			OWSG MWD - Standard	



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredev Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,900.0	8.00	283.97	1,898.7	6.7	-27.1	2.00	2.00	0.00	283.97	
5,764.2	8.00	283.97	5,725.3	136.6	-548.9	0.00	0.00	0.00	0.00	
6,164.2	0.00	0.00	6,124.0	143.3	-576.0	2.00	-2.00	0.00	180.00	
9,383.2	0.00	0.00	9,343.0	143.3	-576.0	0.00	0.00	0.00	0.00	
10,133.2	90.00	179.46	9,820.5	-334.2	-571.5	12.00	12.00	23.93	179.46	
17,696.5	90.00	179.46	9,820.0	-7,897.1	-500.6	0.00	0.00	0.00	0.00	BHL (ACSC #183H)



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredeve Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
100.0	0.00	0.00	100.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
200.0	0.00	0.00	200.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
300.0	0.00	0.00	300.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
400.0	0.00	0.00	400.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
500.0	0.00	0.00	500.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
600.0	0.00	0.00	600.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
700.0	0.00	0.00	700.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
800.0	0.00	0.00	800.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
900.0	0.00	0.00	900.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,000.0	0.00	0.00	1,000.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,100.0	0.00	0.00	1,100.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,200.0	0.00	0.00	1,200.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,300.0	0.00	0.00	1,300.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,400.0	0.00	0.00	1,400.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
1,500.0	0.00	0.00	1,500.0	0.0	0.0	373,485.75	877,704.34	32.0221482	-103.2480049
Start Build 2.00									
1,600.0	2.00	283.97	1,600.0	0.4	-1.7	373,486.17	877,702.64	32.0221494	-103.2480103
1,700.0	4.00	283.97	1,699.8	1.7	-6.8	373,487.43	877,697.56	32.0221530	-103.2480267
1,800.0	6.00	283.97	1,799.5	3.8	-15.2	373,489.54	877,689.11	32.0221591	-103.2480539
1,900.0	8.00	283.97	1,898.7	6.7	-27.1	373,492.48	877,677.28	32.0221675	-103.2480920
Start 3864.2 hold at 1900.0 MD									
1,964.9	8.00	283.97	1,963.0	8.9	-35.8	373,494.66	877,668.51	32.0221737	-103.2481202
Rustler									
2,000.0	8.00	283.97	1,997.7	10.1	-40.6	373,495.84	877,663.78	32.0221771	-103.2481354
2,100.0	8.00	283.97	2,096.8	13.5	-54.1	373,499.20	877,650.27	32.0221867	-103.2481789
2,200.0	8.00	283.97	2,195.8	16.8	-67.6	373,502.56	877,636.76	32.0221963	-103.2482223
2,300.0	8.00	283.97	2,294.8	20.2	-81.1	373,505.92	877,623.26	32.0222059	-103.2482658
2,347.7	8.00	283.97	2,342.0	21.8	-87.5	373,507.52	877,616.82	32.0222105	-103.2482865
Salado									
2,400.0	8.00	283.97	2,393.8	23.5	-94.6	373,509.28	877,609.75	32.0222155	-103.2483093
2,500.0	8.00	283.97	2,492.9	26.9	-108.1	373,512.64	877,596.25	32.0222251	-103.2483527
2,600.0	8.00	283.97	2,591.9	30.3	-121.6	373,516.00	877,582.74	32.0222347	-103.2483962
2,700.0	8.00	283.97	2,690.9	33.6	-135.1	373,519.36	877,569.24	32.0222443	-103.2484397
2,800.0	8.00	283.97	2,789.9	37.0	-148.6	373,522.72	877,555.73	32.0222539	-103.2484831
2,900.0	8.00	283.97	2,889.0	40.3	-162.1	373,526.08	877,542.22	32.0222635	-103.2485266
3,000.0	8.00	283.97	2,988.0	43.7	-175.6	373,529.44	877,528.72	32.0222732	-103.2485700
3,100.0	8.00	283.97	3,087.0	47.1	-189.1	373,532.80	877,515.21	32.0222828	-103.2486135
3,200.0	8.00	283.97	3,186.1	50.4	-202.6	373,536.16	877,501.71	32.0222924	-103.2486570
3,209.0	8.00	283.97	3,195.0	50.7	-203.8	373,536.46	877,500.49	32.0222932	-103.2486609
Tansill									
3,300.0	8.00	283.97	3,285.1	53.8	-216.1	373,539.52	877,488.20	32.0223020	-103.2487004
3,400.0	8.00	283.97	3,384.1	57.1	-229.6	373,542.88	877,474.70	32.0223116	-103.2487439
3,500.0	8.00	283.97	3,483.1	60.5	-243.1	373,546.24	877,461.19	32.0223212	-103.2487874
3,600.0	8.00	283.97	3,582.2	63.9	-256.7	373,549.60	877,447.69	32.0223308	-103.2488308
3,700.0	8.00	283.97	3,681.2	67.2	-270.2	373,552.96	877,434.18	32.0223404	-103.2488743
3,800.0	8.00	283.97	3,780.2	70.6	-283.7	373,556.32	877,420.67	32.0223500	-103.2489177
3,832.1	8.00	283.97	3,812.0	71.6	-288.0	373,557.40	877,416.34	32.0223531	-103.2489317
Capitan									
3,900.0	8.00	283.97	3,879.2	73.9	-297.2	373,559.68	877,407.17	32.0223596	-103.2489612
4,000.0	8.00	283.97	3,978.3	77.3	-310.7	373,563.04	877,393.66	32.0223692	-103.2490047
4,100.0	8.00	283.97	4,077.3	80.7	-324.2	373,566.40	877,380.16	32.0223788	-103.2490481
4,200.0	8.00	283.97	4,176.3	84.0	-337.7	373,569.76	877,366.65	32.0223884	-103.2490916





## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredev Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
4,300.0	8.00	283.97	4,275.3	87.4	-351.2	373,573.12	877,353.15	32.0223981	-103.2491350
4,400.0	8.00	283.97	4,374.4	90.7	-364.7	373,576.48	877,339.64	32.0224077	-103.2491785
4,500.0	8.00	283.97	4,473.4	94.1	-378.2	373,579.84	877,326.13	32.0224173	-103.2492220
4,600.0	8.00	283.97	4,572.4	97.5	-391.7	373,583.20	877,312.63	32.0224269	-103.2492654
4,700.0	8.00	283.97	4,671.5	100.8	-405.2	373,586.56	877,299.12	32.0224365	-103.2493089
4,800.0	8.00	283.97	4,770.5	104.2	-418.7	373,589.92	877,285.62	32.0224461	-103.2493524
4,900.0	8.00	283.97	4,869.5	107.5	-432.2	373,593.28	877,272.11	32.0224557	-103.2493958
5,000.0	8.00	283.97	4,968.5	110.9	-445.7	373,596.64	877,258.61	32.0224653	-103.2494393
5,051.0	8.00	283.97	5,019.0	112.6	-452.6	373,598.35	877,251.72	32.0224702	-103.2494614
<b>Lamar</b>									
5,100.0	8.00	283.97	5,067.6	114.3	-459.2	373,600.00	877,245.10	32.0224749	-103.2494827
5,200.0	8.00	283.97	5,166.6	117.6	-472.7	373,603.36	877,231.60	32.0224845	-103.2495262
5,298.4	8.00	283.97	5,264.0	120.9	-486.0	373,606.67	877,218.31	32.0224940	-103.2495690
<b>Bell Canyon</b>									
5,300.0	8.00	283.97	5,265.6	121.0	-486.2	373,606.72	877,218.09	32.0224941	-103.2495697
5,400.0	8.00	283.97	5,364.6	124.3	-499.8	373,610.08	877,204.58	32.0225037	-103.2496131
5,500.0	8.00	283.97	5,463.7	127.7	-513.3	373,613.44	877,191.08	32.0225133	-103.2496566
5,600.0	8.00	283.97	5,562.7	131.1	-526.8	373,616.80	877,177.57	32.0225230	-103.2497001
5,700.0	8.00	283.97	5,661.7	134.4	-540.3	373,620.16	877,164.07	32.0225326	-103.2497435
5,764.2	8.00	283.97	5,725.3	136.6	-548.9	373,622.32	877,155.39	32.0225387	-103.2497714
<b>Start Drop -2.00</b>									
5,800.0	7.28	283.97	5,760.8	137.7	-553.6	373,623.47	877,150.78	32.0225420	-103.2497863
5,900.0	5.28	283.97	5,860.2	140.4	-564.2	373,626.11	877,140.15	32.0225496	-103.2498205
6,000.0	3.28	283.97	5,959.9	142.2	-571.4	373,627.91	877,132.90	32.0225547	-103.2498438
6,100.0	1.28	283.97	6,059.8	143.1	-575.3	373,628.88	877,129.03	32.0225575	-103.2498563
6,164.2	0.00	0.00	6,124.0	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
<b>Start 3219.0 hold at 6164.2 MD</b>									
6,200.0	0.00	0.00	6,159.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,300.0	0.00	0.00	6,259.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,400.0	0.00	0.00	6,359.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,500.0	0.00	0.00	6,459.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,600.0	0.00	0.00	6,559.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,700.0	0.00	0.00	6,659.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,730.2	0.00	0.00	6,690.0	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
<b>Brushy Canyon</b>									
6,800.0	0.00	0.00	6,759.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
6,900.0	0.00	0.00	6,859.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,000.0	0.00	0.00	6,959.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,100.0	0.00	0.00	7,059.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,200.0	0.00	0.00	7,159.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,300.0	0.00	0.00	7,259.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,400.0	0.00	0.00	7,359.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,500.0	0.00	0.00	7,459.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,557.2	0.00	0.00	7,517.0	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
<b>Bone Spring Lime</b>									
7,600.0	0.00	0.00	7,559.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,700.0	0.00	0.00	7,659.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,800.0	0.00	0.00	7,759.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
7,900.0	0.00	0.00	7,859.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,000.0	0.00	0.00	7,959.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,100.0	0.00	0.00	8,059.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,200.0	0.00	0.00	8,159.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,300.0	0.00	0.00	8,259.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredev Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
8,400.0	0.00	0.00	8,359.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,500.0	0.00	0.00	8,459.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,600.0	0.00	0.00	8,559.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,700.0	0.00	0.00	8,659.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,800.0	0.00	0.00	8,759.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
8,900.0	0.00	0.00	8,859.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
9,000.0	0.00	0.00	8,959.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
9,100.0	0.00	0.00	9,059.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
9,200.0	0.00	0.00	9,159.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
9,300.0	0.00	0.00	9,259.8	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
9,360.2	0.00	0.00	9,320.0	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
<b>First Bone Spring</b>									
9,383.2	0.00	0.00	9,343.0	143.3	-576.0	373,629.05	877,128.34	32.0225580	-103.2498585
<b>Start DLS 12.00 TFO 179.46</b>									
9,400.0	2.02	179.46	9,359.8	143.0	-576.0	373,628.75	877,128.34	32.0225572	-103.2498585
9,500.0	14.02	179.46	9,458.6	129.1	-575.9	373,614.84	877,128.47	32.0225189	-103.2498585
9,600.0	26.02	179.46	9,552.4	94.9	-575.5	373,580.67	877,128.79	32.0224250	-103.2498586
9,700.0	38.02	179.46	9,637.1	42.0	-575.1	373,527.76	877,129.29	32.0222795	-103.2498587
9,800.0	50.02	179.46	9,708.8	-27.3	-574.4	373,458.40	877,129.94	32.0220889	-103.2498589
9,900.0	62.02	179.46	9,764.6	-110.1	-573.6	373,375.64	877,130.71	32.0218614	-103.2498590
9,986.2	72.35	179.46	9,798.0	-189.4	-572.9	373,296.33	877,131.46	32.0216434	-103.2498592
<b>Second Bone Spring</b>									
10,000.0	74.02	179.46	9,802.0	-202.7	-572.8	373,283.08	877,131.58	32.0216070	-103.2498592
10,100.0	86.02	179.46	9,819.3	-301.0	-571.8	373,184.78	877,132.50	32.0213368	-103.2498594
10,133.2	90.00	179.46	9,820.5	-334.2	-571.5	373,151.58	877,132.81	32.0212455	-103.2498595
<b>Start 7563.3 hold at 10133.2 MD</b>									
10,133.5	90.00	179.46	9,820.5	-334.4	-571.5	373,151.33	877,132.82	32.0212448	-103.2498595
<b>FTP (ACSC #183H)</b>									
10,200.0	90.00	179.46	9,820.5	-400.9	-570.9	373,084.81	877,133.44	32.0210620	-103.2498596
10,300.0	90.00	179.46	9,820.5	-500.9	-570.0	372,984.82	877,134.38	32.0207871	-103.2498599
10,400.0	90.00	179.46	9,820.4	-600.9	-569.0	372,884.82	877,135.32	32.0205123	-103.2498601
10,500.0	90.00	179.46	9,820.4	-700.9	-568.1	372,784.83	877,136.25	32.0202374	-103.2498603
10,600.0	90.00	179.46	9,820.4	-800.9	-567.1	372,684.83	877,137.19	32.0199625	-103.2498605
10,700.0	90.00	179.46	9,820.4	-900.9	-566.2	372,584.83	877,138.13	32.0196877	-103.2498607
10,800.0	90.00	179.46	9,820.4	-1,000.9	-565.3	372,484.84	877,139.07	32.0194128	-103.2498609
10,900.0	90.00	179.46	9,820.4	-1,100.9	-564.3	372,384.84	877,140.00	32.0191379	-103.2498611
11,000.0	90.00	179.46	9,820.4	-1,200.9	-563.4	372,284.85	877,140.94	32.0188631	-103.2498613
11,100.0	90.00	179.46	9,820.4	-1,300.9	-562.5	372,184.85	877,141.88	32.0185882	-103.2498615
11,200.0	90.00	179.46	9,820.4	-1,400.9	-561.5	372,084.86	877,142.82	32.0183134	-103.2498617
11,300.0	90.00	179.46	9,820.4	-1,500.9	-560.6	371,984.86	877,143.76	32.0180385	-103.2498620
11,400.0	90.00	179.46	9,820.4	-1,600.9	-559.6	371,884.86	877,144.69	32.0177636	-103.2498622
11,500.0	90.00	179.46	9,820.4	-1,700.9	-558.7	371,784.87	877,145.63	32.0174888	-103.2498624
11,600.0	90.00	179.46	9,820.4	-1,800.9	-557.8	371,684.87	877,146.57	32.0172139	-103.2498626
11,700.0	90.00	179.46	9,820.4	-1,900.9	-556.8	371,584.88	877,147.51	32.0169390	-103.2498628
11,800.0	90.00	179.46	9,820.4	-2,000.9	-555.9	371,484.88	877,148.44	32.0166642	-103.2498630
11,900.0	90.00	179.46	9,820.4	-2,100.9	-555.0	371,384.89	877,149.38	32.0163893	-103.2498632
12,000.0	90.00	179.46	9,820.3	-2,200.9	-554.0	371,284.89	877,150.32	32.0161144	-103.2498634
12,100.0	90.00	179.46	9,820.3	-2,300.9	-553.1	371,184.90	877,151.26	32.0158396	-103.2498636
12,200.0	90.00	179.46	9,820.3	-2,400.8	-552.1	371,084.90	877,152.19	32.0155647	-103.2498638
12,300.0	90.00	179.46	9,820.3	-2,500.8	-551.2	370,984.90	877,153.13	32.0152899	-103.2498640
12,400.0	90.00	179.46	9,820.3	-2,600.8	-550.3	370,884.91	877,154.07	32.0150150	-103.2498643
12,500.0	90.00	179.46	9,820.3	-2,700.8	-549.3	370,784.91	877,155.01	32.0147401	-103.2498645
12,600.0	90.00	179.46	9,820.3	-2,800.8	-548.4	370,684.92	877,155.95	32.0144653	-103.2498647



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredeve Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
12,700.0	90.00	179.46	9,820.3	-2,900.8	-547.5	370,584.92	877,156.88	32.0141904	-103.2498649
12,800.0	90.00	179.46	9,820.3	-3,000.8	-546.5	370,484.93	877,157.82	32.0139155	-103.2498651
12,900.0	90.00	179.46	9,820.3	-3,100.8	-545.6	370,384.93	877,158.76	32.0136407	-103.2498653
13,000.0	90.00	179.46	9,820.3	-3,200.8	-544.6	370,284.94	877,159.70	32.0133658	-103.2498655
13,100.0	90.00	179.46	9,820.3	-3,300.8	-543.7	370,184.94	877,160.63	32.0130909	-103.2498657
13,200.0	90.00	179.46	9,820.3	-3,400.8	-542.8	370,084.94	877,161.57	32.0128161	-103.2498659
13,300.0	90.00	179.46	9,820.3	-3,500.8	-541.8	369,984.95	877,162.51	32.0125412	-103.2498661
13,400.0	90.00	179.46	9,820.3	-3,600.8	-540.9	369,884.95	877,163.45	32.0122663	-103.2498663
13,500.0	90.00	179.46	9,820.3	-3,700.8	-540.0	369,784.96	877,164.39	32.0119915	-103.2498666
13,600.0	90.00	179.46	9,820.3	-3,800.8	-539.0	369,684.96	877,165.32	32.0117166	-103.2498668
13,700.0	90.00	179.46	9,820.2	-3,900.8	-538.1	369,584.97	877,166.26	32.0114418	-103.2498670
13,800.0	90.00	179.46	9,820.2	-4,000.8	-537.1	369,484.97	877,167.20	32.0111669	-103.2498672
13,900.0	90.00	179.46	9,820.2	-4,100.8	-536.2	369,384.97	877,168.14	32.0108920	-103.2498674
14,000.0	90.00	179.46	9,820.2	-4,200.8	-535.3	369,284.98	877,169.07	32.0106172	-103.2498676
14,100.0	90.00	179.46	9,820.2	-4,300.8	-534.3	369,184.98	877,170.01	32.0103423	-103.2498678
14,200.0	90.00	179.46	9,820.2	-4,400.8	-533.4	369,084.99	877,170.95	32.0100674	-103.2498680
14,300.0	90.00	179.46	9,820.2	-4,500.8	-532.4	368,984.99	877,171.89	32.0097926	-103.2498682
14,400.0	90.00	179.46	9,820.2	-4,600.8	-531.5	368,885.00	877,172.83	32.0095177	-103.2498684
14,500.0	90.00	179.46	9,820.2	-4,700.7	-530.6	368,785.00	877,173.76	32.0092428	-103.2498686
14,600.0	90.00	179.46	9,820.2	-4,800.7	-529.6	368,685.01	877,174.70	32.0089680	-103.2498688
14,700.0	90.00	179.46	9,820.2	-4,900.7	-528.7	368,585.01	877,175.64	32.0086931	-103.2498691
14,800.0	90.00	179.46	9,820.2	-5,000.7	-527.8	368,485.01	877,176.58	32.0084182	-103.2498693
14,900.0	90.00	179.46	9,820.2	-5,100.7	-526.8	368,385.02	877,177.51	32.0081434	-103.2498695
15,000.0	90.00	179.46	9,820.2	-5,200.7	-525.9	368,285.02	877,178.45	32.0078685	-103.2498697
15,100.0	90.00	179.46	9,820.2	-5,300.7	-524.9	368,185.03	877,179.39	32.0075936	-103.2498699
15,200.0	90.00	179.46	9,820.2	-5,400.7	-524.0	368,085.03	877,180.33	32.0073188	-103.2498701
15,300.0	90.00	179.46	9,820.1	-5,500.7	-523.1	367,985.04	877,181.27	32.0070439	-103.2498703
15,400.0	90.00	179.46	9,820.1	-5,600.7	-522.1	367,885.04	877,182.20	32.0067691	-103.2498705
15,500.0	90.00	179.46	9,820.1	-5,700.7	-521.2	367,785.05	877,183.14	32.0064942	-103.2498707
15,600.0	90.00	179.46	9,820.1	-5,800.7	-520.3	367,685.05	877,184.08	32.0062193	-103.2498709
15,700.0	90.00	179.46	9,820.1	-5,900.7	-519.3	367,585.05	877,185.02	32.0059445	-103.2498711
15,800.0	90.00	179.46	9,820.1	-6,000.7	-518.4	367,485.06	877,185.95	32.0056696	-103.2498713
15,900.0	90.00	179.46	9,820.1	-6,100.7	-517.4	367,385.06	877,186.89	32.0053947	-103.2498716
16,000.0	90.00	179.46	9,820.1	-6,200.7	-516.5	367,285.07	877,187.83	32.0051199	-103.2498718
16,100.0	90.00	179.46	9,820.1	-6,300.7	-515.6	367,185.07	877,188.77	32.0048450	-103.2498720
16,200.0	90.00	179.46	9,820.1	-6,400.7	-514.6	367,085.08	877,189.71	32.0045701	-103.2498722
16,300.0	90.00	179.46	9,820.1	-6,500.7	-513.7	366,985.08	877,190.64	32.0042953	-103.2498724
16,400.0	90.00	179.46	9,820.1	-6,600.7	-512.8	366,885.08	877,191.58	32.0040204	-103.2498726
16,500.0	90.00	179.46	9,820.1	-6,700.7	-511.8	366,785.09	877,192.52	32.0037455	-103.2498728
16,600.0	90.00	179.46	9,820.1	-6,800.7	-510.9	366,685.09	877,193.46	32.0034707	-103.2498730
16,700.0	90.00	179.46	9,820.1	-6,900.7	-509.9	366,585.10	877,194.39	32.0031958	-103.2498732
16,800.0	90.00	179.46	9,820.1	-7,000.6	-509.0	366,485.10	877,195.33	32.0029210	-103.2498734
16,900.0	90.00	179.46	9,820.0	-7,100.6	-508.1	366,385.11	877,196.27	32.0026461	-103.2498736
17,000.0	90.00	179.46	9,820.0	-7,200.6	-507.1	366,285.11	877,197.21	32.0023712	-103.2498738
17,100.0	90.00	179.46	9,820.0	-7,300.6	-506.2	366,185.12	877,198.15	32.0020964	-103.2498741
17,200.0	90.00	179.46	9,820.0	-7,400.6	-505.3	366,085.12	877,199.08	32.0018215	-103.2498743
17,300.0	90.00	179.46	9,820.0	-7,500.6	-504.3	365,985.12	877,200.02	32.0015466	-103.2498745
17,400.0	90.00	179.46	9,820.0	-7,600.6	-503.4	365,885.13	877,200.96	32.0012718	-103.2498747
17,500.0	90.00	179.46	9,820.0	-7,700.6	-502.4	365,785.13	877,201.90	32.0009969	-103.2498749
17,600.0	90.00	179.46	9,820.0	-7,800.6	-501.5	365,685.14	877,202.83	32.0007220	-103.2498751
<b>LTP (ACSC #183H)</b>									
17,696.5	90.00	179.46	9,820.0	-7,897.1	-500.6	365,588.62	877,203.74	32.0004567	-103.2498753
<b>TD at 17696.5 - BHL (ACSC #183H)</b>									



## Planning Report - Geographic

<b>Database:</b>	AUS-COMPASS - EDM_15 - 32bit	<b>Local Co-ordinate Reference:</b>	Well AMEN CORNER ST COM 26 36 27 #183H
<b>Company:</b>	Ameredev Operating	<b>TVD Reference:</b>	KB=25' @ 2932.0usft
<b>Project:</b>	Lea County, NM (N83-NME)	<b>MD Reference:</b>	KB=25' @ 2932.0usft
<b>Site:</b>	AMEN CORNER ST COM PROJECT	<b>North Reference:</b>	Grid
<b>Well:</b>	AMEN CORNER ST COM 26 36 27 #183H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OWB		
<b>Design:</b>	PWP		

Design Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
FTP (ACSC #183H)	0.00	0.00	9,820.0	-334.4	-571.8	373,151.32	877,132.51	32.0212448	-103.2498605
- plan misses target center by 0.6usft at 10133.5usft MD (9820.5 TVD, -334.4 N, -571.5 E)									
- Point									
BHL (ACSC #183H)	0.00	0.00	9,820.0	-7,897.1	-500.6	365,588.62	877,203.74	32.0004567	-103.2498753
- plan hits target center									
- Point									
LTP (ACSC #183H)	0.00	0.00	9,820.0	-7,847.1	-501.1	365,638.64	877,203.27	32.0005942	-103.2498752
- plan misses target center by 46.5usft at 17600.0usft MD (9820.0 TVD, -7800.6 N, -501.5 E)									
- Point									

Formations						
Measured Depth	Vertical Depth	Name	Lithology	Dip	Dip Direction	
(usft)	(usft)			(°)	(°)	
1,964.9	1,963.0	Rustler		0.00		
2,347.7	2,342.0	Salado		0.00		
3,209.0	3,195.0	Tansill		0.00		
3,832.1	3,812.0	Capitan		0.00		
5,051.0	5,019.0	Lamar		0.00		
5,298.4	5,264.0	Bell Canyon		0.00		
6,730.2	6,690.0	Brushy Canyon		0.00		
7,557.2	7,517.0	Bone Spring Lime		0.00		
9,360.2	9,320.0	First Bone Spring		0.00		
9,986.2	9,798.0	Second Bone Spring				

Plan Annotations					
Measured Depth	Vertical Depth	Local Coordinates			
(usft)	(usft)	+N/-S	+E/-W	Comment	
(usft)	(usft)	(usft)	(usft)		
1,500.0	1,500.0	0.0	0.0	Start Build 2.00	
1,900.0	1,898.7	6.7	-27.1	Start 3864.2 hold at 1900.0 MD	
5,764.2	5,725.3	136.6	-548.9	Start Drop -2.00	
6,164.2	6,124.0	143.3	-576.0	Start 3219.0 hold at 6164.2 MD	
9,383.2	9,343.0	143.3	-576.0	Start DLS 12.00 TFO 179.46	
10,133.2	9,820.5	-334.2	-571.5	Start 7563.3 hold at 10133.2 MD	
17,696.5	9,820.0	-7,897.1	-500.6	TD at 17696.5	



## H<sub>2</sub>S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H<sub>2</sub>S safety instructor to the following:**
  - a. Characteristics of H<sub>2</sub>S
  - b. Physical effects and hazards
  - c. Principal and operation of H<sub>2</sub>S detectors, warning system and briefing areas
  - d. Evacuation procedure, routes and first aid
  - e. Proper use of safety equipment and life support systems
  - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.
2. **Briefing Area:**
  - a. Two perpendicular areas will be designated by signs and readily accessible.
  - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.
3. **H<sub>2</sub>S Detection and Alarm Systems:**
  - a. H<sub>2</sub>S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H<sub>2</sub>S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
  - b. An audio alarm will be installed on the derrick floor and in the top doghouse.
4. **Protective Equipment for Essential Personnel:**
  - a. **Breathing Apparatus:**
    - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
    - ii. Two (SCBA) Units will be stored in safety trailer on location.
    - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
  - b. **Auxiliary Rescue Equipment:**
    - i. Stretcher
    - ii. 2 - OSHA full body harnesses
    - iii. 100 ft. 5/8" OSHA approved rope
    - iv. 1 - 20# class ABC fire extinguisher
5. **Windsock and/or Wind Streamers:**
  - a. Windsock at mud pit area should be high enough to be visible.
  - b. Windsock on the rig floor should be high enough to be visible.
6. **Communication:**
  - a. While working under mask scripting boards will be used for communication where applicable.
  - b. Hand signals will be used when script boards are not applicable.



## H<sub>2</sub>S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.
- 7. **Drill Stem Testing:** - No Planned DST at this time.
- 8. **Mud program:**
  - a. If H<sub>2</sub>S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H<sub>2</sub>S scavengers if necessary.
- 9. **Metallurgy:**
  - a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H<sub>2</sub>S service.
  - b. Drilling Contractor supervisor will be required to be familiar with the effect H<sub>2</sub>S has on tubular goods and other mechanical equipment provided through contractor.



## H<sub>2</sub>S Contingency Plan

### Emergency Procedures

In the event of a release of H<sub>2</sub>S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the “buddy system” to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
  - Detection of H<sub>2</sub>S and
  - Measures for protection against the gas,
  - Equipment used for protection and emergency response.

### Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

### Characteristics of H<sub>2</sub>S and SO<sub>2</sub>

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H <sub>2</sub> S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO <sub>2</sub>	2.21 Air=1	2 ppm	N/A	1000 ppm

### Contacting Authorities

Ameredev Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Ameredev Operating LLC’s response must be in coordination with the State of New Mexico’s “Hazardous Materials Emergency Response Plan” (HMER)





## H<sub>2</sub>S Contingency Plan

<b>Ameredev Operating LLC – Emergency Phone 737-300-4799</b>			
Key Personnel:			
Name	Title	Office	Mobile
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Shane McNeely	Operations Engineer	737-300-4729	432-413-8593
Dayeed Khan	Construction Manager	737-300-4733	281-928-4692

<b><u>Artesia</u></b>	
Ambulance	911
State Police	575-748-9718
City Police	575-746-5000
Sheriff's Office	575-887-7551
Fire Department	575-746-5051
Artesia General Hospital	575-748-3333
New Mexico Oil Conservation Division	575-626-0830
<b><u>Carlsbad</u></b>	
Ambulance	911
State Police	575-885-3138
City Police	575-885-2111
Sheriff's Office	575-887-7551
Fire Department	575-885-3125
Carlsbad Medical Center	575-887-4100
Hobbs Hospital	575-492-5000
BLM Hobbs Field Office	575-689-5981
BLM Carlsbad Field Office	575-361-2822
New Mexico Oil Conservation Division	575-626-0830
<b><u>Santa Fe</u></b>	
Department of Homeland Security and Emergency Management (Santa Fe)	505-476-9600
New Mexico State Emergency Operations Center	505-476-9635
<b><u>National</u></b>	
National Emergency Response Center (Washington, D.C.)	800-424-8802
<b><u>Medical</u></b>	
Aerocare - R3, Box 49F; Lubbock, TX	800-627-2376
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM	505-842-4433
Lifeguard Air Emergency Services- 2505 Clark Carr Loop S.E.; Albuquerque, NM	505-243-2343



State of New Mexico  
Energy, Minerals and Natural Resources DepartmentSubmit Electronically  
Via E-permittingOil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505**NATURAL GAS MANAGEMENT PLAN**

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

**Section 1 – Plan Description****Effective May 25, 2021****I. Operator:** Ameredev II, LLC **OGRID:** 372224 **Date:** 10/17/2023**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Amen Corner 26 36 27 State Com 182H	30025-		200' FNL & 2370' FEL	680	3,412	2,610
Amen Corner 26 36 27 State Com 183H	30025-		230' FSL & 1075' FEL	680	3,412	2,610
Amen Corner 26 36 27 State Com 262H	30025-		230' FSL & 1680' FWL	680	3,412	2,610
Amen Corner 26 36 27 State Com 263H	30025-		200' FNL & 2330' FEL	680	3,412	2,610

**IV. Central Delivery Point Name:** \_\_\_\_\_ [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Amen Corner 26 36 27 State Com 182H	30025-	01/15/2024	03/02/2024	04/02/2024	04/30/2024	05/03/2024
Amen Corner 26 36 27 State Com 183H	30025-	01/15/2024	03/02/2024	04/02/2024	04/30/2024	05/03/2024
Amen Corner 26 36 27 State Com 262H	30025-	01/15/2024	03/02/2024	04/02/2024	04/30/2024	05/03/2024
Amen Corner 26 36 27 State Com 263H	30025-	01/15/2024	03/02/2024	04/02/2024	04/30/2024	05/03/2024

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

## **Section 2 – Enhanced Plan**

### **EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

#### **IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

#### **X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

**XI. Map.** ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: <i>Cesca Yu</i>
Printed Name: Cesca Yu
Title: Engineer
E-mail Address: cyu@ameredev.com
Date: 10/17/2023
Phone: 512-775-1417

**OIL CONSERVATION DIVISION**  
**(Only applicable when submitted as a standalone form)**

Approved By:
Title:
Approval Date:
Conditions of Approval:

## **Natural Gas Management Plan**

### **VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.**

- Separation equipment is sized to allow for retention time and velocity to adequately separate oil, gas, and water at anticipated peak rates.
- All central tank battery equipment is designed to efficiently capture the remaining gas from the liquid phase.
- Valves and meters are designed to service without flow interruption or venting of gas.

### **VII. Operational Practices: Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F 19.15.27.8 NMAC.**

#### **19.15.27.8 (A)**

Ameredev's field operations are designed with the goal of minimizing flaring and preventing venting of natural gas. If capturing the gas is not possible then the gas is combusted/flared using properly sized flares or combustors in accordance with state air permit rules.

#### **19.15.27.8 (B) Venting and Flaring during drilling operations**

- A properly-sized flare stack will be located at a minimum 100' from the nearest surface hole location on the pad.
- All natural gas produced during drilling operations will be flared. Venting will only occur if there is an equipment malfunction and/or to avoid risk of an immediate and substantial adverse impact on safety, public health, or the environment.

#### **19.15.27.8 (C) Venting and Flaring during completions or recompletions operations.**

- During all phases of flowback, wells will flow through a sand separator, or other appropriate flowback separation equipment, and the well stream will be directed to a central tank battery (CTB) through properly sized flowlines
- The CTB will have properly sized separation equipment for maximum anticipated flowrates
- Multiple stages of separation will be used to separate gas from liquids. All gas will be routed to a sales outlet. Fluids will be routed to tanks equipped with a closed loop system that will recover any residual gas from the tanks and route such gas to a sales outlet.

#### **19.15.27.8 (D) Venting and Flaring during production operations.**

- During production, the well stream will be routed to the CTB where multiple stages of separation will separate gas from liquids. All gas will be routed to a sales outlet. Fluids will be routed to tanks with a closed

loop system that will recover any residual gas from the tanks and route such gas to a sales outlet, minimizing tank emissions.

- Flares are equipped with auto-ignition systems and continuous pilot operations.
- Automatic gauging equipment is installed on all tanks.

#### **19.15.27.8 (E) Performance Standards**

- Production equipment will be designed to handle maximum anticipated rates and pressure.
- Automatic gauging equipment is installed on all tanks to minimize venting
- All flared gas will be combusted in a flare stack that is properly sized and designed to ensure proper combustion.
- Flares are equipped with continuous pilots and auto-ignitors along with remote monitoring of the pilot status
- Weekly AVOs and monthly LDAR inspections will be performed on all wells and facilities that produce more than 60 Mcfd.
- Gas/H<sub>2</sub>S detectors will be installed throughout the facilities and wellheads to detect leaks and enable timely repairs.

#### **19.15.27.8 (F) Measurement or estimation of vented and flared natural gas**

- All high pressure flared gas is measured by equipment conforming to API 14.10.
- No meter bypasses are installed.
- When metering is not practical due to low pressure/low rate, the vented or flared volume will be estimated through flare flow curves with the assistance of air emissions consultants, as necessary.

#### **VIII. Best Management Practices: Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.**

- Ameredev will use best management practices to vent as minimally as possible during well intervention operations and downhole well maintenance
- All natural gas is routed into the gas gathering system and directed to one of Ameredev's multiple gas sales outlets.
- All venting events will be recorded and all start-up, shutdown, maintenance logs will be kept for control equipment
- All control equipment will be maintained to provide highest run-time possible
- All procedures are drafted to keep venting and flaring to the absolute minimum