Received by OCD: 1/25/2024 1:07:46 PM

ccciveu by 0 cD. 1/23/20			1 450 1			
Form 3160-5 (June 2019)	UNITED STAT DEPARTMENT OF THE BUREAU OF LAND MA	FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021 5. Lease Serial No.				
Do not use		ORTS ON WELLS to drill or to re-enter an APD) for such proposals.	6. If Indian, Allottee or Tribe Name			
	IIT IN TRIPLICATE - Other ins	tructions on page 2	7. If Unit of CA/Agreement, Name and/or No.			
1. Type of Well	Gas Well Other		8. Well Name and No.			
2. Name of Operator			9. API Well No.			
3a. Address		3b. Phone No. <i>(include area code)</i>	10. Field and Pool or Exploratory Area			
4. Location of Well (Footage, Se	cc., T.,R.,M., or Survey Descriptio	n)	11. Country or Parish, State			
12	2. CHECK THE APPROPRIATE	BOX(ES) TO INDICATE NATURE O	F NOTICE, REPORT OR OTHER DATA			
TYPE OF SUBMISSION		TYPE	OF ACTION			
Notice of Intent	Acidize	Deepen [Hydraulic Fracturing]	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity			
Subsequent Report	Casing Repair Change Plans	New Construction	Recomplete Other			
Final Abandonment Noti	ce Convert to Injection	n Plug Back	Water Disposal			
the proposal is to deepen dir the Bond under which the w completion of the involved of	ectionally or recomplete horizont ork will be perfonned or provide operations. If the operation results ent Notices must be filed only aft	ally, give subsurface locations and mea he Bond No. on file with BLM/BIA. R in a multiple completion or recomplet	tarting date of any proposed work and approximate duration thereof. If asured and true vertical depths of all pertinent markers and zones. Attac Required subsequent reports must be filed within 30 days following ion in a new interval, a Form 3160-4 must be filed once testing has been ion, have been completed and the operator has detennined that the site			

14. I hereby certify that the foregoing is true and co	prrect. Name (Printed/Typed)			
	Т	ĩitle		
Signature	Γ	Date		
Accepted for record –NMOCD gc3/8/2024	THE SPACE FOR FEDEI	RAL OR STATE OF	ICE USE	
Approved by	-			
	Title		Date	
Conditions of approval, if any, are attached. Approv certify that the applicant holds legal or equitable tit which would entitle the applicant to conduct operat				
Title 18 U.S.C Section 1001 and Title 43 U.S.C Sec any false, fictitious or fraudulent statements or repr			fully to make to any o	department or agency of the United States

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SESW / 535 FSL / 1860 FWL / TWSP: 18S / RANGE: 27E / SECTION: 5 / LAT: 32.770899 / LONG: -104.302582 (TVD: 0 feet, MD: 0 feet) PPP: SESW / 352 FSL / 2290 FWL / TWSP: 18S / RANGE: 27E / SECTION: 5 / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet) BHL: SESW / 348 FSL / 2287 FWL / TWSP: 18S / RANGE: 27E / SECTION: 5 / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet)

Plug Abandonment Subsequent Report

OPERATOR NAME:	Redwood Operating, LLC
LEASE NO.:	NMLC055383A
WELL NAME & NO.:	SIMON A5N FEDERAL 3
US WELL NUMBER:	30-015-41436
LOCATION:	Sec 5 T18S R27E
COUNTY:	Eddy, NM

05/30/23 MIRU plugging equipment. Dug out cellar, unflanged well, NU BOP. Began POH w/ tbg. 05/31/23 Killed pressure w/ 15 BBLS Brine H20 down well. Finished POH w/ tbg. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Spotted 25 sx cmt @ 1321-1067'. WOC. 06/01/23 Tagged @ 1103'. ND BOP. Spotted 70 sx class C cmt @ 488' to surface. Rigged down & moved off. 06/02/23 Moved in backhoe and welder. Cut off well head & anchors. Roberto Gonzalez w/ BLM verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Backfilled cellar, cut off deadmen, cleaned location, and moved off.

•

Author: Abby @ BCM Mell Name Field/Point Abby @ BCM Mithing Well No. Prince #3 Field/Point RDLAKG.LYONE Eddy API # Point API # 20015-41436 Prince #3 Spud Date 7/12/2013 GL: 3355 FSL & 1850 FWL 3456 Spid 355 51/2 1/8 4.475 7.78 335 0 Spud Date 7/12/2013 GL: 3456 3456 Spid Spid 1/8 1/8 Spid 1/8 1/8 Spid Spid 1/8 1/8 Spid Spid 1/8 1/8 Spid 1/8	Redwood O	perating		PLUGGED		Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Well Name Sind NA & N FED Well No. #3 Guid/Pool Eddy Location: N-5-185-27E Synd Date NM County Eddy Synd Diff Location: N-5-185-27E Synd Diff Location: N-5-185-27E Synd Diff Location: N-5-185-27E Synd Diff GL S35 FSL All Store FVL Synd Diff GL S35 FSL All Store FVL Synd Diff GL S35 FSL All Store FVL B 5/8 24# CSG @ 438 Hole Size: 12 1/4 B Spotted 70 sx class C cmt @ 488' to surface. Diff Diff 2 Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. Diff Diff Diff 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perf @ 2810-4159 Si/2 17# CSG @ 4,475 Hole Size: 778 Si/2 17# CSG @ 4,475 Hole Size: 778	Author:							J55	24#	438	12 1/4	325	0
County Edity Location: N-5-185-27E State 535 FSL & 1800 FWL 535 FSL & 1800 FWL State 535 FSL & 1800 FWL 535 FSL & 1800 FWL GL: 3456 State 3456 Formation Formation State 51/2 Spud Date 7/12/2013 GL: 3456 State State State State <td></td> <td></td> <td></td> <td></td> <td>420</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>					420								
State M S35 FSL & 1860 FWL Spud Date 7/12/2013 GL: 3456 Spud Date GL: 3456 Spud Date Formation Top Question 8 5/8 24# CSG @ 438 Hole Size: 12 1/4 144 3. Spotted 70 sx class C cmt @ 488' to surface. 144 2. Spotted 25 sx cmt @ 1321-1067. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8						Prod Csg	5 1/2	J55	17#	4,475	7 7/8	935	0
Spud Date 7/12/2013 GL: 3456 Formation Top Orean 612 ORBG 992 SA 1211 B 5/8 24# CSG @ 438 Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 486' to surface. 2. Spotted 70 sx class C cmt @ 486' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760- Ports @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8	-		Location:										
Formation Top 0 1 8<5/8			GL:										
Image: CRBG 992 SA SB													Тор
SA 1271 GL 2260 Yeso 2773 Tubb 4194 Hole Size: 121/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 78			-										
GL 2683 Yess 2773 Tubb 4194 Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface.													
Yeso 2773 Tubb 4194 Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 78												SA	
Tubb 4194 8 5/8 24# CSG @ 438 Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
8 5/8 24# CSG @ 438 Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 778												Tubb	4194
Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 77/8													
Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 77/8													
Hole Size: 12 1/4 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 77/8													
 3. Spotted 70 sx class C cmt @ 488' to surface. 2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 77/8 													
2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760- 2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8				Hole Size: 1	2 1/4								
2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760- 2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2. Spotted 25 sx cmt @ 1321-1067'. WOC & Tagged @ 1103'. 1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760- 2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 77/8	/	1	3. Spotte	d 70 sx class C cm	t @ 488' to sur	face.							
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8	-												
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
1. Set 5 1/2 CIBP @ 2760'. Circ'd hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2760-2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8			2. Spott	ed 25 sx cmt @ 132	1-1067'. WOC 8	& Tagged @ 110	3'.						
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
2506'. Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 Hole Size: 7 7/8													
Perfs @ 2810-4159 5 1/2 17# CSG @ 4,475 TDPB @ 4370 Hole Size: 7 7/8				1/2 CIBP @ 2760'. (Circ'd hole w/ M	ILF. Pressure te	sted cs	g, held	500 PSI. 9	Spotted	25 sx 0	class C cmt	@ 2760-
5 1/2 17# CSG @ 4,475 TDPB @ 4370 Hole Size: 7 7/8			2506'.										
5 1/2 17# CSG @ 4,475 TDPB @ 4370 Hole Size: 7 7/8			Porfs @	2810-4159									
TDPB @ 4370 Hole Size: 7 7/8				2010-4135									
TDPB @ 4370 Hole Size: 7 7/8													
TDPB @ 4370 Hole Size: 7 7/8													
				Hole Size:	7 7/8								
	1	D @ 4417											

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
RILEY PERMIAN OPERATING COMPANY, LLC	372290
29 E Reno Avenue, Suite 500	Action Number:
Oklahoma City, OK 73104	307899
	Action Type:
	[C-103] Sub. Plugging (C-103P)
	[C-103] Sub. Pluggillg (C-103P)

CONDITIONS

Created By		Condition Date
gcordero	None	3/8/2024

Page 6 of 6

.

Action 307899