WAFMSS

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: QPBSSU

Well Location: T18S / R32E / SEC 14 /

TR 12B / NWSE /

County or Parish/State: LEA /

Well Number: 12B-3

Type of Well: INJECTION - ENHANCED Allottee or Tribe Name:

RECOVERY

Unit or CA Name: QUERECHO PLAINS

BONE SPG

Unit or CA Number:

NMNM88523X

US Well Number: 3002530570

Lease Number: NMNM40452

Well Status: Water Injection Well

Operator: MEWBOURNE OIL

COMPANY

LONG VO Date: 2024.03,04 13:55:26 -06'00'

Notice of Intent

Sundry ID: 2773804

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 02/07/2024

Time Sundry Submitted: 06:38

Date proposed operation will begin: 06/01/2024

Procedure Description: Please see attached P&A procedure & wellbore schematics. If you have any questions, please contact Kade Marlatt.

Surface Disturbance

Is any additional surface disturbance proposed?: No

Approval Subject to General Requirements

and Special Stipulations Attached

NOI Attachments

Procedure Description

QPBSSU_12B_3_Proposed_WBS_20240304075000.pdf

QPBSSU_12B_3_Current_WBS_20240304074945.pdf

Procedure_20240207063535.pdf

County or Parish/State: LEA / Well Name: QPBSSU Well Location: T18S / R32E / SEC 14 /

TR 12B / NWSE /

Zip: 88240

Type of Well: INJECTION - ENHANCED Allottee or Tribe Name: Well Number: 12B-3

RECOVERY

Unit or CA Name: QUERECHO PLAINS Unit or CA Number: Lease Number: NMNM40452

BONE SPG NMNM88523X

Operator: MEWBOURNE OIL **US Well Number: 3002530570** Well Status: Water Injection Well COMPANY

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JACKIE LATHAN Signed on: MAR 04, 2024 07:50 AM

Name: MEWBOURNE OIL COMPANY

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs

State: NM

Phone: (575) 393-5905

Email address: Jlathan@mewbourne.com

Field

Representative Name: Kade Marlatt

Street Address: PO Box 5270

City: Hobbs

State: NM

Phone: (575)393-5905

Email address: kmarlatt@mewbourne.com

PLUG AND ABANDONMENT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Mewbourne Oil Company
LEASE NO.:	NMNM40452
WELL NAME & NO.:	QPBSSU 12B-3
US Well Number:	3002530570
LOCATION:	Section 14, T.18 S., R.32 E., NMPM
COUNTY:	Lea County, New Mexico
Sundry ID:	2773804
Karst:	
Potash:	☐Secretary ☐R111P
Special Area:	⊠Prairie Chicken ⊠Capitan Reef

- 1) POOH laying down 2-7/8" tbg.
- 2) TIH 2-3/8" tbg and Gauge Ring to PBTD at 8390'.
- 3) POOH w/tbg. TiH 2-3/8" tbg to 8341' set CIBP. Leak test CIBP and spot 25 sxs Class H cmt on top. Run CBL from top of cement to surface.
- 4) Spot 25 sxs cement from 6871' to 6702'. If no cement behind casing, perf and squeeze instead. (In 17 sxs/Out 23 sxs), WOC and Tag.
- 5) Spot 25 sxs cement from 5706' to 5549'. If no cement behind casing, perf and squeeze instead. (In 16 sxs/Out 21 sxs), WOC and Tag.
- 6) Spot 110 sxs cement from 4961' to 3850'. If no cement behind casing, perf and squeeze instead. (In 110 sxs/Out 146 sxs), WOC and Tag.
- 7) Spot 26 sxs cement from 2777' to 2517'. If no cement behind casing, perf and squeeze instead. (In 26 sxs/Out 38 sxs), WOC and Tag.
- 8) Spot 25 sxs cement from 1561' to 1445'. If no cement behind casing, perf and squeeze instead. (In 12 sxs/Out 17 sxs), WOC and Tag.
- 9) Spot 49 sxs cement from 494' to surface. If no cement behind casing, perf and squeeze instead. (In 49 sxs/Out 73 sxs), WOC and Tag.
- 10) ND BOP and cut off wellhead 5' below surface. RDMO PU, transport trucks, and pump truck.
- 11) Set P&A marker.

Approval Subject to General Requirements and Special Stipulations Attached

- No more than 3000 feet between cement plugs in cased hole.
- Wait on Cement and Tag Top of Cement Requirement:
 - 1. Shoe, Top of Salt, Base of Salt, DV tool, Perforate and Squeeze, Open Perforation.
 - 2. Formation plug is optional if a solid base is established and confirmed.

Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR

F	ORM	APPRO	OVED
C	MB N	lo. 1004	-0137
Exp	ires: C	October	31, 202

. Lea	se S	erial No	NMNM	40452	2		
707	12	A 11	797 11	×1.			

BURE	EAU OF LAND MAN.	AGEMENT			5. Lease Senal No. NN	INM40452
SUNDRY N Do not use this fo abandoned well. L	o drill or to	re-enter an	•	6. If Indian, Allottee or	Tribe Name	
SUBMIT IN T	RIPLICATE - Other instru	uctions on page	9 2		7. If Unit of CA/Agreen	
1. Type of Well Oil Well Gas W	ell 🗸 Other				8. Well Name and No.	S BONE SPG/NMNM88523X QPBSSU/12B-3
2. Name of Operator MEWBOURNE O	OIL COMPANY				9. API Well No. 300253	30570
3a. Address P O BOX 5270, HOBBS		3b. Phone No. (575) 393-590	(include area code)5		10. Field and Pool or Ex	
4. Location of Well (Footage, Sec., T.R. SEC 14/T18S/R32E/NMP	,M., or Survey Description)				11. Country or Parish, S LEA/NM	State
12. CHEC	CK THE APPROPRIATE BO	OX(ES) TO INI	DICATE NATURE	OF NOTI	CE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION			TYF	PE OF ACT	ΓΙΟΝ	
✓ Notice of Intent Subsequent Report	Acidize Alter Casing Casing Repair		en aulic Fracturing Construction	Recla	uction (Start/Resume) amation mplete	Water Shut-Off Well Integrity Other
Final Abandonment Notice	Change Plans Convert to Injection		and Abandon	= :	oorarily Abandon r Disposal	
completed. Final Abandonment Notics ready for final inspection.) Please see attached P&A procured from the procure of the pro	ices must be filed only after edure & wellbore schema	all requirement	s, including reclam	nation, have	e been completed and the	50–4 must be filed once testing has be e operator has detennined that the site
14. I hereby certify that the foregoing is JACKIE LATHAN / Ph: (575) 393-59		inted/Typed)	Regulatory Title	у		
Signature (Electronic Submission	n)		Date		03/04/202	24
	THE SPACE	FOR FEDI	ERAL OR ST	ATE OF	ICE USE	
Approved by			Title		Da	ate
Conditions of approval, if any, are attach certify that the applicant holds legal or e which would entitle the applicant to con-	quitable title to those rights duct operations thereon.	in the subject le	ase Office			
Title 18 U.S.C Section 1001 and Title 43 any false, fictitious or fraudulent stateme	U.S.C Section 1212, make ents or representations as to	it a crime for an any matter with	y person knowing n its jurisdiction.	ly and will	fully to make to any dep	artment or agency of the United State

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

(Form 3160-5, page 2)

Additional Information

Location of Well

 $0. \ SHL: \ NWSE\ /\ TR\ 12B\ /\ 1980\ FSL\ /\ 1980\ FEL\ /\ TWSP: \ 18S\ /\ RANGE: \ 32E\ /\ SECTION: \ 14\ /\ LAT: \ 0.0\ /\ LONG: \ 0.0\ (\ TVD: \ 0\ feet, \ MD: \ 0\ feet)$ BHL: \ NWSE\ /\ TR\ 12B\ /\ 1980\ FSL\ /\ 1980\ FSL\ /\ TWSP: \ 18S\ /\ SECTION: \ 12B\ /\ LAT: \ 0.0\ /\ LONG: \ 0.0\ (\ TVD: \ 0\ feet, \ MD: \ 0\ feet)

QPBSSU 12B-3 P&A Schematic

1980' FSL & 1980' FEL, Sec. 14 – T18S – R32E – Lea Co, NM API 30-025-30570



Submitted by: Kode Morlott 17 ¾" hole 13 3/8" 48# set @ 444', cmt to surface Perf 8 5/8" @ 500' Approval Subject to General Requirements MIF and Special Stipulations Attached 12 1/4" hole 8 5/8" 24# set @ 2727', cmt to surface 50 sks Class C Top Yates - 2897' MIF Top Delaware – 5656' Class C MLE 25 sks Top Bone Springs - 6823' Class C MLF 27 sks Class H 5 1/2" CIBP Set @ 8360' Top 1st Bone Springs Sand - 8350' Top Perf @ 8391' 7 7/8" Hole

5 %" 17# @ 9489'

QPBSSU 12B-3 P&A Schematic

1980' FSL & 1980' FEL, Sec. 14 – T185 – R32E – Lea Co, NM API 30-025-30570



Submitted by: Kode Moriatt 17 ½" hole 13 3/8" 48# set @ 444', cmt to surface 12 1/4" hole 8 5/8" 24# set @ 2727', cmt to surface Top Yates - 2897' Top Delaware – 5656' Top Bone Springs - 6823' Top 1st Bone Springs Sand - 8350' End of Tbg - 8350' Top Perf @ 8391' 77/8" Hole 5 1/2" 17# csg

Set @ 9489'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified BY PHONE (numbers listed under 2. Notification) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Mark Mattozzi Environmental Protection Specialist 575-234-5713

Robert Duenas Environmental Protection Specialist 575-234-2229

Doris Lauger Martinez Environmental Protection Specialist 575-234-5926

Jaden Johnston Environmental Protection Asst. (Intern) 575-234-6252

Sundry ID	2773804						
Plug Type	Тор	Bottom	Length	Tag	Sacks	Cement Class	Notes
Surface Plug	0.00	100.00	100.00	Tag/Verify			
Surface Flug	0.00	100.00	100.00	Tug/ voiny			
13.375 inch- Shoe Plug	389.56	494.00	104.44	Tag/Verify	49.00	С	Spot 49 sxs cement from 494' to surface. Verify at surface. If no cement behind casing perf and squeeze instead. (In 49 sx/Out 73 sxs)
					05.55		Spot 25 sxs cement from 1561' to 1445'. WOC and Tag. If no cement behind casing perf and squeeze instead, WOC and Tag. (In
Top of Salt @ 1511 Base of Salt @ 2593	1445.89 2517.07	1561.00 2643.00		Tag/Verify Tag/Verify	25.00	C	12 sx/Out 17 sxs)
Yates @ 2726	2648.74						
8.625 inch- Shoe Plug	2649.73	2777.00	127.27	Tag/Verify	26.00	С	Spot 26 sxs cement from 2777' to 2517'. WOC and Tag. If no cement behind casing perf and squeeze instead, WOC and Tag. (In 26 sx/Out 38 sxs)
Queen @ 3940	3850.60						
Greyburg @ 4520	4424.80						
Capitan Reef @ 4570	4474.30	4620.00	145.70	If solid			
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio			Spot 110 sxs cement from 4961' to 3850'. If no cement behind casing perf and squeeze instead, WOC and Tag. (In
	4811.89	4961.00	149.11		110.00	1 -	110 sx/Out 146 sxs)

Delaware @ 5656	5549.44	5706.00	156.56	If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio ns	25.00	С	Spot 25 sxs cement from 5706' to 5549'. If no cement behind casing perf and squeeze instead, WOC and Tag. (In 16 sx/Out 21 sxs)
Bonesprings @ 6821	6702.79	6871.00		If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations	25.00	С	Spot 25 sxs cement from 6871' to 6702'. If no cement behind casing perf and squeeze instead, WOC and Tag. (In 17 sx/Out 23 sxs)
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak			
CIBP Plug	8306.00	8341.00	35.00	Test all CIBP if no Open Perforatio		н	Set CIBP at 8341'. Spot 25 sxs on top. Leak test CIBP. Run CBL from top of CIBP to surface.
CIBP Plug Perforations Plug (If No CIBP)	8306.00 8341.00	8341.00 8554.00	35.00 213.00	Test all CIBP if no Open Perforatio	25.00	Н	Spot 25 sxs on top. Leak test CIBP. Run

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole. Class H >7500' Class C<7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft^3/sx Class H: 1.06 ft^3/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement Requirement:	Low	
13.375 inch- Shoe Plug @	444.00	
8.625 inch- Shoe Plug @	2727.00	
5.5 inch- Shoe Plug @	9489.00	TOC @ n/a
Perforatons Top @	8391.00	Perforations 8504.00
		CIBP @ 8341.00

District III

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 325160

COMMENTS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Action Number:
Hobbs, NM 88241	325160
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

COMMENTS

C	Created By	Comment	Comment Date
	plmartinez	DATA ENTRY PM.	3/28/2024

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 325160

CONDITIONS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Action Number:
Hobbs, NM 88241	325160
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Run CBL 8341' - Surface. CBL must be submitted to OCD via OCD Permitting #7. Yates must be plugged from 2947' inside and out Rustler formation must be plugged from 1144' - inside and out	3/27/2024