| eceived by OCD: \$/21/2024 9:03:55 AM U.S. Department of the Interior BUREAU OF LAND MANAGEMENT | | Sundry Print Report |
|---|---|-----------------------------------|
| Well Name: TURNER B | Well Location: T17S / R31E / SEC 20 / SESW / 32.8145664 / -103.8937403 | County or Parish/State: EDDY / NM |
| Well Number: 44 | Type of Well: INJECTION - ENHANCED RECOVERY | Allottee or Tribe Name: |
| Lease Number: NMLC029395B | Unit or CA Name: | Unit or CA Number: |
| US Well Number: 3001505311 | Operator: LH OPERATING LLC | |

Notice of Intent

Sundry ID: 2789299

•

Type of Submission: Notice of Intent

Date Sundry Submitted: 05/09/2024

Date proposed operation will begin: 06/01/2024

Type of Action: Workover Operations Time Sundry Submitted: 10:12 Q

Procedure Description: 1. Move in rig up workover rig. Bleed off well head pressure. ND wellhead and NU BOP. 2. Unhook injection line and meter run. 3. ND wellhead and NU BOP. 4. Unset packer. Pull out of hole with tubing. Inspect tubing as pulling out of hole. 5. Send packer to shop for redress or replace with new packer based on condition. 6. Replace tubing as needed from visual inspection. 7. Pick up reconditioned or new packer and run in hole on the tubing while testing the tubing below the slips to 4500 psi (test tools to be coated). Replace tubing as needed. 8. Once on depth above perforations, circulate in packer fluid (corrosion inhibitor and biocide) mixed in fresh water. 9. Set packer. ND BOP and NU wellhead. Install meter run. 10. Notify NMOCD field representative to witness test. Perform mechanical integrity test. Return to water injection.

Surface Disturbance

Is any additional surface disturbance proposed?: No

| R | eceived by OCD: 5/21/2024 9:03:55 AM Well Name: TURNER B | Well Location: T17S / R31E / SEC 20 / SESW / 32.8145664 / -103.8937403 | County or Parish/State: EDD ² /2 of S |
|-----|---|---|--|
| | Well Number: 44 | Type of Well: INJECTION - ENHANCED RECOVERY | Allottee or Tribe Name: |
| | Lease Number: NMLC029395B | Unit or CA Name: | Unit or CA Number: |
| | US Well Number: 3001505311 | Operator: LH OPERATING LLC | |
| - 1 | | | |

Conditions of Approval

Specialist Review

Workover_or_Vertical_Deepen_COA_20240516125626.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MICHAEL BURTON

State: TX

State:

Name: LH OPERATING LLC

Title: Environmental Manager

Street Address: 3730 KIRBY DR SUITE 1200

City: HOUSTON

Phone: (575) 499-5306

Email address: MIKE@LHOPERATING.COM

Field

Representative Name: Street Address: City: Phone:

Email address:

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD BLM POC Phone: 5752345972 Disposition: Approved Signature: Jonathon Shepard Signed on: MAY 09, 2024 10:12 AM

Zip:

BLM POC Title: Petroleum Engineer

BLM POC Email Address: jshepard@blm.gov

Disposition Date: 05/16/2024

Received by OCD: 5/21/2024 9:03:55 AM

| eceived by OCD: 5/21/202 | 24 9:03:55 AM | | | Page 3 of 9 |
|--|---|---|--|---|
| Form 3160-5 (June 2019) | UNITED STAT | INTERIOR | | FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021 |
|] | BUREAU OF LAND MAN | AGEMENT | 5. Lease Serial N | 0. |
| Do not use t | RY NOTICES AND REP(his form for proposals cell. Use Form 3160-3 (A | to drill or to re-enter an | | ttee or Tribe Name |
| SUBM | T IN TRIPLICATE - Other instr | uctions on page 2 | 7. If Unit of CA/ | Agreement, Name and/or No. |
| 1. Type of Well | Gas Well Other | | 8. Well Name an | d No. |
| 2. Name of Operator | | | 9. API Well No. | |
| 3a. Address | | 3b. Phone No. (include area coa | (e) 10. Field and Po | ol or Exploratory Area |
| 4. Location of Well (Footage, See | c., T.,R.,M., or Survey Description |) | 11. Country or P | arish, State |
| 12 | CHECK THE APPROPRIATE B | OX(ES) TO INDICATE NATUR | E OF NOTICE, REPORT OF | OTHER DATA |
| TYPE OF SUBMISSION | | ТҮ | PE OF ACTION | |
| Notice of Intent | Acidize | Deepen Hydraulic Fracturing | Production (Start/Rest | ume) Water Shut-Off Well Integrity |
| Subsequent Report | Casing Repair | New Construction | Recomplete | Other |
| Final Abandonment Notic | e Convert to Injection | Plug Back | Water Disposal | |
| the proposal is to deepen dire the Bond under which the wo completion of the involved of | ctionally or recomplete horizontal rk will be perfonned or provide th perations. If the operation results i | ly, give subsurface locations and t e Bond No. on file with BLM/BL/ n a multiple completion or recomp | neasured and true vertical de A. Required subsequent repor pletion in a new interval, a Fo | ed work and approximate duration thereof. If pths of all pertinent markers and zones. Attach ts must be filed within 30 days following orm 3160-4 must be filed once testing has been and the operator has detennined that the site |

| 14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>) | | | |
|--|-----------------|---|--------|
| 1 | Fitle | | |
| Signature | Date | | |
| | | | |
| THE SPACE FOR FEDE | RAL OR STATE OF | ICE USE | |
| Approved by | | | |
| | Title | Date | |
| Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject leas which would entitle the applicant to conduct operations thereon. | | | |
| Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any any false, fictitious or fraudulent statements or representations as to any matter within | | fully to make to any department or agency of the United | States |

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: SESW / 660 FSL / 2055 FWL / TWSP: 17S / RANGE: 31E / SECTION: 20 / LAT: 32.8145664 / LONG: -103.8937403 (TVD: 0 feet, MD: 0 feet) BHL: SESW / 660 FSL / 2055 FWL / TWSP: 17S / SECTION: / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 0 feet)

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Conditions of Approval for Workover/Deepening of a Well

- <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any operations. For wells in Eddy County, call 575-361-2822. For wells in Lea County, call 575-689-5981
- <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,100 feet, a 3M system for a well not deeper than 13,600 feet, or a 5M system for a well not deeper than 22,700 feet (all depths are for measured well depth).
- 3. Cement: Notify BLM if cement fails to circulate.
- Subsequent Reporting: Within 30 days after work is completed, file a Subsequent Report (Form 3160-5) to BLM. The report should give in detail the manner in which the work was carried out. Show date work was completed. If producing a new zone, submit a Completion Report (Form 3160-4) with the Subsequent Report.
- 5. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.
- If well location is within the Timing Limitation Stipulation Area for Lesser Prairie-Chicken: From March 1st through June 15th annually, activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted.

Well Name: TURNER B 44 INJ

WellView[®]

| wi 1505311 | | Surface Legal L | | | BURG WEST CENTR | | | NM | | | on Type |
|---|--------------|-----------------|-----------------|---------------------------------|------------------------|-------------|--------------------|------------------------------------|------------------|-------------------|---------------|
| nal KB Elevation 34.00 | (ft) | KB-Tubing Hea | d Distance (ft) | Initial Spud Date 10/30/1955 | | Rig Release | Date | PBTD (All) (ftKB) Original Hole |) ə - 3,340.0 | Total Depth All (| TVD) (ftKB) |
| | | | | | | | | | | | |
| | Des | | Make | Mod | lel | WP (psi) | Service | | WP Top (psi) | | Bore Min (in) |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | Original H | ole, 5/8/2024 3 | :35:27 PM | | Casing Str | ings | | | | | |
| | - | al schematic (a | | | C | sg Des | OD (in) | Wt/Len (lb/ft) | Grade | Top Thread | Set Depth (1 |
| ana | | | | | Surface Production | | 8 5/8 5 1/2 | | | | 47 |
| | | | | | Perforation | ne | 0 172 | 14.00 | 0.00 | | 0,04 |
| | | | | | Date | | Top (ftKB) | Btm (ftKB) | | Linked Zone |) |
| | | 10.5 | | | 2/21/1997 | | 2,914.0 | 2,914 | 1.0 | | |
| | | 1-3; Pa | icker | | 2/21/1997 | | 2,916.0 | 2,916 | | | |
| 806 | 1655 | | | | 2/21/1997 | | 2,934.0 | 2,934 | | | |
| 88 | 1205 | | | | 2/21/1997 | | 2,938.0 | 2,938 | | | |
| | | | | | 2/21/1997 2/21/1997 | | 2,948.0 2,952.0 | 2,948 | | | |
| 202 | 1888 | | | | 2/21/1997 | | 2,952.0 | 2,952 | | | |
| | 822 | | | | 2/21/1997 | | 2,975.0 | 2,975 | | | |
| | 8 8 | | | | 2/21/1997 | | 3,000.0 | 3,000 | | | |
| 898 | 1966 | | | | 2/21/1997 | | 3,012.0 | 3,012 | 2.0 | | |
| 856 | 1888 | | | | 2/21/1997 | | 3,014.0 | 3,014 | 1.0 | | |
| | 1208 1908 | | | | 2/21/1997 | | 3,029.0 | 3,029 | | | |
| | 888 | | | | 2/21/1997 | | 3,044.0 | 3,044 | | | |
| 2005 I | 888 | | | | 2/21/1997 | | 3,048.0 | 3,048 | | | |
| | | | | | 2/21/1997 9/17/1991 | | 3,056.0 | 3,056 | | | |
| 1000 C | 1 | | | | 9/17/1991 | | 3,130.0 3,132.0 | 3,130 3,132 | | | |
| 1999 - C | 1988 | | | | 9/17/1991 | | 3,150.0 | 3,152 | | | |
| | 國際 | | | | 9/17/1991 | | 3,154.0 | 3,154 | | | |
| 200 | 1996 | | | | 11/20/1955 | | 3,161.0 | 3,176 | | | |
| | 1888 | | | | 1/27/1970 | | 3,185.0 | 3,188 | 3.0 | | |
| | 國際 | | | | 9/17/1991 | | 3,197.0 | 3,197 | 7.0 | | |
| 200 | 1000 | | | | 9/17/1991 | | 3,199.0 | 3,199 | | | |
| | 1000 | | | | 9/17/1991 | | 3,201.0 | 3,201 | | | |
| | 醫醫 | | | | 2/21/1997 | | 3,224.0 | 3,224 | | | |
| | 1988 | | | | 2/21/1997 9/17/1991 | | 3,227.0 3,228.0 | 3,227 | | | |
| 656 I | 1000 | | | | 9/17/1991 | | 3,228.0 | 3,228 | | | |
| | 日期 | | | | 9/17/1991 | | 3,248.0 | 3,240 | | | |
| | 833 | | | | 9/17/1991 | | 3,254.0 | 3,254 | | | |
| | 1000 | | | | 1/27/1970 | | 3,257.0 | 3,262 | | | |
| | 醫醫 | | | | 1/27/1970 | 1 | 3,264.0 | 3,269 | 0.0 | | |
| | 100 | | | | 2/21/1997 | | 3,277.0 | 3,277 | | | |
| | 122 | | | | 2/21/1997 | | 3,279.0 | 3,279 | | | |
| | 188 188 | | | | 9/17/1991 | | 3,291.0 | 3,291 | | | |
| 286 | 688 | | | | 9/17/1991 | | 3,293.0 | 3,293 | | | |
| | 88 | | | | 9/17/1991 9/17/1991 | | 3,294.0 3,298.0 | 3,294 3,298 | | | |
| | 1000 | | | | 9/17/1991 | | 3,298.0 | 3,290 | | | |
| 200 | 1655 | | | | 9/17/1991 | | 3,302.0 | 3,302 | | | |
| | 88 | | | | 9/17/1991 | | 3,305.0 | 3,305 | | | |
| | | | | | 9/17/1991 | | 3,307.0 | 3,307 | | | |
| 1000 | 9.92 | | | | 9/17/1991 | | 3,308.0 | 3,308 | | | |
| | | | | | 9/17/1991 | | 3,318.0 | 3,318 | | | |
| | | | | | 9/17/1991 | | 3,320.0 | 3,320 | | | |
| | 888 | | | | 9/17/1991 | | 3,327.0 | 3,327 | | | |
| | | | | | 9/17/1991 | 1 | 3,329.0 | 3,334 | I.U | | |

Downhole Well Profile

Well Name: TURNER B 44 INJ

WellView[®]

| api/uwi 3001505311 | Surface Legal Location | Field Name PBNM - PB-GRAYBURG WEST CENTRAL | Spud Date Notice Info | | State/Province | | II Configuration | | |
|--|------------------------------|---|-----------------------|----------|--|----------------|------------------------|------------|--------------|
| Original KB Elevation (ft) 3,684.00 | KB-Tubing Head Distance (ft) | Initial Spud Date 10/30/1955 00:00 | Rig Release Date | | РВТD (All) (ftКB) Original Hole - 3,340.0 | Tot | al Depth All (| TVD) (ftKB |) |
| | | | | | | | | | |
| Original H | lole, 5/8/2024 3:35:28 PM | Tubing Strir | gs | | | _ | | | |
| | cal schematic (actual) | Tubing Descriptio | | e 007 | String Length (ft) 2,860.00 | | Set Depth (2,856.0 | ftKB) | |
| | | Tubing | Des Jts | Make | e Model | OD (in) | 2,030.0 Wt (lb/ft) | Grade | Len (ft) |
| | | Tubing | 68 | | T&C Upset | 2 3/8 | 4.70 | J-55 | 2,856 .00 |
| | 1-3; Packer | Notched Coll Packer | | Baker | | 2 3/8 4 1/2 | | | 1.00 3.00 |
| | 1-3; Packer | | | Daker | | 4 1/2 | | | 5.00 |
| 800 1000 800 1000 | | Rod Strings Rod Description | Run Date | 9 | String Length (ft) | | Set Depth (| ftKB) | |
| 808 808 808 808 | - | Item | Des Jts | Make | e Model | OD (in) | Wt (lb/ft) | Grade | Len (ft) |
| | - | | | 1 | | | | | |
| | | | | | | | | | |
| www.peroton.com | | P: | age 2/2 | | | Rei | port Print | ed: 5/8 | 3/2024 |

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

| Operator: | OGRID: |
|-------------------|-------------------------------|
| LH Operating, LLC | 329319 |
| 3730 Kirby Drive | Action Number: |
| Houston, TX 77098 | 346167 |
| | Action Type: |
| | [C-103] NOI Workover (C-103G) |

CONDITIONS

| Created By | Condition | Condition Date |
|---------------|--|-------------------|
| mgebremichael | Ensure that the same tube size is replaced as stipulated by the SWD order. The packer shall not be more than 100 feet above the top of the perforations. | 5/29/2024 |

Page 9 of 9

.

Action 346167