Operator Hilcorp Energy Company

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Lease Name LUDWICK LS

Page 1 Revised June 10, 2003

13

Well No.

ocation of We	ell: Unit	Letter G Se	ec 05	Twp 029N	Rge		010W API	# 30-045-08781
	1	Name of Reservoir or Pool		Type of Prod			Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas		Flow		Tubing
Lower Completion	MV		Gas	Gas		Flow		Tubing
			Pre-Flow S	Shut-In Pressu	ıre Data			
Upper Completion	Hour, Date, Shut-In 6/6/2024		Length o	Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No) Yes
Lower Completion		ate, Shut-In 6/2024	100	108 SI Press. PSI		s. PSIG 240	Stabilized?(Yes or No) Yes	
			Flo	w Test No. 1				
Commenced a	at: 6/1	0/2024	110		oducing (U	pper	or Lower): LO	WER
Time (date/time)		Lapsed Time Since*	PRES Upper zone	SSURE Lower zone	Prod Zone Temperature		Remarks	
6/10/2024 12:00 PM		0	160	240			Starting Test, Crossover Target is 160 X .20=32, 160-32=128	
6/10/2024 12:26 PM		0	160	128			Crossover was reached in 26 Min. PC 160 MV 128, Csg 158, Line Psi 67	
6/10/2024 12:56 PM		0	160	113			This is 30 Min after Obtaining Crossover, F 160, MV 113, Csg 160, Line psi 67	
Production rate	during	test						
Dil:	l:BOPD Based on:		Bbls. In Hrs.			Grav.		GOR
Gas		MCFPD; Test th	ru (Orifice or M	leter)				
			Mid-Test S	Shut-In Pressu	ıre Data			
Upper Completion	Hour, Date, Shut-In Hour, Date, Shut-In			Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion						SI Press. PSIG		Stabilized?(Yes or No)
	1		(Continu	ue on reverse s	side)			

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

	at:		Zone Pro	Zone Producing (Upper or Lower)				
Time (date/tim			SSURE	Prod Zone	Remarks			
(date/tim	ie) Sinc	Ce* Upper zone	Lower zone	Temperature	Remarks			
Production rat	•							
Oil:	BOPD Based on:	Bbls. In _	Hrs.	G	ravGOR			
Gas	MCFPI	D; Test thru (Orifice or	Meter)					
Remarks:								
I hereby certify	y that the information	herein contained is tru	e and complete	to the best of m	ny knowledge.			
I hereby certify	y that the information	herein contained is tru		to the best of m				
Approved:	y that the information to Oil Conservation D	20						
Approved:		20 Division	Opera	tor: Hilcorp Er	ergy Company			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- $5. \quad \text{Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.} \\$

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fiften-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 352657

CONDITIONS

Operator:	OGRID:		
HILCORP ENERGY COMPANY	372171		
1111 Travis Street	Action Number:		
Houston, TX 77002	352657		
	Action Type:		
	[UF-PLT] Packer Leakage Test (NW) (PACKER LEAKAGE TEST (NW))		

CONDITIONS

Created By	Condition	Condition Date
jdurham	None	8/14/2024