

Submit a Copy To Appropriate District  
Office  
District I – (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II – (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III – (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV – (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised July 18, 2013

WELL API NO. 30-015-55348	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Little Betty 20	
8. Well Number 504H	
9. OGRID Number 330396	
10. Pool name or Wildcat Fenton; Bone Spring	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> 2. Name of Operator Avant Operating, LLC 3. Address of Operator 1515 Wynkoop Street, Suite 700. Denver, CO 80202 4. Well Location Unit Letter <u>I</u> : <u>2622</u> feet from the <u>S</u> line and <u>310</u> feet from the <u>E</u> line Section <u>20</u> Township <u>21S</u> Range <u>28E</u> NMPM County <u>Eddy</u> 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3221' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Avant Operating, LLC would like to request to update the 13-3/8" casing depth to 955' to avoid the possibility of having to run DV tools in both intermediate sections. Please see attached updated WBS to reflect this change.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Contract Regulatory Analyst DATE 8/28/2024

Type or print name Meghan Twele E-mail address: mtwele@outlook.com PHONE: 720-339-6880

**For State Use Only**

APPROVED BY: \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of Approval (if any):

API:  
REGULATORY: NMOCD  
PERMIT #



Little Betty 20 State #504H

Bone Springs

Eddy County, NM

RIG: H&P 255  
KB: 25.5  
GL: 3221

AFE: NM0046

SHL:

Sec. 20, T-21S, R-28E; 2622 FSL, 310 FEL  
Lat: 32.4656927, Long: -104.1012889 (NAD83)

HOLE SIZE	MD	FORMATION	TVD	MUD	CASING	CEMENT	SPECIAL INSTRUCTIONS
	120	30" Conductor	120	SPUD MW	20 "	Top of Lead: Surface 20% Excess	Circ cmt to surface is a regulatory requirement
24"				8.4 ppg	94# J-55 BTC	Top of Tail: 100' 20% Excess	Casing must be set 25' into the Rustler
	385	Rustler	385	FRESH TD MW	+/- 5 Bowsprings		MUD: Fresh water only
	400	SURF CSG PT	400	10.0 ppg	1 joint shoe track		
17.5"				DRLOUT MW	13 3/8 "	Top of Lead: Surface 20% OH Excess	Circ cmt to surface is a regulatory requirement
	1,025	Solado	1,025	10.0 ppg	54.5# J-55 BTC	Top of Tail: 831' 20% Excess	
				BRINE TD MW	+/- 10 Bowsprings		
	955	INTRM1 CSG PT	955	10.5 ppg	1 joint shoe track		
12.25"				DRILLOUT MW	9 5/8 "	Top of Lead: Surface 20% OH Excess	
	1,181	Capitan Reef	1,181	8.4 ppg	40# J-55 BTC	Top of Tail: 2487' 20% Excess	
				FRESH TD MW	+/- 15 Bowsprings		
	3,009	Cherry Canyon	2,993	8.4 ppg	1 joint shoe track		
	3,109	INTRM2 CSG PT	3,093				
VERT				DRLOUT MW	5 1/2 "		
8.75"	4,443	Brushy Canyon	4,385	9.2 ppg	20# P-110 HC GBCD		
				CUT BRINE KOP MW			
	7,009	1st BS Sand	6,887	9.5 ppg			
CRV	7,730	2nd BS Sand	7,593	EOC MW		TD MW	
8.75"	7,784	KOP	7,648	CUT BRINE 9.5 ppg	OBM	9.5 ppg	13,638 MD
							4,904 VS
LAT							8,125 TVD
8.75"	8,534	EOC	8,125	VS: -199'	Est. BHST = 146°, Est. BHCT = 129°		BHL: 1650' FSL, 100' FWL
					+/- 31 Singlebows 3,009 - 7,584 +/- 27 Doublebows 7,584 - 8,734 +/- 60.8 Solid bodies 8,734 - 13,638	Top of Lead: Surface 20% OH Excess  Top of Tail: 7784' (KOP) 20% Excess	Expected BH Pressure: 3803
DIRECTIONS TO LOCAITON:							

PRELIMINARY

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 378639

CONDITIONS

Operator: Avant Operating, LLC 1515 Wynkoop Street Denver, CO 80202	OGRID: 330396
	Action Number: 378639
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	All original COA's still apply. Additionally if cement is not circulated to surface during cementing operations, then a CBL is required.	8/28/2024