

Submit a Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-11546
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Eaton SE
8. Well Number 5
9. OGRID Number 256073
10. Pool name or Wildcat Langlie Mattix;7Rvrs;Q;Grayburg

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

J R Oil Ltd. Co.

3. Address of Operator

PO Box 2975 Hobbs, NM 88241

4. Well Location

Unit Letter J : 2310 feet from the South line and 1650 feet from the East line
Section 12 Township 25S Range 37E NMPM County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached

Spud Date:

12/04/1955

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Maren Latimer TITLE Agent DATE 2/6/2025

Type or print name Maren Latimer E-mail address: mlatimer@ravenop.com PHONE: 5756916790

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

Plugging Report
JR Oil Ltd. Co.
Eaton SE #5
API 30-025-11546

12/12/2024 Cleared anthill from around the wellhead, set the matting board and rigged up. Unseated the pump. Laid down 132 ¾" rods and the pump. Dug out down to the 10 ¾" surface head, replace the connections and plumbed to ground level.

12/13/2024 Installed BOP. POOH with tubing. 103 joints of 2 3/8" tubing. Made gauge ring run and set 7" CIBP at 3050'. Tagged CIBP with tubing and circulated MLF. Tested casing to 550#. Casing good. Spot 25 sx Class C cement on top of CIBP. POOH and SION.

12/16/2024 Tagged cement at 2904'. Waited on Renegade to arrive on location. Arrived at 11:00 am NM time. They worked on their computer programming until 2:30 pm and then started in the hole with the tools. Ran bond log. TOC at 2060'. Small stringer at 1350' & 1012'. Laid down tools and SION.

12/17/2024 RIH with tubing to 2763' and spot 65 sx cement. POOH and perforated casing at 1180'. Set packer and pressured up on perfs to 550# and held. Bled down to the truck and repeated to 700# with same results. POOH with packer and RIH with tubing to 1250' and spot 35 sx cement. POOH and SION.

12/18/2024 Tagged cement at 1041'. Perforated at 895'. Good communication with surface head. Squeezed perfs with 65 sx cement with CaCl. WOC and tagged at 753'. Perforated at 150'. Pumped cement down 7" casing to perforations at 150' and up the surface annulus. Took 60 sx to get good cement to the pit. Prepped to rig down and SION.

12/19/2024 Rigged down, dug out and removed the wellhead. Good cement to surface. Installed standard marker, removed the anchors and cleaned the pit.

JR Oil Ltd.

Eaton SE #5

Perf 150', circ. 60 sx
Tag TOC 753'
10-3/4" @ 843'
Perf 895', sqz 65 sx
Tag TOC 1,041'
Top of Salt 1,008'
Perf 1,180'
Spot 35 sx 1,250'
ET
To
To
65
ML
Ta
25
CI
Qu
Pe
PE
7" @ 3,445'
TD @ 3,445'

[illegible]

Updated: December 20, 2024 by Ian Petersen

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oecd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 429055

CONDITIONS

Operator: J R OIL, LTD. CO. P.O. Box 53657 Lubbock, TX 79453	OGRID: 256073
	Action Number: 429055
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Clean Location in accordance with 19.15.25.10 NMAC.	3/25/2025
gcordero	Submit C-103Q within one year of plugging.	3/25/2025