

Form 3160-3  
(June 2015)FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No.  6. If Indian, Allottee or Tribe Name  7. If Unit or CA Agreement, Name and No.  8. Lease Name and Well No.
2. Name of Operator		9. API Well No. <div style="color: red; text-align: center;">30-045-38451</div>
3a. Address	3b. Phone No. (include area code)	10. Field and Pool, or Exploratory
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		11. Sec., T. R. M. or Blk. and Survey or Area
14. Distance in miles and direction from nearest town or post office*		12. County or Parish
13. State		
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No of acres in lease	17. Spacing Unit dedicated to this well
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth	20. BLM/BIA Bond No. in file
21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |   |   |
|---|---|
| 1. Well plat certified by a registered surveyor.<br>2. A Drilling Plan.<br>3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).<br>5. Operator certification.<br>6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature	Name (Printed/Typed)	Date
Title		
Approved by (Signature)	Name (Printed/Typed)	Date
Title		
Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
 Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

\*(Instructions on page 2)

## INSTRUCTIONS

**GENERAL:** This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

**ITEM I:** If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

**ITEM 4:** Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

**ITEM 14:** Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

**ITEMS 15 AND 18:** If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

**ITEM 22:** Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

**ITEM 24:** If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48( d) provide that you be furnished the following information in connection with information required by this application.

**AUTHORITY:** 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

**PRINCIPAL PURPOSES:** The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

**ROUTINE USE:** Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

**EFFECT OF NOT PROVIDING INFORMATION:** Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

## Additional Operator Remarks

### Location of Well

0. SHL: NESW / 1363 FSL / 2468 FWL / TWSP: 32N / RANGE: 07W / SECTION: 18 / LAT: 36.977638 / LONG: -107.609755 ( TVD: 0 feet, MD: 0 feet )

PPP: LOT 6 / 1010 FNL / 1020 FWL / TWSP: 32N / RANGE: 07W / SECTION: 19 / LAT: 36.971621 / LONG: -107.614707 ( TVD: 3055 feet, MD: 3638 feet )

PPP: SESW / 397 FSL / 1406 FWL / TWSP: 32N / RANGE: 07W / SECTION: 18 / LAT: 36.975351 / LONG: -107.613385 ( TVD: 3055 feet, MD: 3638 feet )

BHL: LOT 14 / 453 FSL / 2743 FWL / TWSP: 32N / RANGE: 07W / SECTION: 19 / LAT: 36.960762 / LONG: -107.608916 ( TVD: 3055 feet, MD: 9633 feet )

### BLM Point of Contact

Name: CHRISTOPHER P WENMAN

Title: Natural Resource Specialist

Phone: (505) 564-7727

Email: cwenman@blm.gov

### **Review and Appeal Rights**

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

### Conditions of Approval

Operator:	Hilcorp Energy Company
Well Names:	San Juan 32-7 Unit 243H
Legal Location:	T32N R7W Section 18 NESW
NEPA Log Number:	DOI-BLM-NM-F010-2024-0069-EA
Inspection Date:	September 27, 2018
Lease Number:	NMNM078423X

The following conditions of approval will apply to San Juan 32-7 Unit 243H Well and Pad Expansion, and other associated facilities, unless a particular Surface Managing Agency or private surface owner has supplied to Bureau of Land Management and the operator a contradictory environmental stipulation. The failure of the operator to comply with these requirements may result in an assessment or civil penalties pursuant to 43 CFR 3163.1 or 3163.2.

1. **Disclaimers:** BLM's approval of the APD does not relieve the lessee and operator from obtaining any other authorizations that may be required by the BIA, Navajo Tribe, State, or other jurisdictional entities.
2. **Copy of Plans:** A complete copy of the APD package, including Surface Use Plan of Operations, Bare Soil Reclamation Plan, Plan of Development (if required), Conditions of Approval, and Cultural Resource Record of Review shall be at the project area at all times and available to all persons.
3. **Surface Owner:** Any agreement between the operator and fee land owner will take precedence over BLM surface stipulations unless (In reference to 43 CFR Part 3160) 1) BLM determines that the operator's actions will affect adjacent Federal or Indian surface, or 2) the operator does not maintain well area and lease premises in a workmanlike manner with due regard for safety, conservation and appearance, or 3) no such agreement exists, or 4) in the event of well abandonment, minimal Federal restoration requirements will be required. If surface owner changes any stipulations in the conditions of approval, the operator will contact the BLM authorized officer before implementing surface owner stipulation.
4. **Review of NEPA documents:** It is the responsibility of the operator to follow all the design features, best management practices, and mitigation measures as contained in the Environmental Assessment ePlanning DOI-BLM-NM-F010-2024-0069-EA, which contains additional design features and best management practices that must be followed. Copies of the EA, Decision Record, and Finding of No Significant Impact may be obtained from the BLM FFO public room, or online at: [eplanning.blm.gov](http://eplanning.blm.gov).
5. **Best Management Practices (BMPs):** Farmington Field Office established environmental Best Management Practices (BMP's) will be followed during construction and reclamation of well site pads, access roads, pipeline ties, facility placement or any other surface disturbing activity associated with this project. Bureau wide standard BMP's are found in the Gold Book, Fourth Edition-Revised 2007. Farmington Field

Office BMP's are integrated into the Environmental Assessment, Surface Use Plan of Operations, Bare Soil Reclamation Plan, and COAs.

### **Construction, Production, Facilities, Reclamation & Maintenance**

6. **Construction & Reclamation Notification:** The operator or their contractor will contact the Bureau of Land Management, Farmington Field Office Environmental Protection Staff (505) 564-7600 or by email, at least 48 hours prior to any construction or reclamation on this project.
7. **Grazing Permittee Notification and Concerns:** The operator will notify the grazing lease operator(s) at least ten business days prior to beginning any construction activity to ensure there will be no conflicts between construction activities and livestock grazing operations. The operator is not obligated to cease or delay construction unless directed by the Authorized Officer (AO). Any range improvement (fences, pipelines, ponds, etc.) disturbed by construction activities will be repaired immediately following construction and will be repaired to the condition the improvement was in prior to disturbance. Cattle guards will be installed to replace any livestock fencing or gates removed for road construction.
8. **Cattleguards:** If applicable, cattle guards shall have grid identification marks welded into them indicating ownership, well name and number associated with the cattle guard, and foundation designs. Construction shall meet the American Association of State Highway and Transportation Officials (AASHTO) load rating H-20, although AASHTO U-80 rated grids shall be required where heavy loads, (exceeding H-20 loading) are anticipated. (See BLM standard drawings for cattle guards). Cattle guard grid width shall not be less than eight feet and length of not less than 14 feet. A wire gate with a minimum width of 16 feet will be provided on one side of the cattle guard.
9. **Cutting of Fences:** All cut fences are to be tied to H-braces prior to cutting. The opening will be protected as necessary during construction to prevent escape of livestock. A temporary closure will be installed on all cut fences the day the fence is cut. A sixteen-foot gate will be installed adjacent to the cattleguard. The holder shall minimize disturbance to existing fences and other improvements on public land. Holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them.
10. **Crossing Existing Improvements:** Prior to crossing, using or paralleling any improvement on public land, the operator shall contact the owner of the improvement to obtain mitigating measures to prevent damage to the improvements.
11. **Production Facilities:** Design and layout of facilities will be deferred until an onsite with BLM-FFO surface protection staff is conducted to determine the best location. Enduring Resources or their contractor will contact the Bureau of Land Management, Farmington Field Office, Surface, and Environmental Protection Staff (505) 564-7600 to schedule a facility layout onsite. Production equipment [including any facilities associated with pipeline construction] shall be placed on location as not to interfere with

reclaiming the cut and fill slopes to their proper ratio. If equipment is found to interfere with the proper reclamation of the slope, the company will be required to move the equipment so proper re-contouring can occur.

12. **Staking:** The holder shall place slope stakes, culvert location and grade stakes, and other construction control stakes as deemed necessary by the authorized officer to ensure construction in accordance with the plan of development. If stakes are disturbed, they shall be replaced before proceeding with construction.
13. **Weather:** No construction or routine maintenance activities shall be performed during periods when the soil is too wet to adequately support construction equipment. If such equipment creates ruts more than 6 inches deep, the soil shall be deemed too wet.
14. **Stockpile of Soil:** The top 6 inches of soil material will be stripped and stockpiled in the construction zones around the pad [construction zones may be restricted or deleted to provide resource avoidance]. The stockpiled soil will be free of brush and tree limbs, trunks, and roots. The stockpiled soil material will be spread on the reclaimed portions of the pad [including the reserve pit, cut and fill slopes] prior to re-seeding. Spreading shall not be done when the ground or topsoil is frozen or wet.
15. **Painting of Equipment:** Within 90 days of installation, all above ground structures not subject to safety requirements shall be painted by the Holder to blend with the natural color of the landscape. A reflective material may be used to reduce hazards that may occur when such structures are near roads. Otherwise, the paint use shall be a non-glare, non-reflective, non-chalking color of Federal 595a-34127 (Juniper Green).
16. **Storage Tanks:** All open top permanent production or storage tanks regardless of diameter made of fiberglass, steel, or other material used for the containment of oil, condensate, produced water and or other production waste shall be screened, netted, or otherwise covered to protect migratory birds and other wildlife from access.
17. **Compressors:** Compressor units on this well location not equipped with a drip pan for containment of fluids shall be lined with an impervious material at least 8 mils thick and a 12-inch berm. The compressor will be painted to match the well facilities. Any variance to this will be approved by the Authorized Officer (AO). Noise mitigation may be required at the time of compressor installation.
18. **Acquisition of Water:** Water acquired to construct, produce, and maintain actions authorized by this permit to drill must be acquired from permitted water sources, or water authorized for use by the New Mexico Oil Conservation Division (OCD). Upon request, the Authorized Officer shall be provided with documentation of water sources.
19. **New & Existing Access:** All sections of the proposed access road associated with this permit shall be sited, designed, constructed, upgraded and maintained utilizing standards, requirements, guidelines and instructions specified in BLM Manual 9113 "Roads", BLM Manual 9113-1 "Roads Design Handbook", BLM Manual 9113-2 "Roads National Inventory and Condition Assessment Guidance & Instructions Handbook" and Surface Operations and Guidelines for Oil and Gas Exploration and Development "The Gold

Book”.

20. **Driving Surface Area:** All activities associated within the construction, operation, maintenance, and abandonment of the well location is limited to areas approved in the APD or ROW permit. During the production of the well, vehicular traffic is limited to the daily driving surface area established during interim reclamation construction operations. This area typically forms a keyhole or teardrop driving surface from which all production facilities may be serviced or inspected. A v-type ditch will be constructed on the outside of the driving surface to further define the driving surface and to deter vehicular traffic from entering onto the interim reclamation areas.
21. **Berms:** Berms or firewalls will be constructed around all storage facilities sufficient in size to contain the storage capacity of 110% of the largest tank, or 110% of the combined capacity of tanks if a rupture could drain more than one tank. Berm walls will be compacted with appropriate equipment to assure proper construction. Metal containment barriers, used for secondary containment, will be properly installed, per the manufacturer directions.
22. **Contouring of Cut and Fill Slopes:** The interim cut and fill slope grade shall be as close to the original contour as possible. To obtain this ratio, pits and slopes shall be back sloped into the pad during interim reclamation. Only subsurface soil and material shall be utilized in the contouring of the cut and fill slopes. Under no circumstances shall topsoil be utilized as substrate material for contouring of cut and fill slopes.
23. **Maintenance:** In order to perform subsequent well operations, right-of-way (ROW) operations, or install new/additional equipment, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is promptly repaired and reclaimed following use. Where vehicular travel has occurred as a “convenience” and interim reclamation/vegetation has been compromised, immediate remediation of the affected areas is required. Additionally, where erosion has occurred and compromised the reclamation of the well location, the affected area must be promptly remediated so that future erosion is prevented, and the landform is stabilized.
24. **Non-Permitted Disturbance:** Construction maintenance or any other activity outside the areas permitted by the APO will require additional approval and may require a new cultural survey and clearance.
25. **“Hotwork” and Construction Affecting Fire Safety:** The holder or its contractors will notify the BLM of any fires and comply with all rules and regulations administered by the BLM concerning the use, prevention and suppression of fires on federal lands, including any fire prevention orders that may be in effect at the time of the permitted activity. The holder or its contractors may be held liable for the cost of fire suppression, stabilization and rehabilitation. In the event of a fire, personal safety will be the first priority of the holder or its contractors. The holder or its contractors shall:
  1. Operate all internal and external combustion engines (including off-highway vehicles, chainsaws, generators, heavy equipment, etc.) with a qualified spark arrester. Qualified spark arresters are maintained and not modified, and meet the Society of

Automotive Engineers (SAE) Recommended Practices J335 or J350. Refer to 43 CFR §8343.1.

- a. Refueling of any combustible engine equipment must be minimum of 3 meters away from any ignition source (open flame, smoking, etc.).*
2. Maintain and clean all equipment regularly to remove flammable debris buildup and prevent fluid leaks that can lead to ignitions.
3. Carry at least one shovel or wildland fire hand tool (combi, Pulaski, McLeod) per person working, minimum 5 gallons of water, and a fire extinguisher rated at a minimum as ABC - 10 pound on each piece of equipment and each vehicle.
4. When conducting "hotwork" such as, but not limited to welding, grinding, cutting, spark-producing work with metal, work that creates hot material or slag; choose an area large enough to contain all hot material that is naturally free of all flammable vegetation or remove the flammable vegetation in a manner compliant with the permitted activity. If adequate clearance cannot be made, wet an area large enough to contain all hot material prior to the activity and periodically throughout the activity to reduce the risk of wildfire ignition. Regardless of clearance, maintain readiness to respond to an ignition at all times. In addition, keep one hand tool per person and at least one fire extinguisher ready, minimum, as specified earlier (#3) during this activity.
5. Keep apprised of current and forecasted weather at <https://www.weather.gov/abq/forecasts-fireweather-links> and fire conditions at [www.wfas.net](http://www.wfas.net) and take additional fire precautions when fire danger is rated High or greater. Red Flag Warnings are issued by the National Weather Service when fire conditions are most dangerous, and ignitions escape control quickly. Extra precautions are required during these warnings such as additional water, designate a fire watch/patrol and tools. If work is being conducted in an area that is not clear of vegetation within 50 feet of work area; then, when fire danger is rated High or greater and 1. There is a predicted Red Flag warning for your area or 2. If winds are predicted to be greater than 10 mph, stop all hotwork activities for the day at 10 am.
6. In the event of an ignition, initiate fire suppression actions in the work area to prevent fire spread to or on federally administered lands. If a fire spreads beyond the capability of workers with the stipulated tools, all will cease fire suppression action and leave the area immediately via pre-identified escape routes.
7. Call **911** or the **Taos Interagency Fire Dispatch Center (575-758-6208)** immediately of the location and status of any fire.

#### AND

Notify the respective BLM field office for which the permit or contract was issued immediately of the incident.

**Farmington Field Office at 505-564-7600**

**Taos Field Office at 575-758-8851**

#### Noxious Weeds

26. Inventory the proposed site for the presence of noxious and invasive weeds. Noxious weeds are those listed on the New Mexico Noxious Weed List and USDA's Federal Noxious Weed List. The New Mexico Noxious Weed List or USDA's Noxious Weed

List can be updated at any time and should be regularly check for any changes. Invasive species may or may not be listed as a noxious weed but have been identified to likely cause economic or environmental harm or harm to human health. The following noxious weeds have been identified as occurring on lands within the boundaries of the Farmington Field Office (FFO). There are numerous invasive species on the FFO such as Russian thistle (*Salsola spp.*) and field bindweed (*Convolvulus arvensis*).

Russian Knapweed ( <i>Centaurea repens</i> )	Musk Thistle ( <i>Carduus nutans</i> )
Bull Thistle ( <i>Cirsium vulgare</i> )	Canada Thistle ( <i>Cirsium arvense</i> )
Scotch Thistle ( <i>Onopordum acanthium</i> )	Hoary Cress ( <i>Cardaria draba</i> )
Perennial Pepperweed ( <i>Lepidium latifolium</i> )	Halogeton ( <i>Halogeton glomeratus</i> )
Spotted Knapweed ( <i>Centaurea maculosa</i> )	Dalmation Toadflax ( <i>Linaria genistifolia</i> )
Yellow Toadflax ( <i>Linaria vulgaris</i> )	Camelthorn ( <i>Alhagi pseudalhagi</i> )
African Rue ( <i>Peganum harmala</i> )	Salt Cedar ( <i>Tamarix spp.</i> )
Diffuse Knapweed ( <i>Centaurea diffusa</i> )	Leafy Spurge ( <i>Euphorbia esula</i> )

- a. Identified weeds will be treated prior to new surface disturbance if determined by the FFO Noxious Weed Coordinator. A Pesticide Use Proposal (PUP) must be submitted to and approved by the FFO Noxious Weed Coordinator prior to application of pesticide. The FFO Noxious Weeds Coordinator (505-564-7600) can provide assistance in the development of the PUP.
- b. Vehicles and equipment should be inspected and cleaned prior to coming onto the work site. This is especially important on vehicles from out of state or if coming from a weed-infested site.
- c. Construction equipment should be inspected and cleaned prior to coming onto the work site. This is especially important on vehicles from out of state or if coming from a weed-infested site.
- d. Fill dirt or gravel may be needed for excavation, road construction/repair, or for spill remediation. If fill dirt or gravel will be required, the source shall be noxious weed free and approved by the FFO Noxious Weed Coordinator.
- e. The site shall be monitored for the life of the project for the presence of noxious weeds (includes maintenance and construction activities). If weeds are found the FFO Coordinator shall be notified at (505) 564-7600 and provided with a Weed Management Plan and if necessary, a Pesticide Use Proposal (PUP) . The FFO Coordinator can provide assistance developing the Weed Management Plan and/or the Pesticide Use Proposal.
- f. Only pesticides authorized for use on BLM lands would be used and applied by a licensed pesticide applicator. The use of pesticides would comply with federal and state laws and used only in accordance with their registered use and limitations. (Company Name)'s weed-control contractor would contact the BLM-FFO prior to using these chemicals.
- g. Noxious/invasive weed treatments must be reported to the FFO Noxious Weed Coordinator. A Pesticide Application Record (PAR) is required to report any mechanical, chemical, biological or cultural treatments used to eradicate, and/or control noxious or invasive species. Reporting will be required quarterly and annually or per request from the FFO Noxious Weed Coordinator.

27. **Bare ground vegetation trim-out:** If bare ground vegetation treatment (trim-out) is desired around facility structures, the operator will submit a bare ground/trim-out design included in their Surface Use Plan of Operations (SUPO). The design will address vegetation safety concerns of the operator and BLM while minimizing impacts to interim reclamation efforts. The design must include what structures to be treated and buffer distances of trim-out. Pesticide use for vegetation control around anchor structures is not approved. If pesticides are used for bare ground trim-out, the trim-out will not exceed three feet from the edge of any eligible permanent structure (i.e., well heads, fences, tanks). Additional distance/areas may be requested and must be approved by the FFO authorized officer. The additional information below must also be provided to the FFO:
- a. Pesticide use for trim out will require a Pesticide Use Proposal (PUP). A PUP is required **prior** to any treatment and must be approved by the FFO Noxious Weed Coordinator. Only pesticides authorized for use on BLM lands would be used and applied by a licensed pesticide applicator. The use of pesticides would comply with federal and state laws and used only in accordance with their registered use and limitations. Enduring Resources' weed-control contractor would contact the BLM-FFO prior to using these chemicals and provide Pesticide Use Reports (PURs) post treatment.
  - b. A Pesticide Use Report (PUR) or a Biological Use Report (BUR) is required to report any chemical, or biological treatments used to eradicate, or control vegetation on site. Reporting will be required quarterly and annually or per request from the FFO Noxious Weed Coordinator.

### **Paleontology**

28. **Paleontology:** Any paleontological resource discovered by the Operator, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant scientific values. The Holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the Holder.

### **Wildlife Resources**

29. **Wildlife:** The project is within the Rattlesnake Canyon Wildlife SDA. Hilcorp's APDs include a commitment to a closure period beginning December 1 and ending March 31 of each year. This closure period shall apply to construction, drilling, completions, and reclamation, but not standard or routine well maintenance.
30. **Hazards:** Wildlife hazards associated with the proposed project would be fenced, covered, and/or contained in storage tanks, as necessary.
31. **Nesting:** If a bird nest containing eggs or young is encountered in the path of construction the operator will cease construction and consult with BLM to determine appropriate actions.

32. **Threatened, Endangered or Sensitive Species:** If, in operations the operator/holder discovers any Threatened, Endangered, or Sensitive species, work in the vicinity of the discovery will be suspended and the discovery promptly reported to the BLM-FFO T&E specialist at (505) 564-7600. The BLM-FFO will then specify what action is to be taken. Failure to notify the BLM-FFO about a discovery may result in civil or criminal penalties in accordance with The Endangered Species Act (as amended).

### **Soil, Air, Water**

33. **Land Farming:** No excavation, remediation or closure activities will be authorized without prior approval, on any federal or Indian mineral estate, federal surface, or federal ROW. A Sundry Notice (DOI, BLM Form 3160-5) must be submitted with an explanation of the remediation or closure plan for on-lease actions.
34. **Waste Disposal:** Waste materials produced during all phases of operation will be disposed of promptly in an approved manner so it will not impact the air, soil, water, vegetation or animals. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, oil drums, petroleum products, ashes and equipment. All liquid waste, completion fluids and drilling products associated with oil and gas operations will be removed and deposited in an approved disposal site. Portable toilets will remain on site throughout well pad construction, drilling and reclamation. All fluids (i.e. scrubber cleaners) used during washing of production equipment, including compressors, will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife. Construction sites shall be maintained in a sanitary condition at all times; waste materials at those sites shall be disposed of promptly at an appropriate waste disposal site. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, oil drums, petroleum products, ashes and equipment.

### **Cultural Resources**

35. **Discovery of Cultural Resources in the Absence of Monitoring:** If, in its operations, operator/holder discovers any previously unidentified historic or prehistoric cultural resources, then work in the vicinity of the discovery will be suspended and the discovery promptly reported to BLM Field Manager. BLM will then specify what action is to be taken. If there is an approved "discovery plan" in place for the project, then the plan will be executed. In the absence of an approved plan, the BLM will evaluate the significance of the discovery in accordance with 36 CFR Section 800.13, in consultation with the appropriate State or Tribal Historic Preservation Officer(s) and Indian tribe(s) that might attach religious and cultural significance to the affected property, or in accordance with an approved program alternative. Minor recordation, stabilization, or data recovery may be performed by BLM or a third party acting on its behalf, such as a permitted cultural resources consultant. If warranted, more extensive archaeological or alternative mitigation, likely implemented by a permitted cultural resources consultant, may be required of the operator/holder prior to allowing the project to proceed. Further damage to significant cultural resources will not be allowed until any mitigations determined appropriate through the agency's Section 106 consultation are completed. Failure to notify the BLM about a discovery may result in civil or criminal penalties in accordance with the Archeological Resources Protection Act (ARPA) of 1979, as amended, the Native American Graves Protection and Repatriation Act (NAGPRA) of 1990, as amended, and other applicable laws.
36. **Discovery of Cultural Resources during Monitoring:** If monitoring confirms the presence of

previously unidentified historic or prehistoric cultural resources, then work in the vicinity of the discovery will be suspended and the monitor will promptly report the discovery to the BLM Field Manager. BLM will then specify what action is to be taken. If there is an approved "discovery plan" in place for the project, then the plan will be executed. In the absence of an approved plan, the BLM will evaluate the significance of the discovery in accordance with 36 CFR Section 800.13, in consultation with the appropriate State or Tribal Historic Preservation Officer(s) and Indian tribe(s) that might attach religious and cultural significance to the affected property, or in accordance with an approved program alternative. Minor recordation, stabilization, or data recovery may be performed by BLM or a third party acting on its behalf, such as a permitted cultural resources consultant. If warranted, more extensive archaeological or alternative mitigation, likely implemented by a permitted cultural resources consultant, may be required of the operator/holder prior to allowing the project to proceed. Further damage to significant cultural resources will not be allowed until any mitigations determined appropriate through the agency's Section 106 consultation are completed.

37. **Damage to Sites:** If, in its operations, operator/holder damages, or is found to have damaged any previously documented or undocumented historic or prehistoric cultural resources, excluding "discoveries" as noted above, the operator/holder agrees at his/her expense to have a permitted cultural resources consultant prepare a BLM approved damage assessment and/or data recovery plan. The operator/holder agrees at his/her expense to implement a mitigation that the agency finds appropriate given the significance of the site, which the agency determines in consultation with the appropriate State or Tribal Historic Preservation Officer(s) and Indian tribe(s) that might attach religious and cultural significance to the affected property. This mitigation may entail execution of the data recovery plan by a permitted cultural resources consultant and/or alternative mitigations. Damage to cultural resources may result in civil or criminal penalties in accordance with the Archeological Resources Protection Act (ARPA) of 1979, as amended, the Native American Graves Protection and Repatriation Act (NAGPRA) of 1990, as amended, and other applicable laws.
38. **Employee Education:** All employees of the project, including the Project Sponsor and its contractors and sub-contractors will be informed and educated that cultural sites are to be avoided by all personnel, personal vehicles and company equipment. This includes personnel associated with construction, use, maintenance and abandonment of the well pad, well facilities, access and pipeline. They will also be notified that it is illegal to collect, damage, or disturb historic or prehistoric cultural resources, and that such activities are punishable by criminal and or administrative penalties under the provisions of the ARPA (16 U.S.C. 470aa-mm), NAGPRA (25 U.S.C. 3001-3013), and other laws, as applicable (for example, NM Stat. § 18-6-9 through § 18-6-11.2, as amended, and NM Stat. § 30-12-12, as amended).

**See additional cultural resource protection requirements below.**



BLM Report Number: 2019(I)003F  
USGS Map: Burnt Mesa NM  
Activity Code: 1310  
NMCRIS No: 141515

**CULTURAL RESOURCE RECORD OF REVIEW**  
 BUREAU OF LAND MANAGEMENT  
 FARMINGTON FIELD OFFICE

**1. Description of Report/Project:**

Project Name: SJ 32-7 Unit Number 243H Well Pad.

Project Sponsor: Hilcorp Energy.

Arch. Firm & Report No.: La Plata Archaeological Consultants

LAC Report No. 2018-1p.

Location: T32N R7W Section 18.

Well Footages: 1,363' FSL; 2,468' FWL

Split Estate: No.

Project Dimensions: 250 ft x 225 ft – well pad (350 ft x 325 ft w/ 50 ft construction zone).

Sites Located: None.

Determination: No Effect to Historic Properties.

**2. Field Check:** No.

**3. Cultural ACEC:** No.

**4. Sensitive Cultural Area:** No.

**5. Recommendation:** *PROCEED WITH ACTION:* X *STIPULATIONS ATTACHED:*     

**6. Reviewer /Archaeologist:** Kim Adams **Date:** 10/10/2018

Report Summary	BLM	Other	Total
Acres Inventoried	6.6	0	6.6
Sites Recorded	0	0	0
Prev. Recorded Sites	0	0	0
Sites Avoided	0	0	0
Sites Treated	0	0	0

**Discovery of Cultural Resources in the Presence or Absence of Monitoring:** If any previously unidentified historic or prehistoric cultural resources are discovered during construction or project operations, work in the vicinity of the discovery will be suspended and the discovery will promptly be reported to the BLM Field Manager.

**Note:** If there are questions about these stipulations, contact Kim Adams (BLM) at 505.564.7683 or [kadams@blm.gov](mailto:kadams@blm.gov). Or Erik Simpson (BLM) at 505.564.7678 or [dsimpson@blm.gov](mailto:dsimpson@blm.gov).



## United States Department of the Interior

BUREAU OF LAND MANAGEMENT  
Farmington District Office  
6251 College Blvd, Suite A  
Farmington, New Mexico 87402



In Reply Refer To:  
3162.3-1(NMF0110)

**\*HILCORP ENERGY COMPANY**

**SAN JUAN 32-7 UNIT 243H**

Lease: NMSF0078460

Agreement: NMNM078423X

SH: NE $\frac{1}{4}$  SW $\frac{1}{4}$  Section 18, T. 32N., R. 07W.

BH: Lot 14 Section 19, T. 32N., R. 07W.

San Juan County, New Mexico

**\*Above Data Required on Well Sign**

### **GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL AND INDIAN LEASES**

The following special requirements apply and are effective when checked:

- A. ☒ Note all surface/drilling conditions of approval attached.
- B. ☒ The required wait on cement (WOC) time will be a minimum of 500 psi compressive strength at 60 degrees. Blowout preventor (BOP) nipple-up operations may then be initiated
- C. ☒ Test all casing strings below the conductor casing to .22 psi/ft. of casing string length or 1500 psi, whichever is greater, but not to exceed 70% of the minimum internal yield (burst) for a minimum of 30 minutes. If pressure declines more than 10 percent in 30 minutes, corrective action shall be taken.
- D. ☐ Communitization Agreement covering the acreage dedicated to this well must be filed for approval with the Bureau of Land Management, New Mexico State Office, Reservoir Management Group, 301 Dinosaur Trail, Santa Fe, New Mexico 87508.  
The effective date of the agreement must be **prior** to any sales.
- E. ☐ The use of co-flex hose is authorized contingent upon the following:
  1. From the BOP to the choke manifold: the co-flex hose must be hobbled on both ends and saddle to prevent whip.
  2. From the choke manifold to the discharge tank: the co-flex hoses must be as straight as practical, hobbled on both ends and anchored to prevent whip.
  3. The co-flex hose pressure rating must be at least commensurate with approved BOPE.

**INTERIOR REGION 7 • UPPER COLORADO BASIN**

COLORADO, NEW MEXICO, UTAH, WYOMING

## **I. GENERAL**

- A. Full compliance with all applicable laws and regulations, with the approved Permit to drill, and with the approved Surface Use and Operations Plan is required. Lessees and/or operators are fully accountable for the actions of their contractors and subcontractors. Failure to comply with these requirements and the filing of required reports will result in strict enforcement pursuant to 43 CFR 3163.1 or 3163.2.
- B. Each well shall have a well sign in legible condition from spud date to final abandonment. The sign should show the operator's name, lease serial number, or unit name, well number, location of the well, and whether lease is Tribal or Allotted, (See 43 CFR 3162.6(b)).
- C. A complete copy of the approved Application for Permit to Drill, along with any conditions of approval, shall be available to authorized personnel at the drill site whenever active drilling operations are under way.
- D. For Wildcat wells only, a drilling operations progress report is to be submitted, to the BLM-Field Office, weekly from the spud date until the well is completed and the Well Completion Report is filed. The report should be on 8-1/2 x 11 inch paper, and each page should identify the well by; operator's name, well number, location and lease number.
- E. As soon as practical, notice is required of all blowouts, fires and accidents involving life-threatening injuries or loss of life. (See NTL-3A).
- F. BOP equipment (except the annular preventer) shall be tested utilizing a test plug to full working pressure for 10 minutes. No bleed-off of pressure is acceptable. (See 43 CFR 3172.6(b)(9)(ii)).
- G. The operator shall have sufficient weighting materials and lost circulation materials on location in the event of a pressure kick or in the event of lost circulation. (See 43 CFR 3172.8(a)).
- H. The flare line(s) discharge shall be located not less than 100 feet from the well head, having straight lines unless turns are targeted with running tees, and shall be positioned downwind of the prevailing wind direction and shall be anchored. The flare system shall have an effective method for ignition. Where noncombustible gas is likely or expected to be vented, the system shall be provided supplemental fuel for ignition and to maintain a continuous flare. (See 43 CFR 3172.8(b)(7)).
- I. Prior approval by the BLM-Authorized Office (Drilling and Production Section) is required for variance from the approved drilling program and before commencing plugging operations, plug back work, casing repair work, corrective cementing operations, or suspending drilling operations indefinitely. Emergency approval may be obtained orally, but such approval is contingent upon filing of a Notice of Intent sundry within three business days. **Any changes to the approved plan or any questions regarding drilling operations should be directed to BLM during regular business hours at 505-564-7600. Emergency program changes after hours should be directed to Virgil Lucero at 505-793-1836.**
- J. **The Inspection and Enforcement Section (I&E), phone number (505-564-7750) is to be notified at least 24 hours in advance of BOP test, spudding, cementing, or plugging operations so that a BLM representative may witness the operations.**
- K. Unless drilling operations are commenced within three years according to 43 CFR 3171.14, approval of the Application for Permit to Drill will expire. No extensions will be granted.

- L. From the time drilling operations are initiated and until drilling operations are completed, a member of the drilling crew or the tool pusher shall maintain rig surveillance at all times, unless the well is secured with blowout preventers or cement plugs.
- M. If for any reason, drilling operations are suspended for more than 90 days, a written notice must be provided to this office outlining your plans for this well.
- N. **Commingling:** No production (oil, gas, and water) from the subject well should start until Sundry Notices (if necessary) granting variances from applicable regulations as related to commingling and off-lease measurement are approved by this office. (See 43 CFR 3173.14)

## **II. REPORTING REQUIREMENTS**

- A. For reporting purposes, all well Sundry notices, well completion and other well actions shall be referenced by the appropriate lease, communitization agreement and/or unit agreement numbers.
- B. The following reports shall be filed with the BLM-Authorized Officer online through AFMSS 2 within 30 days after the work is completed.
  - 1. Provide complete information concerning.
    - a. Setting of each string of casing. Show size and depth of hole, grade and weight of casing, depth set, depth of all cementing tools that are used, amount (in cubic feet) and types of cement used, whether cement circulated to surface and all cement tops in the casing annulus, casing test method and results, and the date work was done. Show spud date on first report submitted.
    - b. Intervals tested, perforated (include size, number and location of perforations), acidized, or fractured; and results obtained. Provide date work was done on well completion report and completion sundry notice.
    - c. Subsequent Report of Abandonment, show the way the well was plugged, including depths where casing was cut and pulled, intervals (by depths) where cement plugs were replaced, and dates of the operations.
  - 2. Well Completion Report will be submitted with 30 days after well has been completed.
    - a. Initial Bottom Hole Pressure (BHP) for the producing formations. Show the BHP on the completion report. The pressure may be: 1) measured with a bottom hole bomb, or; 2) calculated based on shut in surface pressures (minimum seven day buildup) and fluid level shot.
  - 3. Submit a cement evaluation log if cement is not circulated to surface.
- C. Production Startup Notification is required no later than the 5<sup>th</sup> business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site or resumes production in the case of a well which has been off production for more than 90 days. The operator shall notify the Authorized Officer by letter or Sundry Notice, Form 3160-5, or orally to be followed by a letter or Sundry Notice, of the date on which such production has begun or resumed. CFR 43 3162.4-1(c).

### **III. DRILLER'S LOG**

The following shall be entered in the daily driller's log: 1) Blowout preventer pressures tests, including test pressures and results, 2) Blowout preventer tests for proper functioning, 3) Blowout prevention drills conducted, 4) Casing run, including size, grade, weight, and depth set, 5) How pipe was cemented, including amount of cement, type, whether cement circulated to surface, location of cementing tools, etc., 6) Waiting on cement time for each casing string, 7) Casing pressure tests after cementing, including test pressure and results, and 8) Estimated amounts of oil and gas recovered and/or produced during drill stem test.

### **IV. GAS FLARING**

Gas produced from this well may not be vented or flared beyond an initial, authorized test period of \*  Days, 20 MMCF following its (completion)(recompletion), or flowback has been routed to the production separator, whichever first occurs, without the prior, written approval of the authorized officer in accordance with 43 CFR 3179.81. Should gas be vented or flared without approval beyond the test period authorized above, you may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted. You shall be required to compensate the lessor for the portion of the gas vented or flared without approval which is determined to have been avoidably lost.

*\*30 days, unless a longer test period is specifically approved by the authorized officer. The 30-day period will commence upon the beginning of flowback following completion or recompletion.*

### **V. SAFETY**

- A. All rig heating stoves are to be of the explosion-proof type.
- B. Rig safety lines are to be installed.
- C. Hard hats and other Personal Protective Equipment (PPE) must be utilized.

### **VI. CHANGE OF PLANS OR ABANDONMENT**

- A. Any changes of plans required to mitigate unanticipated conditions encountered during drilling operations, will require approval as set forth in Section 1.I.
- B. If the well is dry, it is to be plugged in accordance with 43 CFR 3162.3-4, approval of the proposed plugging program is required as set forth in Section 1.I. The report should show the total depth reached, the reason for plugging, and the proposed intervals, by depths, where cement plugs are to be placed, type of plugging mud, etc. A Subsequent Report of Abandonment is required as set forth in Section II.B.1c.
- C. Unless a well has been properly cased and cemented, or properly plugged, the drilling rig must not be moved from the drill site without prior approval from the BLM-Authorized Officer.

**VII. PHONE NUMBERS**

- A. For BOPE tests, cementing, and plugging operations the phone number is 505-564-7750 and must be called 24 hours in advance in order that a BLM representative may witness the operations.
- B. Emergency program changes after hours contact:

**Virgil Lucero (505) 793-1836**  
**Kenneth Rennick (505) 564-7742**  
**Matthew Kade (505) 564-7736**

1625 N. French Drive, Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720District II  
811 S. First Street, Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170District IV  
1220 S. St. Francis Drive, Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462State of New Mexico  
Energy, Minerals & Natural Resources DepartmentForm O-022  
Revised August 1, 2011Submit one copy to  
Appropriate District OfficeOIL CONSERVATION DIVISION  
1220 South St. Francis Drive  
Santa Fe, NM 87505☐ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number	<sup>2</sup> Pool Code 71629	<sup>3</sup> Pool Name BASIN FRUITLAND COAL
<sup>4</sup> Property Code	<sup>5</sup> Property Name SAN JUAN 32-7 UNIT	<sup>6</sup> Well Number 243H
<sup>7</sup> GRID No. 372171	<sup>8</sup> Operator Name HILCORP ENERGY COMPANY	<sup>9</sup> Elevation 6361'


<sup>10</sup> Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	18	32N	7W		1363	SOUTH	2468	WEST	SAN JUAN

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	19	32N	7W	14	453	SOUTH	2743	WEST	SAN JUAN

<sup>12</sup> Dedicated Acres 487.72	SW/4 - Section 18 W/2 - Section 19	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
---	---------------------------------------	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED  
TO THIS COMPLETION UNTIL ALL  
INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN  
APPROVED BY THE DIVISIONSURFACE LOCATION (A)  
1363' FSL 2468' FWL  
SEC 18, T32N, R7W  
LAT: 36.977634°N  
LONG: -107.609144°W  
DATUM: NAD1927LAT: 36.977638°N  
LONG: -107.609755°W  
DATUM: NAD1983551°42.9'W  
1348.0'LANDING POINT (B)  
397' FSL 1406' FWL  
SEC 18, T32N, R7W  
LAT: 36.975347°N  
LONG: -107.612773°W  
DATUM: NAD1927LAT: 36.975351°N  
LONG: -107.613385°W  
DATUM: NAD1983515°44.6'W  
1412.0'ANGLE POINT (C)  
1010' FSL 1020' FWL  
SEC 19, T32N, R7W  
LAT: 36.971617°N  
LONG: -107.614096°W  
DATUM: NAD1927LAT: 36.971621°N  
LONG: -107.614707°W  
DATUM: NAD1983523°18.1'E  
4300.0'END OF LATERAL (D)  
453' FSL 2743' FWL  
SEC 19, T32N, R7W  
LAT: 36.960758°N  
LONG: -107.608305°W  
DATUM: NAD1927LAT: 36.960762°N  
LONG: -107.608916°W  
DATUM: NAD1983<sup>17</sup> OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement, or a compulsory pooling order heretofore entered by the division.

Signature

2/27/2024

Date

Amanda Walker

Printed Name

mwalker@hilcorp.com

E-mail Address


<sup>18</sup> SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Date Revised: FEBRUARY 15, 2024

Survey Date: AUGUST 17, 2018

Signature and Seal of Professional Surveyor



JASON C. EDWARDS

Certificate Number 15269

Santa Fe Main Office Phone: (505) 476-3441 Fax: (55) 476-3462 General Information Phone: (505) 629-6116  Online Phone Directory Visit: <a href="https://www.emnrd.nm.gov/ocd/contact-us/">https://www.emnrd.nm.gov/ocd/contact-us/</a>	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION	C-102 Revised July 9, 2024 Submit Electronically via OCD Permitting
		Submittal Type: <input type="checkbox"/> Initial Submittal <input type="checkbox"/> Amended Report <input type="checkbox"/> As Drilled

## WELL LOCATION INFORMATION

API Number 30-045-38451	Pool Code 71629	Pool Name Basin Fruitland Coal (Gas)
Property Code 318434	Property Name San Juan 32-7 Unit	Well Number 243H
OGRID No. 372171	Operator Name Hilcorp Energy Company	Ground Level Elevation 6361'
Surface Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal		Mineral Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal

## Surface Location

UL K	Section 18	Township 32N	Range 7W	Lot	Ft. from N/S 1363' S	Ft. from E/W 2468' W	Latitude 36.977638	Longitude -107.609755	County San Juan
---------	---------------	-----------------	-------------	-----	-------------------------	-------------------------	-----------------------	--------------------------	--------------------

## Bottom Hole Location

UL N	Section 19	Township 32N	Range 7W	Lot 14	Ft. from N/S 453' S	Ft. from E/W 2743' W	Latitude 36.960762	Longitude -107.608916	County San Juan
---------	---------------	-----------------	-------------	-----------	------------------------	-------------------------	-----------------------	--------------------------	--------------------

Dedicated Acres 487.72	Infill or Defining Well Defining (First HZ FC in HZ Spacing Unit)	Defining Well API	Overlapping Spacing Unit (Y/N) N	Consolidation Code Unit
Order Numbers.			Well setbacks are under Common Ownership: <input type="checkbox"/> Yes <input type="checkbox"/> No	

## Kick Off Point (KOP)

UL M	Section 18	Township 32N	Range 7W	Lot Lot 4	Ft. from N/S 397' S	Ft. from E/W 1406' W	Latitude 36.975351	Longitude -107.613385	County San Juan
---------	---------------	-----------------	-------------	--------------	------------------------	-------------------------	-----------------------	--------------------------	--------------------


## First Take Point (FTP)

UL M	Section 18	Township 32N	Range 7W	Lot Lot 4	Ft. from N/S 397' S	Ft. from E/W 1406' W	Latitude 36.975351	Longitude -107.613385	County San Juan
---------	---------------	-----------------	-------------	--------------	------------------------	-------------------------	-----------------------	--------------------------	--------------------

## Last Take Point (LTP)

UL N	Section 19	Township 32N	Range 7W	Lot 14	Ft. from N/S 453' S	Ft. from E/W 2743' W	Latitude 36.960762	Longitude -107.608916	County San Juan
---------	---------------	-----------------	-------------	-----------	------------------------	-------------------------	-----------------------	--------------------------	--------------------

Unitized Area or Area of Uniform Interest	Spacing Unit Type <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Vertical	Ground Floor Elevation:
---	--	-------------------------

<b>OPERATOR CERTIFICATIONS</b>  <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i>  <i>If this well is a horizontal well, I further certify that this organization has received the consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.</i>   Signature 3/28/2025 Date  Amanda Walker Printed Name  mwalker@hilcorp.com Email Address	<b>SURVEYOR CERTIFICATIONS</b>  <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i>  Jason Edwards Signature and Seal of Professional Surveyor  15269 Certificate Number 2/15/2024 Date of Survey
---	--

Note: No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

Surveyors shall use the latest United States government survey or dependent resurvey. Well locations will be in reference to the New Mexico Principal Meridian. If the land is not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be acceptable.






# AERATED FLUID DRILLING LAYOUT

## KEY :

-  AIR
-  FLUID
-  AERATED FLUID
-  RETURNS





Company: Hilcorp Energy Corp.  
 Project: San Juan, NM NAD27  
 Site: San Juan 32-7 Unit 243H  
 Well: San Juan 32-7 Unit 243H  
 Wellbore: Pilot  
 Design: Plan #1



## Well Details: San Juan 32-7 Unit 243H



GL 6361' &amp; KB 17' @ 6378.00ft (Drake 3)

+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
0.00	0.00	2175204.20	565485.90	36.9776341	-107.6091441	



Azimuths to True North  
 Magnetic North: 8.80°

Magnetic Field  
 Strength: 49605.5nT  
 Dip Angle: 63.40°  
 Date: 12/31/2021  
 Model: HDGM2021\_FILE



## FORMATION TOP DETAILS

TVDPath	MDPath	Formation
1873.00	1876.31	Ojo Alamo
2061.00	2072.61	Kirtland
2799.00	3000.43	Fruitland
3048.00	3509.41	Top Big Blue
3064.00	3547.27	Base Big Blue
3234.00	3949.53	Pictured Cliffs

## Plan: Plan #1

10:58, February 08 2024  
 Created By: Janie Collins

## PROJECT DETAILS: San Juan, NM NAD27

Geodetic System: US State Plane 1927 (Exact solution)  
 Datum: NAD 1927 (NADCON CONUS)  
 Ellipsoid: Clarke 1866  
 Zone: New Mexico West 3003

System Datum: Mean Sea Level

## CASING DETAILS

No casing data is available

## SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect
0.00	0.00	0.000	0.00	0.00	0.00	0.00	0.00	0.00
1500.00	0.00	0.000	1500.00	0.00	0.00	0.00	0.00	0.00
3357.15	65.00	235.000	2983.65	-542.14	-774.25	3.50	235.00	945.19
4186.15	65.00	235.000	3334.00	-973.08	-1389.71	0.00	0.00	1696.52

## DESIGN TARGET DETAILS

No target data is available.

Vertical Section at 235.000° (600 ft/in)



## **Hilcorp Energy Corp.**

**San Juan, NM NAD27**

**San Juan 32-7 Unit 243H**

**San Juan 32-7 Unit 243H**

**Pilot**

**Plan: Plan #1**

## **Standard Planning Report**

**08 February, 2024**





# Lonestar Consulting, LLC

## Planning Report



<b>Database:</b>	Grand Junction	<b>Local Co-ordinate Reference:</b>	Well San Juan 32-7 Unit 243H
<b>Company:</b>	Hilcorp Energy Corp.	<b>TVD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Project:</b>	San Juan, NM NAD27	<b>MD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Site:</b>	San Juan 32-7 Unit 243H	<b>North Reference:</b>	True
<b>Well:</b>	San Juan 32-7 Unit 243H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Pilot		
<b>Design:</b>	Plan #1		

<b>Project</b>	San Juan, NM NAD27		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico West 3003		

<b>Site</b>	San Juan 32-7 Unit 243H		
<b>Site Position:</b>		<b>Northing:</b>	2,175,204.20 usft
<b>From:</b>	Map	<b>Easting:</b>	565,485.90 usft
<b>Position Uncertainty:</b>	0.00 ft	<b>Slot Radius:</b>	13.20 in
		<b>Latitude:</b>	36.9776340
		<b>Longitude:</b>	-107.6091441

<b>Well</b>	San Juan 32-7 Unit 243H		
<b>Well Position</b>	<b>+N/-S</b>	0.00 ft	<b>Northing:</b> 2,175,204.20 usft
	<b>+E/-W</b>	0.00 ft	<b>Easting:</b> 565,485.90 usft
<b>Position Uncertainty</b>	0.00 ft	<b>Wellhead Elevation:</b>	ft
<b>Grid Convergence:</b>	0.13 °	<b>Ground Level:</b>	6,361.00 ft

<b>Wellbore</b>	Pilot				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	HDGM2021_FILE	12/31/2021	8.80	63.40	49,605.50000000

<b>Design</b>	Plan #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (ft)</b>	<b>+N/-S (ft)</b>	<b>+E/-W (ft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	235.000

<b>Plan Survey Tool Program</b>	<b>Date</b>	2/7/2024		
<b>Depth From (ft)</b>	<b>Depth To (ft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>
1	0.00	4,186.15 Plan #1 (Pilot)	MWD+HDGM	
			OWSG MWD + HDGM	

<b>Plan Sections</b>										
<b>Measured Depth (ft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (ft)</b>	<b>+N/-S (ft)</b>	<b>+E/-W (ft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
0.00	0.00	0.000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,500.00	0.00	0.000	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00	
3,357.15	65.00	235.000	2,983.65	-542.14	-774.25	3.50	3.50	0.00	235.00	
4,186.15	65.00	235.000	3,334.00	-973.08	-1,389.71	0.00	0.00	0.00	0.00	



## Lonestar Consulting, LLC

## Planning Report



<b>Database:</b>	Grand Junction	<b>Local Co-ordinate Reference:</b>	Well San Juan 32-7 Unit 243H
<b>Company:</b>	Hilcorp Energy Corp.	<b>TVD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Project:</b>	San Juan, NM NAD27	<b>MD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Site:</b>	San Juan 32-7 Unit 243H	<b>North Reference:</b>	True
<b>Well:</b>	San Juan 32-7 Unit 243H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Pilot		
<b>Design:</b>	Plan #1		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.000	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.000	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.000	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.000	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.000	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.000	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.000	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.000	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.000	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.000	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.000	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.000	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.000	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.000	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.000	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.000	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	3.50	235.000	1,599.94	-1.75	-2.50	3.05	3.50	3.50	0.00
1,700.00	7.00	235.000	1,699.50	-7.00	-10.00	12.20	3.50	3.50	0.00
1,800.00	10.50	235.000	1,798.32	-15.72	-22.45	27.41	3.50	3.50	0.00
1,900.00	14.00	235.000	1,896.03	-27.89	-39.83	48.63	3.50	3.50	0.00
2,000.00	17.50	235.000	1,992.26	-43.46	-62.06	75.77	3.50	3.50	0.00
2,100.00	21.00	235.000	2,086.66	-62.37	-89.07	108.73	3.50	3.50	0.00
2,200.00	24.50	235.000	2,178.86	-84.54	-120.74	147.40	3.50	3.50	0.00
2,300.00	28.00	235.000	2,268.54	-109.91	-156.96	191.62	3.50	3.50	0.00
2,400.00	31.50	235.000	2,355.34	-138.36	-197.60	241.23	3.50	3.50	0.00
2,500.00	35.00	235.000	2,438.96	-169.81	-242.51	296.05	3.50	3.50	0.00
2,600.00	38.50	235.000	2,519.07	-204.12	-291.52	355.87	3.50	3.50	0.00
2,700.00	42.00	235.000	2,595.38	-241.18	-344.43	420.48	3.50	3.50	0.00
2,800.00	45.50	235.000	2,667.61	-280.83	-401.07	489.62	3.50	3.50	0.00
2,900.00	49.00	235.000	2,735.48	-322.95	-461.21	563.04	3.50	3.50	0.00
3,000.00	52.50	235.000	2,798.74	-367.36	-524.64	640.47	3.50	3.50	0.00
3,100.00	56.00	235.000	2,857.15	-413.90	-591.11	721.61	3.50	3.50	0.00
3,200.00	59.50	235.000	2,910.51	-462.40	-660.38	806.17	3.50	3.50	0.00
3,300.00	63.00	235.000	2,958.60	-512.68	-732.18	893.83	3.50	3.50	0.00
3,357.15	65.00	235.000	2,983.65	-542.14	-774.25	945.19	3.50	3.50	0.00
3,400.00	65.00	235.000	3,001.76	-564.41	-806.07	984.03	0.00	0.00	0.00
3,500.00	65.00	235.000	3,044.02	-616.40	-880.31	1,074.66	0.00	0.00	0.00
3,600.00	65.00	235.000	3,086.28	-668.38	-954.55	1,165.29	0.00	0.00	0.00
3,700.00	65.00	235.000	3,128.55	-720.37	-1,028.79	1,255.92	0.00	0.00	0.00
3,800.00	65.00	235.000	3,170.81	-772.35	-1,103.03	1,346.55	0.00	0.00	0.00
3,900.00	65.00	235.000	3,213.07	-824.33	-1,177.27	1,437.18	0.00	0.00	0.00
4,000.00	65.00	235.000	3,255.33	-876.32	-1,251.51	1,527.81	0.00	0.00	0.00
4,100.00	65.00	235.000	3,297.59	-928.30	-1,325.75	1,618.44	0.00	0.00	0.00
4,186.15	65.00	235.000	3,334.00	-973.08	-1,389.71	1,696.52	0.00	0.00	0.00



Lonestar Consulting, LLC  
Planning Report



Database:	Grand Junction	Local Co-ordinate Reference:	Well San Juan 32-7 Unit 243H
Company:	Hilcorp Energy Corp.	TVD Reference:	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
Project:	San Juan, NM NAD27	MD Reference:	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
Site:	San Juan 32-7 Unit 243H	North Reference:	True
Well:	San Juan 32-7 Unit 243H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Pilot		
Design:	Plan #1		

Formations						
Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,876.31	1,873.00	Ojo Alamo		0.00	0.000	
2,072.61	2,061.00	Kirtland		0.00	0.000	
3,000.43	2,799.00	Fruitland		0.00	0.000	
3,509.41	3,048.00	Top Big Blue		0.00	0.000	
3,547.27	3,064.00	Base Big Blue		0.00	0.000	
3,949.53	3,234.00	Pictured Cliffs		0.00	0.000	



Company: Hilcorp Energy Corp.  
Project: San Juan, NM NAD27  
Site: San Juan 32-7 Unit 243H  
Well: San Juan 32-7 Unit 243H  
Wellbore: Lateral  
Design: Plan #1

PROJECT DETAILS: San Juan, NM NAD27

Geodetic System: US State Plane 1927 (Exact solution)  
Datum: NAD 1927 (NADCONUS)  
Ellipsoid: Clarke 1866  
Zone: New Mexico West 3003  
System Datum: Mean Sea Level  
Local North: True



WELL DETAILS: San Juan 32-7 Unit 243H

GL 6361' & KB 17' @ 6378.00ft (Drake 3)  
+N/-S+E/-W    Northing    Easting    Longitude  
0.00    0.00    2175204.20    565485.90    36.9776341    -107.6091441

Plan: Plan #1 (San Juan 32-7 Unit 243H/Lateral)

Created By: Janie Collin    Date: 11:07, February 08 2024



Azimuths to True North  
Magnetic North: 8°

Magnetic Field  
Strength: 49605  
Dip Angle: 63.8°  
Date: 12/31/2021  
Model: HDGM2021\_FIT

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
SL 32-7 243H T1	3055.00	-2190.71	-1446.46	2173010.10	564044.60	36.9716165	-107.6140956
SL 32-7 243H BHL	3055.00	-6143.91	245.14	2169060.90	565745.50	36.9607580	-107.6083050
SL 32-7 243H LP	3055.00	-832.61	-1060.16	2174369.10	564427.70	36.9753470	-107.6127734

SECTION DETAILS


MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect
3410.00	65.00	235.000	3005.99	-569.61	-813.49	0.00	0.00	536.73
3638.26	90.00	235.000	3055.00	-696.42	-994.60	10.95	0.00	656.22
3656.12	90.00	234.189	3055.00	-706.77	-1009.16	4.54	-90.00	665.98
3695.39	90.00	234.189	3055.00	-729.75	-1041.00	0.00	0.00	687.67
5333.15	90.00	156.834	3055.00	-2190.71	-1446.46	4.72	-90.00	2131.30
9633.07	90.00	156.834	3055.00	-6143.91	245.14	0.00	0.00	6148.79

CASING DETAILS

No casing data is available

FORMATION DETAILS

No formation data is available





## Hilcorp Energy Corp.

San Juan, NM NAD27

San Juan 32-7 Unit 243H

San Juan 32-7 Unit 243H

Lateral

Plan: Plan #1

## Standard Planning Report

08 February, 2024





# Lonestar Consulting, LLC

## Planning Report



<b>Database:</b>	Grand Junction	<b>Local Co-ordinate Reference:</b>	Well San Juan 32-7 Unit 243H
<b>Company:</b>	Hilcorp Energy Corp.	<b>TVD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Project:</b>	San Juan, NM NAD27	<b>MD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Site:</b>	San Juan 32-7 Unit 243H	<b>North Reference:</b>	True
<b>Well:</b>	San Juan 32-7 Unit 243H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Lateral		
<b>Design:</b>	Plan #1		

<b>Project</b>	San Juan, NM NAD27		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico West 3003		

<b>Site</b>	San Juan 32-7 Unit 243H			
<b>Site Position:</b>		<b>Northing:</b>	2,175,204.20 usft	<b>Latitude:</b> 36.9776340
<b>From:</b>	Map	<b>Easting:</b>	565,485.90 usft	<b>Longitude:</b> -107.6091441
<b>Position Uncertainty:</b>	0.00 ft	<b>Slot Radius:</b>	13.20 in	

<b>Well</b>	San Juan 32-7 Unit 243H			
<b>Well Position</b>	<b>+N/-S</b>	0.00 ft	<b>Northing:</b>	2,175,204.20 usft
	<b>+E/-W</b>	0.00 ft	<b>Easting:</b>	565,485.90 usft
<b>Position Uncertainty</b>		0.00 ft	<b>Wellhead Elevation:</b>	ft
<b>Grid Convergence:</b>		0.13 °	<b>Ground Level:</b>	6,361.00 ft

<b>Wellbore</b>	Lateral				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	HDGM2021_FILE	12/31/2021	8.80	63.40	49,605.50000000

<b>Design</b>	Plan #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	3,410.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (ft)</b>	<b>+N/-S (ft)</b>	<b>+E/-W (ft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	177.715

<b>Plan Survey Tool Program</b>	<b>Date</b>	2/7/2024		
<b>Depth From (ft)</b>	<b>Depth To (ft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>
1	3,410.00	9,633.07	Plan #1 (Lateral)	MWD+HDGM
				OWSG MWD + HDGM

<b>Plan Sections</b>										
<b>Measured Depth (ft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (ft)</b>	<b>+N/-S (ft)</b>	<b>+E/-W (ft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
3,410.00	65.00	235.000	3,005.99	-569.61	-813.49	0.00	0.00	0.00	0.00	
3,638.26	90.00	235.000	3,055.00	-696.42	-994.60	10.95	10.95	0.00	0.00	
3,656.12	90.00	234.189	3,055.00	-706.77	-1,009.16	4.54	0.00	-4.54	-90.00	
3,695.39	90.00	234.189	3,055.00	-729.75	-1,041.00	0.00	0.00	0.00	0.00	
5,333.15	90.00	156.834	3,055.00	-2,190.71	-1,446.46	4.72	0.00	-4.72	-90.00	SL 32-7 243H T1
9,633.07	90.00	156.834	3,055.00	-6,143.91	245.14	0.00	0.00	0.00	0.00	SL 32-7 243H BHL



## Lonestar Consulting, LLC

## Planning Report



<b>Database:</b>	Grand Junction	<b>Local Co-ordinate Reference:</b>	Well San Juan 32-7 Unit 243H
<b>Company:</b>	Hilcorp Energy Corp.	<b>TVD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Project:</b>	San Juan, NM NAD27	<b>MD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Site:</b>	San Juan 32-7 Unit 243H	<b>North Reference:</b>	True
<b>Well:</b>	San Juan 32-7 Unit 243H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Lateral		
<b>Design:</b>	Plan #1		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,410.00	65.00	235.000	3,005.99	-569.61	-813.49	536.73	0.00	0.00	0.00
3,500.00	74.86	235.000	3,036.84	-618.04	-882.65	582.36	10.95	10.95	0.00
3,600.00	85.81	235.000	3,053.60	-674.50	-963.28	635.56	10.95	10.95	0.00
3,638.26	90.00	235.000	3,055.00	-696.42	-994.60	656.22	10.95	10.95	0.00
3,656.12	90.00	234.189	3,055.00	-706.77	-1,009.16	665.98	4.54	0.00	-4.54
3,695.39	90.00	234.189	3,055.00	-729.75	-1,041.00	687.67	0.00	0.00	0.00
3,700.00	90.00	233.971	3,055.00	-732.45	-1,044.73	690.22	4.72	0.00	-4.72
3,800.00	90.00	229.248	3,055.00	-794.54	-1,123.09	749.13	4.72	0.00	-4.72
3,900.00	90.00	224.525	3,055.00	-862.86	-1,196.07	814.49	4.72	0.00	-4.72
4,000.00	90.00	219.801	3,055.00	-936.97	-1,263.17	885.86	4.72	0.00	-4.72
4,100.00	90.00	215.078	3,055.00	-1,016.34	-1,323.95	962.75	4.72	0.00	-4.72
4,200.00	90.00	210.355	3,055.00	-1,100.45	-1,377.98	1,044.64	4.72	0.00	-4.72
4,300.00	90.00	205.632	3,055.00	-1,188.73	-1,424.90	1,130.98	4.72	0.00	-4.72
4,400.00	90.00	200.908	3,055.00	-1,280.57	-1,464.40	1,221.17	4.72	0.00	-4.72
4,500.00	90.00	196.185	3,055.00	-1,375.35	-1,496.20	1,314.60	4.72	0.00	-4.72
4,600.00	90.00	191.462	3,055.00	-1,472.42	-1,520.09	1,410.65	4.72	0.00	-4.72
4,700.00	90.00	186.739	3,055.00	-1,571.14	-1,535.90	1,508.65	4.72	0.00	-4.72
4,800.00	90.00	182.016	3,055.00	-1,670.82	-1,543.53	1,607.95	4.72	0.00	-4.72
4,900.00	90.00	177.292	3,055.00	-1,770.79	-1,542.92	1,707.87	4.72	0.00	-4.72
5,000.00	90.00	172.569	3,055.00	-1,870.37	-1,534.09	1,807.72	4.72	0.00	-4.72
5,100.00	90.00	167.846	3,055.00	-1,968.88	-1,517.09	1,906.83	4.72	0.00	-4.72
5,200.00	90.00	163.123	3,055.00	-2,065.66	-1,492.03	2,004.54	4.72	0.00	-4.72
5,300.00	90.00	158.399	3,055.00	-2,160.05	-1,459.09	2,100.16	4.72	0.00	-4.72
5,333.15	90.00	156.834	3,055.00	-2,190.71	-1,446.46	2,131.30	4.72	0.00	-4.72
5,400.00	90.00	156.834	3,055.00	-2,252.16	-1,420.17	2,193.75	0.00	0.00	0.00
5,500.00	90.00	156.834	3,055.00	-2,344.10	-1,380.83	2,287.19	0.00	0.00	0.00
5,600.00	90.00	156.834	3,055.00	-2,436.04	-1,341.48	2,380.62	0.00	0.00	0.00
5,700.00	90.00	156.834	3,055.00	-2,527.97	-1,302.14	2,474.05	0.00	0.00	0.00
5,800.00	90.00	156.834	3,055.00	-2,619.91	-1,262.80	2,567.48	0.00	0.00	0.00
5,900.00	90.00	156.834	3,055.00	-2,711.85	-1,223.46	2,660.91	0.00	0.00	0.00
6,000.00	90.00	156.834	3,055.00	-2,803.78	-1,184.12	2,754.34	0.00	0.00	0.00
6,100.00	90.00	156.834	3,055.00	-2,895.72	-1,144.78	2,847.78	0.00	0.00	0.00
6,200.00	90.00	156.834	3,055.00	-2,987.66	-1,105.44	2,941.21	0.00	0.00	0.00
6,300.00	90.00	156.834	3,055.00	-3,079.59	-1,066.10	3,034.64	0.00	0.00	0.00
6,400.00	90.00	156.834	3,055.00	-3,171.53	-1,026.76	3,128.07	0.00	0.00	0.00
6,500.00	90.00	156.834	3,055.00	-3,263.47	-987.42	3,221.50	0.00	0.00	0.00
6,600.00	90.00	156.834	3,055.00	-3,355.40	-948.08	3,314.94	0.00	0.00	0.00
6,700.00	90.00	156.834	3,055.00	-3,447.34	-908.74	3,408.37	0.00	0.00	0.00
6,800.00	90.00	156.834	3,055.00	-3,539.28	-869.40	3,501.80	0.00	0.00	0.00
6,900.00	90.00	156.834	3,055.00	-3,631.21	-830.06	3,595.23	0.00	0.00	0.00
7,000.00	90.00	156.834	3,055.00	-3,723.15	-790.72	3,688.66	0.00	0.00	0.00
7,100.00	90.00	156.834	3,055.00	-3,815.09	-751.38	3,782.10	0.00	0.00	0.00
7,200.00	90.00	156.834	3,055.00	-3,907.02	-712.04	3,875.53	0.00	0.00	0.00
7,300.00	90.00	156.834	3,055.00	-3,998.96	-672.70	3,968.96	0.00	0.00	0.00
7,400.00	90.00	156.834	3,055.00	-4,090.89	-633.36	4,062.39	0.00	0.00	0.00
7,500.00	90.00	156.834	3,055.00	-4,182.83	-594.02	4,155.82	0.00	0.00	0.00
7,600.00	90.00	156.834	3,055.00	-4,274.77	-554.68	4,249.26	0.00	0.00	0.00
7,700.00	90.00	156.834	3,055.00	-4,366.70	-515.34	4,342.69	0.00	0.00	0.00
7,800.00	90.00	156.834	3,055.00	-4,458.64	-476.00	4,436.12	0.00	0.00	0.00
7,900.00	90.00	156.834	3,055.00	-4,550.58	-436.66	4,529.55	0.00	0.00	0.00
8,000.00	90.00	156.834	3,055.00	-4,642.51	-397.32	4,622.98	0.00	0.00	0.00
8,100.00	90.00	156.834	3,055.00	-4,734.45	-357.98	4,716.42	0.00	0.00	0.00
8,200.00	90.00	156.834	3,055.00	-4,826.39	-318.64	4,809.85	0.00	0.00	0.00
8,300.00	90.00	156.834	3,055.00	-4,918.32	-279.30	4,903.28	0.00	0.00	0.00



# Lonestar Consulting, LLC Planning Report



<b>Database:</b>	Grand Junction	<b>Local Co-ordinate Reference:</b>	Well San Juan 32-7 Unit 243H
<b>Company:</b>	Hilcorp Energy Corp.	<b>TVD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Project:</b>	San Juan, NM NAD27	<b>MD Reference:</b>	GL 6361' & KB 17' @ 6378.00ft (Drake 3)
<b>Site:</b>	San Juan 32-7 Unit 243H	<b>North Reference:</b>	True
<b>Well:</b>	San Juan 32-7 Unit 243H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Lateral		
<b>Design:</b>	Plan #1		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
8,400.00	90.00	156.834	3,055.00	-5,010.26	-239.96	4,996.71	0.00	0.00	0.00	
8,500.00	90.00	156.834	3,055.00	-5,102.20	-200.61	5,090.14	0.00	0.00	0.00	
8,600.00	90.00	156.834	3,055.00	-5,194.13	-161.27	5,183.57	0.00	0.00	0.00	
8,700.00	90.00	156.834	3,055.00	-5,286.07	-121.93	5,277.01	0.00	0.00	0.00	
8,800.00	90.00	156.834	3,055.00	-5,378.01	-82.59	5,370.44	0.00	0.00	0.00	
8,900.00	90.00	156.834	3,055.00	-5,469.94	-43.25	5,463.87	0.00	0.00	0.00	
9,000.00	90.00	156.834	3,055.00	-5,561.88	-3.91	5,557.30	0.00	0.00	0.00	
9,100.00	90.00	156.834	3,055.00	-5,653.82	35.43	5,650.73	0.00	0.00	0.00	
9,200.00	90.00	156.834	3,055.00	-5,745.75	74.77	5,744.17	0.00	0.00	0.00	
9,300.00	90.00	156.834	3,055.00	-5,837.69	114.11	5,837.60	0.00	0.00	0.00	
9,400.00	90.00	156.834	3,055.00	-5,929.63	153.45	5,931.03	0.00	0.00	0.00	
9,500.00	90.00	156.834	3,055.00	-6,021.56	192.79	6,024.46	0.00	0.00	0.00	
9,600.00	90.00	156.834	3,055.00	-6,113.50	232.13	6,117.89	0.00	0.00	0.00	
9,633.07	90.00	156.834	3,055.00	-6,143.91	245.14	6,148.80	0.00	0.00	0.00	

Design Targets										
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
SL 32-7 243H T1 - plan hits target center - Point	0.00	0.000	3,055.00	-2,190.71	-1,446.46	2,173,010.10	564,044.60	36.9716165	-107.6140956	
SL 32-7 243H BHL - plan hits target center - Point	0.00	0.000	3,055.00	-6,143.91	245.14	2,169,060.90	565,745.50	36.9607580	-107.6083050	
SL 32-7 243H LP - plan misses target center by 69.70ft at 3774.32ft MD (3055.00 TVD, -777.98 N, -1103.46 E) - Point	0.00	0.000	3,055.00	-832.61	-1,060.16	2,174,369.10	564,427.70	36.9753470	-107.6127734	

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Submit Electronically  
Via E-permitting

## NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

### **Section 1 – Plan Description** **Effective May 25, 2021**

**I. Operator:** Hilcorp Energy Company **OGRID:** 372171 **Date:** 02/27/2024

**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
SJ 32-7 Unit 243H	30-045-35904	K-18-32N-07W	1363 FSL & 2468 FWL	0	150	75

**IV. Central Delivery Point Name:** Ignacio Processing Plant [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
<u>SJ 32-7 Unit 243H</u>	<u>30-045-35904</u>					

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

## **Section 2 – Enhanced Plan**

### **EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

#### **IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

#### **X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

**XI. Map.** ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**


1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: 
Printed Name: Amanda Walker
Title: Operations Regulatory Tech Sr.
E-mail Address: <a href="mailto:mwalker@hilcorp.com">mwalker@hilcorp.com</a>
Date: 2/27/2024
Phone: 346.237.2177
<b>OIL CONSERVATION DIVISION</b> <b>(Only applicable when submitted as a standalone form)</b>
Approved By:
Title:
Approval Date:
Conditions of Approval:

## Hilcorp Energy Natural Gas Management Plan Attachments

### VI. Separation Equipment

The operator will select separation equipment for the maximum anticipated throughput and pressure to optimize gas capture. Separation equipment is sized according to manufacturer's design specifications. Separation vessels are built following the A.S.M.E. section VII division 1 codes for pressure vessel design, fabrication, inspection, testing and certification. Anticipated well pressures and production rates are evaluated to select separation equipment according to the equipment's designed operating pressure and throughput.

After completion, the operator utilizes flowback equipment, including separators, to manage wellbore fluids and solids during the initial separation period. After the initial flowback period is complete the operator utilizes iterative facility separation equipment to ensure that optimal separation is achieved.

### VII. Operational Practices 19.15.27.8 NMAC A through F

- A. The operator will maximize the recovery of natural gas and minimize the amount of gas vented or flared when technically and safely feasible as further described and detailed within the following subsections (B-F of 19.15.27.8). In all cases where natural gas venting and flaring requires regulatory reporting, reporting will be submitted accurately and within the required time frames.
- B. Venting and flaring during drilling operations:
  - a. New Drill HZ Gas Wells: The operator drills wells in the area by utilizing a balanced mud to safely drill the wellbore. This technique prevents gas from coming to surface during the drilling process. If there is an emergency or malfunction and natural gas does come to surface the natural gas will be captured and routed to sales if technically and safely feasible.
- C. Venting and flaring during completion or recompletion operations:
  - a. New Drill HZ Gas Wells: The operator's facilities are designed to handle the maximum throughput and pressures from the newly drilled and completed wellbores. The amount of gas vented and flared will be minimized when technically and safely feasible. During initial flowback and initial separation flowback the operator will utilize contracted flowback equipment, including separators, to manage wellbore fluids and solids. The initial flowback period will be minimized and flow will be sent to separation equipment as soon as possible to reduce the amount of gas that is vented to atmosphere. The natural gas will be utilized on site as needed for fuel gas and natural gas will be sold.
- D. Venting and flaring during production operations:
  - a. New Drill HZ Gas Wells: The operator's facilities are designed to handle the maximum throughput and pressures from producing wellbores. The amount of gas vented and flared will be minimized when technically and safely feasible.

Operations will effectively manage the following scenarios to minimize the quantity of natural gas that is vented or flared:

- (a) If there is an emergency or malfunction vented or flared natural gas will be reported, if required, and the emergency or malfunction will be resolved as soon as technically and safely feasible.
- (b) If the wellbore needs to be unloaded to atmosphere the operator will not vent the well after the well has achieved a stabilized rate and pressure. The operator will remain on site during unloading. Plunger lift systems will be optimized to reduce the amount of natural gas venting. Downhole maintenance, such as workovers, swabbing, etc. will only be conducted as needed and best management practices will be utilized to reduce venting of natural gas.
- (c) The operator will minimize the amount of time that natural gas is vented to atmosphere from gauging and sampling a storage tank or low pressure vessel. The formation is only anticipated to produce water and therefore tank emissions are anticipated to be negligible.
- (d) The operator will reduce the amount of time needed for loading out liquids from a storage tanks or other low-pressure vessels whenever feasible. Operations will always utilize the water transfer systems when available. Water loading emissions are anticipated to be negligible.
- (e) Equipment will be repaired and maintained routinely to minimize the venting or flaring of natural gas. Repairs and maintenance will be conducted in a manner that minimizes the amount of natural gas vented to atmosphere through the isolation of the equipment that is being repaired or maintained.
- (f) Electric controllers and pumps will be installed to replace pneumatic controllers whenever feasible. Pneumatic controllers and pumps will be inspected frequently to ensure that no excess gas is vented to atmosphere.
- (g) No dehydration or amine units are anticipated to be set on location.
- (h) Compressors, compressor engines, turbines, flanges, connectors, valves, storage tanks, and other low-pressure vessels and flanges will be routinely inspected to ensure that no excess venting occurs outside of normal operations.
- (i) Regulatory required testing, such as bradenhead and packer testing will be performed in a manner that minimizes the amount of natural gas vented to atmosphere.
- (j) If natural gas does not meet gathering pipeline specifications gas samples will be collected twice per week to determine when pipeline specification gas content has been achieved. During this time frame gas will be flared and not vented to atmosphere. Natural gas that meets pipeline specifications will be sold via pipeline and natural gas that can be utilized for fuel gas will be used during this time.
- (k) If pipeline, equipment, or facilities need purged of impurities gas losses will be minimized as much as technically and safely feasible.

## E. Performance standards:

- a. The production facilities are designed to handle the maximum throughput and pressures from producing wellbores and will be designed to minimize waste. The amount of gas vented and flared will be minimized when technically and safely feasible.
  - b. All tanks that are routed to a control device that is installed after 5/25/2021 will have an automatic gauging system to minimize the amount of vented natural gas.
  - c. If a flare stack is installed or replaced after 5/25/2021 it will be equipped with an automatic ignitor or continuous pilot. The flare stack will be properly sized and designed to ensure proper combustion efficiency. The flare stack will be located 100 feet away from the nearest wellhead or storage tank.
  - d. AVO inspections will be conducted weekly for the year after completion and for all wells producing greater than 60,000 cubic feet of natural gas daily. The AVO inspection will include all components, including flare stacks, thief hatches, closed vent systems, pumps, compressors, pressure relief devices, valves, lines, flanges, connectors, and associated pipeline to identify any leaks and releases by comprehensive auditory, visual, and olfactory inspection. The AVO inspection records will be maintained for 5 years which will be available at the department's request. Identified leaks will be repaired as soon as feasible to minimize the amount of vented natural gas.
- F. Measurement or estimation of vented and flared natural gas.
- a. The volume of natural gas that is vented, flared or consumed for beneficial use will be measured when possible, or estimated, during drilling, completions, or production operations.
  - b. Equipment will be installed to measure the volume of natural gas flared for all APD's issued after 5/25/2021 on facilities that will have an average daily gas rate greater than 60,000 cubic feet of natural gas. Measurement equipment will conform to API MPMS Chapter 14.10 regulations. The measurement equipment will not have a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment. If metering is not practical then the volume of gas will be estimated.

San Juan County, NM

San Juan 32-7 Unit 243H



## Technical Drilling Plan (Rev. 0)

Hilcorp Energy Company proposes to drill and complete the referenced dual lateral horizontal well targeting a coal seam in the Fruitland formation.

*Note: This technical drilling plan will be adjusted based upon actual conditions.*

## 1. Location

Date:	February 21, 2024	Pool:	Fruitland Coal
Well Name:	San Juan 32-7 Unit #243H	Ground Elevation	6,361'
Surface Hole Location:	36.977634° N, -107.609144° W	County, State:	San Juan County, NM
Lateral Depth (ft.)	9,633' MD / 3,055' TVD	Lat 1 BHL:	36.960758° N, -107.608305° W

*Note: All depths in the directional drilling plan are referenced from an estimated RKB datum of 15' above ground level.*

## 2. Geological Markers

Anticipated formation tops with comments of any possible water, gas or oil shows are indicated below:

Formation	Depth (ft. TVD)	Remarks
Ojo Alamo	1,873'	Water (fresh/useable)
Kirtland	2,061'	None
Fruitland	2,799'	Gas, Coal, Water
Pictured Cliffs	3,234'	None

## 3. Pressure Control Equipment

See attached BOP equipment and choke manifold schematics for a diagram of pressure control equipment.

- BOP equipment will be nipped up on top of the wellhead after surface casing is set and cemented.
- Pressure control configurations will be designed to meet the minimum 2M standards.
- All equipment will have a minimum of 3M pressure rating and will be rated for 5,000' (TVD).
- A rotating head will be installed on top of the annular as seen in the attached diagram.
- BOP Testing: The BOPE will be tested to 250 psi (Low) for 5 minutes and 3,000 psi (High) for 10 minutes. Pressure test surface casing to 600 psi for 30 minutes and intermediate casing to 1,500 psi for 30 minutes. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. BOP equipment will be tested upon installation, every 30 days, and after any repairs are made to the BOP equipment. Annular preventors will be functionally tested at least once per week. Pipe and blind rams will be function tested each trip. The COGCC and the BLM will be notified 24 hours in advance of testing BOPE. All tests and inspections will be recorded and logged with time and results. A full BOP test will be conducted if a seal subject to test pressure is broken, following related repairs, and at a minimum of 30-day intervals.

San Juan County, NM

San Juan 32-7 Unit 243H

Hilcorp Energy Company

## 4. Casing &amp; Cement Program

## A. Proposed Casing Program:

Proposed Casing Design						
Casing String	Hole Size	Casing Size	Weight/Grade	Top Depth (MD/TVD)	Shoe Depth (MD/TVD)	
Surface	12-1/4"	9-5/8"	32.3# H40 (or equiv.) STC	0'	300' / 300'	
Intermediate	8-3/4"	7"	23# J55 (or equiv.) LTC	0'	4,144' / 3,316'	
Intermediate Shoe Joint	8-3/4"	5-1/2" shoe joint	15.5# J-55 (or equiv.) LTC	4,144' / 3,316'	4,186' / 3,334'	
Lateral #1 Production Liner (pre-perforated)	6-1/4"	4-1/2"	11.6# J55 (or equiv.) LTC	3,410' / 3,006'	9,633' / 3,055'	
Proposed Casing Design Safety Factors						
Casing String	Casing Description		Burst Design SF	Collapse Design SF	Joint Tensile Design SF	Connection Tensile Design SF
Surface	9-5/8" 32.3# H40 STC		16.2	12.4	37.7	26.2
Intermediate	7" 23# J55 LTC		2.2	2.0	3.8	3.3
Intermediate Shoe Jt	5-1/2" 15.5# J-55 LTC		2.5	2.6	5.1	3.3
Lateral Production Liner (pre-perforated)	4-1/2" 11.6# J55 LTC		N/A	N/A	2.8	2.2

## Notes:

- The production hole sections will be kicked off out of the 7" casing using whipstocks. Actual window depths will be determined after drilling pilot hole section.
- The production liners will be pre-perforated and dropped off in the open hole (uncemented). The top of the production liner will be approximately 5'-10' outside of the casing exit (no overlap between liner and 7" casing).
- If the 6-1/4" hole is not drilled to the total planned measured depth, the production liner setting depth and length will be adjusted accordingly.
- The 7" casing will be set across the setback boundary line and with the casing shoe within the drill block.
- The 7" casing will have a 5-1/2" shoe joint to help get casing to planned depth. The shoe track will not be drilled out.

San Juan County, NM

San Juan 32-7 Unit 243H



## B. Proposed Centralizer Program:

Proposed Centralizer Program	
Interval	Centralizers & Placement
Surface	1 centralizer per joint on bottom 3 joints.
Intermediate	1 centralizer 10' above the shoe with lock collar. 1 centralizer every other joint on bottom 10 joints. 1 centralizer every 4 <sup>th</sup> joint to Ojo Alamo base. 1 Turbolizer at base of Ojo Alamo. 1 centralizer every joint to Ojo Alamo top. 1 Turbolizer placed midway through Ojo Alamo. 1 centralizer every 4 <sup>th</sup> joint from top of Ojo Alamo to surface shoe. 1 centralizer inside the surface casing.
Production	N/A

## C. Proposed Cement Program:

Proposed Cement Design							
Interval	Depth (ft. MD)	Lead/Tail	Volume (ft <sup>3</sup> )	Sacks	Slurry	Density	Planned TOC
Surface	300'	Lead	188 ft <sup>3</sup>	151	Type III Cement 0.25% FL-52, 0.25 pps celloflake 1.25 ft <sup>3</sup> /sk – 5.75 gal/sk	15.2 ppg	Surface
Intermediate	4,186'	Lead	865 ft <sup>3</sup>	406	Premium Lite 3% CaCl, 0.25 pps celloflake, 5 ppm LCM-1, 0.4% FL-52, 8% bentonite, 0.4% SMS 2.13 ft <sup>3</sup> /sk – 11.29 gal/sk	12.1 ppg	Surface
		Tail	120 ft <sup>3</sup>	70	Type III Cement 1% CaCl, 0.25 pps celloflake, 0.2% FL-52 1.38ft <sup>3</sup> /sk – 6.64 gal/sk	14.6 ppg	3,686'
Production Lateral	9,633'	N/A	N/A	N/A	N/A – Uncemented pre-perforated liner.	N/A	N/A

## Notes:

- The cement slurry additives may be adjusted to accommodate required pump and compressive test times.
- For the intermediate hole section, a 2-stage cement job may be performed if hole conditions dictate. If needed, the stage tool will be placed at an approximate depth near the top of the Fruitland Coal (2,619' TVD)
- Cement will be circulated to surface on surface and intermediate casing sections to protect water bearing zones.
- A minimum of 8 hours of wait on cement time will be observed on each hole section to allow adequate time for cement to achieve a minimum of 500 psi of compressive strength. The BOP will not be nipped down, the wellhead will not be installed, the casing will not be tested and the prior casing shoe will not be drilled out until adequate wait on cement time has been observed (8 hours or time to reach 500 psi compressive strength).

San Juan County, NM

San Juan 32-7 Unit 243H

Hilcorp Energy Company

## 5. Drilling Fluids Program

## A. Proposed Drilling Fluids Program:

Interval	Fluid Type	Density (ppg)	Fluid Loss (mL/30 min)	Max Chlorides (mg/L)	Depth (ft. MD)
Surface	Water/Gel	8.3 – 9.2	NC	1,000	0' – 300'
Intermediate	LSND / Gel System	8.4 – 9.5	6-16	1,000	300' – 4,186'
Production Lateral #1	LSND Brine (if needed)	8.5 – 10.5	4-14	1,000 60,000 (if NaCl added for density)	3,410' – 9,633'

## Notes:

- In the 6-1/4" production section, NaCl brine will only be utilized if a weighting agent is needed to increase mud weight (for either well control or wellbore stability).
- Lost circulation material may be added to the mud systems to manage fluid losses as hole conditions dictate.
- The well will be drilled utilizing a closed-loop circulating system. Drill cuttings will be transported to an approved disposal site.
- Estimated total volume of drill cuttings for disposal: 570 bbls (3,200 ft<sup>3</sup>).

## 6. Estimated Pressures &amp; Drilling Hazards

## A. Estimated Pressures

- Estimated Reservoir Pressure of Fruitland Coal: 600 – 900 psi
- Maximum Anticipated Surface Pressure: 700 psi
- No over-pressured intervals expected.
- There is production from the Fruitland Coal formation in offset wells in the area, which could result in these formations being under-pressured.

## B. Water Flows

- Water flows are possible in the intermediate section. Water flows will be mitigated with increased mud weight.

## C. Lost Circulation

- Lost circulation is possible in the coal section. Losses will be mitigated by adding LCM to the mud system.

## D. Hydrogen Sulfide

- No hydrogen sulfide is expected to be encountered based on nearby well production.

San Juan County, NM

San Juan 32-7 Unit 243H



## 7. Testing, Logging, Coring

### A. Mud Logging

- Mud loggers will collect formation samples every 30' from the surface casing shoe to both the TD of the pilot hole and TD of the production laterals.

### B. MWD

- Measurement while drilling tools will be utilized from the surface casing shoe to both the TD of the pilot hole and TD of the production laterals to measure and record inclination and azimuth.

### C. LWD

- Logging while drilling tools (gamma ray) will be utilized in the intermediate section from the surface casing shoe to the pilot hole section TD.
- Logging while drilling tools (gamma ray) will be utilized while drilling the production laterals from the intermediate casing kick-offs to the production laterals' TD to assist in staying in the desired coal seam while drilling the lateral sections.

### D. Open Hole Logging

- There are no planned open hole logs post drilling.

### E. Coring

- There is no coring or formation testing planned.

### F. Cased Hole Logging


- The 7" intermediate casing will be cemented to surface to protect water bearing zones. If cement is not circulated to surface on the intermediate cement job, a temperature survey or a cement bod log will be run to verify top of cement.

## 8. Directional Drilling Plan

- The directional drilling plans and plots are attached.
- The directional plan is built from geologic targets from offset wells and lease boundaries. The production laterals will be landed and drilled horizontally within the target formation utilizing LWD tools to steer the wellbores. On-site adjustments to the directional plans will be made as formation and wellbore dictate.

## Appendix A

### Pressure Control Equipment Configuration



1	Rotating Head	12	Manual Isolation Valve
2	Flow Line	13	Needle Valve & Pressure Gauge
3	Fill-Up Line	14	Spacer Spool (if needed)
4	3M Annular Preventer	15	Manual Choke
5	3M Pipe Rams	16	Manual Choke
6	Manual Isolation Valve	17	Manual Isolation Valve
7	Check Valve	18	Manual Isolation Valve
8	Manual Isolation Valve	19	Manual Isolation Valve
9	Manual Isolation Valve	20	Valve Block & Pressure Gauge
10	High Closing Ratio Valve	21	Manual Isolation Valve
11	3M Blind Rams	22	Manual Isolation Valve

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 446644

**CONDITIONS**

Operator: HILCORP ENERGY COMPANY 1111 Travis Street Houston, TX 77002	OGRID: 372171
	Action Number: 446644
	Action Type: [C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

**CONDITIONS**

Created By	Condition	Condition Date
mray	Cement is required to circulate on both surface and intermediate1 strings of casing.	3/28/2025
mray	If cement does not circulate on any string, a Cement Bond Log (CBL) is required for that string of casing.	3/28/2025
ward.rikala	Notify the OCD 24 hours prior to casing & cement.	4/28/2025
ward.rikala	File As Drilled C-102 and a directional Survey with C-104 completion packet.	4/28/2025
ward.rikala	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string.	4/28/2025
ward.rikala	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.	4/28/2025