

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT**I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT**

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-48531	⁵ Pool Name LOS MEDANOS;BONE SPRING	⁶ Pool Code 40295
⁷ Property Code 326259	⁸ Property Name JAMES RANCH UNIT DI 2	⁹ Well Number 704H

II. ¹⁰ Surface Location

UI or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
K	25	22S	30E		2250	South	2080	West	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	28	22S	30E		0	South	2617	East	Eddy
¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
373073	XTO Permian Midstream	O/G/W

IV. Well Completion Data

²¹ Spud Date 7/12/21	²² Ready Date 7/8/22	²³ TD 24204 MD 9670 TVD	²⁴ PBD 24192 MD 9670 TVD	²⁵ Perforations 11,062 TO 24,026	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
17.5	13.375 J55 54.5#	645	805		
12.25	9.625 J55 40#	3,674	1,375		
8.75	7.625 HCL80 29.7#	9,261	1,565		
6.75	5 P110 18# 2 7/8 L80 6.5#	24,194 9,990	1,715		

V. Well Test Data

³¹ Date New Oil 7/9/22	³² Gas Delivery Date 7/14/22	³³ Test Date 7/14/22	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 341	³⁶ Csg. Pressure 141
³⁷ Choke Size	³⁸ Oil 957	³⁹ Water 3598	⁴⁰ Gas 1564		⁴¹ Test Method Flowing

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Amanda Thames

Printed name:

Amanda Thames

Title:

Regulatory Analyst

E-mail Address:

amanda.thames@exxonmobil.com

Date:

7/28/2022

Phone:

432.221.7340

OIL CONSERVATION DIVISION

Approved by:

Title:

Approval Date:

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT AS-DRILLED PLAT

¹ API Number 30-015-48531	² Pool Code 40295	³ Pool Name LOS MEDANOS; BONE SPRING
⁴ Property Code 326259	⁵ Property Name JAMES RANCH UNIT DI 2	⁶ Well Number 704H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,344'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	25	22 S	30 E		2,550	SOUTH	2,080	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	28	22 S	30 E		0	SOUTH	2,617	EAST	EDDY

¹² Dedicated Acres 400	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY.

¹⁶ SEC. 21 				¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <u>Amanda Thames</u> 7/28/2022 Signature Date <u>Amanda Thames</u> Printed Name <u>amanda.thames@exxonmobil.com</u> E-mail Address	
¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 4-22-2022 Date of Survey Signature and Seal of Professional Surveyor:					
MARK DILLON HARP 23786 Certificate Number JC 2019051248					

Intent ☐ As Drilled ☐

API #		
Operator Name:	Property Name:	Well Number

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude			NAD	

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude			NAD	

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude			NAD	

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018

Schlumberger

XTO James Ranch Unit DI 2 704H 0' to 24204' MD Survey Geodetic Report



(Def Survey)

Report Date:	September 14, 2021 - 01:34 PM	Survey / DLS Computation:	Minimum Curvature / Lubinski
Client:	XTO Energy	Vertical Section Azimuth:	278.740 ° (Grid North)
Field:	NM Eddy County (NAD 27)	Vertical Section Origin:	0.000 ft, 0.000 ft
Structure / Slot:	XTO James Ranch Unit DI 2 704H / Slot of James Ranch Unit DI 2 704H	TVD Reference Datum:	RKB
Well:	James Ranch Unit DI 2 704H	TVD Reference Elevation:	3376.000 ft above MSL
Borehole:	James Ranch Unit DI 2 704H	Seabed / Ground Elevation:	3344.000 ft above MSL
UWI / API#:	Unknown / 30-015-46752	Magnetic Declination:	6.727 °
Survey Name:	XTO James Ranch Unit DI 2 704H 0' to 24204' MD	Total Gravity Field Strength:	998.4601mgn (9.80665 Based)
Survey Date:	July 03, 2021	Gravity Model:	GARM
Tort / AHD / DDI / ERD Ratio:	274.035 ° / 16888.597 ft / 7.058 / 1.721	Total Magnetic Field Strength:	47784.573 nT
Coordinate Reference System:	NAD27 New Mexico State Plane, Eastern Zone, US Feet	Magnetic Dip Angle:	60.046 °
Location Lat / Long:	N 32° 21' 45.81658", W 103° 50' 8.57305"	Declination Date:	July 18, 2021
Location Grid N/E Y/X:	N 496032.500 ftUS, E 653649.600 ftUS	Magnetic Declination Model:	IFR1+MS
CRS Grid Convergence Angle:	0.2664 °	North Reference:	Grid North
Grid Scale Factor:	0.99993613	Grid Convergence Used:	0.2664 °
Version / Patch:	2.10.826.8	Total Corr Mag North->Grid North:	6.4606 °
		Local Coord Referenced To:	Well Head

Comments	MD (ft)	Incl (°)	Azin Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
Surface Location	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	496032.50	653649.60	32.362727	-103.835715	0.00	0.00
	132.00	0.62	174.19	132.00	-0.18	-0.71	0.07	0.47	496031.79	653649.67	32.362725	-103.835715	0.71	174.19
	224.00	0.64	169.15	223.99	-0.48	-1.71	0.22	0.06	496030.79	653649.82	32.362722	-103.835714	1.72	172.69
	316.00	0.52	169.72	315.99	-0.64	-2.63	0.25	0.26	496029.87	653649.85	32.362720	-103.835714	2.64	174.66
	408.00	0.25	177.24	407.99	-0.67	-3.24	0.18	0.31	496029.26	653649.78	32.362718	-103.835714	3.24	176.73
	500.00	0.10	218.82	499.98	-0.67	-3.50	0.14	0.20	496029.00	653649.74	32.362717	-103.835714	3.50	177.64
	557.00	0.26	12.71	556.98	-0.66	-3.41	0.14	0.62	496029.09	653649.74	32.362717	-103.835714	3.42	177.63
13-3/8" Casing	577.00	0.33	11.95	576.98	-0.66	-3.31	0.16	0.36	496029.19	653649.76	32.362718	-103.835714	3.32	177.18
	678.00	0.70	10.53	677.98	-0.70	-2.42	0.34	0.36	496030.08	653649.94	32.362720	-103.835714	2.44	172.07
	769.00	0.83	9.03	768.97	-0.72	-1.22	0.54	0.14	496031.28	653650.14	32.362723	-103.835713	1.34	156.09
	862.00	0.76	10.50	861.96	-0.74	0.05	0.76	0.08	496032.55	653650.36	32.362727	-103.835712	0.76	86.27
	954.00	0.40	20.70	953.96	-0.83	0.95	0.98	0.41	496033.45	653650.58	32.362729	-103.835712	1.37	46.03
	1046.00	0.23	13.83	1045.96	-0.91	1.43	1.14	0.19	496033.93	653650.74	32.362731	-103.835711	1.83	38.63
	1138.00	0.18	34.32	1137.96	-0.99	1.73	1.27	0.10	496034.23	653650.87	32.362732	-103.835711	2.14	36.27
	1229.00	0.26	43.67	1228.96	-1.17	2.00	1.49	0.10	496034.50	653651.09	32.362732	-103.835710	2.49	36.77
	1323.00	0.25	41.39	1322.95	-1.40	2.30	1.77	0.02	496034.80	653651.37	32.362733	-103.835709	2.91	37.60
	1418.00	0.21	54.79	1417.95	-1.64	2.56	2.05	0.07	496035.06	653651.65	32.362734	-103.835708	3.28	38.74
	1512.00	0.27	62.35	1511.95	-1.94	2.76	2.39	0.07	496035.26	653651.99	32.362734	-103.835707	3.65	40.88
	1606.00	0.32	89.98	1605.95	-2.38	2.86	2.85	0.16	496035.36	653652.45	32.362735	-103.835705	4.04	44.84
	1700.00	0.29	104.40	1699.95	-2.88	2.81	3.34	0.09	496035.31	653652.94	32.362734	-103.835704	4.36	49.99
	1794.00	0.39	112.44	1793.95	-3.42	2.62	3.87	0.12	496035.12	653653.47	32.362734	-103.835702	4.67	55.84
	1888.00	0.32	102.50	1887.95	-4.00	2.45	4.42	0.10	496034.95	653654.02	32.362733	-103.835700	5.05	61.05
	1982.00	0.27	120.16	1981.95	-4.47	2.28	4.87	0.11	496034.78	653654.47	32.362733	-103.835699	5.37	64.93
	2077.00	0.25	129.42	2076.94	-4.85	2.03	5.22	0.05	496034.53	653654.82	32.362732	-103.835698	5.60	68.72
	2171.00	0.25	126.14	2170.94	-5.21	1.78	5.55	0.02	496034.28	653655.15	32.362732	-103.835697	5.82	72.18
	2266.00	0.23	101.64	2265.94	-5.58	1.62	5.90	0.11	496034.12	653655.50	32.362731	-103.835696	6.12	74.63
	2360.00	0.21	94.13	2359.94	-5.94	1.57	6.26	0.04	496034.07	653655.86	32.362731	-103.835694	6.45	75.90
	2454.00	0.24	107.64	2453.94	-6.31	1.50	6.62	0.06	496034.00	653656.22	32.362731	-103.835693	6.78	77.23
	2549.00	0.36	72.74	2548.94	-6.78	1.53	7.09	0.22	496034.03	653656.69	32.362731	-103.835692	7.25	77.85
	2642.00	0.39	52.80	2641.94	-7.26	1.81	7.62	0.14	496034.31	653657.22	32.362732	-103.835690	7.83	76.67
	2831.00	0.23	118.23	2830.94	-8.06	2.01	8.47	0.19	496034.51	653658.07	32.362732	-103.835687	8.70	76.62
	3020.00	0.76	127.31	3019.93	-9.52	1.08	9.80	0.28	496033.58	653659.40	32.362730	-103.835683	9.86	83.74
	3115.00	1.66	132.19	3114.91	-11.22	-0.23	11.32	0.95	496032.27	653660.92	32.362726	-103.835678	11.32	91.17
	3209.00	2.00	137.89	3208.86	-13.63	-2.36	13.43	0.41	496030.14	653663.03	32.362720	-103.835671	13.63	99.98
	3303.00	1.25	154.14	3302.82	-15.49	-4.50	14.98	0.93	496028.00	653664.57	32.362714	-103.835666	15.64	106.73
	3398.00	0.56	200.08	3397.81	-15.98	-5.87	15.27	1.00	496026.63	653664.87	32.362710	-103.835665	16.36	111.03
	3492.00	0.81	226.13	3491.80	-15.49	-6.76	14.63	0.42	496025.74	653664.23	32.362708	-103.835667	16.12	114.80
	3586.00	0.84	220.44	3585.79	-14.72	-7.75	13.71	0.09	496024.75	653663.30	32.362705	-103.835670	15.74	119.48
9-5/8" Casing	3684.00	0.63	203.41	3683.78	-14.21	-8.78	13.03	0.31	496023.72	653662.63	32.362703	-103.835673	15.71	123.99
	3764.00	0.52	180.69	3763.78	-14.15	-9.55	12.85	0.31	496022.95	653662.45	32.362700	-103.835673	16.01	126.61
	3858.00	1.80	13.57	3857.77	-14.34	-8.54	13.19	2.46	496023.96	653662.79	32.362703	-103.835672	15.71	122.92
	3952.00	4.74	15.43	3951.60	-14.91	-3.36	14.57	3.13	496029.14	653664.17	32.362717	-103.835668	14.95	102.98
	4047.00	7.94	14.92	4046.01	-16.08	6.77	17.31	3.37	496039.27	653666.90	32.362745	-103.835659	18.58	68.64
	4141.00	11.51	16.05	4138.65	-17.97	22.06	21.57	3.80	496054.56	653671.17	32.362787	-103.835645	30.85	44.36
	4235.00	14.26	12.58	4230.27	-19.94	42.38	26.69	3.04	496074.87	653676.28	32.362843	-103.835628	50.08	32.20
	4329.00	16.95	7.45	4320.80	-20.40	67.27	30.99	3.21	496099.76	653680.58	32.362911	-103.835613	74.06	24.73
	4424.00	19.69	6.07	4410.98	-19.35	96.92	34.47	2.92	496129.41	653684.07	32.362993	-103.835602	102.87	19.58
	4518.00	22.91	2.58	4498.55	-16.65	130.95	36.97	3.68	496163.44	653688.57	32.363086	-103.835593	136.07	15.77
	4612.00	23.03	358.34	4585.10	-11.36	167.61	37.26	1.76	496200.10	653688.86	32.363187	-103.835592	171.71	12.53
	4707.00	23.02	351.25	4672.55	-2.42	204.55	33.90	2.92	496237.04	653693.50	32.363289	-103.835602	207.34	9.41
	4801.00	23.01	343.98	4759.09	10.80	240.39	26.03	3.02	496272.87	653675.63	32.363387	-103.835627	241.79	6.18
	4896.00	22.60	342.89	4846.66	26.53	275.68	15.54	0.62	496308.16	653665.14	32.363484	-103.835660	276.12	3.23
	4989.00	22.98	342.06	4932.40	42.48	310.03	4.69	0.54	496342.51	653654.29	32.363579	-103.835695	310.06	0.87
	5084.00	23.07	340.69	5019.83	59.56	345.24	-7.18	0.57	496377.71	653642.42	32.363676	-103.835733	345.31	358.81
	5178.00	23.02	337.48	5106.34	77.75	379.60	-20.31	1.34	496412.07	653629.29	32.363770	-103.835775	380.14	356.94
	5273.00	23.15	336.47	5193.73	97.36	413.88	-34.88	0.44	496446.35	653614.72	32.363865	-103.835821	415.35	355.18
	5368.00	23.72	336.11	5280.89	117.64	448.47	-50.07	0.62	496480.94	653599.53	32.363960	-103.835870	451.26	353.63
	5462.00	26.17	333.16	5366.12	139.90	484.26	-67.09	2.92	496516.73	653582.51	32.364059	-103.835925	488.89	352.11
	5556.00	25.72	330.08	5450.65	164.70	520.44	-86.63	1.51	496552.90	653562.98	32.364158	-103.835987	527.60	350.55
	5651.00	25.79	326.93	5536.22	191.36	555.62	-108.19	1.44	496588.09	653541.42	32.364255	-103.836057	566.06	348.98
	5745.00	27.60	323.92	5620.20	220.34	590.36	-132.17	2.40	496622.82	653517.44	32.364351	-103.836134	604.97	347.38
	5839.00	30.29	324.69	5702.45	252.18	627.31	-158.70	2.89	496659.77	653490.91	32.364453	-103.836219	647.07	345.80
	5934.00	33.83	325.49	5782.95	286.97	668.67	-187.54	3.75	496701.12	653462.07	32.364567	-103.836312	694.47	344.33
	6028.00	34.85	326.96	5860.56	322.79	712.74	-217.01	1.40	496745.20	653432.61	32.364689	-103.836407	745.05	343.07
	6123.00	34.73	326.24	5938.58	359.16	758.00	-246.85	0.45	496790.45	653402.77	32.364813	-103.836503	797.18	341.96
	6217.00	34.72	325.12	6015.84	395.72	802.22	-277.03	0.68	496834.66	653372.58	32.364935	-103.836600	848.71	340.95
	6312.00	35.89	324.69	6093.37	433.74	847.14	-308.60	1.26	496879.58	653341.02	32.365059	-103.836701	901.60	33

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	8294.00	37.47	323.42	7686.16	1265.62	1801.71	-1003.50	0.58	497834.09	652646.17	32.367692	-103.839837	2062.32	330.86
	8388.00	36.17	323.17	7760.41	1305.76	1846.87	-1037.17	1.39	497879.25	652612.50	32.367816	-103.839046	2118.17	330.68
	8482.00	34.43	321.82	7837.12	1344.98	1889.97	-1070.22	2.03	497922.34	652579.45	32.367935	-103.839152	2171.95	330.48
	8577.00	31.47	321.30	7916.83	1382.87	1930.44	-1102.33	3.13	497962.81	652547.34	32.368047	-103.839256	2223.00	330.27
	8671.00	27.16	316.99	7998.78	1417.81	1965.30	-1132.33	5.10	497997.67	652517.35	32.368143	-103.839352	2268.16	330.05
	8766.00	26.11	312.62	8083.71	1452.20	1995.31	-1162.51	2.34	498027.68	652487.17	32.368226	-103.839450	2309.26	329.77
	8860.00	26.24	310.45	8168.07	1487.05	2022.80	-1193.54	1.03	498055.17	652456.14	32.368302	-103.839550	2348.67	329.46
	8954.00	25.61	309.33	8252.61	1522.21	2049.16	-1225.07	0.85	498081.52	652424.61	32.368375	-103.839651	2387.43	329.13
	9049.00	23.25	310.02	8339.10	1555.92	2074.23	-1255.31	2.50	498106.60	652394.37	32.368444	-103.839749	2424.51	328.82
	9143.00	22.99	310.70	8425.55	1587.35	2098.13	-1283.44	0.40	498130.49	652366.25	32.368510	-103.839840	2459.55	328.55
	9181.00	23.41	310.59	8460.48	1600.06	2107.88	-1294.80	1.11	498140.24	652354.89	32.368537	-103.839876	2473.80	328.44
7-5/8" Casing	9271.00	23.34	311.93	8543.09	1630.16	2131.43	-1321.64	0.60	498163.79	652328.05	32.368602	-103.839963	2507.93	328.20
	9320.00	23.31	312.67	8588.09	1646.33	2144.49	-1335.99	0.60	498176.85	652313.70	32.368638	-103.840009	2526.60	328.08
	9415.00	22.61	307.25	8675.57	1677.98	2168.29	-1364.35	2.34	498200.64	652285.34	32.368704	-103.840101	2561.82	327.82
	9509.00	22.71	306.68	8762.31	1709.89	2190.06	-1393.28	0.26	498222.42	652256.41	32.368764	-103.840194	2595.69	327.54
	9603.00	23.58	306.10	8848.75	1742.62	2211.98	-1423.03	0.96	498244.33	652226.67	32.368825	-103.840290	2630.18	327.25
	9698.00	23.74	310.18	8935.77	1775.81	2235.51	-1452.99	1.73	498267.87	652196.70	32.368890	-103.840387	2666.22	326.98
	9792.00	22.07	306.57	9022.36	1807.57	2258.25	-1481.64	2.32	498290.60	652168.06	32.368953	-103.840479	2700.91	326.73
	9886.00	22.12	298.94	9109.47	1839.81	2277.34	-1511.31	3.05	498309.69	652138.39	32.369006	-103.840575	2733.19	326.43
	9980.00	21.77	296.75	9196.66	1872.99	2293.75	-1542.37	0.95	498326.10	652107.34	32.369051	-103.840675	2764.09	326.08
	10075.00	28.22	316.41	9282.87	1907.62	2318.01	-1573.67	10.99	498350.36	652076.03	32.369118	-103.840776	2801.72	325.83
	10170.00	37.50	322.94	9362.60	1946.23	2357.45	-1606.67	10.44	498389.80	652043.04	32.369227	-103.840883	2852.89	325.72
	10263.00	45.10	320.87	9432.42	1991.02	2405.67	-1644.57	8.30	498438.01	652005.14	32.369360	-103.841005	2914.08	325.64
	10358.00	51.00	309.15	9496.02	2047.96	2455.21	-1694.57	11.06	498487.55	651955.14	32.369497	-103.841166	2983.23	325.39
	10452.00	52.78	300.99	9554.10	2114.18	2497.59	-1755.05	7.09	498529.93	651894.67	32.369614	-103.841361	3052.57	324.90
	10547.00	56.88	292.62	9608.87	2187.93	2532.42	-1824.31	8.39	498564.76	651825.41	32.369711	-103.841585	3121.10	324.23
	10641.00	61.48	290.25	9657.02	2266.66	2561.88	-1899.44	5.35	498594.21	651750.29	32.369793	-103.841828	3189.21	323.45
	10735.00	63.22	291.49	9700.65	2348.06	2591.54	-1977.23	2.19	498623.87	651672.50	32.369875	-103.842079	3259.68	322.66
	10829.00	67.40	292.86	9739.90	2431.10	2623.79	-2056.29	4.64	498655.11	651593.44	32.369965	-103.842335	3333.56	321.91
	10923.00	74.26	285.72	9770.79	2518.29	2652.97	-2140.02	10.23	498685.29	651509.72	32.370046	-103.842605	3408.51	321.11
FTP [55° FNL, 100° FEL]	10984.00	78.56	279.41	9853.13	2577.41	2685.83	-2197.85	12.28	498698.15	651451.89	32.370082	-103.842793	3455.02	320.50
	11017.00	80.94	276.08	9791.01	2609.87	2670.20	-2230.02	12.28	498702.52	651419.72	32.370095	-103.842897	3478.93	320.13
	11112.00	85.93	268.48	9801.88	2703.54	2673.92	-2324.22	9.52	498706.24	651325.53	32.370106	-103.843202	3542.86	319.00
	11206.00	86.73	269.43	9807.90	2795.98	2672.21	-2418.01	1.32	498704.53	651231.74	32.370102	-103.843505	3603.82	317.86
	11301.00	89.77	270.60	9810.80	2889.83	2672.23	-2512.96	3.43	498704.56	651136.81	32.370104	-103.843813	3668.21	316.76
	11395.00	89.86	271.91	9811.10	2983.02	2674.29	-2606.93	1.40	498706.62	651042.84	32.370111	-103.844117	3734.69	315.73
	11489.00	90.35	272.92	9810.93	3076.45	2678.25	-2700.85	1.19	498710.58	650948.93	32.370123	-103.844421	3803.63	314.76
	11584.00	90.33	272.92	9810.37	3170.96	2683.09	-2795.72	0.02	498715.42	650854.06	32.370137	-103.844729	3874.93	313.82
	11678.00	90.21	272.76	9809.92	3264.46	2687.75	-2889.61	0.21	498720.07	650760.18	32.370151	-103.845033	3946.37	312.93
	11772.00	90.90	272.82	9809.01	3357.95	2692.33	-2983.49	0.74	498724.65	650666.31	32.370165	-103.845337	4018.68	312.06
	11867.00	90.60	272.91	9807.77	3452.44	2697.07	-3078.36	0.33	498729.40	650571.44	32.370179	-103.845644	4092.74	311.22
	11961.00	90.71	272.76	9806.69	3545.93	2701.72	-3172.24	0.20	498734.04	650477.57	32.370193	-103.845948	4166.82	310.42
	12055.00	90.65	270.73	9805.58	3639.22	2704.58	-3266.19	2.16	498736.91	650383.63	32.370202	-103.846252	4240.61	309.63
	12150.00	90.73	270.89	9804.43	3733.31	2705.93	-3361.17	0.19	498738.25	650288.65	32.370207	-103.846560	4315.03	308.84
	12238.00	90.85	271.02	9801.84	3919.56	2709.06	-3549.13	0.09	498741.38	650100.71	32.370218	-103.847168	4464.90	307.35
	12433.00	90.90	271.11	9800.39	4013.70	2710.83	-3644.10	0.11	498743.15	650005.74	32.370224	-103.847476	4541.81	306.65
	12527.00	90.69	271.21	9799.09	4106.87	2712.73	-3738.07	0.25	498745.05	649911.78	32.370230	-103.847780	4618.66	305.97
	12621.00	90.73	271.13	9797.92	4200.04	2714.65	-3832.04	0.10	498746.97	649817.81	32.370237	-103.848084	4696.15	305.31
	12715.00	90.79	271.23	9796.68	4293.22	2716.67	-3926.01	0.22	498748.99	649723.85	32.370244	-103.848389	4774.29	304.68
	12810.00	90.75	271.23	9795.40	4387.41	2718.79	-4020.98	0.11	498751.11	649629.88	32.370251	-103.848696	4853.87	304.06
	12909.00	90.85	271.92	9792.76	4574.92	2723.98	-4209.89	0.37	498756.30	649439.99	32.370267	-103.849008	5014.30	302.90
	13094.00	90.80	270.77	9791.39	4669.11	2726.21	-4304.85	1.21	498758.53	649345.03	32.370274	-103.849615	5095.49	302.35
	13188.00	90.61	269.38	9790.24	4762.03	2726.33	-4398.84	1.49	498758.65	649251.05	32.370276	-103.849920	5175.20	301.79
	13283.00	91.12	269.80	9788.80	4855.81	2726.65	-4493.83	0.70	498757.98	649156.07	32.370275	-103.850227	5255.82	301.24
	13377.00	91.22	268.84	9786.88	4948.52	2724.54	-4587.80	1.03	498756.86	649062.10	32.370273	-103.850532	5335.83	300.70
	13471.00	92.05	270.29	9784.20	5041.28	2723.83	-4681.76	1.78	498756.15	648968.15	32.370273	-103.850836	5416.46	300.19
	13566.00	92.34	269.65	9780.56	5135.10	2723.78	-4776.69	0.74	498756.10	648873.23	32.370274	-103.851144	5498.70	299.69
	13660.00	92.40	269.61	9776.67	5227.84	2723.17	-4870.60	0.08	498755.49	648779.32	32.370273	-103.851448	5580.18	299.21
	13754.00	92.80	270.16	9772.41	5320.62	2722.98	-4964.51	0.72	498755.30	648685.42	32.370274	-103.851752	5662.24	298.70
	13849.00	91.94	270.91	9768.48	5414.56	2723.87	-5059.42	1.20	498756.19	648590.51	32.370277	-103.852059	5746.06	298.34
	13943.00	91.21	269.43	9765.90	5507.48	2724.15	-5153.38	1.76	498756.47	648496.56	32.370279	-103.852364	5829.09	297.86
	14037.00	90.54	269.12	9764.46	5600.19	2722.96	-5247.36	0.79	498755.28	648402.58	32.370277	-103.852668	5911.79	297.43
	14132.00	91.21	269.08	9763.01	5693.83	2721.46	-5342.34	0.71	498753.79	648307.61	32.370274	-103.852976	5995.58	296.99
	14226.00	90.52	269.30	9761.59	5786.52	2720.14	-5436.32	0.77	498752.46	648213.64	32.370272	-103.853280	6078.87	296.58
	14320.00	89.92	267.58	9761.23	5879.00	2717.58	-5530.28	1.94	498749.90	648119.69	32.370266	-103.853584	6161.92	296.17
	14415.00	89.87	266.16	9761.41	5971.97	2712.39	-5625.13	1.50	498744.71	648024.84	32.370253	-103.853892	6244.93	295.74
	14505.00	88.41	265.77	9762.76	6059.72	2706.06	-5714.90	1.68	498738.38	647935.08	32.370237	-103.854182	6323.20	295.34
	14600.00	90.25	2											

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	19881.00	90.31	270.04	9708.18	11372.56	2708.41	-11089.79	0.24	498740.73	642560.54	32.370308	-103.871590	11415.73	283.72
	19976.00	90.40	270.17	9707.60	11466.48	2708.58	-11184.79	0.17	498740.91	642465.55	32.370310	-103.871897	11508.08	283.61
	20071.00	90.45	270.36	9706.89	11560.44	2709.02	-11279.78	0.21	498741.35	642370.56	32.370312	-103.872205	11600.53	283.50
	20165.00	90.46	269.77	9706.14	11653.36	2709.13	-11373.78	0.63	498741.45	642276.57	32.370313	-103.872509	11691.98	283.40
	20260.00	90.57	269.16	9705.29	11747.12	2708.24	-11468.77	0.65	498740.57	642181.58	32.370312	-103.872817	11784.20	283.29
	20353.00	90.48	268.73	9704.44	11838.76	2706.53	-11561.75	0.47	498738.85	642088.61	32.370308	-103.873118	11874.32	283.18
	20447.00	90.53	268.62	9703.61	11931.31	2704.36	-11655.72	0.13	498736.68	641994.64	32.370303	-103.873422	11965.34	283.06
	20637.00	90.49	268.98	9701.92	12118.45	2700.38	-11845.67	0.19	498732.70	641804.71	32.370295	-103.874038	12149.57	282.84
	20731.00	90.92	269.21	9700.76	12211.11	2698.89	-11939.66	0.52	498731.22	641710.73	32.370292	-103.874342	12240.89	282.74
	20825.00	90.65	269.21	9699.47	12303.81	2697.60	-12033.64	0.29	498729.92	641616.75	32.370289	-103.874646	12332.29	282.64
	20920.00	90.59	269.56	9698.45	12397.54	2696.58	-12128.63	0.37	498728.90	641521.77	32.370288	-103.874954	12424.78	282.53
	21013.00	90.53	269.83	9697.54	12489.38	2696.08	-12221.62	0.30	498728.41	641428.78	32.370287	-103.875255	12515.47	282.44
	21107.00	90.99	269.95	9696.29	12582.25	2695.90	-12315.61	0.51	498728.23	641334.80	32.370288	-103.875560	12607.23	282.35
	21202.00	88.67	268.86	9696.57	12675.98	2694.92	-12410.60	2.70	498727.24	641239.82	32.370286	-103.875867	12699.82	282.25
	21296.00	90.74	269.43	9697.06	12768.66	2693.51	-12504.58	2.28	498725.84	641145.84	32.370284	-103.876172	12791.39	282.16
	21390.00	90.82	269.68	9695.78	12861.45	2692.78	-12598.57	0.28	498725.11	641051.86	32.370283	-103.876476	12883.13	282.06
	21485.00	90.43	269.66	9694.74	12955.25	2692.24	-12693.56	0.41	498724.56	640956.87	32.370282	-103.876784	12975.93	281.97
	21579.00	90.52	268.93	9693.96	13047.97	2691.08	-12787.55	0.78	498723.40	640862.89	32.370280	-103.877088	13067.65	281.88
	21674.00	90.63	269.22	9693.01	13141.62	2689.55	-12882.53	0.33	498721.87	640767.91	32.370277	-103.877396	13160.29	281.79
	21768.00	90.55	269.48	9692.04	13234.36	2688.48	-12976.52	0.29	498720.80	640673.93	32.370275	-103.877700	13252.10	281.70
	21862.00	90.68	269.59	9691.03	13327.14	2687.72	-13070.51	0.18	498720.04	640579.95	32.370274	-103.878005	13343.99	281.62
	21957.00	90.62	270.28	9689.95	13421.02	2687.61	-13165.51	0.73	498719.93	640484.96	32.370275	-103.878312	13437.03	281.54
	22052.00	90.68	270.15	9688.88	13514.96	2687.97	-13260.50	0.15	498720.29	640389.97	32.370277	-103.878620	13530.19	281.46
	22146.00	91.47	270.21	9687.11	13607.90	2688.26	-13354.48	0.84	498720.58	640296.00	32.370279	-103.878924	13622.37	281.38
	22241.00	91.50	269.78	9684.65	13701.76	2688.25	-13449.45	0.45	498720.58	640201.04	32.370280	-103.879232	13715.48	281.30
	22336.00	91.67	270.35	9682.02	13795.64	2688.36	-13544.41	0.63	498720.68	640106.08	32.370282	-103.879539	13808.64	281.23
	22430.00	91.08	270.32	9679.77	13888.60	2688.91	-13638.38	0.63	498721.23	640012.11	32.370284	-103.879844	13900.93	281.15
	22525.00	91.02	270.37	9678.03	13982.57	2689.48	-13733.37	0.08	498721.81	639917.14	32.370287	-103.880151	13994.24	281.08
	22619.00	91.09	270.35	9676.29	14075.55	2690.07	-13827.35	0.08	498722.40	639823.16	32.370290	-103.880456	14086.59	281.01
	22713.00	91.14	270.42	9674.47	14168.53	2690.70	-13921.33	0.09	498723.03	639729.19	32.370293	-103.880760	14178.97	280.94
	22807.00	91.04	270.07	9672.68	14261.48	2691.11	-14015.31	0.39	498723.43	639635.21	32.370295	-103.881064	14271.34	280.87
	22902.00	91.41	270.27	9670.65	14355.40	2691.39	-14110.29	0.44	498723.71	639540.24	32.370297	-103.881372	14364.67	280.80
	22996.00	89.98	270.28	9669.51	14448.37	2691.84	-14204.28	1.52	498724.16	639446.26	32.370299	-103.881676	14457.09	280.73
	23091.00	90.01	270.24	9669.51	14542.33	2692.27	-14299.28	0.05	498724.59	639351.26	32.370301	-103.881984	14550.52	280.66
	23185.00	90.22	270.24	9669.33	14635.30	2692.66	-14393.28	0.22	498724.99	639257.27	32.370303	-103.882289	14642.98	280.60
	23279.00	90.12	270.05	9669.05	14728.24	2692.90	-14487.28	0.23	498725.22	639163.28	32.370305	-103.882593	14735.43	280.53
	23373.00	89.92	270.27	9669.01	14821.19	2693.16	-14581.28	0.32	498725.49	639069.29	32.370307	-103.882897	14827.90	280.46
	23467.00	90.05	270.26	9669.04	14914.16	2693.60	-14675.27	0.14	498725.92	638975.29	32.370309	-103.883202	14920.43	280.40
	23561.00	89.31	269.53	9669.56	15007.04	2693.43	-14769.27	1.11	498725.75	638881.30	32.370310	-103.883506	15012.86	280.34
	23655.00	90.20	270.23	9669.97	15099.92	2693.23	-14863.27	1.20	498725.55	638787.31	32.370310	-103.883811	15105.31	280.27
	23750.00	89.90	270.21	9669.88	15193.87	2693.60	-14958.27	0.32	498725.92	638692.32	32.370312	-103.884118	15198.86	280.21
	23845.00	90.50	270.45	9669.55	15287.84	2694.14	-15053.27	0.68	498726.46	638597.33	32.370315	-103.884426	15292.46	280.15
	23939.00	89.50	271.13	9669.55	15380.94	2695.44	-15147.25	1.29	498727.76	638503.34	32.370320	-103.884730	15385.21	280.09
	24032.00	89.82	270.06	9670.10	15473.00	2696.40	-15240.25	1.20	498728.73	638410.36	32.370323	-103.885031	15476.94	280.03
LTP [0° FNL, 145° FWL]	24126.00	90.03	270.02	9670.23	15565.92	2696.47	-15334.25	0.23	498728.79	638316.36	32.370325	-103.885336	15569.52	279.97
Final Surveys	24127.00	90.03	270.02	9670.23	15566.91	2696.47	-15335.25	0.23	498728.79	638315.36	32.370325	-103.885339	15570.51	279.97
Projection to Bit [0° FNL, 65° FWL]	24174.00	89.82	270.06	9670.29	15613.36	2696.50	-15382.25	0.45	498728.83	638268.37	32.370325	-103.885491	15616.81	279.94
	24204.00	89.82	270.06	9670.38	15643.02	2696.53	-15412.25	0.00	498728.86	638236.37	32.370326	-103.885589	15646.36	279.92

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 3 *** 3-D 73.854% Confidence 2.0000 sigma
Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
Schlumberger / xBolt	1	0.000	32.000	1/98.425	17.500	13.375	A008Mb_MWD+IFR1+MS-Depth Only	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H 0' to 24204' MD
Schlumberger / xBolt	1	32.000	32.000	Act Stns	17.500	13.375	A008Mb_MWD+IFR1+MS-Depth Only	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H 0' to 24204' MD
Schlumberger / xBolt	1	32.000	577.000	Act Stns	17.500	13.375	A008Mb_MWD+IFR1+MS	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H
Schlumberger / xBolt	1	577.000	3684.000	Act Stns	12.250	9.625	A008Mb_MWD+IFR1+MS	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H
Schlumberger / xBolt	1	3684.000	9271.000	Act Stns	8.750	7.625	A008Mb_MWD+IFR1+MS	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H
Schlumberger / xBolt	1	9271.000	24204.000	Act Stns	6.750	5.500	A008Mb_MWD+IFR1+MS	James Ranch Unit DI 2 704H / XTO James Ranch Unit DI 2 704H

Submit a Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-48531
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☐ X Fed ☐
2. Name of Operator XTO PERMIAN OPERATING LLC.		6. State Oil & Gas Lease No.
3. Address of Operator 6401 HOLIDAY HILL ROAD BUILDING 5, MIDLAND, TX 79707		7. Lease Name or Unit Agreement Name James Ranch Unit DI 2
4. Well Location Unit Letter <u>K</u> : <u>2250</u> feet from the <u>South</u> line and <u>2080</u> feet from the <u>West</u> line Section <u>25</u> Township <u>22S</u> Range <u>30E</u> NMPM County <u>Eddy</u>		8. Well Number <u>704H</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3344 GL		9. OGRID Number <u>373075</u>
		10. Pool name or Wildcat Los Medanos; Bone Spring (Oil)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
DOWNHOLE COMMINGLE ☐	P AND A ☐
CLOSED-LOOP SYSTEM ☐	CASING/CEMENT JOB ☐
OTHER: ☐	OTHER: Completions Sundry ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

XTO Permian Operating LLC respectfully submits this sundry to report the completion operations of the above well.

KOP @ depth 10,020 ft.PBTD = 24,192 ft.12/1/21 Run RCB/GR/CCL 1/30/22 Pressure test 5 in csg to 8,122 psi for 30min test good, open sleeve. 3/26/22 Perf and frac 65 stages, 1,536 total shots, from 11,062 to 24,026 using 687,740 bbls of fluid and 32,500,627 lbs Proppant.Tag and drill out plugs.6/20/22 Run 2-7/8 L80 6.5# tubing set at 9,990 ft.6/20/22 Packer setting depth 9,974 ft.Ready Date: 7/8/2022First Production: 7/9/2022

Spud Date:

7/12/2021

Rig Release Date:

9/16/2021

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Amanda Thames TITLE Regulatory Analyst DATE 7/28/2022

Type or print name Amanda Thames E-mail address: amanda.thames@exxonmobil.com PHONE: 432.221.7340

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017				
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name JAMES RANCH UNIT DI 2		
								6. Well Number: 704H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator XTO PERMIAN OPERATING LLC.						9. OGRID 373075				
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat LOS MEDANOS;BONE SPRING (OIL)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	K	25	22S	30E		2250	South	2080	West	Eddy
BH:	B	28	22S	30E		0	South	2617	East	Eddy
13. Date Spudded 7/12/2021	14. Date T.D. Reached 9/13/2021		15. Date Rig Released 9/16/2021		16. Date Completed (Ready to Produce) 7/8/2022			17. Elevations (DF and RKB, RT, GR, etc.) 3344' GL		
18. Total Measured Depth of Well 24,204			19. Plug Back Measured Depth 24,192		20. Was Directional Survey Made? Yes			21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 11,062 TO 24,026 LOS MEDANOS;BONE SPRING (OIL)										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13 3/8"		54.5		645'		17 1/2"		805		
9 5/8"		40.0		3,674'		12 1/4"		1,375		
7 5/8"		29.7		9,261'		8 3/4"		1,565		
5"		18.0		24,194'		6 3/4"		1,715		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET			
					2 7/8"	9,990	9,974			
26. Perforation record (interval, size, and number) 11,062 TO 24,026 4spf, 1,564 Total Shots 65 stages					27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
					DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
					11,062 TO 24,026		687,740 bbl fluid + 32,500,627 lbs Proppant			
28. PRODUCTION										
Date First Production 7/9/22		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing				Well Status (Prod. or Shut-in) Producing				
Date of Test 7/14/22	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 957	Gas - MCF 1564	Water - Bbl. 3598	Gas - Oil Ratio 1,635			
Flow Tubing Press. 235	Casing Pressure 15	Calculated 24-Hour Rate	Oil - Bbl. 957	Gas - MCF 1564	Water - Bbl. 3598	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold							30. Test Witnessed By			
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.							33. Rig Release Date:			
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude			Longitude			NAD83				
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature <i>Amanda Thames</i>			Printed Name Amanda Thames			Title Regulatory Analyst			Date 7/28/2022	
E-mail Address amanda.thames@exxonmobil.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 681'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 3,567'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 3,822'	T. Morrison	
T. Drinkard	T. Bone Springs 8,501'	T. Todilto	
T. Abo	T. Rustler 381'	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 129647

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 129647
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 129647

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 129647
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
crystal.walker	None	10/1/2025