Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

5. Lease Serial No. NINGERTON

Bord	Enteron Entropy with widewiter vi		ŗ	MSF079366
	OTICES AND REPORTS ON W		6. If Indian, Allottee	or Tribe Name
	orm for proposals to drill or to Jse Form 3160-3 (APD) for suc		EASTERN NAVA	JO
SUBMIT IN 1	TRIPLICATE - Other instructions on pag	e 2	_	ement, Name and/or No.
1. Type of Well				ATE/NMNM78406X
☐ Oil Well ✓ Gas W			8. Well Name and No	RINCON UNIT/715H
2. Name of Operator ENDURING RE	SOURCES LLC		9. API Well No. 3003	3931374
3a. Address 200 ENERGY COURT,	FARMINGTON, NM 8740 3b. Phone No. (505) 497-85		10. Field and Pool or BASIN MANCOS/	
4. Location of Well (Footage, Sec., T.,R	.,M., or Survey Description)		11. Country or Parish	, State
SEC 21/T27N/R6W/NMP			RIO ARRIBA/NM	
12. CHE	CK THE APPROPRIATE BOX(ES) TO INI	DICATE NATURE OF NOTI	CE, REPORT OR OT	HER DATA
TYPE OF SUBMISSION		TYPE OF AC	TION	
Notice of Intent	Acidize Deep Alter Casing Hydr		uction (Start/Resume) amation	Water Shut-Off Well Integrity
Subsequent Report		_	omplete	✓ Other
Final Abandonment Notice			porarily Abandon er Disposal	
completion of the involved operation completed. Final Abandonment Not is ready for final inspection.) Enduring Resources performed EOT: 7126 MD XN Nipple: 7091 MD X Nipple: 6661 MD Job End Date: 10.3.2023	be perfonned or provide the Bond No. on forms. If the operation results in a multiple confices must be filed only after all requirement d a tubing reconfiguration on the subject	npletion or recompletion in a s, including reclamation, hav	new interval, a Form 3 e been completed and	160-4 must be filed once testing has been the operator has detennined that the site
14. I hereby certify that the foregoing is HEATHER HUNTINGTON / Ph: (50	, , ,	Permitting Technician	an	
Signature (Electronic Submission	n)	Date	10/27/2	2023
	THE SPACE FOR FEDI	ERAL OR STATE OF	ICE USE	
Approved by				
MATTHEW H KADE / Ph: (505) 56	4-7736 / Accepted	Petroleum Eng Title	gineer	10/27/2023 Date
	ned. Approval of this notice does not warran quitable title to those rights in the subject le duct operations thereon.		ON .	
Title 18 U.S.C Section 1001 and Title 43	3 U.S.C Section 1212, make it a crime for ar	ny person knowingly and will	fully to make to any d	epartment or agency of the United States

any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

 $0. \ SHL: \ NENE \ / \ 1152 \ FNL \ / \ 1273 \ FEL \ / \ TWSP: \ 27N \ / \ RANGE: \ 6W \ / \ SECTION: \ 21 \ / \ LAT: \ 36.563928 \ / \ LONG: \ -107.467888 \ (\ TVD: \ 0 \ feet, \ MD: \ 0 \ feet \)$ $PPP: \ SWNE \ / \ 2400 \ FNL \ / \ 1613 \ FEL \ / \ TWSP: \ 27N \ / \ RANGE: \ 6W \ / \ SECTION: \ 21 \ / \ LAT: \ 36.56049 \ / \ LONG: \ -107.469134 \ (\ TVD: \ 5933 \ feet, \ MD: \ 5982 \ feet \)$ $BHL: \ SWNE \ / \ 2382 \ FNL \ / \ 785 \ FEL \ / \ TWSP: \ 27N \ / \ RANGE: \ 6W \ / \ SECTION: \ 19 \ / \ LAT: \ 36.560012 \ / \ LONG: \ -107.502169 \ (\ TVD: \ 6518 \ feet, \ MD: \ 15870 \ feet \)$



WellView^s

Enduring Resources IV - Production WBD

Well Name: RINCON UNIT 715H

NOTE: Well schematic is drawn vertically due to space constraints on the report. Please reference the directional surveys as needed.

20 020 24274		Field Name Rincon	**	l .	Well Configuration Type Horizontal
Original KB Elevation (ft) 6,551.00	KB-Tubing Head Distance (ft)	Spud Date 11/12/2018 09:00	Rig Release Date		Total Depth All (TVD) (ftKB) Original Hole - 6,464.4

6,551.0	IU .	11/12/2018 09:00	_ <u>_</u>							riginal Hole	- 6,464.4
	Horizontal	I, Original Hole, 10/6/2023 10:53:21 AM	Wellbore Sect	ions				A of T	n A=4=	Top A=4 B4	A of Dir
MD				tion Des			ize (in)	Act Top (ftKB)	(TVD)	(ftKB) (ftKB)	(TVD) (ftKE
(ftKB)		Vertical schematic (actual)	Surface Hole				17 1/2	13	3.0	350	
` '			Intermediate				12 1/4	350		6,089	.0 5,925.
0.0	1 N		Production				8 1/2	6,089	5,92	2 <mark>5.7</mark> 16,578	.0 6,464.
13.1 —	IIII AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	Des:Tubing Hanger; OD:2 7/8 in; ID:2.44 in;	Rod Strings								
13.5		Length:0.40 ft; Top MD:13.1 ftKB	Rod Description		Run Date			String Len	gth (ft)	Set Depth	(ftKB)
15.4									1		
- 18.0 -			It	em Des			Jts	OD (in)	Len (ft	:) Top (ftKB) Btm (ftKB)
18.7 –											
21.7 –			Tubing - Prod	uction							
40.0			Tubing Description Tubing - Produ	otion	Run Date 10/3/20			String Len 7,112.6		Set Depth 7.125.8	
- 43.3 -			Item Des	Jts	Grade						
88.6	 		Tubing	1	L-80	6.50	2 7/			.40 13	
301.2			Hanger								
302.5			Tubing	204	L-80	6.50	2 7/				
343.8 -			X Nipple	1	L-80	6.50	2 7/		l l	.20 6,661	
345.5			Tubing	13	L-80	6.50	2 7/				
- 348.1 -			XN Nipple No-	1	L-80	6.50	2 7/	8 2.2	1 1	.20 7,091	.2 7,092.
- 350.1 -			Go	1	1.00	0.50	0.7/	0 0 4	4 20	CE 7.000	4 7405
4,779.2			Tubing Half Mule	1	L-80	6.50 6.50	2 7/3			7,092	
- 4,781.8 -			Shoe	1	L-80	6.50	27/	8 2.4	4 0	7,125	.0 7,125.
- 4,791.3 -											
- 4,799.9 -)	Surface Casin					•			
- 4,808.1 -				Wt/Len (54.50	lb/ft)	String Gra	ade	Top Conr	nection	Top (ftKB) 13.0	Set Depth (ftKB) 345.4
- 6,036.1 -			10 0/0	Item D	es	0 00	J	ts	Len (ft)	Top (ftKB)	Btm (ftKB)
- 6,037.4 -			Casing Joints					7	288.26	13.0	301.3
6,077.1			Float Collar Casing Joints					1	1.24	301.3	302.5
- 6,079.1 -								1	41.25	302.5	
- 6,088.9 -		1	Float Shoe 1 1.65 343.8						345.4		
- 6,136.2 -	·······		Intermediate, 6,079.0ftKB								
- 6,138.1 -		[n		Wt/Len (lb/ft)	String Gra	ade	Top Conr	nection		Set Depth (ftKB)
- 6,661.1 -		Des:X Nipple; OD:2 7/8 in; ID:2.31 in; Length:1.20 ft; Top MD:6,661.1 ftKB	9 5/8	36.00	los	J-55		ts LT&C	Len (ft)	15.4 Top (ftKB)	6,079.0 Btm (ftKB)
6,662.4		Length. 1.20 ft, Top MD.0,001.1 ftND	Casing Joints				3	0	0.00	15.4	15.4
- 7,057.4 - - 7.079.4 -	8		Landing Joint					0	0.00	15.4	15.4
, .	8		Casing Hanger	-				1	3.20	15.4	18.6
- 7,091.2 - - 7,092.2 -		Des:XN Nipple No-Go; OD:2 7/8 in; ID:2.21	Pup					1	3.00	18.6	21.6
		in; Length:1.20 ft; Top MD:7,091.2 ftKB	Casing Joints	8			1	120 4	4,757.67	21.6	4,779.3
- 7,125.0 - - 7,125.7 -		Des:Tubing - Production; OD:2 7/8 in;	DV tool					1	2.60	4,779.3	4,781.9
8,962.9		ID:2.21 in; Length:7,112.67 ft; Top MD:13.1 ftKB	Casing Pup Jo					1	9.50	4,781.9	
- 8,984.9 -		L = J'	External Casin	g Pack	er			1	16.60	4,791.4	
10,822.5			Casing Joints					31	1,228.20	4,808.0	
10,822.5			Float Collar					1	1.20	6,036.2	
- 12,728.0 -			Casing Joints					1	39.60	6,037.4	
12,750.0			Shoe					1	1.98	6,077.0	6,079.
	(A)		Production, 1	,							
- 14.631.6				Wt/Len (20.00	lb/ft)	String Gra	ade	Top Conr Buttres			Set Depth (ftKB) 16,568.0
- 14,631.6 - - 14.653.9 -			5 1/2			- 1 10				40.0	10,500.0
14,631.6 - 14,653.9 - 16,269.0 -			5 1/2					Thread			
- 14,653.9 -			5 1/2	Item D	es		J		Len (ft)	Top (ftKB)	Btm (ftKB)
14,653.9 - 16,269.0 -	· · ·		5 1/2 Marker Joint 7)es		J			Top (ftKB) 40.0	40.
14,653.9 - 16,269.0 - 16,270.0 -	· · · · · · · · · · · · · · · · · · ·		Marker Joint 7 Casing Joints		Des		J	ts	Len (ft)		40.
14,653.9 16,269.0 16,270.0 16,490.2 16,495.1	· · · · · · · · · · · · · · · · · · ·		Marker Joint 7 Casing Joints Landing joint	Item D	es .		J	ts 0	0.00 0.00 0.00 0.00	40.0 40.0 40.0	40. 40. 40.
14,653.9 - 16,269.0 - 16,270.0 - 16,490.2 - 16,495.1 - 16,539.0 -			Marker Joint 7 Casing Joints Landing joint Casing Hanger	Item D	les .		J	ts 0 0	0.00 0.00 0.00 0.00 3.20	40.0 40.0 40.0 40.0	40. 40. 40. 43.
14,653.9 16,269.0 16,270.0 16,490.2 16,495.1 16,539.0 16,541.3			Marker Joint 7 Casing Joints Landing joint Casing Hanger Casing w/ pup	Item D	Des			0 0 0 1	0.00 0.00 0.00 0.00 3.20 45.44	40.0 40.0 40.0 40.0 43.2	40. 40. 40. 43. 88.
14,653.9 - 16,269.0 - 16,270.0 - 16,490.2 - 16,495.1 - 16,539.0 - 16,563.0 - 16,563.0 -			Marker Joint 7 Casing Joints Landing joint Casing Hanger Casing w/ pup Casing Joints	Item D	des			0 0 0 1	0.00 0.00 0.00 0.00 3.20 45.44 6,047.60	40.0 40.0 40.0 40.0 43.2 88.7	40. 40. 40. 43. 88. 6,136.
14,653.9 16,269.0 16,270.0 16,490.2 16,495.1 16,539.0 16,563.0 16,565.3			Marker Joint 7 Casing Joints Landing joint Casing Hanger Casing w/ pup Casing Joints Air Lock	Item D	es			0 0 0 1 1 138 0	0.00 0.00 0.00 3.20 45.44 6,047.60	40.0 40.0 40.0 40.0 43.2 88.7 6,136.3	40. 40. 43. 88. 6,136. 6,138.
14,653.9 - 16,269.0 - 16,270.0 - 16,490.2 - 16,490.1 - 16,539.0 - 16,541.3 - 16,565.3 - 16,565.3 - 16,567.9 -			Marker Joint 7 Casing Joints Landing joint Casing Hanger Casing w/ pup Casing Joints Air Lock Casing Joints	Item D	des			0 0 0 1 1 138	0.00 0.00 0.00 3.20 45.44 6,047.60 1.92 919.25	40.0 40.0 40.0 40.0 43.2 88.7 6,136.3 6,138.2	40.0 40.0 43.2 88.3 6,136.3 6,138.3 7,057.9
14,653.9 - 16,269.0 - 16,270.0 - 16,490.2 - 16,495.1 - 16,539.0 - 16,541.3 - 16,563.0 - 16,565.3 -			Marker Joint 7 Casing Joints Landing joint Casing Hanger Casing w/ pup Casing Joints Air Lock	Item D	Des			tts 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.00 0.00 0.00 3.20 45.44 6,047.60	40.0 40.0 40.0 40.0 43.2 88.7 6,136.3	40.0 40.0 43.2 88.3 6,136.3 6,138.2 7,057.9 7,079.4

WellView^s

Enduring Resources IV - Production WBD

Well Name: RINCON UNIT 715H

Released to Imaging: 12/5/2025 10:25:36 AM

NOTE: Well schematic is drawn vertically due to space constraints on the report. Please reference the directional surveys as needed.

Surface Legal Location NE/4, NE/4, Section 21, Twp 27N, Rng 06	**	Well Configuration Type Horizontal
	Rig Release Date	Total Depth All (TVD) (ftKB) Original Hole - 6,464.4

0,001.0	-						original riolo	s, . v
	Horizontal, Origir	nal Hole, 10/6/2023 10:53:22 AM	Item Des Marker 5		Jts 1	Len (ft) 21.78	Top (ftKB) 8,963.1	8,984.9
MD	.,	anticol colores to testing to	Casing Joints		42	1,837.69		10,822.6
(ftKB)	V	ertical schematic (actual)	Marker4		1	-		10,844.3
			Casing Joints		43	1.883.79		12,728.1
- 0.0 -	W M		Marker 3		1	,		12,749.9
_ 13.1 _	D	es:Tubing Hanger; OD:2 7/8 in; ID:2.44 in;	Casing Joints		43	1,881.56		14,631.5
- 13.5 -	Le	ength:0.40 ft; Top MD:13.1 ftKB			1	· · · · · · · · · · · · · · · · · · ·	1	14,653.8
_ 15.4 _			Casing Joints		42	1,836.29		16,490.1
- 18.0 -			Toe Sleeve 10,500		1			16,495.2
- 18.7 -			Casing Joints		1			16,539.0
- 21.7 -			Float Collar			2.42		16.541.4
- 40.0 -			Marker 1		1			16.562.9
- 43.3 -			Float Collar		1			16,565.4
- 88.6 -			Float Shoe		1			16,568.0
301.2			Cement		_		10,00011	,
302.5			Description	Cementing Start	Date	Cer	menting End Date	
- 343.8 -			Surface Casing Cement	11/16/2018		11	/16/2018	
- 345.5 - - 348.1 - - 350.1 -			Comment Pump 20 bbls FW spacer & disp w/ 44.2 bbls H2O, Check float, float held.	bump plug @ Î	145 psi	, circ 30 bbls	s good cmt to s	drop plug surface.
4,779.2 - 4,781.8 - 4,791.3 -			Description Intermediate Casing Cement Comment	Cementing Start 9/27/2022	Date		menting End Date 28/2022	
4,799.9 4,808.1 6,036.1 6,037.4 6,077.1 6,079.1 6,088.9 6,136.2 6,138.1 6,661.1 6,662.4 7,057.4 7,079.4		es:X Nipple ; OD:2 7/8 in; ID:2.31 in; ength:1.20 ft; Top MD:6,661.1 ftKB	Complete Stage 1 as Follines to 2500 psi. Pumper (162 sx) 90:10 Poz:Type I Tail Cement: 36.9 bbls (1 H2O/sk. Dropped plug & FCP at 181 psi and plug the floats held. Lost returns from the surface and got 35 bbls of of tail at 5582 ft MD. Set Pump Stage 2 As Follows Spacer. Pumped Stage 2 12.5 ppg, 2.22 ft3/sk, 12.5 Displaced with 369.4 bbls 2515 psi. DV Tool Close 50 bbl's Cement To Surface Description	d 50 bbls EZ S //II at 12.5 ppg 51 sx) Type I/I began displace por final 60 bbls f good cement Packer. E: PJSM with A 2 Cement: 448 3 gal H2O/sk. FW. FCP at 1 d. Bled back 3	Spacer., 2.22 ft I Blend ement. om to 50 to surfator bls. Dropp 1130 ps 3.0 Bbls es	Pumped Le 3/sk, 12.53 (at 14.6 ppg, Displaced v 000 psi. Blec clace. Top of I are. Top of I (1,127 sx) 9 (1,127 sx) 9 (and I gain and I glug & be and I glug b an	ead Cement: 7 gal H2O/sk. Pu , 1.38 ft3/sk, 6.4 with 466.7 bbls d back 1.0 Bbls Calculated 35 b Lead to 4800 ft g. Pumped 50 90:10 Poz:Type egan displacem umped at 4. bp	4 bbls umped 64 gal FW. s and bbls to t and top bbls EZ e I/II at nent. om to
7,091.2 -	in in	es:XN Nipple No-Go; OD:2 7/8 in; ID:2.21 ; Length:1.20 ft; Top MD:7,091.2 ftKB	Production Casing Cement	10/17/2022	Date		Menting End Date 0/17/2022	
7,125.0 7,125.7 8,962.9 8,984.9 10,822.5 10,844.5 12,728.0 12,750.0 14,631.6 14,653.9 16,269.0	<mark> </mark>	es:Tubing - Production; OD:2 7/8 in; b:2.21 in; Length:7,112.67 ft; Top MD:13.1 KB	Comment Cement Summary: PJSM psi. Pumped 60 bblsEZ S 667 sx) ASTM Type I/II at Cement: 484.5 bbls (1,7: H2O/sk. Washed lines, d bbls FW with cement reta bpm to 3,123- psi. Bled I 12:00 - 10/17/2022 Top of Tail: Calculated 4,9 Top of Lead: Surface Cement Back 40 BBL, Ca	Spacer @11.0 12.4 ppg, 2.37 39 sx) Class (ropped plug & rder in 1st 50 l back 3.5 Bbls 111 ft MD.	ppg. P 7 ft3/sk 3 Ceme began bbls. Fo and floa	Pumped Leac , 13.38 gal h ent at 13.3 pp displacemer CP at 2,216- ats held. C	d Cement: 281 H2O/sk. Pumpi pg, 1.57 ft3/sk, nt. Displaced w psi Bump Plu cement From 06	I.1 bbls ed Tail 7.68 gal vith 367 ug at 4.0 600 To
- 16,270.0 - - 16,490.2 - - 16,495.1 -			Cement in place at 10:55	on 10/17/2022	., Wash	Through All	Cement Lines	·
- 16,495.1 - - 16,539.0 -	8							
- 16,539.0 -	8							
16,563.0								
16,565.3	8							
16,567.9	S S							
16,578.1	W Y							
165,578.1								

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 284269

CONDITIONS

Operator:	OGRID:
ENDURING RESOURCES, LLC	372286
6300 S Syracuse Way	Action Number:
Centennial, CO 80111	284269
	Action Type:
	[C-103] Sub. Workover (C-103R)

CONDITIONS

Created By	Condition	Condition Date
andrew.fordyce	None	12/5/2025