

Form 3160-3  
(October 2024)FORM APPROVED  
OMB No. 1004-0220  
Expires: October 31, 2027UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

|  |  |   |
|--|--|---|
| 1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER   |  | 5. Lease Serial No.<br><b>NMNM108027</b>                                |
| 1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other  |  | 6. If Indian, Allottee or Tribe Name                                    |
| 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone   |  | 7. If Unit or CA Agreement, Name and No.                                |
| 2. Name of Operator<br><b>TAP ROCK OPERATING LLC</b>   |  | 8. Lease Name and Well No.<br><b>PABST FED COM</b><br><b>204H</b>       |
| 3a. Address<br><b>1700 LINCOLN ST SUITE 4700, DENVER, CO 80203</b>   | 3b. Phone No. (include area code)<br><b>(720) 460-3316</b> | 9. API Well No.<br><b>30-015-57537</b>                                  |
| 4. Location of Well (Report location clearly and in accordance with any State requirements. *)<br>At surface <b>NWNE / 778 FNL / 2349 FEL / LAT 32.0769264 / LONG -104.3825663</b><br>At proposed prod. zone <b>SESE / 5 FSL / 990 FEL / LAT 32.0499836 / LONG -104.378658</b> |  | 10. Field and Pool, or Exploratory<br><b>PURPLE SAGE/WOLFCAMP (GAS)</b> |
| 11. Sec., T. R. M. or Blk. and Survey or Area<br><b>SEC 3/T26S/R25E/NMP</b>  |  |   |
| 14. Distance in miles and direction from nearest town or post office*<br><b>7 miles</b>  |  | 12. County or Parish<br><b>EDDY</b>                                     |
| 13. State<br><b>NM</b>   |  |   |
| 15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)<br><b>778 feet</b>   | 16. No of acres in lease                                   | 17. Spacing Unit dedicated to this well<br><b>1280.0</b>                |
| 18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. <b>25 feet</b>  | 19. Proposed Depth<br><b>8154 feet / 18821 feet</b>        | 20. BLM/BIA Bond No. in file<br><b>FED: NMB105800930</b>                |
| 21. Elevations (Show whether DF, KDB, RT, GL, etc.)<br><b>3631 feet</b>  | 22. Approximate date work will start*<br><b>03/01/2026</b> | 23. Estimated duration<br><b>60 days</b>                                |
| 24. Attachments  |  |   |

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

|  |   |                           |
|--|---|---------------------------|
| 25. Signature<br>(Electronic Submission)                     | Name (Printed/Typed)<br><b>CORY WALK / Ph: (720) 460-3316</b>   | Date<br><b>10/06/2025</b> |
| Title<br><b>Permitting Agent</b>                             |   |                           |
| Approved by (Signature)<br>(Electronic Submission)           | Name (Printed/Typed)<br><b>CODY LAYTON / Ph: (575) 234-5959</b> | Date<br><b>11/21/2025</b> |
| Title<br><b>Assistant Field Manager Lands &amp; Minerals</b> |   |                           |
| Office<br><b>Carlsbad Field Office</b>                       |   |                           |

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)



|  |   |                                     |   |
|--|---|-------------------------------------|---|
| C-102<br>Submit Electronically<br>Via OCD Permitting | State of New Mexico<br>Energy, Minerals & Natural Resources Department<br>OIL CONSERVATION DIVISION | Revised July 9, 2024                |   |
|  |   | Submittal<br>Type:                  | <input checked="" type="checkbox"/> Initial Submittal |
|  |   |                                     | <input type="checkbox"/> Amended Report               |
|  |   | <input type="checkbox"/> As Drilled |   |

## WELL LOCATION AND ACREAGE DEDICATION PLAT

|  |   |  |
|--|---|--|
| API Number<br><b>30-015-57537</b>  | Pool Code<br><b>98220</b>                       | Pool Name<br><b>PURPLE SAGE; WOLFCAMP (GAS)</b>  |
| Property Code<br><b>338228</b>   | Property Name<br><b>PABST FED COM</b>           | Well Number<br><b>204H</b>   |
| OGRID No.<br><b>372043</b>   | Operator Name<br><b>TAP ROCK OPERATING, LLC</b> | Ground Level Elevation<br><b>3631'</b>   |
| Surface Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal |   | Mineral Owner: <input type="checkbox"/> State <input type="checkbox"/> Fee <input type="checkbox"/> Tribal <input checked="" type="checkbox"/> Federal |

## Surface Location

|                           |                     |                         |                      |                     |                                    |                                     |                                 |                                   |                       |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|------------------------------------|-------------------------------------|---------------------------------|-----------------------------------|-----------------------|
| UL or lot no.<br><b>B</b> | Section<br><b>3</b> | Township<br><b>26-S</b> | Range<br><b>25-E</b> | Lot Idn<br><b>-</b> | Feet from the N/S<br><b>778' N</b> | Feet from the E/W<br><b>2349' E</b> | Latitude<br><b>N 32.0769264</b> | Longitude<br><b>W 104.3825663</b> | County<br><b>EDDY</b> |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|------------------------------------|-------------------------------------|---------------------------------|-----------------------------------|-----------------------|

## Bottom Hole Location

|                           |                      |                         |                      |                     |                                  |                                    |                                 |                                   |                       |
|---------------------------|----------------------|-------------------------|----------------------|---------------------|----------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|
| UL or lot no.<br><b>P</b> | Section<br><b>10</b> | Township<br><b>26-S</b> | Range<br><b>25-E</b> | Lot Idn<br><b>-</b> | Feet from the N/S<br><b>5' S</b> | Feet from the E/W<br><b>990' E</b> | Latitude<br><b>N 32.0499836</b> | Longitude<br><b>W 104.3786580</b> | County<br><b>EDDY</b> |
|---------------------------|----------------------|-------------------------|----------------------|---------------------|----------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|

|                                       |  |   |   |                               |
|---------------------------------------|--|---|---|-------------------------------|
| Dedicated Acres<br><b>1280</b>        | Infill or Defining Well<br><b>Infill</b> | Defining Well API<br><b>30-015-xxxxx (213H)</b> | Overlapping Spacing Unit (Y/N)<br><b>N</b>  | Consolidated Code<br><b>C</b> |
| Order Numbers<br><b>will file NSP</b> |  |   | Well Setbacks are under Common Ownership: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |                               |

## Kick Off Point (KOP)

|                           |                     |                         |                      |                     |                                   |                                    |                                 |                                   |                       |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|-----------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|
| UL or lot no.<br><b>A</b> | Section<br><b>3</b> | Township<br><b>26-S</b> | Range<br><b>25-E</b> | Lot Idn<br><b>-</b> | Feet from the N/S<br><b>50' N</b> | Feet from the E/W<br><b>990' E</b> | Latitude<br><b>N 32.0789024</b> | Longitude<br><b>W 104.3781803</b> | County<br><b>EDDY</b> |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|-----------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|

## First Take Point (FTP)

|                           |                     |                         |                      |                     |                                    |                                    |                                 |                                   |                       |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|------------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|
| UL or lot no.<br><b>A</b> | Section<br><b>3</b> | Township<br><b>26-S</b> | Range<br><b>25-E</b> | Lot Idn<br><b>-</b> | Feet from the N/S<br><b>330' N</b> | Feet from the E/W<br><b>990' E</b> | Latitude<br><b>N 32.0781326</b> | Longitude<br><b>W 104.3781800</b> | County<br><b>EDDY</b> |
|---------------------------|---------------------|-------------------------|----------------------|---------------------|------------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|

## Last Take Point (LTP)


|                           |                      |                         |                      |                     |                                    |                                    |                                 |                                   |                       |
|---------------------------|----------------------|-------------------------|----------------------|---------------------|------------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|
| UL or lot no.<br><b>P</b> | Section<br><b>10</b> | Township<br><b>26-S</b> | Range<br><b>25-E</b> | Lot Idn<br><b>-</b> | Feet from the N/S<br><b>330' S</b> | Feet from the E/W<br><b>990' E</b> | Latitude<br><b>N 32.0508774</b> | Longitude<br><b>W 104.3786284</b> | County<br><b>EDDY</b> |
|---------------------------|----------------------|-------------------------|----------------------|---------------------|------------------------------------|------------------------------------|---------------------------------|-----------------------------------|-----------------------|

|   |  |  |
|---|--|--|
| Unitized Area or Area of Uniform Interest<br><b>Y</b> | Spacing Unity Type<br><input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Vertical | Ground Floor Elevation<br><b>3631'</b> |
|---|--|--|

## OPERATOR CERTIFICATION


I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief; and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.


If this well is a horizontal well, I further certify that this organization has received The consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.

|   |                           |
|---|---------------------------|
| Signature<br> | Date<br><b>10-03-2025</b> |
| Print Name<br><b>Cory Walk</b>  |                           |
| E-mail Address<br><b>cory@permitswest.com</b>   |                           |

## SURVEYORS CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.



|  |                                     |                                     |
|--|-------------------------------------|-------------------------------------|
| Signature and Seal of Professional Surveyor<br> |                                     | Date<br><b>9/3/2025 11:16:43 AM</b> |
| Certificate Number   | Date of Survey<br><b>08/25/2025</b> |                                     |

|   |  |                                     |   |
|---|--|-------------------------------------|---|
| <b>C-102</b><br><br>Submit Electronically<br>Via OCD Permitting | State of New Mexico<br>Energy, Minerals & Natural Resources Department<br><b>OIL CONSERVATION DIVISION</b> | Revised July 9, 2024                |   |
|   |  | Submittal<br>Type:                  | <input checked="" type="checkbox"/> Initial Submittal |
|   |  |                                     | <input type="checkbox"/> Amended Report               |
| Property Name and Well Number                                   |  | <input type="checkbox"/> As Drilled |   |

**PABST FED COM 204H**

**SURFACE LOCATION (SHL)**

NEW MEXICO EAST  
NAD 1983

X=526089 Y=391727  
LAT.: N 32.0769264  
LONG.: W 104.3825663

**NAD 1927**

X=484906 Y=391670  
LAT.: N 32.0768084  
LONG.: W 104.3820638  
778' FNL 2349' FEL

**KICK OFF POINT (KOP)**

NEW MEXICO EAST  
NAD 1983

X=527447 Y=392445  
LAT.: N 32.0789024  
LONG.: W 104.3781803

**NAD 1927**

X=486265 Y=392389  
LAT.: N 32.0787842  
LONG.: W 104.3776779  
50' FNL 990' FEL

**FIRST TAKE POINT (FTP)**

NEW MEXICO EAST  
NAD 1983

X=527447 Y=392165  
LAT.: N 32.0781326  
LONG.: W 104.3781800

**NAD 1927**

X=486265 Y=392109  
LAT.: N 32.0780145  
LONG.: W 104.3776776  
330' FNL 990' FEL

The survey plat is a detailed technical drawing of a well location. It features a central grid with various points marked and labeled. The points include SHL (Surface Location), KOP (Kick Off Point), FTP (First Take Point), BPP1 (Bottom Hole Point), LTP (Last Take Point), and BHL (Bottom Hole Location). The plat includes bearings and distances for several lines, such as AZ = 180.00°, 280.0°, 62.14°, 1536.9', 180.83°, 9915.7', 181.64°, and 325.3'. It also shows various offsets and distances, such as 778', 2349', 1023', 1061', 330', and 990'. The plat is divided into sections by dashed lines, and the well location is indicated by a red dashed line. The plat is titled 'USA NM 108027' and 'USA NM 140299'. The plat is dated 08/25/2025.

**BLM PERF. POINT (BPP1)**

NEW MEXICO EAST  
NAD 1983

X=527376 Y=387211  
LAT.: N 32.0645137  
LONG.: W 104.3784041

**NAD 1927**

X=486194 Y=387155  
LAT.: N 32.0643954  
LONG.: W 104.3779021  
0' FNL 1061' FEL

**LAST TAKE POINT (LTP)**

NEW MEXICO EAST  
NAD 1983

X=527304 Y=382250  
LAT.: N 32.0508774  
LONG.: W 104.3786284

**NAD 1927**

X=486122 Y=382194  
LAT.: N 32.0507589  
LONG.: W 104.3781269  
330' FSL 990' FEL

**BOTTOM HOLE LOCATION (BHL)**

NEW MEXICO EAST  
NAD 1983

X=527295 Y=381925  
LAT.: N 32.0499836  
LONG.: W 104.3786580

**NAD 1927**

X=486113 Y=381869  
LAT.: N 32.0498651  
LONG.: W 104.3781565  
5' FSL 990' FEL

**SURVEYORS CERTIFICATION**

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.  
08/25/2025


Date of Survey  
Signature and Seal of Professional Surveyor:

The seal is a circular emblem for a professional surveyor. It features the name 'RAMON DOMINGUEZ' around the top edge and 'NEW MEXICO' around the bottom edge. In the center, there is a smaller circle containing the number '24508'. The words 'PROFESSIONAL SURVEYOR' are written around the inner circle.



9/3/2025 11:16:45 AM



SECTION 3, TOWNSHIP 26-S, RANGE 25-E, N.M.P.M.  
EDDY COUNTY, NEW MEXICO




- SURFACE LOCATION (SHL)**  
NEW MEXICO EAST  
NAD 1983  
X=526089 Y=391727  
LAT.: N 32.0769264  
LONG.: W 104.3825663  
778' FNL 2349' FEL
- KICK OFF POINT (KOP)**  
NEW MEXICO EAST  
NAD 1983  
X=527447 Y=392445  
LAT.: N 32.0789024  
LONG.: W 104.3781803  
50' FNL 990' FEL
- FIRST TAKE POINT (FTP)**  
NEW MEXICO EAST  
NAD 1983  
X=527447 Y=392165  
LAT.: N 32.0781326  
LONG.: W 104.3781800  
330' FNL 990' FEL
- BLM PERF. POINT (BPP1)**  
NEW MEXICO EAST  
NAD 1983  
X=527376 Y=387211  
LAT.: N 32.0645137  
LONG.: W 104.3784041  
0' FNL 1061' FEL
- LAST TAKE POINT (LTP)**  
NEW MEXICO EAST  
NAD 1983  
X=527304 Y=382250  
LAT.: N 32.0508774  
LONG.: W 104.3786284  
330' FSL 990' FEL
- BOTTOM HOLE LOCATION (BHL)**  
NEW MEXICO EAST  
NAD 1983  
X=527295 Y=381925  
LAT.: N 32.0499836  
LONG.: W 104.3786580  
5' FSL 990' FEL



LEASE NAME & WELL NO.: PABST FED COM 204H

SECTION 3 TWP 26-S RGE 25-E SURVEY N.M.P.M.  
COUNTY EDDY STATE NM  
DESCRIPTION 778' FNL & 2349' FEL

DISTANCE & DIRECTION  
FROM INT. OF CARLSBAD CAVERN HWY. & US-180/US-62 W. GO  
SOUTHWEST ON US-180/US-62 W ±6.7 MILES. THENCE EAST (LEFT) ON  
DILLAHUNTY RD. ±3.2 MILES, THENCE NORTH (LEFT) ON A PROPOSED  
RD. ±0.86 MILES, TO A POINT ±355 FEET SOUTH OF THE LOCATION.



9/3/2025 11:16:47 AM  
Ramon A. Dominguez, P.S. No. 24508

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO COORDINATE SYSTEM OF 1983, EAST ZONE, U.S. SURVEY FEET  
THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY TAP ROCK OPERATING, LLC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.  
AS OF THE DATE OF SURVEY, ALL ABOVE GROUND APPURTENANCES WITHIN 300' OF THE STAKED LOCATION ARE SHOWN HEREON.

**TOPOGRAPHIC**  
LOYALTY INNOVATION LEGACY  
481 WINSOFT ROAD, Ste. 200 • BENBROOK, TEXAS 76126  
TELEPHONE: (817) 744-7512 • FAX (817) 744-7554  
2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705  
TELEPHONE: (432) 682-1653 OR (800) 767-1653 • FAX (432) 682-1743  
WWW.TOPOGRAPHIC.COM

State of New Mexico  
Energy, Minerals and Natural Resources Department

Submit Electronically  
Via E-permitting

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

## NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

### Section 1 – Plan Description

Effective May 25, 2021

**I. Operator:** \_\_\_\_\_ Tap Rock Operating LLC \_\_\_\_\_ **OGRID:** \_\_\_\_\_ 372043 \_\_\_\_\_ **Date:** 9/29/2025

**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

| Well Name          | API | ULSTR          | Footages            | Anticipated Oil BBL/D | Anticipated Gas MCF/D | Anticipated Produced Water BBL/D |
|--------------------|-----|----------------|---------------------|-----------------------|-----------------------|----------------------------------|
| Pabst Fed Com 202H |     | B, 3, 26S, 25E | 753' FNL, 2374' FEL | 940                   | 3571                  | 5149                             |
| Pabst Fed Com 204H |     | B, 3, 26S, 25E | 778' FNL, 2349' FEL | 940                   | 3571                  | 5149                             |
| Pabst Fed Com 211H |     | B, 3, 26S, 25E | 778' FNL, 2374' FEL | 940                   | 3571                  | 5149                             |
| Pabst Fed Com 213H |     | B, 3, 26S, 25E | 753' FNL, 2349' FEL | 940                   | 3571                  | 5149                             |

**IV. Central Delivery Point Name:** \_\_\_\_\_ Pabst Fed Com CDP \_\_\_\_\_ [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

| Well Name          | API | Spud Date | TD Reached Date | Completion Commencement Date | Initial Flow Back Date | First Production Date |
|--------------------|-----|-----------|-----------------|------------------------------|------------------------|-----------------------|
| Pabst Fed Com 202H |     | 2/1/2026  | 3/1/2026        | 4/1/2026                     | 5/1/2026               | 5/1/2026              |
| Pabst Fed Com 204H |     | 2/1/2026  | 3/1/2026        | 4/1/2026                     | 5/1/2026               | 5/1/2026              |
| Pabst Fed Com 211H |     | 2/1/2026  | 3/1/2026        | 4/1/2026                     | 5/1/2026               | 5/1/2026              |
| Pabst Fed Com 213H |     | 2/1/2026  | 3/1/2026        | 4/1/2026                     | 5/1/2026               | 5/1/2026              |

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

**Section 2 – Enhanced Plan**  
**EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

**IX. Anticipated Natural Gas Production:**

| Well | API | Anticipated Average Natural Gas Rate MCF/D | Anticipated Volume of Natural Gas for the First Year MCF |
|------|-----|--|--|
|      |     |  |  |
|      |     |  |  |

**X. Natural Gas Gathering System (NGGS):**

| Operator | System | ULSTR of Tie-in | Anticipated Gathering Start Date | Available Maximum Daily Capacity of System Segment Tie-in |
|----------|--------|-----------------|----------------------------------|---|
|          |        |                 |                                  |   |
|          |        |                 |                                  |   |

**XI. Map.** ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.



### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

|  |
|--|
| Signature:      |
| Printed Name: Bill Ramsey  |
| Title: Sr. Environmental and Regulatory Specialist   |
| E-mail Address: <a href="mailto:brmasey@taprk.com">brmasey@taprk.com</a>                         |
| Date: 9/29/2025  |
| Phone: 720-238-2787  |
| <b>OIL CONSERVATION DIVISION</b><br><b>(Only applicable when submitted as a standalone form)</b> |
| Approved By:   |
| Title:   |
| Approval Date:   |
| Conditions of Approval:  |





### Tap Rock Operating Natural Gas Management Plan

#### **VI. Separation Equipment:**

Each surface facility design includes the following process equipment: 3-phase separators (1 separator per well), a sales gas scrubber, one or two 3-phase heater treaters, a vapor recovery tower (VRT), a VRU compressor, multiple water and oil tanks, as well as flare knockouts (HP & LP), and flares (HP & LP). All process vessels will be sized to separate oil, water, gas based upon typical/historical & predicted well performance. Each process vessel will be fitted with an appropriately sized PSV as per ASME code requirements to mitigate vessel rupture and loss of containment. Additionally, the process vessels will be fitted with pressure transmitters tied to the facility control system which will allow operations to monitor pressures and when necessary, shut-in the facility to avoid vessel over-pressure and the potential vent of natural gas. Natural gas will preferentially be sold to pipeline, and only during upset/emergency conditions will gas be directed to the HP flare system. Flash gas from both the 3-phase heater treater and the VRT will be recompressed using a VRU compressor and this gas will also preferentially be directed to the gas sales pipeline. Oil tanks & water tanks will be fitted with 16 oz thief hatches as well as PVRVs to protect the tanks from rupture/collapse. Additionally, the tank vapor outlets and tank vapor capture system will be sized to keep tank pressures below 12 oz. The tank vapor capture system will include a tank vapor blower & knockout as well as a low-pressure flare and knockout. Tank vapors will preferentially be directed to the VRU and the sales gas pipeline. Only during process upsets/emergency conditions will tank vapors be directed to the LP flare system.

#### **VII. Operational Practices:**

- During drilling operations- Gas meters will be installed at the shakers and Volume Totalizers will be installed on the pits. In the event that elevated gas levels, or a pit gain are observed, returns will be diverted to a gas buster. Gas coming off the gas buster will be combusted at the flare stack. A 10' or taller flare will be located at least 100' from the SHL.
- During completions operations, including stimulation and frac plug drill out operations, hydrocarbon production to surface is minimized. When gas production does occur, gas will be combusted at a flare stack. A 10' or taller flare will be located at least 100' from the SHL.
- During production operations, all process vessels (separators, heater treaters, VRTs, Tanks) will recompress (where necessary) and route gas outlets into the natural gas gathering pipeline. Gas will preferentially be routed to natural gas gathering pipeline and the flare system will be used only during emergency, malfunction, or if the gas does not meet pipeline specifications. In the event of flaring off-specification gas, operations will pull gas samples twice a week and will also route gas back to pipeline as soon as the gas meets specification. Exceptions to this will include only those qualified emergencies as mentioned in the BLM Waste Prevention Rule.



- To comply with state performance standards, separation and storage equipment will be designed to handle the maximum anticipated throughput and pressure to minimize waste and reduce the likelihood of venting gas to atmosphere. Additionally, each storage atmospheric tank (Oil & Water) will be fitted with a level transmitter to facilitate gauging of the tank without opening of the thief hatch. Any gas collected through the tank vent system is expected to be recompressed and routed to sales. However, in the event of an emergency, the tank vapor capture system will be designed to combust the gas using a flare stack fitted with a continuous or automatic ignitor. The flare stack will be properly anchored and will be located a minimum of 100 feet from the well and storage tanks. Operators will conduct weekly AVO inspections. These AVO inspection records will be stored for the required 5-year period and will be made available upon Division request.

#### **VIII. Best Management Practices:**

- When performing routine or preventive maintenance on a vessel or tank, initially all inlet valves are closed, and the vessel or tank is allowed to depressurize through the normal outlet connections to gas sales and/or liquid tanks. Once the vessel or tank is depressurized to lowest acceptable sales outlet pressure, usually around 20 psig, a temporary low-pressure flowline is connected from the vessel or tank to the Vapor Recovery Unit (VRU) for further pressure reduction. Once depressurized to less than 1-2 psig, the remaining natural gas in the vessel or tank is vented to atmosphere through a controlled pressure relief valve. Once the vessel or tank is depressurized to atmospheric pressure, the vessel or tank can be safely opened, and maintenance performed.



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Drilling Plan Data Report

11/21/2025

**APD ID:** 10400107651

**Submission Date:** 10/06/2025

Highlighted data  
reflects the most  
recent changes

**Operator Name:** TAP ROCK OPERATING LLC

**Well Name:** PABST FED COM

**Well Number:** 204H

**Well Type:** CONVENTIONAL GAS WELL

**Well Work Type:** Drill

[Show Final Text](#)

## Section 1 - Geologic Formations

| Formation ID | Formation Name    | Elevation | True Vertical | Measured Depth | Lithologies                         | Mineral Resources | Producing Formatio |
|--------------|-------------------|-----------|---------------|----------------|-------------------------------------|-------------------|--------------------|
| 16838802     | QUATERNARY        | 3631      | 0             | 0              | OTHER : None                        | NONE              | N                  |
| 16838782     | RUSTLER ANHYDRITE | 3592      | 39            | 39             | ANHYDRITE                           | NONE              | N                  |
| 16838783     | TOP SALT          | 3321      | 310           | 310            | SALT                                | OTHER : Salt      | N                  |
| 16838784     | BASE OF SALT      | 2276      | 1355          | 1358           | SALT                                | OTHER : Salt      | N                  |
| 16838785     | DELAWARE          | 2054      | 1577          | 1583           | OTHER, SANDSTONE :<br>Moutain Group | NONE              | N                  |
| 16838786     | LAMAR             | 2047      | 1584          | 1591           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |
| 16838787     | BELL CANYON       | 2013      | 1618          | 1625           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |
| 16838788     | RAMSEY SAND       | 2002      | 1629          | 1636           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |
| 16838789     | CHERRY CANYON     | 1154      | 2477          | 2512           | LIMESTONE                           | NATURAL GAS, OIL  | N                  |
| 16838790     | BRUSHY CANYON     | 121       | 3510          | 3582           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |
| 16838791     | BONE SPRING LIME  | -1335     | 4966          | 5090           | OTHER : Carbonate                   | NATURAL GAS, OIL  | N                  |
| 16838792     | AVALON SAND       | -1594     | 5225          | 5358           | OTHER : Upper -<br>Carbonate        | NATURAL GAS, OIL  | N                  |
| 16838793     | AVALON SAND       | -1897     | 5528          | 5672           | OTHER : Middle -<br>Carbonate       | NATURAL GAS, OIL  | N                  |
| 16838794     | AVALON SAND       | -2240     | 5871          | 6027           | OTHER : Lower -<br>Carbonate        | NATURAL GAS, OIL  | N                  |
| 16838795     | BONE SPRING 1ST   | -2380     | 6011          | 6172           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |
| 16838796     | BONE SPRING 2ND   | -2674     | 6305          | 6477           | OTHER : Carbonate                   | NATURAL GAS, OIL  | N                  |
| 16838797     | BONE SPRING 2ND   | -3147     | 6778          | 6960           | SANDSTONE                           | NATURAL GAS, OIL  | N                  |

**Operator Name:** TAP ROCK OPERATING LLC**Well Name:** PABST FED COM**Well Number:** 204H

| Formation ID | Formation Name  | Elevation | True Vertical | Measured Depth | Lithologies         | Mineral Resources | Producing Formatio |
|--------------|-----------------|-----------|---------------|----------------|---------------------|-------------------|--------------------|
| 16838798     | BONE SPRING 3RD | -3297     | 6928          | 7112           | OTHER : Carbonate   | NATURAL GAS, OIL  | N                  |
| 16838799     | BONE SPRING 3RD | -4247     | 7878          | 8064           | SANDSTONE           | NATURAL GAS, OIL  | N                  |
| 16838800     | BONE SPRING 3RD | -4511     | 8142          | 8355           | OTHER : W Sandstone | NATURAL GAS, OIL  | N                  |
| 16838801     | WOLFCAMP        | -4601     | 8232          | 8486           | OTHER : A           | NATURAL GAS, OIL  | Y                  |

## Section 2 - Blowout Prevention

**Pressure Rating (PSI):** 5M**Rating Depth:** 10000

**Equipment:** At 18,820', a 5M pressure control system is required. The BOP stack consisting of 3 rams with 2 pipe rams, 1 blind ram, and 1 annular preventer will be used below surface casing to TD. See attachments for BOP and choke manifold diagrams. Also present will be an accumulator that meets the requirements of 43 CFR 3172 for the pressure rating of the BOP stack. A rotating head will also be installed as needed. BOP will be inspected and operated as recommended in 43 CFR 3172. A top drive check valve and sub equipped with a full opening valve sized to fit the drill pipe and collars will be available on the rig floor in the open position. The wellhead will be a multi-bowl speed head.

**Requesting Variance?** YES

**Variance request:** Tap Rock requests a variance to run a multi-bowl speed head for setting the Intermediate and Production Strings. Tap Rock requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Tap Rock requests a variance to have the option of batch drilling this well with other wells on the same pad. If this well is batch drilled, after cementing a casing string, a 5M dry hole cap with bleed off valve will be installed. The rig will then walk to another well on the pad. Tap Rock Operating requests to only test BOP connection breaks after rig walks per the procedures and stipulations set forth in the "BOP Shell Test Procedure" document emailed to the BLM on 8/11/22.

**Testing Procedure:** After surface casing is set and the BOP is nipped up, the BOP pressure tests will be made with a third party tester to 250 psi low, 5000 psi high, and the annular preventer will be tested to 250 psi low, 2500 psi high.

**Choke Diagram Attachment:**

5M\_Choke\_Diagram\_20251004113440.pdf

**BOP Diagram Attachment:**

5M\_BOP\_Diagram\_20251004113449.pdf

Operator Name: TAP ROCK OPERATING LLC

Well Name: PABST FED COM

Well Number: 204H

Section 3 - Casing

| Casing ID | String Type  | Hole Size | Csg Size | Condition | Standard | Tapered String | Top Set MD | Bottom Set MD | Top Set TVD | Bottom Set TVD | Top Set MSL | Bottom Set MSL | Calculated casing length MD | Grade | Weight | Joint Type  | Collapse SF | Burst SF | Joint SF Type | Joint SF | Body SF Type | Body SF |
|-----------|--------------|-----------|----------|-----------|----------|----------------|------------|---------------|-------------|----------------|-------------|----------------|-----------------------------|-------|--------|-------------|-------------|----------|---------------|----------|--------------|---------|
| 1         | SURFACE      | 14.75     | 11.75    | NEW       | API      | N              | 0          | 350           | 0           | 350            | 3631        | 3281           | 350                         | J-55  | 42     | BUTT        | 1.13        | 1.15     | DRY           | 1.6      | DRY          | 1.6     |
| 2         | INTERMEDIATE | 11        | 8.625    | NEW       | API      | N              | 0          | 1641          | 0           | 1634           | 3631        | 1997           | 1641                        | J-55  | 32     | BUTT        | 1.13        | 1.15     | DRY           | 1.6      | DRY          | 1.6     |
| 3         | PRODUCTION   | 7.875     | 5.5      | NEW       | NON API  | N              | 0          | 18820         | 0           | 7813           | 3631        | -4182          | 18820                       | P-110 | 20     | OTHER - TPN | 1.13        | 1.15     | DRY           | 1.6      | DRY          | 1.6     |

Casing Attachments

Casing ID: 1StringSURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Casing\_Design\_Assumptions\_20251004113943.pdf

Operator Name: TAP ROCK OPERATING LLC

Well Name: PABST FED COM

Well Number: 204H

Casing Attachments

Casing ID: 2StringINTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Casing\_Design\_Assumptions\_20251004114004.pdf

Casing ID: 3StringPRODUCTION

Inspection Document:

Spec Document:

5.5in\_TPN\_Casing\_Spec\_20251004114044.pdf

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Casing\_Design\_Assumptions\_20251004114054.pdf

Section 4 - Cement

| String Type  | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives                            |
|--------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|--------------------------------------|
| SURFACE      | Lead      |                  | 0      | 0         | 0            | 0     | 0       | 0     | 0       | None        | None                                 |
| SURFACE      | Tail      |                  | 0      | 350       | 228          | 1.33  | 14.8    | 304   | 100     | Class C     | 5% NCI + LCM                         |
| INTERMEDIATE | Lead      |                  | 0      | 1141      | 165          | 2.7   | 11      | 444   | 75      | Class C     | Bentonite + 1% CaCL2 + 8% NaCl + LCM |
| INTERMEDIATE | Tail      |                  | 1141   | 1641      | 124          | 1.33  | 14.8    | 165   | 30      | Class C     | 5% NaCl + LCM                        |
| PRODUCTION   | Lead      |                  | 0      | 7999      | 482          | 3.35  | 10.5    | 1615  | 20      | Class C     | Fluid Loss + Dispersant +            |



**Operator Name:** TAP ROCK OPERATING LLC**Well Name:** PABST FED COM**Well Number:** 204H

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives                                |
|-------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|--|
|             |           |                  |        |           |              |       |         |       |         |             | Retarder + LCM                           |
| PRODUCTION  | Tail      |                  | 7999   | 18820     | 1382         | 1.63  | 13.2    | 2253  | 20      | Class H     | Fluid Loss + Dispersant + Retarder + LCM |

### Section 5 - Circulating Medium

**Mud System Type:** Closed**Will an air or gas system be Used?** NO**Description of the equipment for the circulating system in accordance with 43 CFR 3172:****Diagram of the equipment for the circulating system in accordance with 43 CFR 3172:**

**Describe what will be on location to control well or mitigate other conditions:** All necessary mud products (i.e., barite, pac) for weight addition and fluid loss control will always be on site. Mud program is subject to change due to hole conditions.

**Describe the mud monitoring system utilized:** Electronic Pason mud monitor system complying with 43 CFR 3172 will be used.

### Circulating Medium Table

| Top Depth | Bottom Depth | Mud Type                     | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | PH | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|------------------------------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
| 0         | 350          | OTHER : Fresh Water Spud Mud | 8.4                  | 8.4                  |                     |                             |    |                |                |                 |                            |
| 350       | 1641         | SALT SATURATED               | 10                   | 10                   |                     |                             |    |                |                |                 |                            |
| 1641      | 18820        | OIL-BASED MUD                | 9                    | 9                    |                     |                             |    |                |                |                 |                            |

**Operator Name:** TAP ROCK OPERATING LLC**Well Name:** PABST FED COM**Well Number:** 204H

## Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

Electric Logging Program: No open-hole logs are planned at this time. GR will be collected while drilling through the MWD tools from KOP to TD. A 2-person mud logging program will be used from KOP to TD. CBL w/ CCL from as far as gravity will let it fall to TOC.

**List of open and cased hole logs run in the well:**

MUD LOG/GEOLOGICAL LITHOLOGY LOG,GAMMA RAY LOG,CEMENT BOND LOG,

**Coring operation description for the well:**

No DSTs or cores are planned at this time.

## Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 3656**Anticipated Surface Pressure:** 1822**Anticipated Bottom Hole Temperature(F):** 170**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO**Describe:****Contingency Plans geohazards description:****Contingency Plans geohazards****Hydrogen Sulfide drilling operations plan required?** YES**Hydrogen sulfide drilling operations**

Pabst\_H2S\_Plan\_20251004114240.pdf

## Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

Pabst\_204H\_Directional\_Plan\_20251004114251.pdf

**Other proposed operations facets description:****Other proposed operations facets attachment:**

Pabst\_204H\_Drill\_Plan\_20251004114302.pdf

Pabst\_204H\_Anticollision\_Report\_20251004114310.pdf

CoFlex\_Certs\_20251004114320.pdf

BOP\_Shell\_Test\_Procedure\_20251004114327.pdf

Wellhead\_Diagram\_3T\_20251004114335.pdf

Pabst\_WMP\_20251004114336.pdf

**Other Variance request(s)?:** N**Other Variance attachment:**

**Operator Name:** TAP ROCK OPERATING LLC

**Well Name:** PABST FED COM

**Well Number:** 204H





Company: Tap Rock Operating  
Well: Pabst Fed Com 204H  
County: Eddy County, New Mexico (NAD 83)  
Rig: H&P 466  
Wellbore: Wellbore #1  
Design: Design #1  
Date: 11:58, September 25 2025

Geodetic System: US State Plane 1983  
Datum: North American Datum 1983  
Ellipsoid: GRS 1980  
Zone: New Mexico Eastern Zone  
System Datum: Mean Sea Level

WELL DETAILS: Pabst Fed Com 204H

|        |       |              |                              |                 |                   |
|--------|-------|--------------|------------------------------|-----------------|-------------------|
| +N/-S  | +E/-W | GL @ 3631.00 | Well @ 3657.00usft (H&P 466) |                 |                   |
| -24.97 | 25.01 | 391726.55    | 526088.62                    | 32° 4' 36.935 N | 104° 22' 57.239 W |

|            |          |                         |                   |
|------------|----------|-------------------------|-------------------|
| Depth From | Depth To | Survey/Plan             | Tool              |
| 0.00       | 18820.54 | Design #1 (Wellbore #1) | MWD+IFR1+SAG+FDIR |


SURVEY PROGRAM

DESIGN TARGET DETAILS







| Name                           | TVD     | +N/-S    | +E/-W   | Northing  | Easting   | Latitude        | Longitude         |
|--------------------------------|---------|----------|---------|-----------|-----------|-----------------|-------------------|
| BPP1_Pabst Fed Com 204H        | 0.00    | -4540.92 | 1312.28 | 387210.59 | 527375.89 | 32° 3' 52.249 N | 104° 22' 42.255 W |
| FTP_Pabst Fed Com 204H         | 0.00    | 413.22   | 1383.76 | 392164.74 | 527447.37 | 32° 4' 41.277 N | 104° 22' 41.448 W |
| KOP_Pabst Fed Com 204H         | 0.00    | 693.26   | 1383.78 | 392444.77 | 527447.39 | 32° 4' 44.049 N | 104° 22' 41.449 W |
| LTP_Pabst Fed Com 204H         | 0.00    | -9501.39 | 1240.72 | 382250.12 | 527304.33 | 32° 3' 3.159 N  | 104° 22' 43.062 W |
| PBHL_Pabst Fed Com 204H        | 8154.16 | -9826.53 | 1231.41 | 381924.99 | 527295.02 | 32° 2' 59.941 N | 104° 22' 43.169 W |
| T1-3500' VS_Pabst Fed Com 204H | 8334.00 | -3544.13 | 1322.40 | 388207.39 | 527386.01 | 32° 4' 2.114 N  | 104° 22' 42.142 W |
| T2-5500' VS_Pabst Fed Com 204H | 8306.07 | -5543.92 | 1293.44 | 386207.60 | 527357.05 | 32° 3' 42.323 N | 104° 22' 42.469 W |
| T3-7500' VS_Pabst Fed Com 204H | 8253.70 | -7543.71 | 1264.47 | 384207.81 | 527328.08 | 32° 3' 22.533 N | 104° 22' 42.796 W |

SECTION DETAILS

| MD       | Inc   | Azi    | TVD     | +N/-S    | +E/-W   | Dleg  | TFace   | VFace   | Annotation                   |
|----------|-------|--------|---------|----------|---------|-------|---------|---------|------------------------------|
| 0.00     | 0.00  | 0.00   | 0.00    | -24.97   | 25.01   | 0.00  | 0.000   | 0.00    | KOP, 1.00°/100' Build        |
| 500.00   | 0.00  | 0.00   | 500.00  | -24.97   | 25.01   | 0.00  | 0.000   | 0.00    | Begin 15.11° Tangent         |
| 2010.59  | 15.11 | 62.14  | 1993.15 | 67.55    | 200.05  | 1.00  | 62.140  | -95.04  | Begin 1.00°/100' Drop        |
| 6388.70  | 15.11 | 62.14  | 6219.98 | 600.74   | 1208.75 | 0.00  | 0.000   | -642.78 | Begin Vertical Hold          |
| 7899.29  | 0.00  | 0.00   | 7713.13 | 693.26   | 1383.78 | 1.00  | 180.000 | -737.83 | KOP, 11.00°/100' Build       |
| 7999.29  | 0.00  | 0.00   | 7813.13 | 693.26   | 1383.78 | 0.00  | 0.000   | -737.83 | Begin 90.00° Lateral         |
| 8817.47  | 90.00 | 180.83 | 8334.00 | 172.44   | 1376.24 | 11.00 | 180.830 | -216.96 | Begin 2.00°/100' Build       |
| 12534.43 | 90.00 | 180.83 | 8334.00 | -3544.13 | 1322.40 | 0.00  | 0.000   | 3500.00 | Hold 90.81° Inc, 180.83° Azm |
| 12574.84 | 90.81 | 180.83 | 8333.72 | -3584.53 | 1321.82 | 2.00  | -0.016  | 3540.40 | Begin 2.00°/100' Build       |
| 14534.62 | 90.81 | 180.83 | 8306.07 | -5543.92 | 1293.44 | 0.00  | 0.000   | 5500.00 | Hold 91.51° Inc, 180.83° Azm |
| 14569.52 | 91.51 | 180.83 | 8305.37 | -5578.80 | 1292.94 | 2.00  | 0.024   | 5534.89 | Begin 2.00°/100' Build       |
| 16535.31 | 91.51 | 180.83 | 8253.70 | -7543.71 | 1264.47 | 0.00  | 0.000   | 7500.00 | Hold 92.51° Inc, 180.83° Azm |
| 16585.38 | 92.51 | 180.83 | 8251.95 | -7593.74 | 1263.75 | 2.00  | -0.012  | 7550.04 | Begin 2.00°/100' Build       |
| 18820.54 | 92.51 | 180.83 | 8154.16 | -9826.53 | 1231.41 | 0.00  | 0.000   | 9783.06 | PBHL                         |



To convert a Magnetic Direction to a Grid Direction, Add 6.843°  
To convert a Magnetic Direction to a True Direction, Add 6.817° East  
To convert a True Direction to a Grid Direction, Add 0.026°







## **Tap Rock Operating**

**Eddy County, New Mexico (NAD 83)**

**Pabst Fed Com (202H, 204H, 211H, 213H)**

**Pabst Fed Com 204H**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report**

**25 September, 2025**





## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

|                    |                                  |                      |                |
|--------------------|----------------------------------|----------------------|----------------|
| <b>Project</b>     | Eddy County, New Mexico (NAD 83) |                      |                |
| <b>Map System:</b> | US State Plane 1983              | <b>System Datum:</b> | Mean Sea Level |
| <b>Geo Datum:</b>  | North American Datum 1983        |                      |                |
| <b>Map Zone:</b>   | New Mexico Eastern Zone          |                      |                |

|                       |  |              |                 |            |                   |
|-----------------------|--|--------------|-----------------|------------|-------------------|
| Site                  | Pabst Fed Com (202H, 204H, 211H, 213H) |              |                 |            |                   |
| Site Position:        |  | Northing:    | 391,751.51 usft | Latitude:  | 32° 4' 37.182 N   |
| From:                 | Lat/Long                               | Easting:     | 526,063.61 usft | Longitude: | 104° 22' 57.530 W |
| Position Uncertainty: | 0.00 usft                              | Slot Radius: | 13-3/16 "       |            |                   |

| Well                 |          | Pabst Fed Com 204H |                     |                 |               |                   |
|----------------------|----------|--------------------|---------------------|-----------------|---------------|-------------------|
| Well Position        | +N/-S    | 0.00 usft          | Northing:           | 391,726.55 usft | Latitude:     | 32° 4' 36.935 N   |
|                      | +E/-W    | 0.00 usft          | Easting:            | 526,088.62 usft | Longitude:    | 104° 22' 57.239 W |
| Position Uncertainty |          | 0.00 usft          | Wellhead Elevation: | usft            | Ground Level: | 3,631.00 usft     |
| Grid Convergence:    | -0.026 ° |                    |                     |                 |               |                   |

|                  |                   |                    |                        |                      |                            |
|------------------|-------------------|--------------------|------------------------|----------------------|----------------------------|
| <b>Wellbore</b>  | Wellbore #1       |                    |                        |                      |                            |
| <b>Magnetics</b> | <b>Model Name</b> | <b>Sample Date</b> | <b>Declination (°)</b> | <b>Dip Angle (°)</b> | <b>Field Strength (nT)</b> |
|                  | HDGM2025          | 9/25/2025          | 6.817                  | 59.433               | 47,004.80                  |

|                          |                                |                     |                     |                      |      |
|--------------------------|--------------------------------|---------------------|---------------------|----------------------|------|
| <b>Design</b>            | Design #1                      |                     |                     |                      |      |
| <b>Audit Notes:</b>      |                                |                     |                     |                      |      |
| <b>Version:</b>          |                                | <b>Phase:</b>       | PLAN                | <b>Tie On Depth:</b> | 0.00 |
| <b>Vertical Section:</b> | <b>Depth From (TVD) (usft)</b> | <b>+N/-S (usft)</b> | <b>+E/-W (usft)</b> | <b>Direction (°)</b> |      |
|                          | 0.00                           | 0.00                | 0.00                | 180.83               |      |

|                                 |                        |                          |                         |                       |  |
|---------------------------------|------------------------|--------------------------|-------------------------|-----------------------|--|
| <b>Plan Survey Tool Program</b> | <b>Date</b>            | 9/25/2025                |                         |                       |  |
| <b>Depth From (usft)</b>        | <b>Depth To (usft)</b> | <b>Survey (Wellbore)</b> | <b>Tool Name</b>        | <b>Remarks</b>        |  |
| 1                               | 0.00                   | 18,820.54                | Design #1 (Wellbore #1) | MWD+IFR1+SAG+FDIR     |  |
|                                 |                        |                          |                         | OWSG MWD + IFR1 + Sag |  |





## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Plan Sections         |                 |             |                       |              |              |                         |                        |                       |         |                   |
|-----------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|------------------------|-----------------------|---------|-------------------|
| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) | TFO (°) | Target            |
| 0.00                  | 0.00            | 0.00        | 0.00                  | 0.00         | 0.00         | 0.00                    | 0.00                   | 0.00                  | 0.000   |                   |
| 500.00                | 0.00            | 0.00        | 500.00                | 0.00         | 0.00         | 0.00                    | 0.00                   | 0.00                  | 0.000   |                   |
| 2,010.59              | 15.11           | 62.14       | 1,993.15              | 92.52        | 175.03       | 1.00                    | 1.00                   | 0.00                  | 62.140  |                   |
| 6,388.70              | 15.11           | 62.14       | 6,219.98              | 625.70       | 1,183.74     | 0.00                    | 0.00                   | 0.00                  | 0.000   |                   |
| 7,899.29              | 0.00            | 0.00        | 7,713.13              | 718.22       | 1,358.77     | 1.00                    | -1.00                  | 0.00                  | 180.000 |                   |
| 7,999.29              | 0.00            | 0.00        | 7,813.13              | 718.22       | 1,358.77     | 0.00                    | 0.00                   | 0.00                  | 0.000   |                   |
| 8,817.47              | 90.00           | 180.83      | 8,334.00              | 197.41       | 1,351.23     | 11.00                   | 11.00                  | 0.00                  | 180.830 |                   |
| 12,534.43             | 90.00           | 180.83      | 8,334.00              | -3,519.16    | 1,297.39     | 0.00                    | 0.00                   | 0.00                  | 0.000   | T1-3500' VS_Pabst |
| 12,574.84             | 90.81           | 180.83      | 8,333.72              | -3,559.56    | 1,296.80     | 2.00                    | 2.00                   | 0.00                  | -0.016  |                   |
| 14,534.62             | 90.81           | 180.83      | 8,306.07              | -5,518.95    | 1,268.43     | 0.00                    | 0.00                   | 0.00                  | 0.000   | T2-5500' VS_Pabst |
| 14,569.52             | 91.51           | 180.83      | 8,305.37              | -5,553.84    | 1,267.92     | 2.00                    | 2.00                   | 0.00                  | 0.024   |                   |
| 16,535.31             | 91.51           | 180.83      | 8,253.70              | -7,518.74    | 1,239.46     | 0.00                    | 0.00                   | 0.00                  | 0.000   | T3-7500' VS_Pabst |
| 16,585.38             | 92.51           | 180.83      | 8,251.95              | -7,568.78    | 1,238.74     | 2.00                    | 2.00                   | 0.00                  | -0.012  |                   |
| 18,820.54             | 92.51           | 180.83      | 8,154.16              | -9,801.56    | 1,206.40     | 0.00                    | 0.00                   | 0.00                  | 0.000   | PBHL_Pabst Fed C  |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Planned Survey               |                 |             |                       |              |              |                         |                         |                        |                       |
|------------------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft)        | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| 0.00                         | 0.00            | 0.00        | 0.00                  | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 39.00                        | 0.00            | 0.00        | 39.00                 | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| <b>Rustler</b>               |                 |             |                       |              |              |                         |                         |                        |                       |
| 100.00                       | 0.00            | 0.00        | 100.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 200.00                       | 0.00            | 0.00        | 200.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 300.00                       | 0.00            | 0.00        | 300.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 310.00                       | 0.00            | 0.00        | 310.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| <b>Top Salt</b>              |                 |             |                       |              |              |                         |                         |                        |                       |
| 400.00                       | 0.00            | 0.00        | 400.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 500.00                       | 0.00            | 0.00        | 500.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| <b>KOP, 1.00°/100' Build</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 600.00                       | 1.00            | 62.14       | 599.99                | 0.41         | 0.77         | -0.42                   | 1.00                    | 1.00                   | 0.00                  |
| 700.00                       | 2.00            | 62.14       | 699.96                | 1.63         | 3.09         | -1.68                   | 1.00                    | 1.00                   | 0.00                  |
| 800.00                       | 3.00            | 62.14       | 799.86                | 3.67         | 6.94         | -3.77                   | 1.00                    | 1.00                   | 0.00                  |
| 900.00                       | 4.00            | 62.14       | 899.68                | 6.52         | 12.34        | -6.70                   | 1.00                    | 1.00                   | 0.00                  |
| 1,000.00                     | 5.00            | 62.14       | 999.37                | 10.19        | 19.28        | -10.47                  | 1.00                    | 1.00                   | 0.00                  |
| 1,100.00                     | 6.00            | 62.14       | 1,098.90              | 14.67        | 27.75        | -15.07                  | 1.00                    | 1.00                   | 0.00                  |
| 1,200.00                     | 7.00            | 62.14       | 1,198.26              | 19.96        | 37.76        | -20.50                  | 1.00                    | 1.00                   | 0.00                  |
| 1,300.00                     | 8.00            | 62.14       | 1,297.40              | 26.06        | 49.30        | -26.77                  | 1.00                    | 1.00                   | 0.00                  |
| 1,358.21                     | 8.58            | 62.14       | 1,355.00              | 29.98        | 56.72        | -30.80                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Base Salt</b>             |                 |             |                       |              |              |                         |                         |                        |                       |
| 1,400.00                     | 9.00            | 62.14       | 1,396.30              | 32.96        | 62.36        | -33.86                  | 1.00                    | 1.00                   | 0.00                  |
| 1,500.00                     | 10.00           | 62.14       | 1,494.93              | 40.68        | 76.96        | -41.79                  | 1.00                    | 1.00                   | 0.00                  |
| 1,583.45                     | 10.83           | 62.14       | 1,577.00              | 47.73        | 90.30        | -49.03                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Delaware Mountain Gp</b>  |                 |             |                       |              |              |                         |                         |                        |                       |
| 1,590.57                     | 10.91           | 62.14       | 1,584.00              | 48.36        | 91.48        | -49.68                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Lamar</b>                 |                 |             |                       |              |              |                         |                         |                        |                       |
| 1,600.00                     | 11.00           | 62.14       | 1,593.26              | 49.19        | 93.07        | -50.54                  | 1.00                    | 1.00                   | 0.00                  |
| 1,625.22                     | 11.25           | 62.14       | 1,618.00              | 51.47        | 97.37        | -52.87                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Bell Canyon</b>           |                 |             |                       |              |              |                         |                         |                        |                       |
| 1,636.44                     | 11.36           | 62.14       | 1,629.00              | 52.50        | 99.31        | -53.93                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Ramsey Sand</b>           |                 |             |                       |              |              |                         |                         |                        |                       |
| 1,700.00                     | 12.00           | 62.14       | 1,691.25              | 58.51        | 110.69       | -60.11                  | 1.00                    | 1.00                   | 0.00                  |
| 1,800.00                     | 13.00           | 62.14       | 1,788.87              | 68.62        | 129.83       | -70.50                  | 1.00                    | 1.00                   | 0.00                  |
| 1,900.00                     | 14.00           | 62.14       | 1,886.11              | 79.53        | 150.47       | -81.70                  | 1.00                    | 1.00                   | 0.00                  |
| 2,000.00                     | 15.00           | 62.14       | 1,982.92              | 91.23        | 172.60       | -93.72                  | 1.00                    | 1.00                   | 0.00                  |
| 2,010.59                     | 15.11           | 62.14       | 1,993.15              | 92.52        | 175.03       | -95.04                  | 1.00                    | 1.00                   | 0.00                  |
| <b>Begin 15.11° Tangent</b>  |                 |             |                       |              |              |                         |                         |                        |                       |
| 2,100.00                     | 15.11           | 62.14       | 2,079.47              | 103.41       | 195.63       | -106.23                 | 0.00                    | 0.00                   | 0.00                  |
| 2,200.00                     | 15.11           | 62.14       | 2,176.02              | 115.59       | 218.67       | -118.74                 | 0.00                    | 0.00                   | 0.00                  |
| 2,300.00                     | 15.11           | 62.14       | 2,272.56              | 127.76       | 241.71       | -131.25                 | 0.00                    | 0.00                   | 0.00                  |
| 2,400.00                     | 15.11           | 62.14       | 2,369.10              | 139.94       | 264.75       | -143.76                 | 0.00                    | 0.00                   | 0.00                  |
| 2,500.00                     | 15.11           | 62.14       | 2,465.65              | 152.12       | 287.79       | -156.27                 | 0.00                    | 0.00                   | 0.00                  |
| 2,511.76                     | 15.11           | 62.14       | 2,477.00              | 153.55       | 290.50       | -157.75                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Cherry Canyon</b>         |                 |             |                       |              |              |                         |                         |                        |                       |
| 2,600.00                     | 15.11           | 62.14       | 2,562.19              | 164.30       | 310.83       | -168.79                 | 0.00                    | 0.00                   | 0.00                  |
| 2,700.00                     | 15.11           | 62.14       | 2,658.74              | 176.48       | 333.87       | -181.30                 | 0.00                    | 0.00                   | 0.00                  |
| 2,800.00                     | 15.11           | 62.14       | 2,755.28              | 188.66       | 356.91       | -193.81                 | 0.00                    | 0.00                   | 0.00                  |
| 2,900.00                     | 15.11           | 62.14       | 2,851.83              | 200.84       | 379.95       | -206.32                 | 0.00                    | 0.00                   | 0.00                  |
| 3,000.00                     | 15.11           | 62.14       | 2,948.37              | 213.01       | 402.99       | -218.83                 | 0.00                    | 0.00                   | 0.00                  |
| 3,100.00                     | 15.11           | 62.14       | 3,044.92              | 225.19       | 426.03       | -231.34                 | 0.00                    | 0.00                   | 0.00                  |
| 3,200.00                     | 15.11           | 62.14       | 3,141.46              | 237.37       | 449.07       | -243.85                 | 0.00                    | 0.00                   | 0.00                  |
| 3,300.00                     | 15.11           | 62.14       | 3,238.01              | 249.55       | 472.11       | -256.36                 | 0.00                    | 0.00                   | 0.00                  |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Planned Survey               |                 |             |                       |              |              |                         |                         |                        |                       |
|------------------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft)        | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| 3,400.00                     | 15.11           | 62.14       | 3,334.55              | 261.73       | 495.15       | -268.87                 | 0.00                    | 0.00                   | 0.00                  |
| 3,500.00                     | 15.11           | 62.14       | 3,431.10              | 273.91       | 518.19       | -281.38                 | 0.00                    | 0.00                   | 0.00                  |
| 3,581.73                     | 15.11           | 62.14       | 3,510.00              | 283.86       | 537.02       | -291.61                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Brushy Canyon</b>         |                 |             |                       |              |              |                         |                         |                        |                       |
| 3,600.00                     | 15.11           | 62.14       | 3,527.64              | 286.08       | 541.23       | -293.89                 | 0.00                    | 0.00                   | 0.00                  |
| 3,700.00                     | 15.11           | 62.14       | 3,624.18              | 298.26       | 564.27       | -306.40                 | 0.00                    | 0.00                   | 0.00                  |
| 3,800.00                     | 15.11           | 62.14       | 3,720.73              | 310.44       | 587.31       | -318.92                 | 0.00                    | 0.00                   | 0.00                  |
| 3,900.00                     | 15.11           | 62.14       | 3,817.27              | 322.62       | 610.35       | -331.43                 | 0.00                    | 0.00                   | 0.00                  |
| 4,000.00                     | 15.11           | 62.14       | 3,913.82              | 334.80       | 633.39       | -343.94                 | 0.00                    | 0.00                   | 0.00                  |
| 4,100.00                     | 15.11           | 62.14       | 4,010.36              | 346.98       | 656.43       | -356.45                 | 0.00                    | 0.00                   | 0.00                  |
| 4,200.00                     | 15.11           | 62.14       | 4,106.91              | 359.15       | 679.47       | -368.96                 | 0.00                    | 0.00                   | 0.00                  |
| 4,300.00                     | 15.11           | 62.14       | 4,203.45              | 371.33       | 702.51       | -381.47                 | 0.00                    | 0.00                   | 0.00                  |
| 4,400.00                     | 15.11           | 62.14       | 4,300.00              | 383.51       | 725.55       | -393.98                 | 0.00                    | 0.00                   | 0.00                  |
| 4,500.00                     | 15.11           | 62.14       | 4,396.54              | 395.69       | 748.59       | -406.49                 | 0.00                    | 0.00                   | 0.00                  |
| 4,600.00                     | 15.11           | 62.14       | 4,493.09              | 407.87       | 771.63       | -419.00                 | 0.00                    | 0.00                   | 0.00                  |
| 4,700.00                     | 15.11           | 62.14       | 4,589.63              | 420.05       | 794.67       | -431.51                 | 0.00                    | 0.00                   | 0.00                  |
| 4,800.00                     | 15.11           | 62.14       | 4,686.18              | 432.22       | 817.71       | -444.02                 | 0.00                    | 0.00                   | 0.00                  |
| 4,900.00                     | 15.11           | 62.14       | 4,782.72              | 444.40       | 840.74       | -456.54                 | 0.00                    | 0.00                   | 0.00                  |
| 5,000.00                     | 15.11           | 62.14       | 4,879.26              | 456.58       | 863.78       | -469.05                 | 0.00                    | 0.00                   | 0.00                  |
| 5,089.84                     | 15.11           | 62.14       | 4,966.00              | 467.52       | 884.48       | -480.29                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Bone Spring Lime</b>      |                 |             |                       |              |              |                         |                         |                        |                       |
| 5,100.00                     | 15.11           | 62.14       | 4,975.81              | 468.76       | 886.82       | -481.56                 | 0.00                    | 0.00                   | 0.00                  |
| 5,200.00                     | 15.11           | 62.14       | 5,072.35              | 480.94       | 909.86       | -494.07                 | 0.00                    | 0.00                   | 0.00                  |
| 5,300.00                     | 15.11           | 62.14       | 5,168.90              | 493.12       | 932.90       | -506.58                 | 0.00                    | 0.00                   | 0.00                  |
| 5,358.11                     | 15.11           | 62.14       | 5,225.00              | 500.19       | 946.29       | -513.85                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Upper Avalon</b>          |                 |             |                       |              |              |                         |                         |                        |                       |
| 5,400.00                     | 15.11           | 62.14       | 5,265.44              | 505.30       | 955.94       | -519.09                 | 0.00                    | 0.00                   | 0.00                  |
| 5,500.00                     | 15.11           | 62.14       | 5,361.99              | 517.47       | 978.98       | -531.60                 | 0.00                    | 0.00                   | 0.00                  |
| 5,600.00                     | 15.11           | 62.14       | 5,458.53              | 529.65       | 1,002.02     | -544.11                 | 0.00                    | 0.00                   | 0.00                  |
| 5,671.95                     | 15.11           | 62.14       | 5,528.00              | 538.41       | 1,018.60     | -553.11                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Middle Avalon</b>         |                 |             |                       |              |              |                         |                         |                        |                       |
| 5,700.00                     | 15.11           | 62.14       | 5,555.08              | 541.83       | 1,025.06     | -556.62                 | 0.00                    | 0.00                   | 0.00                  |
| 5,800.00                     | 15.11           | 62.14       | 5,651.62              | 554.01       | 1,048.10     | -569.13                 | 0.00                    | 0.00                   | 0.00                  |
| 5,900.00                     | 15.11           | 62.14       | 5,748.17              | 566.19       | 1,071.14     | -581.64                 | 0.00                    | 0.00                   | 0.00                  |
| 6,000.00                     | 15.11           | 62.14       | 5,844.71              | 578.37       | 1,094.18     | -594.15                 | 0.00                    | 0.00                   | 0.00                  |
| 6,027.23                     | 15.11           | 62.14       | 5,871.00              | 581.68       | 1,100.46     | -597.56                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Lower Avalon</b>          |                 |             |                       |              |              |                         |                         |                        |                       |
| 6,100.00                     | 15.11           | 62.14       | 5,941.25              | 590.54       | 1,117.22     | -606.67                 | 0.00                    | 0.00                   | 0.00                  |
| 6,172.24                     | 15.11           | 62.14       | 6,011.00              | 599.34       | 1,133.87     | -615.70                 | 0.00                    | 0.00                   | 0.00                  |
| <b>1st Bone Spring Sand</b>  |                 |             |                       |              |              |                         |                         |                        |                       |
| 6,200.00                     | 15.11           | 62.14       | 6,037.80              | 602.72       | 1,140.26     | -619.18                 | 0.00                    | 0.00                   | 0.00                  |
| 6,300.00                     | 15.11           | 62.14       | 6,134.34              | 614.90       | 1,163.30     | -631.69                 | 0.00                    | 0.00                   | 0.00                  |
| 6,388.70                     | 15.11           | 62.14       | 6,219.98              | 625.70       | 1,183.74     | -642.78                 | 0.00                    | 0.00                   | 0.00                  |
| <b>Begin 1.00°/100' Drop</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 6,400.00                     | 14.99           | 62.14       | 6,230.89              | 627.07       | 1,186.33     | -644.19                 | 1.00                    | -1.00                  | 0.00                  |
| 6,476.59                     | 14.23           | 62.14       | 6,305.00              | 636.10       | 1,203.41     | -653.47                 | 1.00                    | -1.00                  | 0.00                  |
| <b>2nd Bone Spring Carb</b>  |                 |             |                       |              |              |                         |                         |                        |                       |
| 6,500.00                     | 13.99           | 62.14       | 6,327.71              | 638.77       | 1,208.46     | -656.21                 | 1.00                    | -1.00                  | 0.00                  |
| 6,600.00                     | 12.99           | 62.14       | 6,424.95              | 649.67       | 1,229.08     | -667.41                 | 1.00                    | -1.00                  | 0.00                  |
| 6,700.00                     | 11.99           | 62.14       | 6,522.58              | 659.78       | 1,248.21     | -677.79                 | 1.00                    | -1.00                  | 0.00                  |
| 6,800.00                     | 10.99           | 62.14       | 6,620.57              | 669.09       | 1,265.82     | -687.36                 | 1.00                    | -1.00                  | 0.00                  |
| 6,900.00                     | 9.99            | 62.14       | 6,718.90              | 677.60       | 1,281.92     | -696.10                 | 1.00                    | -1.00                  | 0.00                  |
| 6,959.96                     | 9.39            | 62.14       | 6,778.00              | 682.32       | 1,290.85     | -700.95                 | 1.00                    | -1.00                  | 0.00                  |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Planned Survey                |                 |             |                       |              |              |                         |                         |                        |                       |
|-------------------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft)         | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| <b>2nd Bone Spring Sand</b>   |                 |             |                       |              |              |                         |                         |                        |                       |
| 7,000.00                      | 8.99            | 62.14       | 6,817.53              | 685.31       | 1,296.50     | -704.02                 | 1.00                    | -1.00                  | 0.00                  |
| 7,100.00                      | 7.99            | 62.14       | 6,916.43              | 692.21       | 1,309.56     | -711.11                 | 1.00                    | -1.00                  | 0.00                  |
| 7,111.68                      | 7.88            | 62.14       | 6,928.00              | 692.96       | 1,310.99     | -711.88                 | 1.00                    | -1.00                  | 0.00                  |
| <b>3rd Bone Spring Carb</b>   |                 |             |                       |              |              |                         |                         |                        |                       |
| 7,200.00                      | 6.99            | 62.14       | 7,015.57              | 698.30       | 1,321.09     | -717.37                 | 1.00                    | -1.00                  | 0.00                  |
| 7,300.00                      | 5.99            | 62.14       | 7,114.93              | 703.59       | 1,331.09     | -722.80                 | 1.00                    | -1.00                  | 0.00                  |
| 7,400.00                      | 4.99            | 62.14       | 7,214.47              | 708.06       | 1,339.55     | -727.39                 | 1.00                    | -1.00                  | 0.00                  |
| 7,500.00                      | 3.99            | 62.14       | 7,314.16              | 711.72       | 1,346.47     | -731.15                 | 1.00                    | -1.00                  | 0.00                  |
| 7,600.00                      | 2.99            | 62.14       | 7,413.98              | 714.57       | 1,351.86     | -734.08                 | 1.00                    | -1.00                  | 0.00                  |
| 7,700.00                      | 1.99            | 62.14       | 7,513.88              | 716.60       | 1,355.71     | -736.17                 | 1.00                    | -1.00                  | 0.00                  |
| 7,800.00                      | 0.99            | 62.14       | 7,613.84              | 717.82       | 1,358.01     | -737.42                 | 1.00                    | -1.00                  | 0.00                  |
| 7,899.29                      | 0.00            | 0.00        | 7,713.13              | 718.22       | 1,358.77     | -737.83                 | 1.00                    | -1.00                  | 0.00                  |
| <b>Begin Vertical Hold</b>    |                 |             |                       |              |              |                         |                         |                        |                       |
| 7,999.29                      | 0.00            | 0.00        | 7,813.13              | 718.22       | 1,358.77     | -737.83                 | 0.00                    | 0.00                   | 0.00                  |
| <b>KOP, 11.00°/100' Build</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,050.00                      | 5.58            | 180.83      | 7,863.76              | 715.76       | 1,358.73     | -735.36                 | 11.00                   | 11.00                  | 0.00                  |
| 8,064.33                      | 7.15            | 180.83      | 7,878.00              | 714.17       | 1,358.71     | -733.77                 | 11.00                   | 11.00                  | 0.00                  |
| <b>3rd Bone Spring Sand</b>   |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,100.00                      | 11.08           | 180.83      | 7,913.21              | 708.52       | 1,358.63     | -728.12                 | 11.00                   | 11.00                  | 0.00                  |
| 8,150.00                      | 16.58           | 180.83      | 7,961.75              | 696.57       | 1,358.46     | -716.18                 | 11.00                   | 11.00                  | 0.00                  |
| 8,200.00                      | 22.08           | 180.83      | 8,008.91              | 680.03       | 1,358.22     | -699.64                 | 11.00                   | 11.00                  | 0.00                  |
| 8,250.00                      | 27.58           | 180.83      | 8,054.27              | 659.05       | 1,357.91     | -678.65                 | 11.00                   | 11.00                  | 0.00                  |
| 8,300.00                      | 33.08           | 180.83      | 8,097.41              | 633.81       | 1,357.55     | -653.41                 | 11.00                   | 11.00                  | 0.00                  |
| 8,350.00                      | 38.58           | 180.83      | 8,137.93              | 604.56       | 1,357.12     | -624.15                 | 11.00                   | 11.00                  | 0.00                  |
| 8,355.22                      | 39.15           | 180.83      | 8,142.00              | 601.28       | 1,357.08     | -620.88                 | 11.00                   | 11.00                  | 0.00                  |
| <b>3rd BS W Sand</b>          |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,400.00                      | 44.08           | 180.83      | 8,175.47              | 571.56       | 1,356.65     | -591.15                 | 11.00                   | 11.00                  | 0.00                  |
| 8,450.00                      | 49.58           | 180.83      | 8,209.66              | 535.11       | 1,356.12     | -554.70                 | 11.00                   | 11.00                  | 0.00                  |
| 8,485.93                      | 53.53           | 180.83      | 8,232.00              | 506.98       | 1,355.71     | -526.56                 | 11.00                   | 11.00                  | 0.00                  |
| <b>Wolfcamp A X Sand</b>      |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,500.00                      | 55.08           | 180.83      | 8,240.21              | 495.55       | 1,355.54     | -515.14                 | 11.00                   | 11.00                  | 0.00                  |
| 8,550.00                      | 60.58           | 180.83      | 8,266.82              | 453.25       | 1,354.93     | -472.83                 | 11.00                   | 11.00                  | 0.00                  |
| 8,600.00                      | 66.08           | 180.83      | 8,289.26              | 408.59       | 1,354.29     | -428.17                 | 11.00                   | 11.00                  | 0.00                  |
| 8,625.44                      | 68.88           | 180.83      | 8,299.00              | 385.10       | 1,353.94     | -404.67                 | 11.00                   | 11.00                  | 0.00                  |
| <b>Wolfcamp A Y Sand</b>      |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,650.00                      | 71.58           | 180.83      | 8,307.31              | 361.99       | 1,353.61     | -381.56                 | 11.00                   | 11.00                  | 0.00                  |
| 8,700.00                      | 77.08           | 180.83      | 8,320.81              | 313.87       | 1,352.91     | -333.44                 | 11.00                   | 11.00                  | 0.00                  |
| 8,750.00                      | 82.58           | 180.83      | 8,329.64              | 264.68       | 1,352.20     | -284.24                 | 11.00                   | 11.00                  | 0.00                  |
| 8,800.00                      | 88.08           | 180.83      | 8,333.71              | 214.87       | 1,351.48     | -234.43                 | 11.00                   | 11.00                  | 0.00                  |
| 8,817.47                      | 90.00           | 180.83      | 8,334.00              | 197.41       | 1,351.23     | -216.96                 | 11.00                   | 11.00                  | 0.00                  |
| <b>Begin 90.00° Lateral</b>   |                 |             |                       |              |              |                         |                         |                        |                       |
| 8,900.00                      | 90.00           | 180.83      | 8,334.00              | 114.89       | 1,350.03     | -134.43                 | 0.00                    | 0.00                   | 0.00                  |
| 9,000.00                      | 90.00           | 180.83      | 8,334.00              | 14.90        | 1,348.58     | -34.43                  | 0.00                    | 0.00                   | 0.00                  |
| 9,100.00                      | 90.00           | 180.83      | 8,334.00              | -85.09       | 1,347.13     | 65.57                   | 0.00                    | 0.00                   | 0.00                  |
| 9,200.00                      | 90.00           | 180.83      | 8,334.00              | -185.08      | 1,345.69     | 165.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,300.00                      | 90.00           | 180.83      | 8,334.00              | -285.07      | 1,344.24     | 265.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,400.00                      | 90.00           | 180.83      | 8,334.00              | -385.06      | 1,342.79     | 365.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,500.00                      | 90.00           | 180.83      | 8,334.00              | -485.05      | 1,341.34     | 465.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,600.00                      | 90.00           | 180.83      | 8,334.00              | -585.04      | 1,339.89     | 565.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,700.00                      | 90.00           | 180.83      | 8,334.00              | -685.03      | 1,338.44     | 665.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,800.00                      | 90.00           | 180.83      | 8,334.00              | -785.02      | 1,337.00     | 765.57                  | 0.00                    | 0.00                   | 0.00                  |
| 9,900.00                      | 90.00           | 180.83      | 8,334.00              | -885.01      | 1,335.55     | 865.57                  | 0.00                    | 0.00                   | 0.00                  |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Planned Survey                      |                 |             |                       |              |              |                         |                         |                        |                       |
|-------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft)               | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| 10,000.00                           | 90.00           | 180.83      | 8,334.00              | -985.00      | 1,334.10     | 965.57                  | 0.00                    | 0.00                   | 0.00                  |
| 10,100.00                           | 90.00           | 180.83      | 8,334.00              | -1,084.99    | 1,332.65     | 1,065.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,200.00                           | 90.00           | 180.83      | 8,334.00              | -1,184.98    | 1,331.20     | 1,165.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,300.00                           | 90.00           | 180.83      | 8,334.00              | -1,284.97    | 1,329.75     | 1,265.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,400.00                           | 90.00           | 180.83      | 8,334.00              | -1,384.96    | 1,328.30     | 1,365.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,500.00                           | 90.00           | 180.83      | 8,334.00              | -1,484.95    | 1,326.86     | 1,465.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,600.00                           | 90.00           | 180.83      | 8,334.00              | -1,584.94    | 1,325.41     | 1,565.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,700.00                           | 90.00           | 180.83      | 8,334.00              | -1,684.92    | 1,323.96     | 1,665.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,800.00                           | 90.00           | 180.83      | 8,334.00              | -1,784.91    | 1,322.51     | 1,765.57                | 0.00                    | 0.00                   | 0.00                  |
| 10,900.00                           | 90.00           | 180.83      | 8,334.00              | -1,884.90    | 1,321.06     | 1,865.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,000.00                           | 90.00           | 180.83      | 8,334.00              | -1,984.89    | 1,319.61     | 1,965.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,100.00                           | 90.00           | 180.83      | 8,334.00              | -2,084.88    | 1,318.17     | 2,065.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,200.00                           | 90.00           | 180.83      | 8,334.00              | -2,184.87    | 1,316.72     | 2,165.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,300.00                           | 90.00           | 180.83      | 8,334.00              | -2,284.86    | 1,315.27     | 2,265.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,400.00                           | 90.00           | 180.83      | 8,334.00              | -2,384.85    | 1,313.82     | 2,365.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,500.00                           | 90.00           | 180.83      | 8,334.00              | -2,484.84    | 1,312.37     | 2,465.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,600.00                           | 90.00           | 180.83      | 8,334.00              | -2,584.83    | 1,310.92     | 2,565.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,700.00                           | 90.00           | 180.83      | 8,334.00              | -2,684.82    | 1,309.48     | 2,665.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,800.00                           | 90.00           | 180.83      | 8,334.00              | -2,784.81    | 1,308.03     | 2,765.57                | 0.00                    | 0.00                   | 0.00                  |
| 11,900.00                           | 90.00           | 180.83      | 8,334.00              | -2,884.80    | 1,306.58     | 2,865.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,000.00                           | 90.00           | 180.83      | 8,334.00              | -2,984.79    | 1,305.13     | 2,965.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,100.00                           | 90.00           | 180.83      | 8,334.00              | -3,084.78    | 1,303.68     | 3,065.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,200.00                           | 90.00           | 180.83      | 8,334.00              | -3,184.77    | 1,302.23     | 3,165.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,300.00                           | 90.00           | 180.83      | 8,334.00              | -3,284.76    | 1,300.79     | 3,265.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,400.00                           | 90.00           | 180.83      | 8,334.00              | -3,384.75    | 1,299.34     | 3,365.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,500.00                           | 90.00           | 180.83      | 8,334.00              | -3,484.74    | 1,297.89     | 3,465.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,534.43                           | 90.00           | 180.83      | 8,334.00              | -3,519.16    | 1,297.39     | 3,500.00                | 0.00                    | 0.00                   | 0.00                  |
| <b>Begin 2.00°/100' Build</b>       |                 |             |                       |              |              |                         |                         |                        |                       |
| 12,574.84                           | 90.81           | 180.83      | 8,333.72              | -3,559.56    | 1,296.80     | 3,540.40                | 2.00                    | 2.00                   | 0.00                  |
| <b>Hold 90.81° Inc, 180.83° Azm</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 12,600.00                           | 90.81           | 180.83      | 8,333.36              | -3,584.72    | 1,296.44     | 3,565.57                | 0.00                    | 0.00                   | 0.00                  |
| 12,700.00                           | 90.81           | 180.83      | 8,331.95              | -3,684.70    | 1,294.99     | 3,665.56                | 0.00                    | 0.00                   | 0.00                  |
| 12,800.00                           | 90.81           | 180.83      | 8,330.54              | -3,784.68    | 1,293.54     | 3,765.55                | 0.00                    | 0.00                   | 0.00                  |
| 12,900.00                           | 90.81           | 180.83      | 8,329.13              | -3,884.66    | 1,292.10     | 3,865.54                | 0.00                    | 0.00                   | 0.00                  |
| 13,000.00                           | 90.81           | 180.83      | 8,327.72              | -3,984.64    | 1,290.65     | 3,965.53                | 0.00                    | 0.00                   | 0.00                  |
| 13,100.00                           | 90.81           | 180.83      | 8,326.31              | -4,084.62    | 1,289.20     | 4,065.52                | 0.00                    | 0.00                   | 0.00                  |
| 13,200.00                           | 90.81           | 180.83      | 8,324.90              | -4,184.60    | 1,287.75     | 4,165.51                | 0.00                    | 0.00                   | 0.00                  |
| 13,300.00                           | 90.81           | 180.83      | 8,323.49              | -4,284.58    | 1,286.31     | 4,265.50                | 0.00                    | 0.00                   | 0.00                  |
| 13,400.00                           | 90.81           | 180.83      | 8,322.08              | -4,384.56    | 1,284.86     | 4,365.49                | 0.00                    | 0.00                   | 0.00                  |
| 13,500.00                           | 90.81           | 180.83      | 8,320.67              | -4,484.54    | 1,283.41     | 4,465.48                | 0.00                    | 0.00                   | 0.00                  |
| 13,600.00                           | 90.81           | 180.83      | 8,319.26              | -4,584.52    | 1,281.96     | 4,565.47                | 0.00                    | 0.00                   | 0.00                  |
| 13,700.00                           | 90.81           | 180.83      | 8,317.85              | -4,684.50    | 1,280.51     | 4,665.46                | 0.00                    | 0.00                   | 0.00                  |
| 13,800.00                           | 90.81           | 180.83      | 8,316.43              | -4,784.48    | 1,279.07     | 4,765.45                | 0.00                    | 0.00                   | 0.00                  |
| 13,900.00                           | 90.81           | 180.83      | 8,315.02              | -4,884.46    | 1,277.62     | 4,865.44                | 0.00                    | 0.00                   | 0.00                  |
| 14,000.00                           | 90.81           | 180.83      | 8,313.61              | -4,984.44    | 1,276.17     | 4,965.43                | 0.00                    | 0.00                   | 0.00                  |
| 14,100.00                           | 90.81           | 180.83      | 8,312.20              | -5,084.42    | 1,274.72     | 5,065.42                | 0.00                    | 0.00                   | 0.00                  |
| 14,200.00                           | 90.81           | 180.83      | 8,310.79              | -5,184.39    | 1,273.27     | 5,165.41                | 0.00                    | 0.00                   | 0.00                  |
| 14,300.00                           | 90.81           | 180.83      | 8,309.38              | -5,284.37    | 1,271.83     | 5,265.40                | 0.00                    | 0.00                   | 0.00                  |
| 14,400.00                           | 90.81           | 180.83      | 8,307.97              | -5,384.35    | 1,270.38     | 5,365.39                | 0.00                    | 0.00                   | 0.00                  |
| 14,500.00                           | 90.81           | 180.83      | 8,306.56              | -5,484.33    | 1,268.93     | 5,465.38                | 0.00                    | 0.00                   | 0.00                  |
| 14,534.62                           | 90.81           | 180.83      | 8,306.07              | -5,518.95    | 1,268.43     | 5,500.00                | 0.00                    | 0.00                   | 0.00                  |
| <b>Begin 2.00°/100' Build</b>       |                 |             |                       |              |              |                         |                         |                        |                       |
| 14,569.52                           | 91.51           | 180.83      | 8,305.37              | -5,553.84    | 1,267.92     | 5,534.89                | 2.00                    | 2.00                   | 0.00                  |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Planned Survey                      |                 |             |                       |              |              |                         |                         |                        |                       |
|-------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft)               | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| <b>Hold 91.51° Inc, 180.83° Azm</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 14,600.00                           | 91.51           | 180.83      | 8,304.57              | -5,584.30    | 1,267.48     | 5,565.36                | 0.00                    | 0.00                   | 0.00                  |
| 14,700.00                           | 91.51           | 180.83      | 8,301.94              | -5,684.26    | 1,266.04     | 5,665.32                | 0.00                    | 0.00                   | 0.00                  |
| 14,800.00                           | 91.51           | 180.83      | 8,299.31              | -5,784.21    | 1,264.59     | 5,765.29                | 0.00                    | 0.00                   | 0.00                  |
| 14,900.00                           | 91.51           | 180.83      | 8,296.68              | -5,884.17    | 1,263.14     | 5,865.25                | 0.00                    | 0.00                   | 0.00                  |
| 15,000.00                           | 91.51           | 180.83      | 8,294.05              | -5,984.12    | 1,261.69     | 5,965.22                | 0.00                    | 0.00                   | 0.00                  |
| 15,100.00                           | 91.51           | 180.83      | 8,291.43              | -6,084.08    | 1,260.24     | 6,065.18                | 0.00                    | 0.00                   | 0.00                  |
| 15,200.00                           | 91.51           | 180.83      | 8,288.80              | -6,184.03    | 1,258.80     | 6,165.15                | 0.00                    | 0.00                   | 0.00                  |
| 15,300.00                           | 91.51           | 180.83      | 8,286.17              | -6,283.99    | 1,257.35     | 6,265.11                | 0.00                    | 0.00                   | 0.00                  |
| 15,400.00                           | 91.51           | 180.83      | 8,283.54              | -6,383.94    | 1,255.90     | 6,365.08                | 0.00                    | 0.00                   | 0.00                  |
| 15,500.00                           | 91.51           | 180.83      | 8,280.91              | -6,483.90    | 1,254.45     | 6,465.04                | 0.00                    | 0.00                   | 0.00                  |
| 15,600.00                           | 91.51           | 180.83      | 8,278.28              | -6,583.85    | 1,253.00     | 6,565.01                | 0.00                    | 0.00                   | 0.00                  |
| 15,700.00                           | 91.51           | 180.83      | 8,275.66              | -6,683.81    | 1,251.56     | 6,664.98                | 0.00                    | 0.00                   | 0.00                  |
| 15,800.00                           | 91.51           | 180.83      | 8,273.03              | -6,783.76    | 1,250.11     | 6,764.94                | 0.00                    | 0.00                   | 0.00                  |
| 15,900.00                           | 91.51           | 180.83      | 8,270.40              | -6,883.72    | 1,248.66     | 6,864.91                | 0.00                    | 0.00                   | 0.00                  |
| 16,000.00                           | 91.51           | 180.83      | 8,267.77              | -6,983.67    | 1,247.21     | 6,964.87                | 0.00                    | 0.00                   | 0.00                  |
| 16,100.00                           | 91.51           | 180.83      | 8,265.14              | -7,083.63    | 1,245.76     | 7,064.84                | 0.00                    | 0.00                   | 0.00                  |
| 16,200.00                           | 91.51           | 180.83      | 8,262.51              | -7,183.58    | 1,244.32     | 7,164.80                | 0.00                    | 0.00                   | 0.00                  |
| 16,300.00                           | 91.51           | 180.83      | 8,259.89              | -7,283.54    | 1,242.87     | 7,264.77                | 0.00                    | 0.00                   | 0.00                  |
| 16,400.00                           | 91.51           | 180.83      | 8,257.26              | -7,383.49    | 1,241.42     | 7,364.73                | 0.00                    | 0.00                   | 0.00                  |
| 16,500.00                           | 91.51           | 180.83      | 8,254.63              | -7,483.45    | 1,239.97     | 7,464.70                | 0.00                    | 0.00                   | 0.00                  |
| 16,535.31                           | 91.51           | 180.83      | 8,253.70              | -7,518.74    | 1,239.46     | 7,500.00                | 0.00                    | 0.00                   | 0.00                  |
| <b>Begin 2.00°/100' Build</b>       |                 |             |                       |              |              |                         |                         |                        |                       |
| 16,585.38                           | 92.51           | 180.83      | 8,251.95              | -7,568.78    | 1,238.74     | 7,550.04                | 2.00                    | 2.00                   | 0.00                  |
| <b>Hold 92.51° Inc, 180.83° Azm</b> |                 |             |                       |              |              |                         |                         |                        |                       |
| 16,600.00                           | 92.51           | 180.83      | 8,251.31              | -7,583.38    | 1,238.52     | 7,564.64                | 0.00                    | 0.00                   | 0.00                  |
| 16,700.00                           | 92.51           | 180.83      | 8,246.93              | -7,683.27    | 1,237.08     | 7,664.55                | 0.00                    | 0.00                   | 0.00                  |
| 16,800.00                           | 92.51           | 180.83      | 8,242.56              | -7,783.17    | 1,235.63     | 7,764.45                | 0.00                    | 0.00                   | 0.00                  |
| 16,900.00                           | 92.51           | 180.83      | 8,238.18              | -7,883.06    | 1,234.18     | 7,864.35                | 0.00                    | 0.00                   | 0.00                  |
| 17,000.00                           | 92.51           | 180.83      | 8,233.81              | -7,982.95    | 1,232.74     | 7,964.26                | 0.00                    | 0.00                   | 0.00                  |
| 17,100.00                           | 92.51           | 180.83      | 8,229.43              | -8,082.85    | 1,231.29     | 8,064.16                | 0.00                    | 0.00                   | 0.00                  |
| 17,200.00                           | 92.51           | 180.83      | 8,225.06              | -8,182.74    | 1,229.84     | 8,164.07                | 0.00                    | 0.00                   | 0.00                  |
| 17,300.00                           | 92.51           | 180.83      | 8,220.68              | -8,282.63    | 1,228.40     | 8,263.97                | 0.00                    | 0.00                   | 0.00                  |
| 17,400.00                           | 92.51           | 180.83      | 8,216.31              | -8,382.53    | 1,226.95     | 8,363.88                | 0.00                    | 0.00                   | 0.00                  |
| 17,500.00                           | 92.51           | 180.83      | 8,211.93              | -8,482.42    | 1,225.50     | 8,463.78                | 0.00                    | 0.00                   | 0.00                  |
| 17,600.00                           | 92.51           | 180.83      | 8,207.56              | -8,582.32    | 1,224.06     | 8,563.68                | 0.00                    | 0.00                   | 0.00                  |
| 17,700.00                           | 92.51           | 180.83      | 8,203.18              | -8,682.21    | 1,222.61     | 8,663.59                | 0.00                    | 0.00                   | 0.00                  |
| 17,800.00                           | 92.51           | 180.83      | 8,198.81              | -8,782.10    | 1,221.16     | 8,763.49                | 0.00                    | 0.00                   | 0.00                  |
| 17,900.00                           | 92.51           | 180.83      | 8,194.43              | -8,882.00    | 1,219.72     | 8,863.40                | 0.00                    | 0.00                   | 0.00                  |
| 18,000.00                           | 92.51           | 180.83      | 8,190.06              | -8,981.89    | 1,218.27     | 8,963.30                | 0.00                    | 0.00                   | 0.00                  |
| 18,100.00                           | 92.51           | 180.83      | 8,185.68              | -9,081.78    | 1,216.82     | 9,063.21                | 0.00                    | 0.00                   | 0.00                  |
| 18,200.00                           | 92.51           | 180.83      | 8,181.31              | -9,181.68    | 1,215.38     | 9,163.11                | 0.00                    | 0.00                   | 0.00                  |
| 18,300.00                           | 92.51           | 180.83      | 8,176.93              | -9,281.57    | 1,213.93     | 9,263.01                | 0.00                    | 0.00                   | 0.00                  |
| 18,400.00                           | 92.51           | 180.83      | 8,172.56              | -9,381.47    | 1,212.48     | 9,362.92                | 0.00                    | 0.00                   | 0.00                  |
| 18,500.00                           | 92.51           | 180.83      | 8,168.18              | -9,481.36    | 1,211.04     | 9,462.82                | 0.00                    | 0.00                   | 0.00                  |
| 18,600.00                           | 92.51           | 180.83      | 8,163.81              | -9,581.25    | 1,209.59     | 9,562.73                | 0.00                    | 0.00                   | 0.00                  |
| 18,700.00                           | 92.51           | 180.83      | 8,159.43              | -9,681.15    | 1,208.14     | 9,662.63                | 0.00                    | 0.00                   | 0.00                  |
| 18,800.00                           | 92.51           | 180.83      | 8,155.06              | -9,781.04    | 1,206.70     | 9,762.53                | 0.00                    | 0.00                   | 0.00                  |
| 18,820.54                           | 92.51           | 180.83      | 8,154.16              | -9,801.56    | 1,206.40     | 9,783.06                | 0.00                    | 0.00                   | 0.00                  |
| <b>PBHL</b>                         |                 |             |                       |              |              |                         |                         |                        |                       |





## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

| Design Targets   |                  |                 |               |                 |                 |                    |                   |                 |                   |
|--|------------------|-----------------|---------------|-----------------|-----------------|--------------------|-------------------|-----------------|-------------------|
| Target Name<br>- hit/miss target<br>- Shape  | Dip Angle<br>(°) | Dip Dir.<br>(°) | TVD<br>(usft) | +N/-S<br>(usft) | +E/-W<br>(usft) | Northing<br>(usft) | Easting<br>(usft) | Latitude        | Longitude         |
| LTP_Pabst Fed Com :<br>- plan misses target center by 8160.64usft at 18820.54usft MD (8154.16 TVD, -9801.56 N, 1206.40 E)<br>- Point | 0.00             | 0.00            | 0.00          | -9,476.43       | 1,215.71        | 382,250.12         | 527,304.33        | 32° 3' 3.159 N  | 104° 22' 43.062 W |
| BPP1_Pabst Fed Con<br>- plan misses target center by 4695.84usft at 0.00usft MD (0.00 TVD, 0.00 N, 0.00 E)<br>- Point                | 0.00             | 0.00            | 0.00          | -4,515.96       | 1,287.27        | 387,210.59         | 527,375.89        | 32° 3' 52.249 N | 104° 22' 42.255 W |
| KOP_Pabst Fed Com<br>- plan misses target center by 1536.91usft at 0.00usft MD (0.00 TVD, 0.00 N, 0.00 E)<br>- Point                 | 0.00             | 0.00            | 0.00          | 718.22          | 1,358.77        | 392,444.77         | 527,447.40        | 32° 4' 44.049 N | 104° 22' 41.449 W |
| FTP_Pabst Fed Com<br>- plan misses target center by 1427.66usft at 0.00usft MD (0.00 TVD, 0.00 N, 0.00 E)<br>- Point                 | 0.00             | 0.00            | 0.00          | 438.19          | 1,358.75        | 392,164.74         | 527,447.37        | 32° 4' 41.277 N | 104° 22' 41.448 W |
| PBHL_Pabst Fed Con<br>- plan hits target center<br>- Point   | 0.00             | 360.00          | 8,154.16      | -9,801.56       | 1,206.40        | 381,924.99         | 527,295.02        | 32° 2' 59.941 N | 104° 22' 43.169 W |
| T3-7500' VS_Pabst F<br>- plan hits target center<br>- Point  | 0.00             | 0.00            | 8,253.70      | -7,518.74       | 1,239.46        | 384,207.81         | 527,328.08        | 32° 3' 22.533 N | 104° 22' 42.796 W |
| T2-5500' VS_Pabst F<br>- plan hits target center<br>- Point  | 0.00             | 0.00            | 8,306.07      | -5,518.95       | 1,268.43        | 386,207.60         | 527,357.05        | 32° 3' 42.323 N | 104° 22' 42.469 W |
| T1-3500' VS_Pabst F<br>- plan hits target center<br>- Point  | 0.00             | 0.00            | 8,334.00      | -3,519.16       | 1,297.39        | 388,207.39         | 527,386.01        | 32° 4' 2.114 N  | 104° 22' 42.142 W |



## Planning Report



|                  |  |                                     |                              |
|------------------|--|-------------------------------------|------------------------------|
| <b>Database:</b> | TRG_EDMConroe                          | <b>Local Co-ordinate Reference:</b> | Well Pabst Fed Com 204H      |
| <b>Company:</b>  | Tap Rock Operating                     | <b>TVD Reference:</b>               | Well @ 3657.00usft (H&P 466) |
| <b>Project:</b>  | Eddy County, New Mexico (NAD 83)       | <b>MD Reference:</b>                | Well @ 3657.00usft (H&P 466) |
| <b>Site:</b>     | Pabst Fed Com (202H, 204H, 211H, 213H) | <b>North Reference:</b>             | Grid                         |
| <b>Well:</b>     | Pabst Fed Com 204H                     | <b>Survey Calculation Method:</b>   | Minimum Curvature            |
| <b>Wellbore:</b> | Wellbore #1                            |                                     |                              |
| <b>Design:</b>   | Design #1                              |                                     |                              |

## Formations

| Measured Depth (usft) | Vertical Depth (usft) | Name                 | Lithology | Dip (°) | Dip Direction (°) |
|-----------------------|-----------------------|----------------------|-----------|---------|-------------------|
| 39.00                 | 39.00                 | Rustler              |           |         |                   |
| 310.00                | 310.00                | Top Salt             |           |         |                   |
| 1,358.21              | 1,355.00              | Base Salt            |           |         |                   |
| 1,583.45              | 1,577.00              | Delaware Mountain Gp |           |         |                   |
| 1,590.57              | 1,584.00              | Lamar                |           |         |                   |
| 1,625.22              | 1,618.00              | Bell Canyon          |           |         |                   |
| 1,636.44              | 1,629.00              | Ramsey Sand          |           |         |                   |
| 2,511.76              | 2,477.00              | Cherry Canyon        |           |         |                   |
| 3,581.73              | 3,510.00              | Brushy Canyon        |           |         |                   |
| 5,089.84              | 4,966.00              | Bone Spring Lime     |           |         |                   |
| 5,358.11              | 5,225.00              | Upper Avalon         |           |         |                   |
| 5,671.95              | 5,528.00              | Middle Avalon        |           |         |                   |
| 6,027.23              | 5,871.00              | Lower Avalon         |           |         |                   |
| 6,172.24              | 6,011.00              | 1st Bone Spring Sand |           |         |                   |
| 6,476.59              | 6,305.00              | 2nd Bone Spring Carb |           |         |                   |
| 6,959.96              | 6,778.00              | 2nd Bone Spring Sand |           |         |                   |
| 7,111.68              | 6,928.00              | 3rd Bone Spring Carb |           |         |                   |
| 8,064.33              | 7,878.00              | 3rd Bone Spring Sand |           |         |                   |
| 8,355.22              | 8,142.00              | 3rd BS W Sand        |           |         |                   |
| 8,485.93              | 8,232.00              | Wolfcamp A X Sand    |           |         |                   |
| 8,625.44              | 8,299.00              | Wolfcamp A Y Sand    |           |         |                   |

## Plan Annotations

| Measured Depth (usft) | Vertical Depth (usft) | Local Coordinates |              | Comment                      |
|-----------------------|-----------------------|-------------------|--------------|------------------------------|
|                       |                       | +N/-S (usft)      | +E/-W (usft) |                              |
| 500.00                | 500.00                | 0.00              | 0.00         | KOP, 1.00°/100' Build        |
| 2,010.59              | 1,993.15              | 92.52             | 175.03       | Begin 15.11° Tangent         |
| 6,388.70              | 6,219.98              | 625.70            | 1,183.74     | Begin 1.00°/100' Drop        |
| 7,899.29              | 7,713.13              | 718.22            | 1,358.77     | Begin Vertical Hold          |
| 7,999.29              | 7,813.13              | 718.22            | 1,358.77     | KOP, 11.00°/100' Build       |
| 8,817.47              | 8,334.00              | 197.41            | 1,351.23     | Begin 90.00° Lateral         |
| 12,534.43             | 8,334.00              | -3,519.16         | 1,297.39     | Begin 2.00°/100' Build       |
| 12,574.84             | 8,333.72              | -3,559.56         | 1,296.80     | Hold 90.81° Inc, 180.83° Azm |
| 14,534.62             | 8,306.07              | -5,518.95         | 1,268.43     | Begin 2.00°/100' Build       |
| 14,569.52             | 8,305.37              | -5,553.84         | 1,267.92     | Hold 91.51° Inc, 180.83° Azm |
| 16,535.31             | 8,253.70              | -7,518.74         | 1,239.46     | Begin 2.00°/100' Build       |
| 16,585.38             | 8,251.95              | -7,568.78         | 1,238.74     | Hold 92.51° Inc, 180.83° Azm |
| 18,820.54             | 8,154.16              | -9,801.56         | 1,206.40     | PBHL                         |

## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

|                             |                         |
|-----------------------------|-------------------------|
| <b>OPERATOR'S NAME:</b>     | Tap Rock Operating LLC  |
| <b>WELL NAME &amp; NO.:</b> | Pabst Fed Com 204H      |
| <b>LOCATION:</b>            | Sec 03-26S-25E-NMP      |
| <b>COUNTY:</b>              | Eddy County, New Mexico |

Create COAs

|  |  |   |
|--|--|---|
| <b>H<sub>2</sub>S</b>  | <b>Cave / Karst</b>  | <b>Waste Prevention Rule</b>  |
| <input type="text" value="Not Reported"/>  | <input type="text" value="Critical"/>  | <input type="text" value="Waste Minimization Plan"/>                  |
| <b>Potash</b>  | <b>R-111-Q Design</b>  |   |
| <input type="text" value="None"/>  | <input type="text"/>   |   |
| <b>Wellhead</b>  | <b>Casing</b>  |   |
| <input type="text" value="Multibowl"/>   | <input type="text" value="3-String Well"/>   |   |
| <input checked="" type="checkbox"/> Flex Hose<br><input checked="" type="checkbox"/> Break Testing | <input type="checkbox"/> Liner <input type="checkbox"/> Fluid Filled <input type="checkbox"/> Casing Clearance   |   |
|  | <b>Cementing</b>   |   |
|  | <input type="checkbox"/> DV Tool <input type="checkbox"/> Bradenhead <input type="checkbox"/> Echometer<br><input type="checkbox"/> Offline Cement <input type="checkbox"/> Open Annulus <input type="checkbox"/> Pilot Hole |   |
| <b>Special Requirements</b>  |  |   |
| <input type="checkbox"/> Capitan Reef  | <input type="checkbox"/> Water Disposal  | <input checked="" type="checkbox"/> COM <input type="checkbox"/> Unit |

### A. HYDROGEN SULFIDE

Hydrogen Sulfide (H<sub>2</sub>S) monitors shall be installed prior to drilling out the surface shoe. If H<sub>2</sub>S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet 43 CFR 3176 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

### B. CASING

1. The 11-3/4 inch surface casing shall be set at approximately **350** feet (a minimum of **70'** into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic-type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the

- cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or **500 pounds compressive strength**, whichever is greater (including lead cement.)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **8-5/8** inch intermediate casing (**set at 1600' per BLM geologist**) is **cement to surface**. If cement does not circulate, see B.1.a, c-d above.
    - **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry** due to the presence of cave/karst, Capitan Reef, or potash features.
  3. The minimum required fill of cement behind the **5-1/2** inch production casing is **cement to surface**. If cement does not circulate, see B.1.a, c-d above.
    - **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry** due to the presence of cave/karst, Capitan Reef, or potash features.

### C. PRESSURE CONTROL

1. Operator has proposed a multi-bowl wellhead assembly. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M) psi**.
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one-inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172 must be followed.
2. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
3. Break testing has been approved for this well ONLY on those intervals utilizing a 5M BOPE or less. **(Annular preventer must be tested to a minimum of 70% of BOPE**

**working pressure and shall be higher than the MASP.)** If in the event break testing is not utilized, then a full BOPE test would be conducted.

- a. Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation. **BOPE Break Testing is NOT permitted to drill the production hole section.**
- b. While in transfer between wells, BOPE shall be secured by the hydraulic carrier or cradle.
- c. A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- d. As a minimum, a full BOPE test shall be performed at 21-day intervals.
- e. In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per **43 CFR 3172**. Any well control event while drilling require notification to the BLM Petroleum Engineer (**575-706-2779**) prior to the commencement of any BOPE Break Testing operations.

#### **D. SPECIAL REQUIREMENT(S)**

##### **Communitization Agreement:**

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in 43 CFR 3171 and 3172.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

### Contact Eddy County Petroleum Engineering Inspection Staff:

Email or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220;  
[BLM NM CFO DrillingNotifications@BLM.GOV](mailto:BLM_NM_CFO_DrillingNotifications@BLM.GOV); (575) 361-2822

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - i. Notify the BLM when moving in and removing the Spudder Rig.
    - ii. Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - iii. BOP/BOPE test to be conducted per **43 CFR 3172** as soon as 2<sup>nd</sup> Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. For intervals in which cement to surface is required, cement to surface should be verified with a visual check and density or pH check to differentiate cement from spacer and drilling mud. The results should be documented in the driller's log and daily reports.

### A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or



- if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends of both lead and tail cement, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
  3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
  4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
  5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
  6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
  7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
  8. Whenever a casing string is cemented in the R-111-Q potash area, the NMOCD requirements shall be followed.

## **B. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR 3172**.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible

- hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
  4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
    - i. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
    - ii. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
    - iii. Manufacturer representative shall install the test plug for the initial BOP test.
    - iv. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
    - v. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
    - i. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
    - ii. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
    - iii. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve

open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for 8 hours or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).

- iv. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- v. The results of the test shall be reported to the appropriate BLM office.
- vi. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- vii. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- viii. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR 3172**.

### **C. DRILLING MUD**

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

### **D. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



## Hydrogen Sulfide Drilling

### Operations Plan

#### Tap Rock Resources

##### 1 H2S safety instructions to the following:

- Characteristics of H2S
- Physical effects and hazards
- Principal and operation of H2S detectors, warning system and briefing areas
- Evacuation procedures, routes and first aid
- Proper use of safety equipment & life support systems
- Essential personnel meeting medical evaluation criteria will receive additional training on the proper use of 30min pressure demand air packs

##### 2 H2S Detection and Alarm Systems:

- H2S sensor/detectors to be located on the drilling rig floor, in the base of the sub structure / cellar area, on the mud pits in the shale shaker area. Additional H2S detectors may be placed as deemed necessary
- An audio alarm system will be installed on the derrick floor and in the doghouse

##### 3 Windssocks and / Wind Streamers:

- Windssocks at mud pit area should be high enough to be visible
- Windssock on the rig floor and / top of doghouse should be high enough to be visible

##### 4 Condition Flags and Signs:

- Warning sign on access road to location
- Flags to be displayed on sign at entrance to location
  - Green Flag – Normal Safe Operation Condition
  - Yellow Flag – Potential Pressure and Danger
  - Red Flag – Danger (H2S present in dangerous concentrations) Only H2S trained personnel admitted on location

##### 5 Well Control Equipment:

- See Drilling Operations Plan Schematics

##### 6 Communication:

- While working under masks chalkboards will be used for communications
- Hand signals will be used where chalk board is inappropriate
- Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.



#### 7 Drilling Stem Testing:

- No DST cores are planned at this time



8 Drilling contractor supervisor will be required to be familiar with the effects H<sub>2</sub>S has on tubulars good and other mechanical equipment

9 If H<sub>2</sub>S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H<sub>2</sub>S scavengers if necessary

#### 11 Emergency Contacts

| <b>Emergency Contacts</b>  |              |     |
|----------------------------|--------------|-----|
| Carlsbad Police Department | 575.887.7551 | 911 |
| Carlsbad Medical Center    | 575.887.4100 | 911 |
| Eddy County Fire Service   | 575.628.5450 | 911 |
| Eddy County Sherriff       | 575.887.7551 | 911 |
| Lea County Fire Service    | 575.391.2983 | 911 |
| Lea County Sherriff        | 575.396.3611 | 911 |
| Jal Police Department      | 575.395.2121 | 911 |
| Jal Fire Department        | 575.395.2221 | 911 |
| Tap Rock Resources         | 720.772.5090 |     |

Rig Diagram  
Pabst Fed Com  
Tap Rock Operating, LLC  
3-26S-25E  
Eddy County, NM






# Tap Rock Operating LLC

Pabst Fed Com Well Pad  
H2S Contingency Plan:  
2 Mile Radius Map

Sec. 3, Township 26S, Range 25E  
Eddy County, New Mexico


 Well Pad Location




NAD 1983 New Mexico State Plane East  
FIPS 3001 Feet



Prepared by Permits West, Inc., October 3, 2025  
for Tap Rock Operating, LLC







Schematic Closed Loop Drilling Rig\*

1. Pipe Rack
2. Drill Rig
3. House Trailers/ Offices
4. Generator/Fuel/Storage
5. Overflow-Frac Tank
6. Skids
7. Roll Offs
8. Hopper or Centrifuge
9. Mud Tanks
10. Loop Drive
11. Generator (only for use with centrifuge)

\*Not drawn to scale: Closed loop system requires at least 30 feet beyond mud tanks. Ideally 60 feet would be available

**PERMITS WEST, INC.**  
 PROVIDING PERMITS for LAND USERS  
 37Verano Loop, Santa Fe, New Mexico 87508 (505) 466-8120




Above: Centrifugal Closed Loop System



Closed Loop Drilling System: Mud tanks to right (1)  
 Hopper in air to settle out solids (2)  
 Water return pipe (3)  
 Shaker between hopper and mud tanks (4)  
 Roll offs on skids (5)

#### Flow Chart for Drilling Fluids and Solids



Photos Courtesy of Gandy Corporation Oil  
 Field Service

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 529246

ACKNOWLEDGMENTS

|   |   |
|---|---|
| Operator:<br>TAP ROCK OPERATING, LLC<br>1700 Lincoln St<br>Denver, CO 80203 | OGRID:<br>372043  |
|   | Action Number:<br>529246  |
|   | Action Type:<br>[C-101] BLM - Federal/Indian Land Lease (Form 3160-3) |

ACKNOWLEDGMENTS

|                                     |  |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | I hereby certify that no additives containing PFAS chemicals will be added to the completion or recompletion of this well. |
|-------------------------------------|--|

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 529246

**CONDITIONS**

|   |   |
|---|---|
| Operator:<br>TAP ROCK OPERATING, LLC<br>1700 Lincoln St<br>Denver, CO 80203 | OGRID:<br>372043  |
|   | Action Number:<br>529246  |
|   | Action Type:<br>[C-101] BLM - Federal/Indian Land Lease (Form 3160-3) |

**CONDITIONS**

| Created By  | Condition   | Condition Date |
|-------------|---|----------------|
| permitsw    | Cement is required to circulate on both surface and intermediate1 strings of casing.  | 11/24/2025     |
| permitsw    | If cement does not circulate on any string, a Cement Bond Log (CBL) is required for that string of casing.  | 11/24/2025     |
| ward.rikala | Notify the OCD 24 hours prior to casing & cement.   | 12/9/2025      |
| ward.rikala | File As Drilled C-102 and a directional Survey with C-104 completion packet.  | 12/9/2025      |
| ward.rikala | Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string. | 12/9/2025      |
| ward.rikala | Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.                  | 12/9/2025      |