

Well Name: GUSS FED COM 0731	Well Location: T26S / R36E / SEC 7 / SWSE / 32.0517189 / -103.3007343	County or Parish/State: LEA / NM
Well Number: 213H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM140366	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002555291	Operator: MATADOR PRODUCTION COMPANY	

### Notice of Intent

Sundry ID: 2887407

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 12/17/2025

Time Sundry Submitted: 10:26

Date proposed operation will begin: 12/18/2025

**Procedure Description:** BLM Bond# NMB001079, Surety Bond# RLB0015172 Matador requests to plug and abandon the current GUSS FED COM 0731 213H (API 30-025-55291), as reflected in this sundry, due to surface casing collapse at the original location. We plan to plug and abandon the original location by means of filling the currently set surface casing with neat Class C cement to surface upon receiving the API # for the new surface location from the NMOCD. Please see the attached supporting documents.

### Surface Disturbance

Is any additional surface disturbance proposed?: No

### NOI Attachments

#### Procedure Description

Guss\_Fed\_Com\_0731\_213H\_WBS\_P\_A\_20251217102555.pdf

Well Name: GUSS FED COM 0731

Well Location: T26S / R36E / SEC 7 /  
SWSE / 32.0517189 / -103.3007343County or Parish/State: LEA7  
NM

Well Number: 213H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM140366

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002555291

Operator: MATADOR PRODUCTION  
COMPANY

## Conditions of Approval

### Specialist Review

SKID\_P\_A\_COA\_20251222104520.pdf

## Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CASSIE HAHN

Signed on: DEC 17, 2025 10:26 AM

Name: MATADOR PRODUCTION COMPANY

Title: Senior Landman

Street Address: 5400 LBJ FREEWAY, SUITE 1500

City: DALLAS State: TX

Phone: (972) 371-5440

Email address: CHAHN@MATADORRESOURCES.COM

## Field

Representative Name:

Street Address:

City: State:

Zip:

Phone:

Email address:

## BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234

BLM POC Email Address: CWALLS@BLM.GOV

Disposition: Approved

Disposition Date: 12/22/2025

Signature: Chris Walls

Form 3160-5  
(October 2024)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**SUNDRY NOTICES AND REPORTS ON WELLS**  
***Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.***FORM APPROVED  
OMB No. 1004-0220  
Expires: October 31, 2027

<b>SUBMIT IN TRIPPLICATE - Other instructions on page 2</b>			5. Lease Serial No.
1. Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other			6. If Indian, Allottee or Tribe Name
2. Name of Operator			7. If Unit of CA/Agreement, Name and/or No.
3a. Address		3b. Phone No. (include area code)	8. Well Name and No.
4. Location of Well (Footage, Sec., T.R.M., or Survey Description)			9. API Well No.
			10. Field and Pool or Exploratory Area
			11. Country or Parish, State

## 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon		
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)	Title	
Signature	Date	

**THE SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		
Office		

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

## GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

## SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13*: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240


## Additional Information

### Location of Well

0. SHL: SWSE / 430 FSL / 1581 FEL / TWSP: 26S / RANGE: 36E / SECTION: 7 / LAT: 32.0517189 / LONG: -103.3007343 ( TVD: 0 feet, MD: 0 feet )  
PPP: NWNE / 100 FNL / 2307 FEL / TWSP: 26S / RANGE: 36E / SECTION: 18 / LAT: 32.0502579 / LONG: -103.3030766 ( TVD: 12069 feet, MD: 12114 feet )  
PPP: NWNE / 0 FSL / 2306 FEL / TWSP: 26S / RANGE: 36E / SECTION: 30 / LAT: 32.0214801 / LONG: -103.303028 ( TVD: 12380 feet, MD: 22703 feet )  
PPP: SWNE / 2639 FNL / 2307 FEL / TWSP: 26S / RANGE: 36E / SECTION: 30 / LAT: 32.0142263 / LONG: -103.3030157 ( TVD: 12380 feet, MD: 25341 feet )  
PPP: NWNE / 1100 FSL / 2307 FEL / TWSP: 26S / RANGE: 36E / SECTION: 31 / LAT: 32.0033333 / LONG: -103.3029973 ( TVD: 12380 feet, MD: 29304 feet )  
PPP: SWSE / 0 FNL / 2307 FEL / TWSP: 26S / RANGE: 36E / SECTION: 18 / LAT: 32.0360174 / LONG: -103.3030526 ( TVD: 12380 feet, MD: 17413 feet )  
BHL: LOT 4 / 110 FSL / 2307 FEL / TWSP: 26S / RANGE: 36E / SECTION: 31 / LAT: 32.0006115 / LONG: -103.3029926 ( TVD: 12380 feet, MD: 30294 feet )

CONFIDENTIAL

## WELLBORE SCHEMATIC

Well: Guss Fed Com #213H		Prospect: Wolfcamp A		AFE No: 500006.274.01.001		API No: 30-025-55291 v3		
GL Elev: 2973' RKB Elev: 3001.5'		Surface Hole Location: 400' FSL & 1611' FEL Section 7 26S 36E, Lea County, NM N 32.0515085, W 103.3003725 (NAD27)		Bottom Hole Location: 110' FSL & 1652' FEL Section 31 26S 36E, Lea County, NM N 32.0004832, W 103.3004232 (NAD27)				
Formation Tops (TVD @ 0' VS)	MW (PPG)	Directional and BHA Details	Casing Diagram	Depth (MD)	Hole Size	Casing and Cementing Details 20" Conductor @ +/- 148"		Logs/Notes
Hole in casing	220'	8.4-8.6 Spud Mud		17-1/2"	P&A Cement Job: 1. Rig up and RIH open-ended. Pick up 2-7/8" tubing and TIH to TD if able (surface casing float collar @ 1,347') or a minimum of 270' (50' below hole in casing casing). 2. Rig up Nine Energy cementers. 3. Break circulation and pump cement plug: a. 40 bbls of 10 ppg Gel Spacer b. Pump 1,319 sacks of 14.8 ppg Class-C cement, stop cementing when cement reaches surface. c. If no cement to surface, WOC 8 hours. RIH to tag top of cement. d. Confirm TOC and pump 14.8 ppg Class-C cement until cement circulates to surface. e. Confirm cement to surface with BLM Representative present. f. RD cementers and auxiliary equipment. 4. Cut casing off 3' below ground level or at the base of the cellar (whichever is deeper), verify cement to surface, cover wellbore with metal plate greater than or equal to 1/4" thick and cut weep hole			
Rustler	1,214'				13-3/8", 54.5#, J-55, BTC, 0'-1,347'			
Top Salt - Salado	1,623'							

**BUREAU OF LAND MANAGEMENT**  
**Carlsbad Field Office**  
**620 East Greene Street**  
**Carlsbad, New Mexico 88220**  
**575-234-5972**

**Permanent Abandonment of Federal Wells**  
**Conditions of Approval (SKID)**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Lea County, call 575-689-5981. Eddy County, please email notifications to: [BLM\\_NM\\_CFO\\_PluggingNotifications@BLM.GOV](mailto:BLM_NM_CFO_PluggingNotifications@BLM.GOV). The Eddy County inspector on call phone, 575-361-2822, will remain active as a secondary contact.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **fresh** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours for Class C or accelerated cement (calcium chloride) and 6 hours for Class H. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

Fluid used to mix the cement in R111Q shall be saturated with the salts common to the section penetrated, and in suitable proportions but not less than 1% and not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

6. Below Ground Level Cap (SKID): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified BY PHONE (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 14<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

Upon the plugging and subsequent abandonment of well the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least  $\frac{1}{4}$  inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 536965

**CONDITIONS**

Operator:  MATADOR PRODUCTION COMPANY One Lincoln Centre Dallas, TX 75240	OGRID: 228937
	Action Number: 536965
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	None	1/8/2026