

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT**I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT**

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-45849	⁵ Pool Name PURPLE SAGE; WOLF CAMP (GAS)	⁶ Pool Code 98220
⁷ Property Code 325339	⁸ Property Name POKER LAKE UNIT 25 BD	⁹ Well Number 108H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
H	25	25S	30E		2310	North	600	East	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	25	25S	30E		2310	South	332	East	Eddy
¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
34053	Plains Marketing, LP	O
343065	XTO Permian Op	G/W

IV. Well Completion Data

²¹ Spud Date 9/24/2020	²² Ready Date 10/30/2021	19862 MD ²³ TD 12051 TVD	19850 MD ²⁴ PBTB 12051 TVD	²⁵ Perforations 12,587 - 19,752	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
14.75	11.75	1124	945		
8.75	7.625	11274	1820		
6.75	5.0	19852/-	1145		

V. Well Test Data

³¹ Date New Oil 10/31/21	³² Gas Delivery Date 11/16/21	³³ Test Date 11/16/21	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 0	³⁶ Csg. Pressure 2060
³⁷ Choke Size	³⁸ Oil 2130	³⁹ Water 14990	⁴⁰ Gas 17867		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Cassie Evans</i>			OIL CONSERVATION DIVISION		
Printed name: Cassie Evans			Approved by:		
Title: Regulatory Analyst			Title:		
E-mail Address: cassie.evans@exxonmobil.com			Approval Date:		
Date: 12/03/2021	Phone: 432.218.3671				

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

AS-DRILLED PLAT

¹ API Number 30-015-45849	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325339	⁵ Property Name POKER LAKE UNIT 25 BD	⁶ Well Number 108H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC	⁹ Elevation 3,366'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	25	25 S	30 E		2,310	NORTH	600	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	36	25 S	30 E		243	SOUTH	332	EAST	EDDY

¹² Dedicated Acres 480	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY.

	SHL (NAD83 NME) Y = 401,272.5 X = 697,824.8 LAT. = 32.102169 °N LONG. = 103.827958 °W KOP (NAD83 NME) Y = 401,295.9 X = 698,037.0 LAT. = 32.102231 °N LONG. = 103.827272 °W FTP (NAD83 NME) Y = 400,467.0 X = 698,086.4 LAT. = 32.099952 °N LONG. = 103.827125 °W	LTP (NAD83 NME) Y = 393,303.7 X = 698,088.1 LAT. = 32.080261 °N LONG. = 103.827228 °W BHL (NAD83 NME) Y = 393,193.7 X = 698,085.3 LAT. = 32.079958 °N LONG. = 103.827239 °W	17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Signature 12/03/2021 Date Printed Name cassie.evans@exxonmobil.com E-mail Address
	CORNER COORDINATES (NAD83 NME) A - Y = 400,922.9 N , X = 698,427.0 E B - Y = 398,269.0 N , X = 698,399.2 E C - Y = 395,615.4 N , X = 698,415.7 E D - Y = 392,953.5 N , X = 698,417.0 E E - Y = 400,916.2 N , X = 697,084.1 E F - Y = 398,260.4 N , X = 697,066.8 E G - Y = 395,604.7 N , X = 697,080.6 E H - Y = 392,942.5 N , X = 697,086.9 E		
	SHL (NAD27 NME) Y = 401,214.6 X = 656,639.3 LAT. = 32.102045 °N LONG. = 103.827478 °W KOP (NAD27 NME) Y = 401,238.0 X = 656,851.5 LAT. = 32.102106 °N LONG. = 103.826793 °W FTP (NAD27 NME) Y = 400,409.1 X = 656,900.9 LAT. = 32.099827 °N LONG. = 103.826646 °W		
	LTP (NAD27 NME) Y = 393,246.0 X = 656,902.3 LAT. = 32.080136 °N LONG. = 103.826750 °W BHL (NAD27 NME) Y = 393,136.0 X = 656,899.5 LAT. = 32.079834 °N LONG. = 103.826761 °W		
18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 10-21-2021 Date of Survey Signature and Seal of Professional Surveyor: MARK DILLON HARP 23786 Certificate Number			

Intent ☐ As Drilled ☒

API # 30-015-45849		
Operator Name: XTO PERMIAN OPERATING, LLC.	Property Name: POKER LAKE UNIT 25 BD	Well Number 108H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
H	25	25S	30E		2,288	FNL	388	FEL	EDDY
Latitude 32.102231					Longitude 103.827272				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
I	25	25S	30E		2,200	FSL	336	FEL	EDDY
Latitude 32.099952					Longitude 103.827125				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
P	36	25S	30E		353	FSL	329	FEL	EDDY
Latitude 32.080261					Longitude 103.827228				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018



Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)

October 15, 2020

XTO Permian Operating LLC
6401 Holiday Hill Road BLDG 5
Midland, TX 79707

Re:

25 25S 30E Eddy
N 32.102045 W -103.827478

CLIENT: XTO Permian Operating LLC
WELL: Poker Lake Unit 25 BD 108H
FIELD: Purple Sage-Wolfcamp (Gas)

RIG: Nabors X-15
COUNTY: Eddy
API NO: 3001545849
JOB NO: 20MLE0812

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements, a division of Schlumberger Technology Corporation (P-5 No. 754900).

Other information required by your office is as follows.

<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Cody Jacks	Poker Lake Unit 25 BD 108H	11399.00 Ft	October 4, 2020	XBOLT
FE	Original Hole	19831.00 Ft	October 12, 2020	

Schlumberger-Private

Oilfield Services, Central U.S. Land

Schlumberger Drilling and Measurements

Drilling Group

Geo Market Area: South West Texas Basin

7220 W I-H 20

Midland, Texas 79706

Phone : (432) 742-5400 (Main)

Fax : (432) 742-5606 (Shared)



Well Reference:

25 25S 30E Eddy
N 32.102045 W -103.827478

I, Cody Jacks certify that; I am employed by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I did on the day(s) of October 04, 2020 through October 12, 2020, conduct or supervise the taking of the XBOLT surveys from a depth of 11399.00 feet to a depth of 19831.00 feet referenced to driller's depth; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Permian Operating LLC for the Poker Lake Unit 25 BD 108H Well (Original Hole) API No. 3001545849 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.

By
Cody Jacks
FE

Subscribed and Sworn to before me this _____ day of _____ (month) _____ (yr)

My Commission expires:

Notary Public

(signature)

(County State)



NABORS DRILLING TECHNOLOGIES USA, INC.
 515 West Greens Road
 Houston, TX 77067
 Phone: 281.874.0035
 Fax: 281.872.5205

Thursday, October 1, 2020

State of New Mexico
 County of Eddy

Subject: **Survey Certification Letter**

Survey Company: **NABORS DRILLING TECH USA, INC.**

Job Number: **T8995**

Survey Job Type: **Nabors MWD**

Customer: **XTO Permian Operarating LLC**

Well Name: **PLU 25 BD 108H**

Rig Name: **Nabors X15**

Surface: **32.102045 N 103.827478**

A.P.I. No: **30-015-45849**

Location: **Eddy, NM**

RKB Height: **3399'**

Distance to Bit: **71'**

Surveyor Name	Surveyor Title	Borehole Number	Start Depth	End Depth	Start Date	End Date	Type of	TD Straight
								Line Projection
Mohammed Al Saqi	MWD Supervisor	OH	155'	11213'	09/24/20	10/01/20	MWD	11284'

The data and calculations for this survey have been checked by me and conform to the calibration standards and operational procedures set forth by NABORS DRILLING TECHNOLOGIES USA, INC. I am authorized and qualified to review the data, calculations and these reports; the reports represents true and correct Directional Surveys of this well based on the original data, the minimum curvature method, corrected to Grid North and obtained at the well site.

Mohammed Al Saqi

MWD Supervisor

NABORS DRILLING TECHNOLOGIES USA, INC.



Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)

October 15, 2020

XTO Permian Operating LLC
6401 Holiday Hill Road BLDG 5
Midland, TX 79707

Re:

25 25S 30E Eddy
N 32.102045 W -103.827478

CLIENT: XTO Permian Operating LLC
WELL: Poker Lake Unit 25 BD 108H
FIELD: Purple Sage-Wolfcamp (Gas)

RIG: Nabors X-15
COUNTY: Eddy
API NO: 3001545849
JOB NO: 20MLE0812

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements, a division of Schlumberger Technology Corporation (P-5 No. 754900).

Other information required by your office is as follows.

<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Cody Jacks	Poker Lake Unit 25 BD 108H	11399.00 Ft	October 4, 2020	XBOLT
FE	Original Hole	19831.00 Ft	October 12, 2020	

Schlumberger-Private

Oilfield Services, Central U.S. Land

Schlumberger Drilling and Measurements

Drilling Group

Geo Market Area: South West Texas Basin

7220 W I-H 20

Midland, Texas 79706

Phone : (432) 742-5400 (Main)

Fax : (432) 742-5606 (Shared)

Schlumberger

Well Reference:

25 25S 30E Eddy

N 32.102045 W -103.827478

I, Cody Jacks certify that; I am employed by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I did on the day(s) of October 04, 2020 through October 12, 2020, conduct or supervise the taking of the XBOLT surveys from a depth of 11399.00 feet to a depth of 19831.00 feet referenced to driller's depth; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Permian Operating LLC for the Poker Lake Unit 25 BD 108H Well (Original Hole) API No. 3001545849 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.



By

Cody Jacks

FE

Subscribed and Sworn to before me this _____ day of _____ (month) _____ (yr)

My Commission expires:

Notary Public

(signature)

(County State)

Schlumberger-Private

Schlumberger

XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD Survey Geodetic Report



(Def Survey)

Report Date: October 12, 2020 - 03:54 PM
Client: XTO Energy
Field: NM Eddy County (NAD 27)
Structure / Slot: XTO Poker Lake Unit 25 BD 108H / New Slot
Well: XTO Poker Lake Unit 25 BD 108H
Borehole: XTO Poker Lake Unit 25 BD 108H
UWI / API#: Unknown / 30-015-45649
Survey Name: XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD
Survey Date: September 26, 2020
Tort / AHD / DDI / ERD Ratio: 226.083' / 8655.863 ft / 6.507 / 0.716
Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
Location Lat / Long: N 32° 6' 7.36147", W 103° 49' 38.92242"
Location Grid N/E Y/X: N 401214.600 RUS, E 656639.300 RUS
CRS Grid Convergence Angle: 0.2688°
Grid Scale Factor: 0.99993719
Version / Patch: 2.10.821.3

Survey / DLS Computation: Minimum Curvature / Lubinski
Vertical Section Azimuth: 179.660° (Grid North)
Vertical Section Origin: 0.000 ft, 0.000 ft
TVD Reference Datum: RKB
TVD Reference Elevation: 3399.000 ft above MSL
Sealed / Ground Elevation: 3366.000 ft above MSL
Magnetic Declination: 6.658°
Total Gravity Field Strength: 998.4191mg (9.80665 Based)
Gravity Model: GARM
Total Magnetic Field Strength: 47658.000 nT
Magnetic Dip Angle: 59.700°
Declination Date: September 26, 2020
Magnetic Declination Model: IFR1+MS
North Reference: Grid North
Grid Convergence Used: 0.2670°
Total Corr Mag North→Grid: 6.3910°
Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
Surface	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	401214.60	656639.30	32.102045	-103.827478	0.00	0.00
	155.00	1.20	287.96	154.99	-0.51	0.50	-1.54	0.77	401215.10	656637.76	32.102046	-103.827483	1.62	287.96
	245.00	0.41	336.15	244.98	-1.10	1.09	-2.57	1.08	401215.69	656636.73	32.102048	-103.827487	2.79	292.89
	338.00	0.61	341.79	337.98	-1.88	1.86	-2.86	0.22	401216.46	656636.44	32.102050	-103.827488	3.41	303.04
	431.00	0.75	351.50	430.97	-2.95	2.93	-3.10	0.19	401217.53	656636.20	32.102053	-103.827488	4.27	313.37
	523.00	0.59	330.68	522.96	-3.96	3.94	-3.43	0.31	401218.54	656635.87	32.102056	-103.827489	5.22	319.00
	617.00	0.71	323.49	616.96	-4.85	4.83	-4.01	0.15	401219.43	656635.29	32.102058	-103.827491	6.28	320.31
	709.00	0.83	339.61	708.95	-5.94	5.91	-4.58	0.27	401220.51	656634.72	32.102061	-103.827493	7.48	322.24
	802.00	1.00	308.20	801.94	-7.08	7.05	-5.45	0.56	401221.65	656633.85	32.102064	-103.827496	8.91	322.27
	894.00	1.33	290.75	893.92	-7.96	7.92	-7.08	0.52	401222.52	656632.22	32.102067	-103.827501	10.63	318.20
	987.00	1.43	294.20	986.89	-8.83	8.78	-9.15	0.14	401223.38	656630.15	32.102069	-103.827508	12.68	313.82
	1080.00	1.60	287.19	1079.86	-9.71	9.64	-11.45	0.27	401224.24	656627.85	32.102071	-103.827515	14.97	310.10
	1092.00	1.57	292.08	1091.85	-9.82	9.75	-11.76	1.15	401224.35	656627.54	32.102072	-103.827516	15.28	309.66
11-3/4" Casing	1135.10	1.91	286.62	1134.94	-10.25	10.18	-12.99	0.87	401224.78	656626.31	32.102073	-103.827520	16.51	308.07
	1168.00	2.17	283.61	1167.81	-10.56	10.48	-14.12	0.87	401225.08	656625.18	32.102074	-103.827524	17.59	306.58
	1261.00	1.25	305.72	1260.77	-11.59	11.49	-16.66	1.20	401226.09	656622.64	32.102077	-103.827532	20.24	304.59
	1354.00	1.14	47.81	1353.76	-12.80	12.70	-16.80	2.00	401227.30	656622.50	32.102080	-103.827532	21.06	307.09
	1447.00	1.81	67.16	1446.73	-13.98	13.89	-14.76	0.89	401228.49	656624.54	32.102083	-103.827526	20.27	313.27
	1541.00	2.69	78.06	1540.66	-14.99	14.92	-11.23	1.04	401229.52	656626.07	32.102086	-103.827514	18.68	323.04
	1636.00	3.01	88.59	1635.54	-15.49	15.45	-6.56	0.64	401230.05	656632.74	32.102087	-103.827499	16.78	337.00
	1730.00	4.31	78.92	1729.35	-16.19	16.19	-0.62	1.53	401230.79	656638.68	32.102089	-103.827480	16.20	357.79
	1824.00	6.08	83.57	1822.96	-17.38	17.42	7.79	1.93	401232.02	656647.09	32.102093	-103.827453	19.09	24.09
	1918.00	5.88	90.39	1916.45	-17.84	17.95	17.55	0.78	401232.55	656656.85	32.102094	-103.827422	25.10	44.36
	2013.00	5.47	87.38	2010.98	-17.96	18.12	26.94	0.53	401232.72	656666.24	32.102094	-103.827391	32.47	56.07
	2107.00	6.75	78.70	2104.45	-19.19	19.41	36.83	1.68	401234.01	656676.13	32.102098	-103.827359	41.64	62.21
	2202.00	6.35	81.43	2198.83	-21.00	21.29	47.50	0.53	401235.88	656686.80	32.102103	-103.827325	52.06	65.86
	2295.00	8.00	76.99	2291.10	-23.16	23.51	58.90	1.87	401238.11	656698.19	32.102109	-103.827288	63.42	68.24
	2390.00	9.70	75.50	2384.96	-26.57	27.00	73.09	1.81	401241.60	656712.38	32.102118	-103.827242	77.92	69.72
	2484.00	11.08	69.04	2477.42	-31.69	32.22	89.19	1.92	401246.81	656728.48	32.102132	-103.827190	94.83	70.14
	2579.00	9.37	70.82	2570.91	-37.40	38.02	105.02	1.83	401252.62	656744.31	32.102148	-103.827139	111.69	70.10
	2673.00	8.46	74.01	2663.77	-41.74	42.44	118.89	1.10	401257.04	656758.19	32.102160	-103.827094	126.24	70.35
	2768.00	7.96	75.44	2757.80	-45.24	46.02	131.98	0.57	401260.62	656771.27	32.102170	-103.827052	139.77	70.78
	2862.00	7.16	71.92	2850.98	-48.62	49.47	143.85	0.98	401264.07	656783.14	32.102179	-103.827013	152.12	71.02
	2957.00	7.75	68.81	2945.18	-52.70	53.63	155.45	0.75	401268.22	656794.74	32.102190	-103.826976	164.44	70.97
	3051.00	7.24	66.34	3038.38	-57.30	58.30	166.78	0.64	401272.89	656806.07	32.102203	-103.826939	176.68	70.73
	3146.00	7.70	59.33	3132.57	-62.89	63.94	177.74	1.07	401278.54	656817.03	32.102218	-103.826904	188.89	70.21
	3240.00	6.80	64.62	3225.82	-68.42	69.54	188.18	1.19	401284.14	656827.47	32.102234	-103.826870	200.62	69.72
	3334.00	7.39	74.06	3319.10	-72.41	73.59	199.03	1.39	401288.18	656838.31	32.102245	-103.826835	212.19	69.71
	3428.00	9.46	78.44	3412.09	-75.53	76.80	212.41	2.30	401291.39	656851.69	32.102253	-103.826791	225.87	70.12
	3522.00	7.86	78.98	3505.01	-78.23	79.57	226.29	1.70	401294.17	656865.57	32.102261	-103.826747	239.87	70.63
	3617.00	8.78	83.94	3599.01	-80.16	81.58	239.87	1.23	401296.17	656879.16	32.102266	-103.826703	253.37	71.22
	3712.00	10.46	90.04	3692.67	-80.82	82.34	255.71	2.07	401296.93	656894.99	32.102268	-103.826651	268.64	72.15
	3806.00	8.73	82.85	3785.36	-81.61	83.22	271.32	2.24	401297.82	656910.60	32.102270	-103.826601	283.80	72.95
	3900.00	6.67	67.42	3878.52	-84.52	86.21	283.44	3.09	401300.80	656922.72	32.102278	-103.826562	299.26	73.08
	3995.00	3.38	53.54	3973.14	-86.26	89.99	290.79	3.67	401304.58	656930.07	32.102288	-103.826538	304.40	72.80
	4089.00	2.04	39.10	4067.04	-91.19	92.94	294.07	1.59	401307.53	656933.36	32.102297	-103.826527	308.41	72.46
	4183.00	1.76	359.98	4160.99	-93.92	95.68	295.13	1.38	401310.27	656934.41	32.102304	-103.826524	310.25	72.04
	4278.00	1.84	3.18	4255.94	-96.91	98.66	295.21	0.14	401313.25	656934.49	32.102312	-103.826524	311.26	71.52
	4372.00	1.86	2.94	4349.89	-99.93	101.69	295.38	0.02	401316.28	656934.66	32.102321	-103.826523	312.39	71.00
	4466.00	1.89	5.63	4443.84	-103.00	104.76	295.61	0.10	401319.35	656934.89	32.102329	-103.826522	313.62	70.49
	4561.00	2.08	6.99	4538.78	-106.27	108.03	295.97	0.21	401322.62	656935.25	32.102338	-103.826521	315.07	69.95
	4655.00	2.29	18.53	4632.72	-109.74	111.50	296.77	0.52	401326.09	656936.05	32.102348	-103.826518	317.03	69.41
	4749.00	2.00	8.45	4726.65	-113.13	114.90	297.61	0.51	401329.50	656936.89	32.102357	-103.826516	319.02	68.89
	4844.00	1.94	320.24	4821.60	-116.02	117.78	298.83	1.69	401332.37	656936.11	32.102365	-103.826518	319.34	68.36
	4938.00	1.56	274.09	4915.56	-117.34	119.09	294.53	1.51	401333.69	656933.81	32.102368	-103.826526	317.70	67.98
	5032.00	1.53	275.25	5009.53	-117.56	119.30	292.01	0.05	401333.89	656931.29	32.102369	-103.826534	315.44	67.78
	5127.00	1.44	281.50	5104.49	-117.93	119.65	289.57	0.19	401334.25	656928.86	32.102370	-103.826542	313.32	67.55
	5221.00	1.40	278.93	5198.47	-118.36	120.07	287.28	0.08	401334.66	656926.56	32.102371	-103.826549	311.36	67.32
	5315.00	1.27	282.81	5292.44	-118.78	120.48	285.13	0.17	401335.07	656924.41	32.102372	-103.826556	309.54	67.09
	5409.00	1.29	289.69	5386.42	-119.38	121.06	283.12	0.16	401335.66	656922.40	32.102374	-103.826562	307.92	66.85
	5504.00	1.14	296.52	5481.40	-120.17	121.85	281.27	0.22	401336.44	656920.55	32.102376	-103.826568	306.53	66.58
	5599.00	1.18	297.79	5576.38	-121.06	122.72	279.56	0.05	401337.32	656918.84	32.102379	-103.826574	305.31	66.30
	5693.00	1.35	285.85	5670.35	-121.83	123.48	277.64	0.33	401338.07	656916.92	32.102381	-103.826580	303.86	66.02
	5787.00	1.47	281.78	5764.33	-122.39	124.03	275.39	0.17	401338.62	656914.67	32.102382	-103.826587	302.03	65.75
	5881.00	1.40	280.40	5858.30	-122.86	124.48	273.08	0.08	401339.07	656912.36	32.102383	-103.826595	300.11	65.49
	5976.00	1.40	280											

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	8330.00	1.47	259.63	8306.79	-102.29	103.71	239.45	0.61	401318.30	656878.73	32.102327	-103.826704	260.94	66.58
	8424.00	1.26	250.14	8400.76	-101.73	103.14	237.29	0.33	401317.73	656876.58	32.102325	-103.826711	258.74	66.51
	8518.00	1.00	287.17	8494.75	-101.63	103.03	235.53	0.81	401317.62	656874.82	32.102325	-103.826716	257.08	66.37
	8613.00	0.76	287.91	8589.73	-102.08	103.47	234.14	0.25	401318.06	656873.43	32.102326	-103.826721	255.99	66.16
	8707.00	1.21	290.52	8683.72	-102.63	104.01	232.62	0.48	401318.60	656871.91	32.102328	-103.826726	254.81	65.91
	8801.00	0.92	299.46	8777.70	-103.35	104.73	231.03	0.35	401319.32	656870.32	32.102330	-103.826731	253.66	65.82
	8896.00	0.93	281.43	8872.69	-103.89	105.26	229.61	0.31	401319.85	656868.90	32.102331	-103.826735	252.59	65.37
	8989.00	0.94	283.09	8965.68	-104.22	105.58	228.13	0.03	401320.17	656867.42	32.102332	-103.826740	251.38	65.17
	9084.00	1.01	275.74	9060.67	-104.49	105.84	226.54	0.15	401320.43	656865.82	32.102333	-103.826745	250.04	64.96
	9178.00	0.70	260.94	9154.66	-104.49	105.83	225.15	0.40	401320.42	656864.43	32.102333	-103.826750	248.78	64.82
	9272.00	0.92	239.39	9248.65	-104.03	105.36	223.93	0.40	401319.95	656863.22	32.102332	-103.826754	247.48	64.80
	9366.00	0.85	254.56	9342.64	-103.46	104.79	222.61	0.26	401319.38	656861.90	32.102330	-103.826758	246.04	64.79
	9460.00	1.13	231.38	9436.62	-102.71	104.02	221.21	0.51	401318.62	656860.50	32.102328	-103.826763	244.45	64.82
	9555.00	1.08	202.25	9531.60	-101.30	102.61	220.14	0.59	401317.20	656859.43	32.102324	-103.826766	242.88	65.01
	9649.00	0.76	205.51	9625.59	-99.92	101.23	219.54	0.34	401315.82	656858.82	32.102320	-103.826768	241.75	65.25
	9743.00	0.61	224.24	9719.59	-99.00	100.30	218.92	0.28	401314.90	656858.21	32.102318	-103.826770	240.81	65.38
	9837.00	0.58	251.09	9813.58	-98.50	99.79	218.12	0.30	401314.39	656857.41	32.102316	-103.826773	239.87	65.42
	9931.00	0.38	246.11	9907.58	-98.22	99.51	217.39	0.22	401314.11	656856.67	32.102316	-103.826775	239.08	65.40
	10026.00	0.69	220.08	10002.57	-97.66	98.95	216.73	0.41	401313.54	656856.02	32.102314	-103.826777	238.25	65.40
	10120.00	0.79	217.60	10096.57	-96.72	98.00	215.97	0.11	401312.59	656855.26	32.102311	-103.826780	237.17	65.59
	10214.00	1.59	200.32	10190.54	-94.99	96.26	215.12	0.92	401310.86	656854.41	32.102307	-103.826782	235.68	65.89
	10309.00	3.94	178.24	10285.43	-90.49	91.76	214.77	2.67	401306.36	656854.05	32.102294	-103.826784	233.55	66.86
	10403.00	4.85	168.30	10379.15	-83.36	84.65	215.67	1.26	401299.24	656854.96	32.102275	-103.826781	231.69	68.57
	10497.00	5.24	166.83	10472.79	-75.28	76.57	217.45	0.44	401291.17	656856.74	32.102253	-103.826775	230.54	70.80
	10592.00	4.91	173.43	10567.42	-67.01	68.31	218.91	0.71	401282.91	656858.19	32.102230	-103.826771	229.32	72.67
	10686.00	4.17	178.14	10661.12	-59.60	60.90	219.48	0.88	401275.50	656858.76	32.102209	-103.826769	227.71	74.49
	10781.00	3.49	187.44	10755.91	-53.28	54.58	219.22	0.97	401269.18	656858.50	32.102192	-103.826770	225.91	76.02
	10875.00	2.88	195.12	10849.77	-48.17	49.46	218.23	0.79	401264.06	656857.52	32.102178	-103.826773	223.77	77.23
	10970.00	2.73	201.57	10944.65	-43.77	45.06	216.78	0.37	401259.65	656856.06	32.102166	-103.826778	221.41	78.26
	11065.00	2.94	197.29	11039.54	-39.35	40.62	215.22	0.31	401255.22	656854.51	32.102154	-103.826783	219.02	79.31
	11159.00	2.82	192.92	11133.42	-34.80	36.07	213.99	0.27	401250.67	656853.27	32.102141	-103.826787	217.01	80.43
	11213.00	2.99	193.60	11187.35	-32.14	33.41	213.36	0.32	401248.00	656852.64	32.102134	-103.826789	215.96	81.10
7 5/8" Casing	11284.00	3.04	189.71	11258.25	-28.49	29.75	212.60	0.30	401244.35	656851.89	32.102124	-103.826791	214.68	82.03
	11312.00	3.07	188.21	11286.21	-27.01	28.27	212.37	0.30	401242.87	656851.66	32.102120	-103.826792	214.25	82.42
	11367.00	4.54	179.24	11341.09	-23.38	24.64	212.19	2.88	401239.24	656851.48	32.102110	-103.826793	213.62	83.38
	11399.00	6.57	181.91	11372.94	-20.28	21.54	212.15	6.39	401236.14	656851.43	32.102101	-103.826793	213.24	84.20
	11430.00	8.74	187.02	11403.66	-16.17	17.43	211.80	7.33	401232.03	656851.09	32.102090	-103.826794	212.52	85.30
	11462.00	10.78	190.98	11435.19	-10.83	12.08	210.93	6.71	401226.68	656850.22	32.102075	-103.826797	211.28	86.72
	11514.00	14.12	192.66	11485.96	0.12	1.11	208.62	6.46	401215.71	656847.90	32.102045	-103.826805	208.62	89.69
	11556.00	16.93	184.26	11526.43	11.22	-9.99	207.04	8.55	401204.61	656846.32	32.102015	-103.826810	207.28	92.76
	11651.00	23.34	175.93	11615.60	43.82	-42.59	207.35	7.38	401172.01	656846.63	32.101925	-103.826810	211.68	101.61
	11744.00	30.48	176.95	11698.47	85.82	-84.58	209.91	7.69	401130.03	656849.20	32.101818	-103.826802	226.31	111.95
	11839.00	39.61	178.64	11776.17	140.28	-139.03	211.92	9.66	401075.58	656851.20	32.101660	-103.826796	253.45	123.27
	11934.00	48.65	176.99	11844.29	206.32	-205.05	214.51	9.59	401009.56	656853.80	32.101478	-103.826789	296.75	133.71
	12028.00	56.19	172.96	11901.59	280.48	-279.17	221.16	8.71	400935.45	656860.45	32.101275	-103.826789	356.16	141.61
	12123.00	63.60	171.83	11949.21	361.94	-360.57	232.06	7.87	400854.06	656871.35	32.101051	-103.826735	428.79	147.23
	12217.00	69.41	172.36	11986.67	447.36	-445.92	243.91	6.20	400768.71	656883.19	32.100816	-103.826988	508.27	151.32
	12311.00	73.13	176.73	12016.86	535.59	-534.50	252.33	5.92	400680.13	656891.61	32.100572	-103.826672	591.07	154.73
FTP [344' FNL, 338' FEL]	12406.00	77.63	176.37	12040.83	627.75	-626.23	257.86	4.75	400588.41	656897.14	32.100320	-103.826655	677.25	157.82
	12476.00	81.85	178.17	12053.30	696.56	-695.02	261.13	6.54	400519.63	656900.42	32.100111	-103.826646	742.46	168.41
	12500.00	83.30	178.78	12066.40	720.35	-718.61	261.76	6.54	400495.84	656901.05	32.100086	-103.826644	784.99	169.89
	12594.00	88.31	181.48	12063.27	814.06	-812.52	261.55	6.05	400402.13	656900.83	32.099808	-103.826646	853.58	162.16
	12688.00	89.03	183.37	12065.46	907.92	-906.40	257.57	2.15	400308.26	656896.85	32.099550	-103.826660	942.29	164.14
	12783.00	87.89	181.20	12068.01	1002.77	-1001.29	253.78	2.58	400213.38	656893.07	32.099289	-103.826674	1032.95	165.78
	12877.00	88.44	180.05	12071.02	1096.71	-1095.23	252.76	1.36	400119.44	656892.04	32.099031	-103.826679	1124.02	167.00
	12971.00	89.41	179.77	12072.78	1190.69	-1189.21	252.91	1.07	400025.46	656892.19	32.098773	-103.826680	1215.81	167.99
	13065.00	88.50	178.01	12074.50	1284.66	-1283.17	254.73	2.11	399931.51	656894.01	32.098514	-103.826675	1308.21	168.77
	13159.00	88.64	179.02	12076.84	1378.61	-1377.11	257.16	1.08	399837.58	656896.44	32.098256	-103.826669	1400.92	169.42
	13254.00	88.68	179.82	12079.07	1473.59	-1472.08	258.12	0.84	399742.61	656897.41	32.097995	-103.826667	1494.54	170.05
	13348.00	88.87	179.21	12081.08	1567.56	-1566.06	258.92	0.68	399648.65	656898.20	32.097737	-103.826666	1587.31	170.61
	13443.00	88.91	179.12	12082.92	1662.54	-1661.03	260.30	0.10	399553.68	656899.59	32.097476	-103.826663	1681.30	171.09
	13537.00	89.19	178.59	12084.47	1756.52	-1755.00	262.18	0.64	399459.72	656901.46	32.097217	-103.826658	1774.47	171.50
	13632.00	90.21	180.19	12084.97	1851.51	-1849.98	263.19	2.00	399364.74	656902.47	32.096956	-103.826657	1868.61	171.90
	13727.00	90.67	179.99	12084.24	1946.55	-1944.98	263.04	0.53	399269.74	656902.33	32.096695	-103.826659	1962.69	172.30
	13821.00	90.65	181.48	12083.16	2040.48	-2038.96	261.84	1.59	399175.77	656901.12	32.096437	-103.826664	2055.71	172.68
	14010.00	90.98	180.54	12080.47	2229.41	-2227.91	258.51	0.53	398986.83	656897.79	32.095918	-103.826678	2242.86	173.38
	14105.00	90.79	179.99	12079.00	2324.39	-2322.90	258.07	0.61	398891.85	656897.35	32.095656	-103.826680	2337.19	173.66
	14294.00	90.77	179.45	12076.43	2513.37	-2511.88	258.99	0.29	398702.88	656898.27	32.095137	-103.826680	2525.20	174.11
	14389.00	90.69	180.08	12075.22	2608.36	-2606.87	259.38	0.67	398607.90	656898.66	32.094876	-103.826680	2619.74	

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (*100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	18981.00	90.49	180.24	12051.36	7199.81	-7198.31	273.41	0.34	394016.76	656912.69	32.082255	-103.826705	7203.50	177.82
	19076.00	90.45	179.67	12050.58	7294.80	-7293.31	273.48	0.60	393921.77	656912.76	32.081994	-103.826706	7298.43	177.85
	19170.00	89.96	179.77	12050.24	7388.80	-7387.30	273.94	0.53	393827.77	656913.22	32.081735	-103.826706	7392.38	177.88
	19264.00	90.02	180.16	12050.26	7482.80	-7481.30	274.00	0.42	393733.78	656913.28	32.081477	-103.826707	7486.32	177.90
	19359.00	89.96	180.81	12050.78	7577.79	-7576.30	273.19	0.98	393638.79	656912.48	32.081216	-103.826711	7581.22	177.93
	19453.00	89.79	181.55	12051.47	7671.75	-7670.27	271.26	0.91	393544.82	656910.54	32.080958	-103.826719	7675.07	177.97
	19548.00	90.10	181.43	12051.56	7766.70	-7765.24	268.79	0.35	393449.86	656908.07	32.080697	-103.826728	7769.89	178.02
	19642.00	90.14	181.78	12051.37	7860.65	-7859.21	266.15	0.37	393355.90	656905.44	32.080438	-103.826738	7863.71	178.06
	19736.00	89.72	181.53	12051.48	7954.59	-7953.17	263.44	0.52	393261.95	656902.72	32.080180	-103.826748	7957.53	178.10
LTP [330' FSL, 328' FEL]	19775.00	89.80	181.48	12051.64	7993.57	-7992.15	262.41	0.25	393222.97	656901.70	32.080073	-103.826752	7996.46	178.12
Last Survey	19831.00	89.92	181.41	12051.78	8049.54	-8048.13	261.00	0.25	393166.99	656900.29	32.079919	-103.826758	8052.36	178.14
Projection to Bit [242' FSL, 331' FEL]	19862.00	89.92	181.41	12051.82	8080.53	-8079.12	260.24	0.00	393136.00	656899.52	32.079834	-103.826761	8083.31	178.16

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma

Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
	1	0.000	33.000	1/98.425	14.750	11.750	NAL_MWD_IFR1+MS-Depth Only	XTO Poker Lake Unit 25 BD 108H / XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD
	1	33.000	33.000	Act Stns	14.750	11.750	NAL_MWD_IFR1+MS-Depth Only	XTO Poker Lake Unit 25 BD 108H / XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD
	1	33.000	1135.100	Act Stns	14.750	11.750	NAL_MWD_IFR1+MS	XTO Poker Lake Unit 25 BD 108H / XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD
	1	1135.100	11284.000	Act Stns	8.750	7.625	NAL_MWD_IFR1+MS	XTO Poker Lake Unit 25 BD 108H / XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD
	1	11284.000	19862.000	Act Stns	6.750	5.500	NAL_MWD_IFR1+MS	XTO Poker Lake Unit 25 BD 108H / XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD

...XTO Poker Lake Unit 25 BD 108H\XTO Poker Lake Unit 25 BD 108H 0 to 19862' MD

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

12/03/2021

Well Name: POKER LAKE UNIT 25 BD	Well Location: T25S / R30E / SEC 25 / SENE / 32.102169 / -103.827958	County or Parish/State: EDDY / NM
Well Number: 108H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMLC0063079A, NMLC063079A	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001545849	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Subsequent Report

Sundry ID: 2636455

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 09/28/2021

Time Sundry Submitted: 05:57

Date Operation Actually Began: 09/12/2021

Actual Procedure: XTO PERMIAN OPERATING LLC respectfully submits this sundry notice to report the completion operations of the referenced well. KOP @ depth 11,380 ft. PBTD = 19,850 ft. 7/7/21 Run RCB/GR/CCL 8/22/21 Pressure test 5.5 in csg to 10,195 psi for 30min test good, open sleeve. 9/12/21 Perf and frac 36 stages, 864 total shots, from 12,587 to 19,752 using 372,397 bbls of fluid and 18,011,260 lbs Proppant. Tag and drill out plugs

Well Name: POKER LAKE UNIT 25 BD	Well Location: T25S / R30E / SEC 25 / SENE / 32.102169 / -103.827958	County or Parish/State: EDDY / NM
Well Number: 108H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMLC0063079A, NMLC063079A	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001545849	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS

Signed on: SEP 28, 2021 05:57 PM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland

State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: Jonathon W Shepard

BLM POC Title: Petroleum Engineer


BLM POC Phone: 5752345972

BLM POC Email Address: jshepard@blm.gov

Disposition: Accepted

Disposition Date: 11/10/2021

Signature: Jonathon Shepard

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 25 BD		
								6. Well Number: 108H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator XTO PERMIAN OPERATING LLC.						9. OGRID 373075				
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat PURPLE SAGE;WOLF CAMP (GAS)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	H	25	25S	30E		2310	North	600	East	Eddy
BH:	P	36	25S	30E		243	South	332	East	Eddy
13. Date Spudded 9/24/2020	14. Date T.D. Reached 10/3/20		15. Date Rig Released 10/15/2020			16. Date Completed (Ready to Produce) 10/30/2021		17. Elevations (DF and RKB, RT, GR, etc.) 3366' GL		
18. Total Measured Depth of Well 19,862			19. Plug Back Measured Depth 19,850			20. Was Directional Survey Made? Yes		21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 12,587 - 19,752 PURPLE SAGE;WOLF CAMP (GAS)										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
11 3/4"		54.0		1,124'		14 3/4"		945		
7 5/8"		29.7		11,274'		8 3/4"		1820		
5"		18.0		19,852'		6 3/4"		1145		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET	PACKER SET		
L-80 #6.50						2 7/8"	0	0		
26. Perforation record (interval, size, and number) 12,587 - 19,752 2spf, 864 Total Shots 36 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						12,587 - 19,752		372,397 bbl fluid + 18,011,260 lbs proppant		
28. PRODUCTION										
Date First Production 10/31/21		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>)				Well Status (<i>Prod. or Shut-in</i>) Producing				
Date of Test 11/16/21	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 2130	Gas - MCF 17867	Water - Bbl. 14990	Gas - Oil Ratio 8,388			
Flow Tubing Press. 0	Casing Pressure 2060	Calculated 24-Hour Rate	Oil - Bbl. 2130	Gas - MCF 17867	Water - Bbl. 14990	Oil Gravity - API - (<i>Corr.</i>)				
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) Sold								30. Test Witnessed By		
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude				Longitude				NAD83		
<i>I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief</i>										
Signature 		Name Cassie Evans			Title Regulatory Analyst			Date 12/3/2021		
E-mail Address cassie.evans@exxonmobil.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 1,118'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 3,876'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 3,968'	T. Morrison	
T. Drinkard	T. Bone Springs 7,797'	T. Todilto	
T. Abo	T. Rustler 962'	T. Entrada	
T. Wolfcamp 11,158'	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology



XTO Energy Inc.
EMHC.W4.4A.293
22777 Springwoods Village Pkwy
Spring TX 77389-1425
832-625-4370 - Direct Phone
carlos.salinas@exxonmobil.com

October 6, 2020

XTO Energy Inc.
22777 Springwoods Village Pkwy
Spring, Texas 77389

Re: Waiver of Objection: Non-Standard Spacing Unit or Units for:

SW/4 Sec 25, T25S-R30E, for PLU 25 Brushy Draw 124H
SW/4 Sec 25, T25S-R30E, for PLU 25 Brushy Draw 104H
SW/4 Sec 25, T25S-R30E, for PLU 25 Brushy Draw 703H

To Whom It May Concern:

XTO Energy Inc., as designated operator of the Southwest Quarter (SW/4) of Section 25, Township 25South, Range 30 East, hereby waives objection for approval of a non-standard spacing unit or units comprised of the following:

SW/4 Sec 25 T25S R30E for PLU 25 Brushy Draw 124H;
SW/4 Sec 25 T25S R30E for PLU 25 Brushy Draw 104H;
SW/4 Sec 25 T25S R30E for PLU 25 Brushy Draw 703H;

in Eddy County, New Mexico. The acreage is expected to be placed in the Purple Sage; Wolfcamp Pool (Pool Code 98820) with a designation of 800-acre spacing per well. The SW/4 of Section 25 is located in adjacent horizontal spacing unit tracts with 0-acreage being stranded or abandoned.

Should you have any questions, please do not hesitate to contact me directly at 832-625-4370.

Thank you in advance for your prompt attention to this matter.

Sincerely,

XTO Energy Inc.

A handwritten signature in blue ink, appearing to read 'CR Salinas'.

Sr. Landman

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 85126

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 85126
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 85126

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 85126
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	None	1/13/2026