

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT**I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT**

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-46717	⁵ Pool Name PURPLE SAGE; WOLFCAMP (GAS)	⁶ Pool Code 98220
⁷ Property Code 325469	⁸ Property Name POKER LAKE UNIT 17 TWR	⁹ Well Number 905H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
B	20	24S	31E		65	North	1863	East	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	29	24S	31E		214	South	2290	East	Eddy

¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date
------------------------------------	---	-----------------------------------	-----------------------------------	------------------------------------	-------------------------------------

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
373073	XTO Permian Operating	Gas/Wtr
34053	Plains Marketing, LP	Oil

IV. Well Completion Data

²¹ Spud Date 6/3/20	²² Ready Date 10/6/21	^{21742 MD} TD 11862 TVD	^{21731 MD} PBT 11862 TVD	²⁵ Perforations 12,251 - 21,513	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
14.75	11.75	895	605		
9.875	7.625	10,964	2776		
6.75	5.5	21733	1180		
	2 7/8	11097			

V. Well Test Data

³¹ Date New Oil 10/7/21	³² Gas Delivery Date 10/10/21	³³ Test Date 10/10/21	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 899	³⁶ Csg. Pressure 285
³⁷ Choke Size	³⁸ Oil 2051	³⁹ Water 5563	⁴⁰ Gas 5448		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <u>Cassie Evans</u>			OIL CONSERVATION DIVISION		
Printed name: Cassie Evans			Approved by:		
Title: Regulatory Analyst			Title:		
E-mail Address: cassie.evans@exxonmobil.com			Approval Date:		
Date: 10/27/2021	Phone: 432.218.3671				

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT AS-DRILLED PLAT

¹ API Number 30-015-46717	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325469	⁵ Property Name POKER LAKE UNIT 17 TWR	⁶ Well Number 905H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,519'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	20	24 S	31 E		65	NORTH	1,863	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	29	24 S	31 E		214	SOUTH	2,290	EAST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY

	SHL (NAD83 NME) Y = 440,509.0 X = 707,117.1 LAT. = 32.209900 "N LONG. = 103.797318 "W KOP (NAD83 NME) Y = 440,490.0 X = 706,640.7 LAT. = 32.209854 "N LONG. = 103.798859 "W FTP (NAD83 NME) Y = 439,704.6 X = 706,659.2 LAT. = 32.207695 "N LONG. = 103.798812 "W CORNER COORDINATES (NAD83 NME) A - Y = 440,568.9 N, X = 706,335.3 E B - Y = 440,577.6 N, X = 707,657.5 E C - Y = 437,929.1 N, X = 706,352.2 E D - Y = 437,938.4 N, X = 707,674.2 E E - Y = 435,288.4 N, X = 706,369.2 E F - Y = 435,296.6 N, X = 707,690.8 E G - Y = 432,647.4 N, X = 706,386.6 E H - Y = 432,655.5 N, X = 707,707.7 E I - Y = 430,006.2 N, X = 706,403.9 E J - Y = 430,014.3 N, X = 707,724.7 E SHL (NAD27 NME) Y = 440,450.2 X = 665,933.0 LAT. = 32.209776 "N LONG. = 103.796835 "W KOP (NAD27 NME) Y = 440,431.2 X = 665,456.6 LAT. = 32.209731 "N LONG. = 103.798375 "W FTP (NAD27 NME) Y = 439,645.7 X = 665,475.3 LAT. = 32.207571 "N LONG. = 103.798328 "W CORNER COORDINATES (NAD27 NME) A - Y = 440,510.0 N, X = 665,151.3 E B - Y = 440,518.7 N, X = 666,473.5 E C - Y = 437,870.2 N, X = 665,168.2 E D - Y = 437,879.6 N, X = 666,490.2 E E - Y = 435,229.6 N, X = 665,185.1 E F - Y = 435,237.8 N, X = 666,506.6 E G - Y = 432,588.7 N, X = 665,202.3 E H - Y = 432,596.8 N, X = 666,523.5 E I - Y = 429,947.5 N, X = 665,219.6 E J - Y = 429,955.7 N, X = 666,540.4 E	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Cassie Evans</i> 10/25/2021 Signature Date Cassie Evans Printed Name cassie.evans@exxonmobil.com E-mail Address
	¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 10-8-2021 Date of Survey <i>Mark Dillon Harp</i> Signature and Seal of Professional Surveyor: MARK DILLON HARP 23786 Certificate Number JC 2018010211	

Intent ☐ As Drilled ☒

API # 30-015-46717		
Operator Name: XTO PERMIAN OPERATING, LLC.	Property Name: POKER LAKE UNIT 17 TWR	Well Number 905H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	20	24S	31E		81	FNL	2,340	FEL	EDDY
Latitude 32.209854					Longitude 103.798859				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	20	24S	31E		866	FNL	2,326	FEL	EDDY
Latitude 32.207695					Longitude 103.798812				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
O	29	24S	31E		444	FSL	2,288	FEL	EDDY
Latitude 32.182260					Longitude 103.798653				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018

Oilfield Services, Central U.S. Land

Schlumberger Drilling and Measurements

Drilling Group

Geo Market Area: South West Texas Basin

7220 W I-H 20

Midland, Texas 79706

Phone : (432) 742-5400 (Main)

Fax : (432) 742-5606 (Shared)

Schlumberger

July 6, 2020

XTO Permian Operating LLC

6401 Holiday Hill Road BLDG 5

Midland, TX 79707

Re:

CLIENT: XTO Permian Operating LLC
WELL: Poker Lake Unit 17 TWR 905H
FIELD: Purple Sage Wolfcamp

RIG: H&P 552
COUNTY: Eddy
API NO: 30-015-46717-00
JOB NO: 20MLE0703

20 24S 31E Eddy NM
N 32.209776 W -103.796835

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements, a division of Schlumberger Technology Corporation (P-5 No. 754900).

Other information required by your office is as follows.

<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Cody Jacks	Poker Lake Unit 17	82.87 Ft	June 3, 2020	XBOLT
FE	TWR 905H Original Hole	21698.00 Ft	July 2, 2020	SlimPulse

Schlumberger-Private

Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)



Well Reference:

20 24S 31E Eddy NM
N 32.209776 W -103.796835

I, Cody Jacks certify that; I am employed by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I did on the day(s) of June 03, 2020 through July 02, 2020, conduct or supervise the taking of the XBOLT & SlimPulse surveys from a depth of 82.87 feet to a depth of 21698.00 feet referenced to driller's depth; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Permian Operating LLC for the Poker Lake Unit 17 TWR 905H Well (Original Hole) API No. 300154671700 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.

By
Cody Jacks
FE

Subscribed and Sworn to before me this _____ day of _____ (month) _____ (yr)

My Commission expires:

_____- (signature)
Notary Public

(County State)

Schlumberger

XTO Poker Lake Unit 17 TWR 905H 0 to 21743ft MD Survey Geodetic

Report
(Def Survey)

Report Date: September 01, 2020 - 05:41 PM
Client: XTO Energy
Field: NW Eddy County (NAD 27)
Structure / Slot: XTO Poker Lake Unit 17 TWR 905H / New Slot
Well: XTO Poker Lake Unit 17 TWR 905H
Borehole: XTO Poker Lake Unit 17 TWR 905H
UWI / API#: Unknown / 30-015-46717
Survey Name: XTO Poker Lake Unit 17 TWR 905H 0 to 21743ft MD
Survey Date: June 03, 2020
Tort / AHD / DDI / ERD Ratio: 353.323 * 10834.638 ft / 6.846 / 0.913
Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
Location Lat / Long: N 32° 12' 35.19485", W 103° 47' 48.60521"
Location Grid N/E Y/X: N 440460.200 ftUS, E 665933.000 ftUS
CRS Grid Convergence Angle: 0.2860 °
Grid Scale Factor: 0.99994063
Version / Patch: 2.10.818.0

Survey / DLS Computation: Minimum Curvature / Lubinski
Vertical Section Azimuth: 179.630 ° (Grid North)
Vertical Section Origin: 0.000 ft, 0.000 ft
TVD Reference Datum: RKB
TVD Reference Elevation: 3549.000 ft above MSL
Seabed / Ground Elevation: 3519.000 ft above MSL
Magnetic Declination: 6.648 °
Total Gravity Field Strength: 998.4272mgn (9.80665 Based)
Gravity Model: GARM
Total Magnetic Field Strength: 47791.305 nT
Magnetic Dip Angle: 59.872 °
Declination Date: June 03, 2020
Magnetic Declination Model: HDGM 2020
North Reference: Grid North
Grid Convergence Used: 0.2860 °
Total Corr Mag North->Grid North: 6.3618 °
Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (ft/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth
Surface	0.00	0.00	202.48	0.00	0.00	0.00	0.00	N/A	440450.20	665933.00	32.209776	-103.796835	0.00	0.00
	82.87	0.19	171.13	82.87	0.14	-0.14	0.02	0.23	440450.06	665933.02	32.209776	-103.796835	0.14	171.13
	224.28	0.92	35.50	224.27	-0.55	0.56	0.72	0.75	440450.76	665933.72	32.209778	-103.796832	0.91	52.15
	316.00	1.29	70.00	315.98	-1.50	1.51	2.11	0.81	440451.71	665935.11	32.209780	-103.796828	2.60	54.48
	408.00	1.15	63.14	407.96	-2.26	2.28	3.91	0.22	440452.48	665936.91	32.209783	-103.796822	4.53	59.75
	501.00	1.27	63.02	500.94	-3.13	3.17	5.66	0.13	440453.37	665938.66	32.209785	-103.796816	6.49	60.76
	593.00	1.55	61.81	592.91	-4.17	4.22	7.67	0.31	440454.42	665940.67	32.209788	-103.796810	8.75	61.17
	779.00	1.43	74.45	778.85	-5.95	6.03	12.12	0.19	440456.23	665945.12	32.209793	-103.796795	13.54	63.55
	831.00	1.36	81.05	830.83	-6.21	6.30	13.36	0.34	440456.50	665946.35	32.209793	-103.796792	14.77	64.74
11-3/4" Casing	907.00	1.31	88.25	906.81	-6.37	6.47	15.12	0.23	440456.67	665948.12	32.209794	-103.796786	16.44	66.84
	940.00	1.30	91.52	939.80	-6.37	6.47	15.87	0.23	440456.67	665948.87	32.209794	-103.796783	17.14	67.82
	1033.00	0.87	94.76	1032.78	-6.27	6.38	17.63	0.47	440456.58	665950.63	32.209794	-103.796778	18.75	70.10
	1125.00	0.08	232.57	1124.78	-6.17	6.29	18.27	1.01	440456.49	665951.27	32.209793	-103.796776	19.32	71.02
	1220.00	0.09	156.06	1219.78	-6.06	6.18	18.25	0.11	440456.38	665951.25	32.209793	-103.796776	19.27	71.30
	1316.00	0.10	276.59	1315.78	-6.00	6.12	18.20	0.17	440456.32	665951.20	32.209793	-103.796776	19.20	71.42
	1411.00	0.11	122.78	1410.78	-5.96	6.08	18.19	0.22	440456.28	665951.19	32.209793	-103.796776	19.18	71.53
	1506.00	0.12	2.88	1505.78	-6.01	6.13	18.27	0.21	440456.33	665951.27	32.209793	-103.796776	19.27	71.46
	1601.00	0.11	57.49	1600.78	-6.16	6.28	18.36	0.11	440456.48	665951.35	32.209793	-103.796775	19.40	71.12
	1697.00	0.12	49.68	1696.78	-6.27	6.39	18.51	0.02	440456.59	665951.51	32.209794	-103.796775	19.58	70.95
	1792.00	0.11	332.63	1791.78	-6.42	6.54	18.54	0.15	440456.74	665951.54	32.209794	-103.796775	19.66	70.58
	1887.00	0.11	90.84	1886.78	-6.50	6.62	18.59	0.20	440456.82	665951.59	32.209794	-103.796775	19.73	70.41
	1982.00	0.12	69.62	1981.78	-6.53	6.65	18.78	0.05	440456.85	665951.78	32.209794	-103.796774	19.92	70.50
	2078.00	0.11	339.97	2077.78	-6.65	6.77	18.84	0.17	440456.97	665951.84	32.209795	-103.796774	20.02	70.23
	2174.00	0.12	4.93	2173.78	-6.84	6.96	18.82	0.05	440457.16	665951.82	32.209795	-103.796774	20.06	69.71
	2270.00	0.10	170.79	2269.78	-6.85	6.98	18.84	0.23	440457.17	665951.84	32.209795	-103.796774	20.09	69.68
	2366.00	0.11	292.31	2365.78	-6.81	6.93	18.77	0.19	440457.13	665951.77	32.209795	-103.796774	20.00	69.74
	2462.00	0.11	14.95	2461.78	-6.93	7.05	18.71	0.15	440457.25	665951.70	32.209795	-103.796774	19.99	69.35
	2558.00	1.59	286.63	2557.77	-7.41	7.52	17.45	1.66	440457.72	665950.45	32.209797	-103.796778	19.00	66.69
	2654.00	4.03	279.36	2653.64	-8.37	8.45	12.85	2.56	440458.65	665945.85	32.209799	-103.796793	15.38	56.66
	2750.00	5.91	282.16	2749.28	-10.01	10.04	4.69	1.97	440460.24	665937.69	32.209804	-103.796819	11.08	25.02
	2846.00	6.44	285.33	2844.72	-12.54	12.51	-5.34	0.66	440462.71	665927.66	32.209811	-103.796852	13.60	336.89
	2942.00	6.36	288.78	2940.12	-15.74	15.64	-15.56	0.41	440465.84	665917.44	32.209820	-103.796885	22.06	315.14
	3038.00	6.27	286.97	3035.54	-19.05	18.88	-25.81	0.23	440469.08	665907.39	32.209829	-103.796917	31.82	306.40
	3134.00	6.19	285.72	3130.98	-22.04	21.82	-35.61	0.16	440472.01	665897.39	32.209837	-103.796950	41.76	201.49
	3230.00	6.41	277.19	3226.40	-24.18	23.89	-45.91	1.00	440474.09	665887.10	32.209843	-103.796983	51.75	297.49
	3420.00	3.59	273.61	3415.66	-25.99	25.59	-62.37	1.49	440475.79	665870.63	32.209848	-103.797036	67.41	292.31
	3515.00	3.14	256.36	3510.49	-25.60	25.16	-67.87	1.16	440475.36	665865.14	32.209846	-103.797054	72.38	290.34
	3610.00	6.30	242.86	3605.16	-22.66	22.17	-75.04	3.50	440472.37	665857.97	32.209838	-103.797077	78.24	286.46
	3705.00	6.09	239.72	3699.61	-17.80	17.25	-84.03	0.42	440467.45	665848.98	32.209825	-103.797106	85.78	281.60
	3800.00	6.35	237.68	3794.05	-12.50	11.90	-92.82	0.36	440462.10	665840.19	32.209810	-103.797135	93.58	277.31
	3894.00	6.59	236.98	3887.45	-6.84	6.19	-101.73	0.27	440456.38	665831.27	32.209795	-103.797164	101.92	273.48
	3989.00	6.73	239.61	3981.81	-1.12	0.40	-111.10	0.35	440450.60	665821.90	32.209779	-103.797194	111.11	270.21
	4084.00	6.82	250.96	4076.15	3.47	-4.26	-121.24	1.41	440445.94	665811.77	32.209766	-103.797227	121.31	267.99
	4179.00	6.36	264.53	4170.53	5.75	-6.60	-131.81	1.70	440443.60	665801.20	32.209760	-103.797261	131.97	267.13
	4274.00	5.69	282.33	4265.01	5.18	-6.10	-141.65	2.08	440444.10	665791.36	32.209762	-103.797293	141.78	267.54
	4369.00	6.31	294.47	4359.49	1.95	-2.93	-151.00	1.48	440447.27	665782.01	32.209770	-103.797323	151.03	268.89
	4464.00	6.60	279.82	4453.90	-1.21	0.17	-161.13	1.76	440450.37	665771.88	32.209779	-103.797356	161.13	270.06
	4559.00	6.51	262.00	4548.29	-1.46	0.35	-171.85	2.13	440450.55	665761.16	32.209780	-103.797390	171.85	270.12
	4654.00	6.81	251.39	4642.67	0.97	-2.15	-182.36	1.28	440448.05	665750.65	32.209773	-103.797424	182.38	269.33
	4749.00	6.58	251.86	4737.04	4.34	-5.59	-192.72	0.97	440444.61	665740.29	32.209764	-103.797458	192.80	268.34
	4844.00	6.26	260.20	4831.45	8.85	-6.18	-202.99	1.04	440442.04	665730.02	32.209757	-103.797491	203.16	267.70
	4939.00	6.50	266.76	4925.86	7.97	-9.35	-213.47	0.81	440440.85	665719.55	32.209755	-103.797525	213.67	267.49
	5034.00	6.50	266.76	5020.25	8.51	-9.96	-224.20	0.00	440440.25	665708.81	32.209752	-103.797560	224.42	267.46
	5129.00	6.44	279.00	5114.65	7.91	-9.43	-234.84	1.45	440440.77	665698.18	32.209754	-103.797594	235.02	267.70
	5224.00	6.43	281.31	5209.05	5.96	-7.55	-245.31	0.27	440442.65	665687.70	32.209759	-103.797628	245.43	268.24
	5319.00	6.03	272.50	5303.49	4.64	-6.29	-255.52	1.09	440443.91	665677.50	32.209763	-103.797661	255.59	268.59
	5414.00	6.50	263.34	5397.93	4.98	-6.69	-265.84	1.16	440443.51	665667.18	32.209762	-103.797694	265.93	268.56
	5509.00	7.79	257.75	5492.19	6.89	-6.88	-277.47	1.54	440441.52	665655.54	32.209756	-103.797732	277.61	268.21
	5604.00	6.44	247.75	5586.46	10.20	-12.07	-288.70	1.92	440438.13	665644.32	32.209747	-103.797768	288.95	267.61
	5793.00	6.54	250.97	5774.25	17.60	-19.59	-308.68	0.20	440430.61	665624.34	32.209727	-103.797833	309.30	266.37
	5888.00	6.41	253.54	5868.64	20.80	-22.86	-318.88	0.33	440427.34	665614.14	32.209718	-103.797866	319.70	265.90
	5983.00	6.06	256.71	5963.08	23.39	-25.51	-328.85	0.52	440424.69	665604.17	32.209711	-103.797898	329.84	265.56
	6078.00	6.37	261.79	6057.52	25.23	-27.42	-338.95	0.66	440422.78	665594.07	32.209706	-103.797931	340.05	265.38
	6172.00	6.40	265.53	6150.94	26.31	-28.57	-349.33	0.44	440421.63	665583.69	32.209703	-103.797965	350.50	265.32
	6267.00	6.43	265.81	6245.34	27.05	-29.37	-359.91	0.05	440420.83	665573.11	32.209701	-103.797999	361.11	265.33
	6362.00	6.45	270.07	6339.74	27.36	-29.75	-370.56	0.50	440420.45	665562.47	32.209700	-103.798003	371.75	265.41
	6457.00	6.39	277.21	6434.15	26.62	-28.78	-381.14	0.84	440421.12	665551.89	32.209702	-103.7980		

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	9117.00	1.37	302.30	9089.99	12.67	-15.72	-472.89	0.35	440434.48	665460.14	32.209740	-103.798364	473.15	268.10
	9212.00	1.75	309.95	9184.95	11.12	-14.18	-474.96	0.46	440436.02	665458.07	32.209744	-103.798371	475.17	268.29
	9402.00	0.60	253.32	9374.92	9.52	-12.61	-478.14	0.79	440437.60	665454.89	32.209748	-103.798381	478.30	268.49
	9497.00	0.09	250.31	9469.91	9.68	-12.77	-478.68	0.54	440437.43	665454.35	32.209748	-103.798383	478.85	268.47
	9592.00	0.21	306.25	9564.91	9.60	-12.70	-478.89	0.19	440437.51	665454.14	32.209748	-103.798383	479.06	268.48
	9687.00	0.34	251.04	9659.91	9.59	-12.68	-479.30	0.29	440437.52	665453.73	32.209748	-103.798385	479.47	268.48
	9782.00	0.48	85.22	9754.91	9.65	-12.74	-479.17	0.86	440437.46	665453.86	32.209748	-103.798384	479.34	268.48
	9876.00	0.41	109.41	9848.91	9.73	-12.82	-478.46	0.21	440437.38	665454.57	32.209748	-103.798382	478.63	268.47
	9971.00	0.49	47.18	9943.91	9.57	-12.66	-477.84	0.49	440437.54	665455.19	32.209749	-103.798380	478.01	268.48
	10066.00	0.24	16.14	10038.90	9.11	-12.19	-477.49	0.33	440438.01	665455.54	32.209749	-103.798379	477.64	268.54
	10161.00	0.34	156.08	10133.90	9.17	-12.26	-477.32	0.57	440437.94	665455.71	32.209749	-103.798378	477.48	268.53
	10256.00	0.16	311.60	10228.90	9.34	-12.43	-477.30	0.52	440437.77	665455.73	32.209749	-103.798378	477.47	268.51
	10351.00	0.32	206.99	10323.90	9.49	-12.58	-477.52	0.41	440437.63	665455.51	32.209748	-103.798379	477.69	268.49
	10445.00	0.32	193.31	10417.90	9.98	-13.06	-477.70	0.08	440437.14	665455.33	32.209747	-103.798379	477.88	268.43
	10540.00	0.74	166.85	10512.90	10.84	-13.92	-477.62	0.50	440436.28	665455.40	32.209745	-103.798379	477.83	268.33
	10635.00	0.72	196.70	10607.89	12.00	-15.09	-477.66	0.40	440435.11	665455.37	32.209741	-103.798379	477.89	268.19
	10730.00	0.10	72.60	10702.89	12.55	-15.64	-477.75	0.82	440434.56	665455.28	32.209740	-103.798380	478.00	268.13
	10825.00	0.32	326.34	10797.89	12.30	-15.39	-477.82	0.38	440434.81	665455.21	32.209741	-103.798380	478.06	268.16
	10919.00	0.34	161.52	10891.89	12.35	-15.44	-477.87	0.70	440434.76	665455.16	32.209740	-103.798380	478.12	268.15
	10946.00	0.46	171.42	10918.89	12.53	-15.62	-477.83	0.51	440434.58	665455.20	32.209740	-103.798380	478.09	268.13
7-5/8" Casing	10986.00	0.65	42.78	10958.88	12.53	-15.61	-477.66	2.50	440434.59	665455.37	32.209740	-103.798379	477.91	268.13
	10987.00	0.67	42.01	10959.88	12.52	-15.60	-477.65	2.50	440434.60	665455.38	32.209740	-103.798379	477.90	268.13
	11082.00	0.36	221.54	11054.88	12.33	-15.42	-477.47	1.08	440434.79	665455.56	32.209741	-103.798379	477.72	268.15
	11177.00	11.50	180.78	11149.23	22.05	-25.14	-477.80	11.82	440425.06	665455.23	32.209714	-103.798380	478.46	266.99
	11272.00	24.91	178.16	11239.27	51.66	-54.74	-477.29	14.14	440395.46	665455.74	32.209632	-103.798379	480.41	263.46
	11367.00	31.32	172.32	11323.03	96.20	-99.26	-473.34	7.34	440350.95	665459.69	32.209510	-103.798367	483.63	258.16
	11462.00	37.00	168.53	11401.62	148.79	-151.80	-464.35	6.38	440298.41	665468.68	32.209365	-103.798338	488.53	251.90
	11556.00	43.76	169.17	11473.19	208.59	-211.51	-452.60	7.20	440238.70	665480.43	32.209201	-103.798301	499.58	244.95
FTP [339° FWL, 330° FNL]	11643.00	48.19	171.71	11533.64	270.32	-273.18	-442.26	5.51	440177.03	665490.76	32.209032	-103.798269	519.83	238.30
	11652.00	48.05	171.95	11539.61	272.99	-279.85	-441.31	5.51	440170.37	665491.72	32.209013	-103.798266	522.56	237.62
	11747.00	47.33	180.34	11603.32	347.30	-330.14	-438.77	8.55	440100.08	665494.26	32.208820	-103.798259	561.35	231.41
	11841.00	51.29	193.96	11664.68	417.42	-420.33	-430.07	9.03	440026.89	665492.95	32.208627	-103.798257	615.83	223.86
	11936.00	63.54	184.73	11715.82	496.10	-499.10	-462.59	15.25	439951.13	665470.44	32.208411	-103.798338	680.51	222.83
	12031.00	71.47	178.02	11752.18	583.70	-586.72	-464.54	10.59	439863.52	665468.49	32.208170	-103.798346	748.36	218.37
	12126.00	84.49	176.13	11771.92	676.32	-679.31	-459.78	13.84	439770.94	665473.25	32.207915	-103.798332	820.27	214.09
	12221.00	89.38	182.54	11777.00	771.11	-774.09	-458.69	8.48	439676.16	665474.34	32.207655	-103.798330	899.78	210.65
	12316.00	88.58	179.10	11778.70	866.06	-869.05	-460.05	3.72	439581.21	665472.98	32.207394	-103.798336	983.30	207.90
	12411.00	87.16	179.78	11782.23	960.99	-963.97	-459.12	1.66	439486.29	665473.91	32.207133	-103.798335	1067.72	205.47
	12506.00	87.05	180.27	11787.02	1055.86	-1058.85	-459.16	0.53	439391.41	665473.87	32.206872	-103.798336	1154.12	203.44
	12601.00	87.02	179.86	11791.94	1150.73	-1153.72	-459.27	0.43	439296.55	665473.76	32.206611	-103.798338	1241.78	201.71
	12790.00	86.71	180.00	11802.27	1339.45	-1342.44	-459.04	0.18	439107.84	665473.99	32.206093	-103.798340	1418.75	198.88
	12885.00	86.66	178.75	11807.77	1434.29	-1437.27	-458.00	1.31	439013.01	665475.03	32.205832	-103.798339	1508.48	197.68
	13075.00	98.18	181.56	11799.76	1623.77	-1626.77	-458.50	6.24	438823.53	665474.53	32.205311	-103.798343	1690.14	195.74
	13170.00	88.40	179.50	11794.31	1718.48	-1721.48	-459.36	10.52	438728.82	665473.66	32.205051	-103.798348	1781.72	194.94
	13265.00	89.18	182.12	11796.32	1813.43	-1816.44	-460.71	2.88	438633.87	665472.32	32.204790	-103.798353	1873.96	194.23
	13360.00	88.78	182.38	11798.01	1908.32	-1911.36	-464.44	0.50	438538.96	665468.59	32.204529	-103.798367	1966.97	193.66
	13454.00	88.35	179.48	11799.53	2002.26	-2005.31	-465.96	3.09	438445.01	665467.07	32.204271	-103.798373	2056.74	193.08
	13549.00	89.35	180.25	11801.50	2097.25	-2100.30	-465.74	0.95	438350.03	665467.29	32.204010	-103.798374	2147.83	192.11
	13640.00	88.41	179.60	11803.18	2188.23	-2191.28	-465.82	1.25	438255.05	665467.41	32.203760	-103.798375	2240.21	192.00
	13830.00	87.01	178.18	11810.77	2378.05	-2381.09	-461.94	1.05	438069.26	665471.09	32.203238	-103.798367	2425.48	190.98
	13925.00	89.05	179.18	11814.03	2472.98	-2476.00	-459.75	2.39	437974.35	665473.27	32.202977	-103.798361	2518.32	190.52
	14114.00	89.98	180.96	11815.63	2661.96	-2664.98	-459.99	1.06	437875.38	665473.04	32.202457	-103.798365	2704.39	189.79
	14209.00	90.18	180.63	11815.50	2756.94	-2759.97	-461.30	0.41	437690.40	665471.72	32.202196	-103.798371	2798.26	189.49
	14409.00	89.97	181.54	11815.24	2956.87	-2959.93	-465.09	0.47	437490.45	665467.94	32.201647	-103.798386	2996.25	188.93
	14493.00	90.24	180.69	11815.08	3040.84	-3043.92	-466.73	1.06	437406.47	665466.30	32.201416	-103.798393	3079.49	188.72
	14588.00	89.89	179.36	11814.98	3135.84	-3138.91	-466.77	1.45	437311.48	665466.26	32.201155	-103.798394	3173.43	188.46
	14682.00	89.99	179.25	11815.08	3229.83	-3232.91	-465.63	0.16	437217.49	665467.40	32.200896	-103.798392	3266.27	188.20
	14777.00	89.27	179.20	11815.69	3324.83	-3327.90	-464.34	0.76	437122.51	665468.69	32.200635	-103.798389	3360.14	187.94
	14872.00	94.00	182.58	11812.98	3419.73	-3422.81	-465.81	6.12	437027.60	665467.22	32.200374	-103.798396	3454.36	187.75
	14967.00	90.67	180.86	11809.11	3514.57	-3517.67	-468.66	3.94	436932.75	665464.37	32.200114	-103.798407	3548.75	187.59
	15061.00	88.74	179.26	11809.59	3608.56	-3611.66	-468.76	2.67	436838.76	665464.27	32.199855	-103.798408	3641.95	187.40
	15156.00	88.27	180.22	11812.07	3703.52	-3706.62	-468.33	1.12	436743.80	665464.70	32.199594	-103.798408	3736.09	187.20
	15252.00	88.92	181.15	11814.42	3799.48	-3802.59	-469.47	1.18	436647.85	665463.55	32.199331	-103.798414	3831.46	187.04
	15347.00	89.19	179.99	11815.99	3894.45	-3897.57	-470.42	1.25	436552.87	665462.61	32.199069	-103.798418	3925.85	186.88
	15442.00	88.72	179.59	11817.72	3989.43	-3992.55	-471.07	0.65	436457.89	665462.96	32.198808	-103.798424	4020.13	186.71
	15536.00	90.74	178.04	11818.17	4083.41	-4086.52	-468.13	2.71	436363.93	665464.90	32.198550	-103.798414	4113.25	186.53
	15631.00	90.11	179.17	11817.46	4178.39	-4181.49	-465.82	1.36	436268.97	665467.21	32.198289	-103.798408	4207.35	186.36
	15726.00	89.71	179.59	11817.61	4273.39	-4276.48	-464.79	0.61	436173.98	665468.24	32.198028	-103.798406	4301.67	186.20
	15820.00	90.94	181.16	11817.08	4367.38	-4370.47	-465.40	2.12	436079.99	665467.				

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	20939.00	90.24	183.26	11865.05	9481.22	-9483.90	-383.77	1.48	430966.89	665549.25	32.183713	-103.798228	9491.66	182.32
	21034.00	89.97	180.90	11864.88	9576.13	-9578.83	-387.22	2.50	430871.96	665545.80	32.183452	-103.798241	9586.65	182.31
	21129.00	90.38	178.35	11864.59	9671.12	-9673.82	-386.60	2.72	430776.98	665546.43	32.183191	-103.798240	9681.54	182.29
	21223.00	90.38	175.74	11863.96	9765.01	-9767.68	-381.75	2.78	430683.12	665551.27	32.182933	-103.798226	9775.14	182.24
	21318.00	90.21	174.76	11863.48	9859.73	-9862.35	-373.89	1.05	430588.45	665559.14	32.182673	-103.798202	9869.44	182.17
	21413.00	90.10	177.14	11863.22	9954.53	-9957.11	-367.18	2.51	430493.70	665565.85	32.182412	-103.798182	9963.88	182.11
	21508.00	90.41	179.36	11862.80	10049.49	-10052.06	-364.28	2.36	430398.76	665568.75	32.182151	-103.798174	10058.65	182.08
	21603.00	90.48	179.81	11862.06	10144.49	-10147.05	-363.59	0.48	430303.77	665569.43	32.181890	-103.798173	10153.56	182.05
LTP [352' FWL, 330' FSL]	21622.00	90.49	180.01	11861.90	10163.49	-10166.05	-363.56	1.04	430284.77	665569.46	32.181838	-103.798174	10172.55	182.05
Last Survey	21698.00	90.55	180.80	11861.20	10239.48	-10242.04	-364.09	1.04	430208.78	665568.93	32.181629	-103.798177	10248.51	182.04
Projection to Bit [352' FWL, 213' FSL]	21743.00	90.55	180.80	11860.77	10284.47	-10287.04	-364.72	0.00	430163.79	665568.30	32.181505	-103.798179	10293.50	182.03

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma
Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
	1	0.000	30.000	1/98.425	14.750	11.750	NAL_MWD_1.0_DEG-Depth Only	XTO Poker Lake Unit 17 TWR 905H / XTO Poker Lake Unit 17 TWR 905H 0 to 21743ft MD XTO Poker Lake Unit 17 TWR
	1	30.000	30.000	Act Stns	14.750	11.750	NAL_MWD_1.0_DEG-Depth Only	905H / XTO Poker Lake Unit 17 TWR 905H 0 to 21743ft MD XTO Poker Lake Unit 17 TWR
	1	30.000	869.000	Act Stns	14.750	11.750	NAL_MWD_1.0_DEG	905H / XTO Poker Lake Unit 17 XTO Poker Lake Unit 17 TWR
	1	869.000	11177.000	Act Stns	9.875	7.625	NAL_MWD_1.0_DEG	905H / XTO Poker Lake Unit 17 XTO Poker Lake Unit 17 TWR
	1	11177.000	21743.000	Act Stns	6.750	5.500	NAL_MWD_JFR1+MS	905H / XTO Poker Lake Unit 17

Well Name: POKER LAKE UNIT 17 TWR	Well Location: T24S / R31E / SEC 20 / NWNE / 32.209969 / -103.797317	County or Parish/State: EDDY / NM
Well Number: 905H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMLC0061705B, NMLC061705B	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001546717	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Subsequent Report

Sundry ID: 2630724

Type of Submission: Subsequent Report	Type of Action: Drilling Operations
Date Sundry Submitted: 08/26/2021	Time Sundry Submitted: 08:27
Date Operation Actually Began: 07/03/2021	

Actual Procedure: XTO PERMIAN OPERATING LLC respectfully submits this sundry notice to report the completion operations of the referenced well. KOP @ depth 11,114 ft. PBTD = 21,731 ft. 6/5/21 Run RCB/GR/CCL 6/10/21 Pressure test 5.5 in csg to 8,530 psi for 30min test good, open sleeve. 7/3/21 Perf and frac 46 stages, 1104 total shots, from 12,251 to 21,513 using 469,856 bbls of fluid and 22,919,117 lbs Proppant. Tag and drill out plugs. 8/15/21 Run 2-7/8 L80 6.5# tubing set at 11,097 ft. 8/15/21 Packer setting depth 11,081 ft.

Well Name: POKER LAKE UNIT 17 TWR	Well Location: T24S / R31E / SEC 20 / NWNE / 32.209969 / -103.797317	County or Parish/State: EDDY / NM
Well Number: 905H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMLC0061705B, NMLC061705B	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001546717	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS	Signed on: AUG 26, 2021 08:27 AM
Name: XTO PERMIAN OPERATING LLC	
Title: Regulatory Analyst	
Street Address: 6401 Holiday Hill Road, Bldg 5	
City: Midland	State: TX
Phone: (432) 218-3671	
Email address: CASSIE.EVANS@EXXONMOBIL.COM	

Field Representative

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: Jonathon W Shepard	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5752345972	BLM POC Email Address: jshepard@blm.gov
Disposition: Accepted	Disposition Date: 09/28/2021
Signature: Jonathon Shepard	

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG								1. WELL API NO. 30-015-46717		
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								2. Type of Lease ☐ STATE ☐ FEE ☒ FED/INDIAN		
								3. State Oil & Gas Lease No.		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 17 TWR		
8. Name of Operator XTO PERMIAN OPERATING LLC.						9. OGRID 373075				
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat PURPLE SAGE;WOLFCAMP (GAS)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	B	20	24S	31E		65	North	1863	East	Eddy
BH:	O	29	24S	31E		214	South	2290	East	Eddy
13. Date Spudded 6/3/2020	14. Date T.D. Reached 06/22/20		15. Date Rig Released 7/4/2020		16. Date Completed (Ready to Produce) 10/06/2021			17. Elevations (DF and RKB, RT, GR, etc.) 3515 GL		
18. Total Measured Depth of Well 21,742			19. Plug Back Measured Depth 21,731		20. Was Directional Survey Made? Yes			21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 12,251 - 21,513 PURPLE SAGE;WOLFCAMP (GAS)										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
11 3/4"		54.0		895'		14 3/4"		605		
7 5/8"		29.7		10,964		9 7/8"		2776		
5.5"		18		21,733'		6 3/4"		1180		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET	PACKER SET		
						2 7/8"	11,097	11,081		
26. Perforation record (interval, size, and number) 12,251 - 21,513 2spf, 1104 Total Shots 46 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						12,251 - 21,513		469,856 bbl fluid + 22,919,117 lbs proppant		
28. PRODUCTION										
Date First Production 10/7/21		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in) Producing				
Date of Test 10/10/21	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 2051	Gas - MCF 5448	Water - Bbl. 5563	Gas - Oil Ratio 2,656			
Flow Tubing Press. 899	Casing Pressure 285	Calculated 24-Hour Rate	Oil - Bbl. 2051	Gas - MCF 5448	Water - Bbl. 5563	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold								30. Test Witnessed By		
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude				Longitude				NAD83		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature 		Printed Name Cassie Evans		Title Regulatory Analyst			Date 10/27/2021			
E-mail Address cassie.evans@xtoenergy.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 964	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 4,148'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 4,351'	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T. Rustler 569'	T. Entrada	
T. Wolfcamp 11,554'	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 84995

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 84995
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 84995

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 84995
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
matthew.gomez	File 3160-4 within 10 days of BLM Approval.	10/23/2024