Office	State of New Mexico	Form C-103
District 1	Energy, Minerals and Natural Resources	October 13, 2009 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II		30-059-20453
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE S FEE
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No. L-6247
87505		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name BRAVO DOME CARBON DIOXIDE GAS UNIT (BDCDGU)
1. Type of Well: Oil Well	Gas Well Other CO2 PRODUCER	8. Well Number 072
2. Name of Operator OXY USA Inc.		9. OGRID Number 16696
3. Address of Operator		10. Pool name or Wildcat
	303, AMISTAD , NM 88410	BRAVO DOME CARBON DIOXIDE GAS UNIT 640 ACRE AREA
4. Well Location	- Control of the Cont	ALAE AREA
Unit Letter H : 2310 feet from the NORTH line and 990 feet from the EAST line		
Section 7	Township 22N Range 34E	NMPM UNION County
	11. Elevation (Show whether DR, RKB, RT, GR, etc.	
	GL: 4933,4'	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
•• •		
	1	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	<u>=</u>	_
PULL OR ALTER CASING		
DOWNHOLE COMMINGLE	_	
OTHER:	☐ OTHER:	П
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or rec	completion.	
WELL PRODUCTION HAS DECLINED TO A MARGINAL STATUS		
WELL PRODUCTION HAS DECI	INED TO A MARGINAL STATUS	
	LINED TO A MARGINAL STATUS	
PROPOSED WORK:		EEL).
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT.	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST	EEL).
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST	EEL).
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT.	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART.	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART.	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM.	eel). well loss to Sauta Fe
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM.	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. VITH 350 SX	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM.	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 ½" SET @ 2439", W	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. VITH 350 SX	
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 ½" SET @ 2439", W Spud Date:	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST 00 MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date:	nd well loss to SAUTA
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 ½" SET @ 2439", W Spud Date:	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST TO MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. VITH 350 SX	nd well loss to SAUTA
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738' WITH PRODUCTION: 5 ½" SET @ 2439", W Spud Date: I hereby certify that the information	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. OLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date:	ee and belief.
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 ½" SET @ 2439", W Spud Date:	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. OLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date:	nd well loss to SAUTA
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 1/4" SET @ 2439", W Spud Date: I hereby certify that the information SIGNATURE	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date: TITLE_SR ENG ADVISOR	pul well 1055 To SAUTA Fe ge and belief. DATE06/08/2016
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 1/4" SET @ 2439", W Spud Date: I hereby certify that the information SIGNATURE	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. OLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date:	pul well 1055 To SAUTA Fe ge and belief. DATE06/08/2016
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRE DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738' WITH PRODUCTION: 5 ½" SET @ 2439', W Spud Date: I hereby certify that the information SIGNATURE Type or print nameAL OUSSAL For State Use Only	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date: TITLE_SR ENG ADVISOR_ NI E-mail address: _albert_giussat	ge and belief. DATE06/08/2016 ni@oxy.com PHONE:_806-638-1296
PROPOSED WORK: SET UP BRIDGE PLUG ON WIRI DUMP 5 SX CEMENT. TEST CASING TO 550 PSI FOR 3 ISOLATE WELLHEAD FROM CO WELLBORE SCHEMATICS: SURFACE: 8 5/8" SET @ 738" WITH PRODUCTION: 5 1/1" SET @ 2439", W Spud Date: I hereby certify that the information SIGNATURE Type or print nameAL CAUSSAL	ELINE @ 2129' (CROSSOVER FIBERGLASS TO ST O MINUTES- RECORD ON CHART. DLLECTION SYSTEM. 400 SX. //ITH 350 SX Rig Release Date: TITLE_SR ENG ADVISOR	ge and belief. DATE06/08/2016 ni@oxy.com PHONE:_806-638-1296