12003	State of New Mexico	Form C-14 July 21, 200		
RÉGISTÈR	ED partment rvation Division h St. Francis Dr	For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.		
UUU KIO Brazos Kd., Aztec, NM 87410 <u>District IV</u> 220 S. St. Francis Dr., Santa Fe, NM, 87505	Santa Fe, NM 87505	For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.		
220 S. St. Francis DI., Sand Fe, HW 07505	Pit. Closed-Loop System, Below-Grad	ie Tank, or		
Propo	sed Alternative Method Permit or Closu	re Plan Application		
Type of action:	X Permit of a pit. closed-loop system, below-grade	tank, or proposed alternative method		
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Closure of a pit, closed-loop system, below-grad Modification to an existing permit	e tank, or proposed alternative method		
	Closure plan only submitted for an existing perm below-grade tank, or proposed alternative metho	itted or non-permitted pit, closed-loop system, d		
Instructions: Please submit one	application (Form C-144) per individual pit, closed-le	oop system, below-grade tank or alternative request		
Please be advised that approval	of this request does not relieve the operator of liability should operations	result in pollution of surface water, ground water or the		
environment. Nor does approval re	sneve me operator of its responsibility to comply with any other applicable	e governmental autionty's rules, regulations or ordinances.		
Operator: Burlington Resources C	Dil & Gas Company, LP	OGRID#: 14538		
Address: PO Box 4289, Farming	ton, NM 87499			
acility or well name: SAN JUAN	28-6 UNIT 156N			
API Number:	3003927761 OCD Permit Numb	er:		
J/L or Qtr/Qtr: C Sect	ion: 29 Township: 28N Range:	6W County: Rio Arriba		
Center of Proposed Design: Latitud	de: <u>36.63676°N</u> Longitude:	-107.49103°W NAD: X 1927 1983		
Surface Owner: X Federal	State Private Tribal Trust or India	an Allotment		
Temporary: Drilling Wo	orkover Cavitation P&A			
Lined Unlined I String-Reinforced Liner Seams: Welded I	Liner type: Thickness mil LLDPE	HDPE PVC Other bbl Dimensions L x W x D		
Lined Unlined I String-Reinforced Liner Seams: Welded I <u>Closed-loop System:</u> Subsect Type of Operation: P&A	Liner type: Thickness mil LLDPE Factory Other Volume: ction H of 19.15.17.11 NMAC Drilling a new well Workover or Drilling (Applies to notice of intent)	HDPE PVC Other bbl Dimensions Lx Wx D o activities which require prior approval of a permit or		
Lined Unlined I String-Reinforced Liner Seams: Welded I <u>Closed-loop System:</u> Subset Type of Operation: P&A [Drying Pad Above Groon Lined Unlined Line Liner Seams: Welded I	Liner type: Thickness mil LLDPE Factory Other Volume: ction H of 19.15.17.11 NMAC Drilling a new well Workover or Drilling (Applies t notice of intent) pund Steel Tanks Haul-off BinsOther ner type: Thickness milLLDPE FactoryOther	HDPE PVC Other		
Lined Unlined I String-Reinforced Liner Seams: Welded I Closed-loop System: Subset Type of Operation: P&A Drying Pad Above Gro Lined Unlined Lin Liner Seams: Welded I X Below-grade tank: Subsection Volume: 120 Tank Construction material:	Liner type: Thickness mil LLDPE Factory Other Volume: ction H of 19.15.17.11 NMAC Drilling a new well Workover or Drilling (Applies to notice of intent) pund Steel Tanks Haul-off Bins Other ner type: Thickness mil LLDPE Factory Other Factory Other n1 of 19.15.17.11 NMAC bbl Type of fluid: <u>Produced Water</u> Metal	HDPE PVC Other		
Lined Unlined I String-Reinforced Liner Seams: Welded Closed-loop System: Subsect Type of Operation: P&A Drying Pad Above Grc Lined Unlined Line Liner Seams: Welded I X Below-grade tank: Subsection Volume: 120 Tank Construction material: Secondary containment with leak of Visible sidewalls and liner Liner Type: Thickness	Liner type: Thickness mil LLDPE	HDPE PVC Other		
Lined Unlined I String-Reinforced Liner Seams: Welded I 3 Closed-loop System: Subset 7 Closed-loop System: Subset 8 Operation: P&A 9 Drying Pad Above Growthing 1 Lined Unlined Line 1 Lined Unlined Line 4 X Below-grade tank: Subsection Volume: 120 Tank Construction material: Secondary containment with leak of 1 Visible sidewalls and liner Liner Type: Thickness 3 Alternative Method: String-Reinforced	Liner type: Thickness mil LLDPE	HDPE PVC Other		
Lined Unlined I String-Reinforced Liner Seams: Welded I 3 Closed-loop System: Subset Type of Operation: P&A I Drying Pad Above Gro Lined Unlined Lined Unlined Lir Lined Unlined Lir Liner Seams: Welded I X Below-grade tank: Subsection Volume: 120 Tank Construction material: Secondary containment with leak Visible sidewalls and liner Liner Type: Thickness Submittal of an exception request is represented by the starter of	Liner type: Thickness mil LLDPE	HDPE PVC Other		

.

b. <u>Fencing:</u> Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Reginred if located within 1000 feet of a permanent residence, school, hospital, Four foot height, four strands of barbed wire evenly spaced between one and four feet X Alternate. Please specify <u>4"hog wire fencing topped with two strands barbed wire.</u> 7 Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) X Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	institution or c	hurch)
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers		
Signed in compliance with 19.15.3.103 NMAC Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for co (Fencing/BGT Liner) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	onsideration of	approval.
10		
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source muterial are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	XNo
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	XNo
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	XNo
(Applies to temporary, emergency, or cavitation pits and helow-grade tanks)	□ NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		_
(Applied to permanent pits)	Yes XNA	No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizonal feet of a private demostic fractionable and and a private demostic fractionable and a private demostic fractic demostic fractionable and a private demostic fractic demostic fractic and a private demostic fractic and a private demostic demostic and a private demostic and a pr		_
purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	XNo
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality: Written approval obtained from the municipality	Yes	XNo
Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	XNo
Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	XNo
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	XNo
Within a 100-year floodplain FEMA map	Yes	XNo

.

,		
<u>Temporary Pits, Emergency Pits and Below-gr</u> Instructions: Each of the following items must be attacc	ade Tanks Permit Application Atta hed to the application. Please indicate, a	ichment Checklist: Subsection B of 19.15.17.9 NMAC by a check mark in the box, that the documents are attached
X Hydrogeologic Report (Below-grade Tanks)	based upon the requirements of Pa	ragraph (4) of Subsection B of 19 15 17 9 NMAC
Hydrogeologic Data (Temporary and Emerg	ency Pits) - based upon the requirem	ents of Paragraph (2) of Subsection B of 19.15.17.9
X Siting Criteria Compliance Demonstrations	- based upon the appropriate require	nents of 19.15.17.10 NMAC
X Design Plan - based upon the appropriate re	minements of 10 15 17 11 NMAC	nens of 17.15.17.10 (NVIAC.
X Operating and Maintenance Plan - based up	on the oppropriate sources of the	16 17 12 10 10 40 6
V Closure Plan (Plana) approach Down 11 the	on the appropriate requirements of 19	0.15.17.12 NMAC
19.15.17.9 NMAC and 19.15.17.13 NMAC	ougn 18, if applicable) - based upon (he appropriate requirements of Subsection C of
Previously Approved Design (attach copy of des	sign) API	or Permit
12 Closed-loop Systems Permit Application Attach Instructions: Each of the following items must be attach Geologic and Hydrogeologic Data (only for Siting Criteria Compliance Demonstrations Disign Plan - based upon the appropriate red Operating and Maintenance Plan - based upon Closure Plan (Please complete Boxes 14 thrown NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of desting)	ment Checklist: Subsection B of 19.1 ed to the application. Please indicate, b, on-site closure) - based upon the requi (only for on-site closure) - based upon quirements of 19.15.17.11 NMAC on the appropriate requirements of 19 bugh 18, if applicable) - based upon the ign) API	5.17.9 NMAC s a check mark in the box, that the documents are attached, irements of Paragraph (3) of Subsection B of 19.15.17.9 in the appropriate requirements of 19.15.17.10 NMAC .15.17.12 NMAC he appropriate requirements of Subsection C of 19.15.17.9
Previously Approved Operating and Maintenance	e Plan API	
Permanent Pits Permit Application Checklist: Instructions: Each of the following items must be attact Hydrogeologic Report - based upon the requit Siting Criteria Compliance Demonstrations - Climatological Factors Assessment Certified Engineering Design Plans - based u Dike Protection and Structural Integrity Design Leak Detection Design - based upon the appr Liner Specifications and Compatibility Asses Quality Control/Quality Assurance Construct Operating and Maintenance Plan - based upon Freeboard and Overtopping Prevention Plan - Nuisance or Hazardous Odors, including H2S Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate required	Subsection B of 19.15.17.9 NMAC hed to the application. Please indicate, rements of Paragraph (1) of Subsection hased upon the appropriate requirements of the appropriate requirements of 19.15.17.111 sment - based upon the appropriate require ion and Installation Plan in the appropriate requirements of 19. based upon the appropriate requirements of prevention Plan in the appropriate requirements of 19. based upon the appropriate requirements of Prevention Plan	by a check mark in the box, that the documents are attached. on B of 19.15.17.9 NMAC ents of 19.15.17.10 NMAC 19.15.17.11 NMAC ements of 19.15.17.11 NMAC NMAC equirements of 19.15.17.11 NMAC 15.17.12 NMAC ents of 19.15.17.11 NMAC 27.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC		
Instructions: Please complete the applicable boxes, Box	es 14 through 18. in regards to the prope	osed closure plan.
Type: Drilling Workover Emergency [Cavitation P&A Permane	nt Pit XBelow-grade Tank Closed-loop System
Proposed Closure Method: X Waste Excavation and	i Removal (Below-Grade Tar	ık)
Waste Removal (Clos	ed-loop systems only)	
On-site Closure Meth	od (only for temporary pits and closed-	loop systems)
In-place	Burial On-site Trench	
Alternative Closure M	lethod (Exceptions must be submitted	to the Santa Fe Environmental Bureau for consideration)
15		
Waste Excavation and Removal Closure Plan ChePlease indicate, by a check mark in the box, that the doctXProtocols and Procedures - based upon the appXConfirmation Sampling Plan (if applicable) - bXDisposal Facility Name and Permit Number (forXSoil Backfill and Cover Design SpecificationsXRe-vegetation Plan - based upon the appropriate	cklist: (19.15.17.13 NMAC) Instruction iments are attached. ropriate requirements of 19.15 17.13 ased upon the appropriate requirement or liquids, drilling fluids and drill cutt - based upon the appropriate requirements of Subsection 1 of 19	ns: Each of the following items must be attached to the closure plan. NMAC hts of Subsection F of 19.15.17.13 NMAC ings) hents of Subsection H of 19.15.17.13 NMAC 15.17.13 NMAC
X Site Reclamation Plan - based upon the approp	riate requirements of Subsection G of	19.15.17.13 NMAC

16		
Waste Removal Closure For Closed-loop Systems That Utilize Above Groun	d Steel Tanks or Haul-off Bins Only: (19.15.17-13.D NMAC)
are required.	elling fluids and drill cuttings. Use attachment if more than w	o favilities
Disposal Facility Name:	Disposal Facility Permit #:	
Disposal Facility Name:	Disposal Facility Permit #:	
Will any of the proposed closed-loop system operations and associated act Yes (If yes, please provide the information	ivities occur on or in areas that will not be used for future	service and operations?
Required for impacted areas which will not be used for future service and operat	tions:	
Soil Backfill and Cover Design Specification - based upon the app	ropriate requirements of Subsection H of 19.15.17.13 NM	AC
Re-vegetation Plan - based upon the appropriate requirements of Si	ubsection 1 of 19.15.17.13 NMAC	
	f Subsection G of 19.15.17.13 NMAC	
Sing Uniteria (Regarding on-site closure methods only: 19.15.17.10 N Instructions: Each siting criteria requires a demonstration of compliance in the data of the	IMAC	
certain sting criteria may require administrative approval from the appropriate district o	ual. Recommendations of acceptable source material are provided by office or may be considered an exception which must be submitted to b	dow: Requests regarding changes to be Santa Fe Environmental Bassim above
for consideration of approval. Justifications and/or demonstrations of equivalency are re-	quired. Please refer to 19.15, 17, 10 NMAC for guidance.	and a contraction of the contraction of the
Ground water is less than 50 feet below the bottom of the buried waste.		Yes No
 NM Office of the State Engineer - iWATERS database search: USGS: Data 	obtained from nearby wells	N/A
Ground water is between 50 and 100 feet below the bottom of the buried w	vaste	
 NM Office of the State Engineer - iWATERS database search; USGS; Data 	obtained from nearby wells	
Ground water is more than 100 feet below the bottom of the buried waste.		
 NM Office of the State Engineer - iWATERS database search; USGS: Data 	obtained from nearby wells	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other sig (measured from the ordinary high-water mark).	enificant watercourse or lakebed, sinkhole, or playa lake	Yes No
 Topographic map: Visual inspection (certification) of the proposed site 		
 Within 300 feet from a permanent residence, school, hospital, institution, or churcl Visual inspection (certification) of the proposed site: Aerial photo; satellite in 	h in existence at the time of initial application. tage	Yes No
Within 500 horizontal feet of a private, domestic fresh water well or spring that les purposes, or within 1000 horizontal fee of any other fresh water well or spring, in e - NM Office of the State Engineer - iWATERS dutabase. Visual inspection (use	s than five households use for domestic or stock watering existence at the time of the initial application.	
Within incorporated municipal boundaries or within a defined municipal fresh wate pursuant to NMSA 1978, Section 3-27-3, as amended.	er well field covered under a municipal ordinance adopted	Yes No
Written confirmation or verification from the municipality: Written approval. Within 500 feet of a wetland	obtained from the municipality	
- US Fish and Wildlife Wetland Identification map: Topographic map: Visual i	nspection (certification) of the proposed site	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or man from the NM EMNRD-Mining on	d Minami Division	Yes No
Within an unstable area.		
 Engineering measures incorporated into the design; NM Bureau of Geology & Topographic map 	Mineral Resources; USGS; NM Geological Society;	
Within a 100-year floodplain.		
- FEMA map		
18		
<u>On-Site Closure Plan Checklist:</u> (19.15.17.13 NMAC) Instructions: Eac by a check mark in the box, that the documents are attached.	ch of the following items must bee attached to the closure	plan. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the appropri	ate requirements of 19.15.17.10 NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirem	tents of Subsection F of 19.15.17.13 NMAC	
Construction/Design Plan of Burial Trench (if applicable) based upon	the appropriate requirements of 19.15.17.11 NMAC	
Construction/Design Plan of Temporary Pit (for in place burial of a dr	ying pad) - based upon the appropriate requirements of 19	15.17.11 NMAC
Confirmation Sampling Dispute and the appropriate requirements of	of 19.15.17.13 NMAC	
Waste Material Sampling Plan (II applicable) - based upon the appropria	ate requirements of Subsection F of 19.15.17.13 NMAC	
waste Material Sampling Plan - based upon the appropriate requireme	ents of Subsection F of 19.15.17.13 NMAC	

Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)

Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC

Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

hereby certify that the	information submitted with this application is town w	munto and espectate to at a	and of much shared a basis of the test
Name (Print):	Crystal Fafoya	Title	est of my knowledge and belief.
Signature	ALADTO DOLOGIA	The:	Regulatory Technician
mail addroses	- mpian craffery	Date:	12/22/2008
		Telephone:	505-326-9837
1			
CD Approval:	Permit Application (including closure plan)	Closure Plan (only)	
CD D		_ closure r lan (omy)	OCD Conditions (see attachment)
CD Representativ	2 Signature:		Approval Date:
itle:		()('D Dt	
		UCD Permi	
losure Report (req	uired within 60 days of closure completion): Su	ibsection K of 19.15.17.13 NMAC	
structions: Operators	are required to obtain an approved closure plan prior	to implementing any closure	e activities and submitting the closure report. The closure
port is required to be proved closure plan	submitted to the division within 60 days of the complet has been obtained and the closure antiviting burns by	tion of the closure activities.	Please do not complete this section of the form until an
,	as been obtained and the closure activities have been	completed.	
		Closure (Completion Date:
osure Method:			
Waste Excavation	n and Removal On-site Closure Method	Alternative Closure M	ethod Waste Removal (Closed-loop systems only)
If different from	approved plan, please explain.		
sure Report Regard	ing Waste Removal Closure For Closed-loop System	ns That Litilian About Com	
tructions: Please ide	ntify the facility or facilities for where the liquids, dri	lling fluids and drill cutting	nd Steel Lanks or Haul-off Bins Only:
re utilized.		and arm campy	s were assosed. Use allochment if more than two facilities
Disposal Facility Nat	ne:	Disposal Facility Pe	rmit Number:
Disposal Facility Nat	1e:	Disposal Facility Pe	mit Number:
Were the closed-loop	system operations and associated activities performed	on or in areas that will not b	e used for future service and opeartions?
Yes (If yes, pleas	e demonstrate complilane to the items below)	No	
Required for impacte	Lareas which will not be used for future service and ϕ_{i}	perations:	
Site Reclamation	(Photo Documentation)		
Soil Backfilling	nd Cover Installation		
Re-vegetation Ap	plication Rates and Seeding Technique		
Closure Report At	achment Checklist: Instructions: Each of the foll	owing items must be attache	d to the closure report. Please indicate, by a check mark in
he box, that the docu	ments are attached.		
Proof of Closure	Notice (surface owner and division)		
Proof of Deed N	otice (required for on-site closure)		
Plot Plan (for or	-site closures and temporary pits)		
Confirmation Sa	mpling Analytical Results (if applicable)		
Waste Material	Sampling Analytical Results (if applicable)		
Disposal Facility	Name and Permit Number		
Soil Backfilling	and Cover Installation		
Re-vegetation A	plication Rates and Seeding Technique		
Site Reclamation	(Photo Documentation)		
On-site Closure	ocation: Latitude:	Longitude	NAD 0027 0 1027
			1727 [1983
	ification:		
rator Closure Cer	Formation and attachments submitted with this closure	Present in these and many and	
rator Closure Cer	ill applicable closure requirements and conditions one	cified in the approved closur	complete to the best of my knowledge and belief. I also certify that w plan
rator Closure Cer eby certify that the in losure complies with	appretable crostile requirements and conditions spe	a second a second s	c prosent
rator Closure Cer eby certify that the in losure complies with	appreciate crossive requirements and conditions spe		
rator Closure Cer eby certify that the in losure complies with ne (Print):	- apprendie coosie requirements and conditions spe	Title:	
rator Closure Cer eby certify that the in losure complies with te (Print): ature:	- approache coosine requirements and conditions spe	Title:	
rator Closure Cer eby certify that the in losure complies with the (Print):		Title: Date:	
rator Closure Cer eby certify that the in losure complies with te (Print): ature:		Title: Date: Telephone:	

_			
۰,	1111	(-)	144

New Mexico Office of the State Engineer POD Reports and Downloads
Township: 28N Range: 06W Sections:
NAD27 X: Y: Zone: Search Radius:
County: Basin: Number: Suffix:
Owner Name: (First) (Last) C Non-Domestic C Domestic All
POD / Surface Data Report Avg Depth to Water Report Water Column Report
Clear Form iWATERS Menu Help

WATER COLUMN REPORT 08/20/2008

	(quarters are 1=NW 2=NE 3 (quarters are biggest to				(quarters are 1=NW 2=NE 3=SW 4=SE) (quarters are biggest to smallest)			Depth Depth	Depth Depth	Water (in	(in		
POD Number	Tws	Rng	Sec	q	q	g	Zone	х	Y	Well	Water	Column	
SJ 03700 POD1	28N	06W	12	2	2	4				450	200	250	
SJ 03675	28N	06W	14	4	3	4	С	153167	2059732	420	100	320	
SJ 03700	28N	06W	21	2	4	4				450	200	250	
SJ 03043	28N	06W	21	4	2	2				290	240	50	
SJ 03005	28N	06W	21	4	2	2				245	175	70	
SJ 03443	28N	06W	22	3	3	3				300			
SJ 00200	28N	06W	23	3	3					1551			
SJ 03091	28N	06W	29	2	2	3				150	90	60	

Record Count: 8



AERIAL MAP SAN JUAN 28-6 UNIT 156N



Aerial flown bcally Sedgewick in 2005.

ConocoPhillips

300FT

500	
1:6,000	

NAD_1983_SP_ NM West_FIPS_3003 8/08

Mines, Mills and Quarries Web Map.

SAN JUAN 28-6 UNIT 156N

Unit Letter: C, Section: 29, Town: 028N, Range: 006W





SAN JUAN 28-6 UNIT 156N

Site Specific Hydrogeology

A visual site inspection confirming the information contained herein was performed on the well 'SAN JUAN 28-6 UNIT 156N', which is located at 36.63676 degrees North latitude and 107.49103 degrees West longitude. This location is located on the Four mile Canyon 7.5' USGS topographic quadrangle. This location is in section 29 of Township 28 North Range 6 West of the Public Land Survey System (New Mexico Principal Meridian). This location is located in Rio Arriba County, New Mexico. The nearest town is Turley, located 17.9 miles to the northwest. The nearest large town (population greater than 10,000) is Farmington, located 40.2 miles to the west (National Atlas). The nearest highway is US Highway 64, located 4.2 miles to the north. The location is on BLM land and is 192 feet from the edge of the parcel as notated in the BLM land status layer updated January 2008. This location is in the Blanco Canyon. New Mexico, Subbasin. This location is located 1958 meters or 6422 feet above sea level and receives 12.5 inches of rain each year. The vegetation at this location is classified as Colorado Plateau Pinion-Juniper Woodland as per the Southwest Regional Gap Analysis Program.

The estimated depth to ground water at this point is 158 feet. This estimation is based on the data published on the New Mexico Engineer's iWaters Database website and water depth data from ConocoPhillips' Cathodic wells. Groundwater data available from the NM State Engineer's iWaters Database for wells near the proposed site are attached. The nearest stream is 208 feet to the northeast and is classified by the USGS as an intermittent stream. The nearest perrenial stream is 2,031 feet to the west. The nearest water body is 2,029 feet to the west. It is classified by the USGS as an intermittent lake and is 0.3 acres in size. The nearest spring is 6,716 feet to the northeast. All stream, river, water body and spring information was determined as per the USGS Hydrographic Dataset (High Resolution), downloaded 3/2008. The nearest water well is 1,792 feet to the east. The nearest wetland is a 2.9 acre Freshwater Forested/Shrub Wetland located 7,430 feet to the south. The slope at this location is 5 degrees to the northeast as calculated from USGS 30M National Elevation Dataset. This information is also discerned from the aerial and topographic map included. The surface geology at this location is SAN JOSE FORMATION--Siltstone, shale, and sandstone with a Sandstone dominated formations of all ages substrate. The soil at this location is 'Rock outcrop-Vessilla-Menefee complex, 15 to 45 percent slopes' and is well drained and not hydric with not rated erosion potential as taken from the NRCS SSURGO map unit, downloaded January 2008. The nearest underground mine is 16.1 miles to the northeast as indicated on the Mines, Mills and Quarries Map of New Mexico provided.

Regional Hydrogeological context:

The San Jose Formation of Eocene age occurs in New Mexico and Colorado, and its outcrop forms the land surface over much of the eastern half of the central basin. It overlies the Nacimiento Formation in the area generally south of the Colorado-New Mexico State line and overlies the Animas Formation in the area generally north of the State line. The San Jose Formation was deposited in various fluvial-type environments. In general, the unit consists of an interbedded sequence of sandstone, siltstone, and variegated shale. Thickness of the San Jose Formation generally increases from west to east (200 feet in the west and south to almost 2,700 feet in the center of the structural basin). Ground water is associated with alluvial and fluvial sandstone aquifers. Thus, the occurrence of ground water is mainly controlled by the distribution of sandstone in the formation. The distribution of such sandstone is the result of original depositional extent plus any post-depositional modifications, namely erosion and structural deformation. Transmissivity data for San Jose Formation are minimal. Values of 40 and 120 feet squared per day were determined from two aguifer tests (Stone et al, 1983, table 5). The reported or measured discharge from 46 water wells completed in San Jose Formation ranges from 0.15 to 61 gallons per minute and the median is 5 gallons per minute. Most of the wells provide water for livestock and domestic use. The San Jose Formation is a very suitable unit for recharge from precipitation because soils that form on the unit are sandy and highly permeable and therefore readily adsorb precipitation. However, low annual precipitation, relatively high transpiration and evaporation rates, and deep dissection of the San Jose Formation by the San Juan River and its tributaries all tend to reduce the effective recharge to the unit.

Stone et al., 1983, Hydrogeology and Water Resources of the San Juan Basin, New Mexico: Socorro, New Mexico Bureau of Mines and Mineral Resources Hydrologic Report 6, 70 p.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Design and Construction

In accordance with NMAC 19.15.17 the following information describes the design and construction of below grade tanks on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all below grade tanks (BGT). A separate plan will be submitted for any BGT which does not conform to this plan.

General Plan:

- 1. BR will design and construct a properly sized and approved BGT which will contain liquids and should prevent contamination of fresh water to protect the public health and environment.
- 2. BR signage will comply with 19.15.3.103 NMAC when BR is the operator. If BR is not the operator it will comply with 19.15.17.11NMAC. BR includes Emergency Contact information on all signage.
- 3. BR has approval to use alternative fencing that provides better protection. BR constructs fencing around the BGT using 4 foot hog wire fencing topped with two strands of barbed wire, or with a pipe top rail. A six foot chain link fence topped with three strands of barbed wire will be use if the well location is within 1000 feet of permanent residence, school, hospital, institution or church. BR ensures that all gates associated with the fence are closed and locked when responsible personnel are not onsite.
- 4. BR will construct a screened, expanded metal covering, on the top of the BGT.
- 5. BR shall ensure that a below-grade tank is constructed of materials resistant to the below-grade tank's particular contents and resistant to damage from sunlight as shown on design drawing and specification sheet.
- 6. The BR below-grade tank system shall have a properly constructed foundation consisting of a level base free of rocks, debris, sharp edges or irregularities to prevent punctures, cracks or indentations of the liner or tank bottom as shown on design drawing.
- 7. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a belowgrade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 8. BR will construct and use a below-grade tank that does not have double walls. The below-grade tank's side walls will be open for visual inspection for leaks, the below-grade tank's bottom is elevated a minimum of six inches above the underlying ground surface and the below-grade tank is underlain with a geomembrane liner to divert leaked liquid to a location that can be visually inspected.

- 9. BR has equipped the below-grade tanks with the ability to detect high level in the tank and provide alarm notification and shutdown process streams into the tank. Once high level is detected RTU logic closes the inlet separator sales valve and does not permit vent valve to open. This shutdown of the sales valve and gagging of the vent valves prevents any hydrocarbon process streams from entering the pit tank once a high level is detected. Furthermore, an electronic page is sent to the BR MSO for that well site and to the designated contract "Water-Hauling" Company indicating a high level and that action must be taken to address this alarm. The environmental drain line from BR's compressor skid under normal operating conditions is in the open position. The environmental drain line is in place to capture any collected rain water or spilled lubricants from our compressor skids. The swab drain line is a manually operated drain and by normal operating procedures is in the closed position. The tank drain line is also a manually operated drain and during normal operations it is in the closed position.
- 10. The geomembrane liner consists of a 45-mil flexible LLDPE material manufactured by Raven Industries as J45BB. This product is a four layer reinforced laminated containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. The J45BB is reinforced with 1300 denier (minimum) tri-directional scrim reinforcement. It exceeds ASTMD3083 standard by 10%. J45BB has a warranty for 20 years from Raven Industries and is attached. It is typically used in Brine Pond, Oilfield Pit liner and other industrial applications. The manufacture specific sheet is attached and the design attached displays the proper installation of the liner.
- 11. The general specification for design and construction are attached in the BR document.



DURA-SKRIM®

J30, J36 a J45

ROPERTIES TEST METHOD			J3	J36BB J45			
	Min. Roll Averages	Typical Roll Averages	Міп. Roll Averages	Typical Roll Averages	Min. Roll Averages	Typical Roll	
	Bla	ck/Black	Blac	<td>Blac</td> <td>(Black</td>	Blac	(Black	
ASTM D 5199	27 mil	30 mil	32 mil	36 mil	40 mil	45 mil	
ASTM D 5261	126 lbs (18.14)	140 lbs (20.16)	151 lbs (21.74)	168 lbs (24,19)	189 lbs (27 21)	210 lbs (30.24)	
	**Ext	trusion laminate	d with encapsula	ated tri-direction	al scrim roinfor	(30.24)	
ASTM D 413	16 lbs	20 lbs	19 lbs	24 lbs	25 lbs	31 lbs	
ASTM D 7003	88 lbf MD 63 lbf DD	110 lbf MD 79 lbf DD	90 lbf MD 70 lbf DD	113 lbf MD 87 lbf DD	110 lbf MD 84 lbf DD	138 lbf MD 105 lbf DD	
ASTM D 7003	550 MD 550 DD	750 MD 750 DD	550 MD 550 DD	750 MD 750 DD	550 MD 550 DD	750 MD 750 DD	
ASTM D 7003	20 MD 20 DD	33 MD 33 DD	20 MD 20 DD	30 MD 31DD	20 MD 20 DD	36 MD 36 DD	
ASTM D 5884	75 lbf MD 75 lbf DD	97 lbf MD 90 lbf DD	75 ibf MD 75 ibf DD	104 lbf MD 92 lbf DD	100 lbf MD 100 lbf DD	117 lbf MD 118 lbf DD	
ASTM D 7004	180 lbf MD 180 lbf DD	218 lbf MD 210 lbf DD	180 lbf MD 180 lbf DD	222 lbf MD 223 lbf DD	220 lbf MD 220 lbf DD	257 lbf MD 258 lbf DD	
ASTM D 4533	120 lbf MD 120 lbf DD	146 lbf MD 141 lbf DD	130 lbf MD 130 lbf DD	189 lbf MD 172 lbf DD	160 lbf MD 160 lbf DD	193 lbf MD 191 lbf DD	
ASTM D 1204	<1	<0.5	<1	<0.5	<1	<0.5	
ASTM D 4833	50 lbf	64 lbf	65 lbf	83 lbf	80 lbf	00.bf	
	180° F	180° F	180° F	180° F	180° F	190% 5	
	-70° F	-70° F	-70° F	-70° F	-70° F	-70° F	
	TEST METHOD ASTM D 5199 ASTM D 5261 ASTM D 5261 ASTM D 413 ASTM D 7003 ASTM D 7003 ASTM D 7003 ASTM D 7003 ASTM D 7004 ASTM D 4533 ASTM D 1204 ASTM D 4833	TEST METHOD Min. Roll Averages Min. Roll Averages Bla ASTM D 5199 27 mil ASTM D 5261 126 lbs (18.14) ASTM D 5261 126 lbs (18.14) ASTM D 413 16 lbs ASTM D 7003 88 lbf MD 63 lbf DD ASTM D 7003 550 MD 550 DD ASTM D 7003 20 MD 20 DD ASTM D 7003 20 MD 20 DD ASTM D 5884 75 lbf MD 75 lbf DD ASTM D 5884 75 lbf MD 180 lbf DD ASTM D 4533 120 lbf MD 120 lbf DD ASTM D 1204 <1	TEST METHOD J30BB Min. Roll Averages Typical Roll Averages Black/Black ASTM D 5199 27 mil ASTM D 5199 27 mil ASTM D 5261 126 lbs (18.14) ASTM D 5261 126 lbs (18.14) ASTM D 413 16 lbs ASTM D 7003 88 lbf MD 63 lbf DD ASTM D 7003 550 MD 550 DD ASTM D 7003 550 MD 750 DD ASTM D 7003 550 MD 33 DD ASTM D 7003 20 MD 33 DD ASTM D 7003 20 MD 20 DD ASTM D 7003 20 MD 20 DD ASTM D 7004 180 lbf MD 20 DD ASTM D 5884 75 lbf MD 75 lbf DD ASTM D 5884 75 lbf MD 210 lbf DD ASTM D 4533 120 lbf MD 180 lbf DD ASTM D 4533 120 lbf MD 141 lbf DD ASTM D 1204 <1	TEST METHOD J30BB J3 Min. Roll Averages Typical Roll Averages Min. Roll Averages Min. Roll Averages Black/Black Black/Black Black ASTM D 5199 27 mil 30 mil 32 mil ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) ASTM D 7003 88 lbf MD 63 lbf DD 110 lbf MD 79 lbf DD 90 lbf MD 70 lbf DD ASTM D 7003 550 MD 550 DD 750 MD 750 DD 550 MD 20 DD ASTM D 7003 20 MD 20 DD 33 MD 20 DD 20 MD 20 DD ASTM D 5884 75 lbf MD 75 lbf DD 90 lbf MD 75 lbf DD 180 lbf MD 180 lbf DD ASTM D 7004 180 lbf MD 180 lbf DD 130 lbf MD 130 lbf DD 130 lbf MD 130 lbf DD ASTM D 4533 50 lbf <	TEST METHOD J30BB J36BB J36BB Min. Roll Averages Min. Roll Averages Typical Roll Averages Min. Roll Averages Typical Roll Averages Black/Black Black/Black Black/Black Black/Black ASTM D 5199 27 mil 30 mil 32 mil 36 mil ASTM D 5261 126 lbs (18.14) 140 lbs (20.16) 151 lbs (21.74) 168 lbs (24.19) **Extrusion laminated with encapsulated tri-direction **Extrusion laminated with encapsulated tri-direction ASTM D 413 16 lbs 20 lbs 19 lbs 24 lbs ASTM D 7003 88 lbf MD 63 lbf DD 110 lbf MD 79 lbf DD 90 lbf MD 70 lbf DD 113 lbf MD 87 lbf DD ASTM D 7003 20 MD 63 lbf DD 750 MD 750 DD 550 MD 750 DD 750 MD 750 DD 30 MD 31DD ASTM D 7003 20 MD 20 DD 33 MD 20 DD 20 MD 31DD 20 MD 20 DD 31 MD 20 DD 22 lbf MD 210 lbf DD 104 lbf MD 223 lbf DD ASTM D 5884 75 lbf MD 75 lbf DD 97 lbf MD 210 lbf DD 130 lbf MD 180 lbf DD 222 lbf MD 223 lbf DD ASTM D 4533 120 lbf MD 120 lbf DD	TEST METHOD J30BB J36BB J36BB	

MD = Machine Direction DD = Diagonal Directions

Note: Minimum Roll Averages are set to take into account product variability in addition to testing variability between laboratories.

*Dimensional Stability Maximum Value

**DURA-SKRIM J30BB, J36BB & J45BB are a four layer reinforced laminate containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. DURA-SKRIM J30BB, J36BB & J45BB are reinforced with a 1300 denier (minimum) tri-directional scrim reinforcement.

Note: RAVEN INDUSTRIES MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and asclaims all liability for resulting loss or damage.



PLANT LOCATION

Sioux Falls, South Dakota

SALES OFFICE

P.O. Box 5107 Sioux Falls, SD 57117-5107 (605) 335-0174 (605) 331-0333 FAX **800-635-3456**



08/06

RAVEN INDUSTRIES INC. EXPOSED GEOMEMBRANE LIMITED WARRANTY

Raven Industries Inc. warrants Dura-Skrim J30BB, J36BB, and J45BB to be free from manufacturing defects and to be able to withstand normal exposure to sunlight for a period of 20 years from the date of sale for normal use in approved applications in the U.S and Canada, excluding Hawaii. This warranty is effective for products sold and shipped from January 1, 2008 to December 31, 2008.

This Limited Warranty does not include damages or defects in the Raven geomembrane resulting from acts of God, casualty or catastrophe including but not limited to: earthquakes, floods, piercing hail, or tornadoes. The term "normal use" as used herein does not include, among other things improper handling during transportation, unloading, storage or installation, the exposure of Raven geomembranes to harmful chemicals, atypical atmospheric conditions, abuse of Raven geomembranes by machinery, equipment or people; improper site preparation or covering materials, excessive pressures or stresses from any source or improper application or installation. Raven geomembrane material warranty is intended for commercial use only and is not in effect for the consumer as defined in the Magnuson Moss Warranty or any similar federal, state, or local statues. The parties expressly agree that the sale hereunder is for commercial or industrial use only.

Should defects or premature loss of use within the scope of the above Limited Warranty occur, Raven Industries Inc. will, at its option, repair or replace the Raven geomembrane on a pro-rata basis at the then current price in such manner as to charge the Purchaser/User only for that portion of the warranted life which has elapsed since purchase of the material. Raven Industries Inc. will have the right to inspect and determine the cause of any alleged defect in the Raven geomembrane and to take appropriate steps to repair or replace the Raven geomembrane if a defect exists which is covered under this warranty. This Limited Warranty extends only to Raven's geomembrane, and does not extend to the installation service of third parties nor does it extend to materials furnished or installed by others in connection with the intended use of the Raven geomembranes.

Any claim for any alleged breach of this warranty must be made in writing, by certified mail, to the General Manager of Engineered Films Division of Raven Industries Inc. within ten (10) days of becoming aware of the alleged defect. Should the required notice not be given, the defect and all warranties are waived by the Purchaser, and Purchaser shall not have any rights under this warranty. Raven Industries Inc. shall not be obligated to perform repairs or replacements under this warranty unless and until the area to be repaired or replaced is clean, dry, and unencumbered. This includes, but is not limited to, the area made available for repair and/or replacement of Raven geomembrane to be free from all water, dirt, sludge, residuals and liquids of any kind. If after inspection it is determined that there is no claim under this Limited Warranty, Purchaser shall reimburse Raven Industries Inc. for its costs associated with the site inspection.

In the event the exclusive remedy provided herein fails in its essential purpose, and in that event only, the Purchaser shall be entitled to a return of the purchase price for so much of the material as Raven Industries Inc. determines to have violated the warranty provided herein. Raven Industries Inc. shall not be liable for direct, indirect, special, consequential or incidental damages resulting from a breach of this warranty including, but not limited to, damages for loss of production, lost profits, personal injury or property damage. Raven Industries Inc. shall not be obligated to reimburse Purchaser for any repairs, replacement, modifications or alterations made by Purchaser unless Raven Industries Inc. specifically authorized, in writing, said repairs, replacements, modifications or alteration in advance of them having been made. Raven Industry's liability under this warranty shall in no event exceed the replacement cost of the material sold to the Purchaser for the particular installation in which it failed.

Raven Industries Inc. neither assumes nor authorizes any person other than the undersigned of Raven Industries Inc. to assume for it any other or additional liability in connection with the Raven geomembrane made on the basis of the Limited Warranty. The Limited Warranty on the Raven geomembrane herein is given in lieu of all other possible material warranties, either expressed or implied, and by accepting delivery of the material; Purchaser waives all other possible warranties, except those specifically given. This Limited Warranty may only be modified by written document mutually executed by Owner and Raven Industries Inc.

Limited Warranty is extended to the purchaser/owner and is non-transferable and non-assignable; i.e., there are no third-party beneficiaries to this warranty.

Purchaser acknowledges by acceptance that the Limited Warranty given herein is accepted in preference to any and other possible materials warranties.

THIS LIMITED WARRANTY SHALL BE GOVERNED BY SOUTH DAKOTA LAW AND VENUE FOR ALL LEGAL PROCEEDINGS IN CONNECTION WITH THIS LIMITED WARRANTY SHALL BE IN MINNEHAHA COUNTY, SOUTH DAKOTA. RAVEN INDUSTRIES INC. MAKES NO WARRANTY OF ANY KIND OTHER THAN THAT GIVEN ABOVE AND HEREBY DISCLAIMS ALL WARRANTIES, BOTH EXPRESSED OR IMPLIED, OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THIS IS THE ONLY WARRANTY THAT APPLIES TO THE MATERIALS REFERRED TO HEREIN AND RAVEN INDUSTRIES INC. DISCLAIMS ANY LIABILITY FOR ANY WARRANTIES GIVEN BY ANY OTHER PERSON OR ENTITY, EITHER WRITTEN OR ORAL.

RAVEN INDUSTRIES' WARRANTY BECOMES AN OBLIGATION OF RAVEN INDUSTRIES INC. TO PERFORM UNDER THE WARRANTY ONLY UPON RECEIPT OF FINAL PAYMENT AND EXECUTION BY A DULY AUTHORIZED OFFICER OF RAVEN INDUSTRIES INC.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Maintenance and Operating Plan

In accordance with Rule 19.15.17 the following information describes the operation and maintenance of Below Grade Tank (BGT) on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all BGT. A separate plan will be submitted for any BGT which does not conform to this plan.

General Plan:

- BR will operate and maintain a BGT to contain liquids and solids and maintain the integrity of the liner, liner system and secondary containment system to prevent contamination of fresh water and protect public health and environment. BR will accomplish this by performing an inspection on a monthly basis, installing cathodic protection, and automatic overflow shutoff devices as seen on the design plan.
- 2. BR will not discharge into or store any hazardous waste in the BGT.
- 3. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a below-grade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 4. As per 19.17.15.12 Subsection D, Paragraph 3, BR will inspect the below-grade tank at least monthly reviewing several items which include 1) containment berms adequate and no oil present, 2) tanks had no visible leaks or sign of corrosion, 3) tank valves, flanges, and hatches had no visible leaks and 4) no evidence of significant spillage of produced liquids. In addition, BR's multi-skilled operators (MSOs) are required to visit each well location once per week. If detected on either inspection, BR shall remove any visible or measurable layer of oil from the fluid surface of a below-grade tank in an effort to prevent significant accumulation of oil overtime. The written record of the monthly inspections will include the items listed above and will be maintained for five years.
- 5. BR shall require and maintain a 10" adequate freeboard to prevent overtopping of the below-grade tank.
- 6. If the below grade tank develops a leak, or if any penetration of the pit liner or below grade tank, occurs below the liquid's surface, then BR shall remove all liquid above the damage or leak line within 48 hours. BR shall notify the appropriate district office. BR shall repair or replace the pit liner or below grade tank, within 48 hours of discovery. If the below grade tank or pit liner does not demonstrate integrity, BR shall promptly remove and install a below grade tank or pit liner that complies with Subsection I of 19.15.17.11 NMAC. BR shall notify the appropriate district office of a discovery of leaks less than 25 barrels as required pursuant to Subsection B of 19.15.3.116 NMAC shall be reported within twenty-four (24) hours of discovery of leaks greater than 25 barrels. In addition, immediate verbal notification pursuant to Subsection B, Paragraph (1), and Subparagraph (d) of 19.15.3.116 NMAC shall be reported to the division's Environmental Bureau Chief.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Closure Plan

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of Below Grade Tanks (BGTs) on Burlington Resources Oil & Gas Company, LP locations hereinafter known as BR locations. This is BR's standard procedure for all BGTs. A separate plan will be submitted for any BGT which does not conform to this plan.

General Requirements:

- BR shall close a below-grade tank within the time periods provided in Subsection A of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) permitted below-grade tanks within 60 days of cessation of the below-grade tank's operation., or c) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.
- 2. BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.
- 3. BR will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves. Documentation of how the below-grade tank was disposed of or recycled will be provided in the closure report.
- 4. If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless the equipment is required for some other purpose.
- 5. BR shall test the soils beneath the below-grade tank to determine whether a release has occurred. BR shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyze for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 50 mg/kg; or other EPA method 300.1 or other EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration, whichever is greater. BR shall notify the division of its results on form C-141.
- 6. If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

- 7. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site.
- Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.
- 9. The surface owner shall be notified of BR's closing of the below-grade tank prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 11. BR shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federally jurisdicted lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. BR will repeat seeding or planting will be continued until successful vegetative growth occurs.
- 12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.
- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation
 - Re-vegetation application rates and seeding techniques
 - Photo documentation of the site reclamation
 - Confirmation Sampling Results
 - Proof of closure notice