| 1625 N Forder De Habbe Nik 00040 Distr 1301 | RED Francis Dr. | Form C-144 July 21, 2008 For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office. |
|--|--|---|
| 1000 kio brazos ku., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505 | Santa Fe, NM 87505 | For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office. |
| Pi | t, Closed-Loop System, Below-Grad | le Tank. or |
| Proposed | Alternative Method Permit or Closu | re Plan Application |
| Type of action: | Permit of a pit, closed-loop system, below-grade | tank, or proposed alternative method |
| | Closure of a pit, closed-loop system, below-grade | e tank, or proposed alternative method |
| | Modification to an existing permit | |
| | Closure plan only submitted for an existing perm below-grade tank, or proposed alternative method | itted or non-permitted pit, closed-loop system, |
| Instructions: Please submit one appli | cation (Form C-144) per individual pit, closed-la | oop system, below-grade tank or alternative request |
| Please be advised that approval of this environment. Nor does approval relieve the | request does not relieve the operator of liability should operations he operator of its responsibility to comply with any other applicable | result in pollution of surface water, ground water or the e governmental authority's rules, regulations or ordinances. |
| 1 Operator: Burlington Resources Oil & | Gas Company, LP | OGRID#: 14538 |
| Address: PO Box 4289, Farmington, N | NM 87499 | |
| Facility or well name: SAN JUAN 27-5 | UNIT NP 55 | |
| API Number: 3003 | 907205 OCD Permit Numb | er: |
| U/L or Qtr/Qtr: <u>A</u> Section: | 1 Township: 27N Range: | 5W County: Rio Arriba |
| Center of Proposed Design: Latitude: | <u>36.60618°N</u> Longitude: | -107.30311°W NAD: X 1927 1983 |
| Surface Owner: X Federal | State Private Tribal Trust or India | |
| Prt: Subsection F or G or 19.15.17.11 Temporary: Drilling Workove Permanent Emergency Cavitz Lined Unlined Liner t String-Reinforced Liner Seams: Welded | NMAC rr ation P&A ype: Thickness mil LLDPE y Other Volume: | HDPE PVC Other |
| 3 Closed-loop System: Subsection H Type of Operation: P&A Dr Orying Pad Above Ground.S Lined Unlined Liner typ Liner Seams: Welded Factor | H of 19.15.17.11 NMAC illing a new well Workover or Drilling (Applies to notice of intent) teel Tanks Haul-off Bins Other e: Thickness mil LLDPE y Other | o activities which require prior approval of a permit or HDPE PVD Other |
| 4 X Below-grade tank: Subsection I of I Volume: 120 bbl Tank Construction material: | 19.15.17.11 NMAC Type of fluid: Produced Water Metal ion X Visible sidewalls, liner, 6-inch lift and au Visible sidewalls only Other mil HDPE PVC X Other | tomatic overflow shut-off |
| 5 Alternative Method: | | |
| Calculated a Company to the second to an average to an average | d Exagnitions must be submitted to the Santa Fe Envir | |
| Submittal of an exception request is require | a. Exceptions must be submitted to the sama re Envir | onmental Bureau office for consideration of approval. |

| 6 Fencine: Subsection D of 10.15.17.11 NRA VELAND | |
|--|----------------------------|
| Consection 1244 (2014) 12:13:17:11 NMAC. (Applies to permanent pit, temporary pits, and below-grade tanks) | |
| Chain link, six feet in height, two strands of barbed wire at top (Reunired if located within 1000 for a strands) | |
| Four foot height, four strands of barbed wire evenly spaced between one and four feet | d, institution of church) |
| X Alternate. Please specify 4' hog wire fencing topped with two strands bashed wire | |
| | |
| Netting: Subsection F of 19.15.17.11 NMAC (Analysis | |
| X Screen Netting Other | |
| Monthly inspections (If netting at screening is not school at the first school at the | |
| contraction of the second | |
| 8 Signs: Subsection C of 19.15.17.11 NMAC | |
| 12" X 24". 2" lettering, providing Operator's name, site formition, and an an and an and an and an an and an | |
| X Signed in compliance with 19.15.3.103 NMAC | |
| 9 | |
| Administrative Approvals and Exceptions: | |
| Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance | |
| Please check a box if one or more of the following is requested, if not leave blank: | |
| X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for | |
| | consideration of approval. |
| [Exception(s)] Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. | |
| | |
| Siting Criteria (regarding permitting): 19.15.17.10 NMAC | |
| source material are provided below. Requests regarding changes to certain siting criteria below in the application. Recommendations of acceptable | |
| appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Buegay Office for | |
| does not apply to drying pads or above grade-tanks accounted with a start list of the start of t | |
| associated with a closed-loop system. | |
| Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search: USGS; Data obtained from nearby wells | Yes XNo |
| Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa | |
| - Topographic map: Visual interaction (activity of the second sec | Tes X No |
| The second site | |
| within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. | Yes XNo |
| (Applies to temporary, emergency, or cavitation pits and below-grade tanks) | |
| - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image | |
| Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. | |
| (Applied to permanent pits) | |
| - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image | |
| Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. | Yes XNo |
| - NM Office of the State Engineer - iWATERS database search: Visual inspection (certification) of the second to | |
| Within incorporated municipal boundaries or within a defined municipal fresh water well field governed under a much in the | |
| adopted pursuant to NMSA 1978, Section 3-27-3, as amended | Yes X No |
| - written continuation or ventication from the municipality: Written approval obtained from the municipality Within 500 feet of a wetland | |
| - US Fish and Wildlife Wetland Identification man: Tonographic map: Viewel increase in the state | Yes X No |
| Within the area overlying a subsurface mine. | |
| Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division | Yes XNo |
| Within an unstable area. | |
| - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map | |
| Within a 100-year floodplain | |
| - FEMA map | Tes X No |
| | 1 |

| • | |
|---|--|
| | |

| Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklict, School and Below-grade Tanks Permit Application Attachment Applicat |
|--|
| Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. |
| A Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC |
| Siting Criteria Compliance D |
| V Design Plan based upon the appropriate requirements of 19.15.17.10 NMAC |
| X Operating and Maintenance Plan, have been defined as the set of |
| X Closure Plan (Please complete Porce) 14 there is the interview of 19,15,17,12 NMAC |
| 19.15.17.9 MAC and 19.15.17.13 NMAC |
| Dreviously Approved Design (attach copy of design) API or Permit |
| Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Closed-loop Attached the following itom mus be attached to the application. Please indicate, by a check mark in the box, that the downnens are attached. Geologie and Hydrogeologic Data (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Plase complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 MMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Previously Approved Operating and Maintenance Plan API Tarmanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the appropriate requirements of 19.15.17.1 NMAC Other following items must be attached to the appropriate requirements of 19.15.17.1 NMAC Climatological Factors Assessment Climatological Factors Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection Design Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection Design Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection Design Plans - based upon the appropriate requirements of 19 |
| Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit X Below-grade Tank Closed-loop System |
| Proposed Closure Method: X Waste Excavation and Removal (Below-Grade Tank) Waste Removal (Closed-loop systems only) |
| Un-site Closure Method (only for temporary pits and closed-loop systems) |
| Alternative Closure Method (Examplified and the second sec |
| La consideration (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration) |
| Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. |
| X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC |
| X Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC |
| Disposal Pacifity Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - base to be a set of the set |
| Revenue of Subsection H of 19.15.17.13 NMAC |
| |
| X Site Reclamation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC |

| Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NM Instructions: Please identify the facility or facilities for the disposal of liquids, drilling thids and drill cuttings. Use attachment if more that are required. | AAC) n two facilities |
|---|--|
| Disposal Facility Name: Disposal Facility Permit #- | |
| Disposal Facility Name: Disposal Facility Permit #: | |
| Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for fu | nure service and operations? |
| Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC | NMAC |
| 17 <u>Siting Criteria (Regarding on-site closure methods only:</u> 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provid certain sting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submittea for consideration of approval. Justifications and/or denomstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. | éd below: Requests regarding changes to (to the Santa Fe Environmental Bureau office |
| Ground water is less than 50 feet below the bottom of the buried waste. | |
| - NM Office of the State Engineer - iWATERS database search: USGS: Data obtained from nearby wells | |
| Ground water is between 50 and 100 feet below the bottom of the buried waste | |
| - NM Office of the State Engineer - iWATERS database search: USGS; Data obtained from nearby wells | |
| Ground water is more than 100 feet below the bottom of the buried waste. | |
| - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells | |
| Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). | Yes No |
| - Topographic map: Visual inspection (certification) of the proposed site | |
| Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. • Visual inspection (certification) of the proposed site; Aerial photo; satellite image | Yes No |
| Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application: - NM Office of the State Engineer - iWATERS database: Visual inspection (certification) of the proposed site | Yes No |
| within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality. | Yes No |
| Within 500 feet of a wetland | Yes No |
| Within the area overlying a subsurface mine | |
| - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division | Yes No |
| Vithin an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Tunoggaphic acts | Yes No |
| Vithin a 100-year floodplain. - FEMA map | Yes No |
| 8 <u>On-Site Closure Plan Checklist:</u> (19.15.17.13 NMAC) Instructions: Each of the following items must bee attached to the close y a check mark in the box, that the documents are attached | sure plan. Please indicate, |
| Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC | |
| Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC | |
| Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC | |
| Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of | 19 15 17 11 NMAC |
| Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC | |
| Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAG | 2 |
| | |
| Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC | |
| Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards of Soil Course Design - based and the standards of the soil Course Design - based and the standards of the soil Course Design - based and the soil Course - based and t | annot be achieved) |

 Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC

 Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

٠.

.

| Name (Print): | Crystal Tafoya | Title: | Regulatory Technician |
|---|---|--|---|
| Signature: | Costa Talana | Data | Regulatory Technician |
| e-mail address: | Instal taleyard concoptilities com | Telephope | 505.334.0827 |
| | | receptione. | 305-326-9837 |
| 0 CD Approval: | Durmit Application (including to a f | | |
| XD Representation | (remit Application (including closure plan) | Closure Plan (only) | OCD Conditions (see attachment) |
| CO Representative | Signature: | | Approval Date: |
| l'itle: | | OCD Permit | Number: |
| 21 | | | |
| Insure Report (requ Instructions: Operators a | ired within 60 days of closure completion): s re required to obtain an approved closure plan price | Subsection K of 19.15.17.13 NMAC | |
| eport is required to be s | ibmitted to the division within 60 days of the compl | etion of the closure activities. I | activities and submitting the closure report. The closure Please do not complete this section of the form until an |
| pproved closure plan ha | s been obtained and the closure activities have been | n completed. | , |
| | | Closure Co | ompletion Date: |
| 2 Yosure Method: | | | |
| Waste Excavation | and Removal On-site Closure Method | | |
| If different from a | Droved plan, please explain | Alternative Closure Met | thod Waste Removal (Closed-loop systems only) |
| 2 | the second | | |
| o losure Report Regardi | ng Waste Removal Closure For Closed-loop Syste | ms That Iftilize Above Crown | d Caral Tables II - L MIDL - C - |
| structions: Please iden | ify the facility or facilities for where the liquids, d | rilling fluids and drill cuttings | a Steel Tanks or Haul-off Bins Only: were disposed. Use attachment if more than two facilities |
| Disputed. | | | appoint out anachment if more man two juctimes |
| Disposal Facility Name | H | Disposal Facility Perr | mit Number: |
| Wara the aloved loop a | | Disposal Facility Perr | mit Number: |
| Yes (If ves please | demonstrate compliane to the items haloin) | d on or in areas that will not be | used for future service and opeartions? |
| Barrier (fresh picase | demonstrate compriane to the items below) | []No | |
| Site Reclamation (| areas which will not be used for future service and a Photo Documentation) | operations: | |
| Soil Backfilling an | d Cover Installation | | |
| Re-vegetation App | lication Rates and Seeding Technique | | |
| | | | |
| Closure Report Atta | chment Checklist: Instructions: Each of the fa | Nowing items must be attached | |
| the box, that the docum | tents are attached. | wowing uems musi de allachea | to the closure report. Please indicate, by a check mark in |
| Proof of Closure | Notice (surface owner and division) | | |
| Proof of Deed No | tice (required for on-site closure) | | |
| Plot Plan (for on- | site closures and temporary pits) | | |
| Confirmation Sar | npling Analytical Results (if applicable) | | |
| Waste Material S | ampling Analytical Results (if applicable) | | |
| Disposal Facility | Name and Permit Number | | |
| Soil Backfilling a | nd Cover Installation | | |
| Re-vegetation Ap | plication Rates and Seeding Technique | | |
| Site Dealerster | (Photo Documentation) | | |
| She Reclamation | ocation: Latitude: | Longitude: | |
| On-site Closure L | | | NAD 1927 1983 |
| On-site Closure L | | | |
| On-site Closure L | | | |
| On-site Closure L | lication: | | |
| On-site Closure L | fication: mation and attachments submitted with this closur | e report is ture, accurate and co | mplete to the best of my knowledge and ballef. Labor constitution |
| erator Closure Certi reby certify that the info closure complies with an | fication: rmation and attachments submitted with this closure l applicable closure requirements and conditions sp | e report is ture, accurate and co ecified in the approved closure | omplete to the best of my knowledge and belief. I also certify that plan. |
| erator Closure Certi reby certify that the infa closure complies with at ne (Print): | fication: mation and attachments submitted with this closur l applicable closure requirements and conditions sp | e report is ture, accurate and co becified in the approved closure Title: | mplete to the best of my knowledge and belief. I also certify that plan. |
| Site Reclamation On-site Closure L erator Closure Certi reby certify that the info closure complies with at me (Print): nature: | fication: rmation and attachments submitted with this closure l applicable closure requirements and conditions sp | e report is ture, accurate and co recified in the approved closure Title: | omplete to the best of my knowledge and belief. I also certify that plan. |
| erator Closure Certi reby certify that the info closure complies with an me (Print): | fication: rmation and attachments submitted with this closur I applicable closure requirements and conditions sp | e report is ture, accurate and co becified in the approved closure Title: Date: | omplete to the best of my knowledge and belief. I also certify that plan. |

* * ·

New Mexico Office of the State Engineer

| New Mexico Office of the State Engineer POD Reports and Downloads |
|---|
| Township: 27N Range: 05W Sections: |
| NAD27 X: Y: Zone: Search Radius: |
| County: Basin: Number: Suffix: |
| Owner Name: (First) (Last) CNon-Domestic CDomestic All |
| POD / Surface Data Report Avg Depth to Water Report Water Column Report |
| Clear Form WATERS Menu Help |
| WATER COLUMN REPORT 08/20/2008 |

(quarters are 1=NW 2=NE 3=SW 4=SE) (quarters are biggest to smallest) Depth Depth Water (in POD Number Tws Rng Sec q q q Zone х Y Well Water Column RG 81026 27N 05W 27 4 4 3 460 186 274 SJ 00199 27N 05W 03 2 1 1840 SJ 00046 27N 05W 04 4 4 506 260 246

Record Count: 3

| New | Mexico Office of the State POD Reports and Down | te Engineer Noads |
|---------------------------|--|-------------------------------|
| Township: 27N Ran | ge: 04W Sections: | |
| NAD27 X: | Zone: | Search Radius: |
| County: Basin: | | Number: Suffix: |
| Owner Name: (First) | (Last) | C Non-Domestic C Domestic C A |
| POD / Surface Data Report | Avg Depth to Water | Report Water Column Report |

WATER COLUMN REPORT 08/20/2008

| | (quarter: (quarter: | s are s are | e 1=1 e big | nw 994 | 2= est | =NE to | 3=SW 4=SE) smallest) | | | Depth | Depth | Water | (in |
|------------|------------------------|----------------|----------------|-----------|-----------|-----------|-------------------------|---|---|-------|-------|--------|-----|
| POD Number | Tws | Rng | Sec | đ | Ð | đ | Zone | х | Y | Well | Water | Column | |
| SJ 00048 | 27N | 04W | 01 | | | | | | | 143 | | | |
| SJ 01049 | 27N | 04W | 18 | 4 | 2 | 2 | | | | 15 | | 0204 | |
| SJ 01205 | 27N | 04W | 34 | 4 | 4 | 4 | | | | 3054 | 750 | 2304 | |

Record Count: 3

New Mexico Office of the State Engineer POD Reports and Downloads

| TOD Reports and Dominouus |
|---|
| Township: 28N Range: 04W Sections: |
| NAD27 X: Y: Zone: Search Radius: |
| County: Basin: Number: Suffix: |
| Owner Name: (First) (Last) ONOn-Domestic ODomestic All |
| POD / Surface Data Report Avg Depth to Water Report Water Column Report |
| Clear Form iWATERS Menu Help |
| |

WATER COLUMN REPORT 08/20/2008

| | (quarter: (quarter: | s are s are | e 1=: e bi | NW gge | 2= est | =NE to | 3=SW 4=SE) smallest) | | | Depth | Depth | Water | (in |
|------------|------------------------|----------------|---------------|-----------|-----------|-----------|-------------------------|---|---|-------|-------|--------|-----|
| POD Number | Tws | Rng | Sec | g | g | g | Zone | x | Y | Well | Water | Column | |
| SJ 00045 | 28N | 04W | 07 | | | | | | | 600 | | | |
| SJ 02385 | 28N | 04W | 26 | 1 | 1 | 1 | | | | 160 | 85 | 75 | |

Record Count: 2

| IUSCIOLI | Page | 1 | of | 1 |
|----------|------|---|----|---|
|----------|------|---|----|---|

| | | Λ | lew N | <i>Mexica</i> POD I | o <i>Off</i> Repo | <i>ice of th</i> rts and | he State Down | e Engi Ioads | neer | | | | |
|------------------|-----------|--------|---|------------------------|----------------------|-----------------------------|------------------|-----------------|-------|------------|-----------|---------|-----|
| Tow | nship: 28 | N F | Range | e: 05V | V | Section | ns: | | | | | | |
| NAD27 | X: | | Y: | | | Zone | : | | Sear | ch Radiu | s: | | |
| County: | | Basin: | | | | | | Num | ber: | | Suffix: | | _ |
| Owner Name: (Fin | rst) | | | - (La | st) | | | - C | Non-I | Domestic | C Dom | estic • | All |
| POD / Surfac | ce Data R | eport | 2000) 1990 - 1990 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1990 - 1 | | Avg | Depth to | Water | Report | | Wat | er Column | Report | |
| | | | Clear | Form | | įWATE | RS Mei | nu | Help | | | | |
| | | | | WAT | rer | COLUMN | REPOR | T 08/ | 20/20 | 008 | | | |
| (| quarter | s are | 1=1 | W 2=1 | NE 3 | =SW 4= | SE) | | | | | | |
| (| quarter | s are | big | gest | to | smalle | st) | | | Depth | Depth | Water | (in |
| POD Number | TWB | Rng | Sec | a a a | a | Zone | X | | ¥ | 200 | Water | Column | |
| SJ 01893 | 28N | 05W | 7.0 | 4 | | | | | | 390 465 | 290 | 200 | |
| SJ 00036 | 28N | 05W | 28 | 3 | | | | | | 303 | 243 | 60 | |
| Record Count: 3 | | | 1.0 | _ | | | | | | | | | |







Aerial flown bcally Sedgewick in 2005.

ConocoPhillips

1:6,000

NAD_1983_SP_ NM West_FIPS_3003 8/08

Mines, Mills and Quarries Web Map

SAN JUAN 27-5 UNIT NP 55

Unit Letter: A, Section: 01, Town: 027N, Range: 005W







A



SAN JUAN 27-5 UNIT NP 55

Site Specific Hydrogeology

A visual site inspection confirming the information contained herein was performed on the well 'SAN JUAN 27-5 UNIT NP 55', which is located at 36.60618 degree, North latitude and 107.30311 degree, West longitude. This location is located on the Vigas Canyon 7.5' USGS topographic quadrangle. This location is in section 1 of Township 27 North Range 5 West of the Public Land Survey System (New Mexico Principal Meridian). This location is located in Rio Arriba County, New Mexico. The nearest town is Dulce, located 28.3 miles to the northeast. The nearest large town (population greater than 10,000) is Farmington, located 50.9 miles to the west (National Atlas). The nearest highway is US Highway 64, located 7.1 miles to the north. The location is on BLM land and is 824 feet from the edge of the parcel as notated in the BLM land status layer updated January 2008. This location is in the Blanco Canyon. New Mexico, Sub-basin. This location is located 2231 meters or 7317 feet above sea level and receives 14 inches of rain each year. The vegetation at this location is classified as Colorado Plateau Pinon-Juniper Woodland as per the Southwest Regional Gap Analysis Program.

The estimated depth to ground water at this point is 624 feet. This estimation is based on the data published on the New Mexico Engineer's iWaters Database website and water depth data from ConocoPhillips' Cathodic wells. Groundwater data available from the NM State Engineer's iWaters Database for wells near the proposed site are attached. The nearest stream is 569 feet to the east and is classified by the USGS as an intermittent stream. The nearest perennial stream is 3,603 feet to the southeast. The nearest water body is 3,560 feet to the southeast. It is classified by the USGS as an intermittent lake and is 0.3 acres in size. The nearest spring is 646 feet to the east. All stream, river, water body and spring information was determined as per the USGS Hydrographic Dataset (High Resolution), downloaded 3/2008. The nearest water well is 5,606 feet to the east. The nearest wetland is a 0.6 acre other located 9,831 feet to the south. The slope at this location is 12 degree, to the southeast as calculated from USGS 30M National Elevation Dataset. This information is also discerned from the aerial and topographic map included. The surface geology at this location is SAN JOSE FORMATION -- Siltstone, shale, and sandstone with a Sandstone dominated formations of all ages substrate. The soil at this location is 'Vessilla-Menefee-Orlie complex, 1 to 30 percent slopes' and is well drained and not hydric with severe erosion potential as taken from the NRCS SSURGO map unit, downloaded January 2008. The nearest underground mine is 15.8 miles to the north as indicated on the Mines, Mills and Quarries Map of New Mexico provided.

Regional Hydrogeological context:

The San Jose Formation of Eocene age occurs in New Mexico and Colorado, and its outcrop forms the land surface over much of the eastern half of the central basin. It overlies the Nacimiento Formation in the area generally south of the Colorado-New Mexico State line and overlies the Animas Formation in the area generally north of the State line. The San Jose Formation was deposited in various fluvial-type environments. In general, the unit consists of an interbedded sequence of sandstone, siltstone, and variegated shale. Thickness of the San Jose Formation generally increases from west to east (200 feet in the west and south to almost 2,700 feet in the center of the structural basin). Ground water is associated with alluvial and fluvial sandstone aquifers. Thus, the occurrence of ground water is mainly controlled by the distribution of sandstone in the formation. The distribution of such sandstone is the result of original depositional extent plus any post-depositional modifications, namely erosion and structural deformation. Transmissivity data for San Jose Formation are minimal. Values of 40 and 120 feet squared per day were determined from two aquifer tests (Stone et al, 1983, table 5). The reported or measured discharge from 46 water wells completed in San Jose Formation ranges from 0.15 to 61 gallons per minute and the median is 5 gallons per minute. Most of the wells provide water for livestock and domestic use. The San Jose Formation is a very suitable unit for recharge from precipitation because soils that form on the unit are sandy and highly permeable and therefore readily adsorb precipitation. However, low annual precipitation, relatively high transpiration and evaporation rates, and deep dissection of the San Jose Formation by the San Juan River and its tributaries all tend to reduce the effective recharge to the unit.

Stone et al., 1983, Hydrogeology and Water Resources of the San Juan Basin, New Mexico: Socorro, New Mexico Bureau of Mines and Mineral Resources Hydrologic Report 6, 70 p.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Design and Construction

In accordance with NMAC 19.15.17 the following information describes the design and construction of below grade tanks on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all below grade tanks (BGT). A separate plan will be submitted for any BGT which does not conform to this plan.

General Plan:

ς.

- 1. BR will design and construct a properly sized and approved BGT which will contain liquids and should prevent contamination of fresh water to protect the public health and environment.
- 2. BR signage will comply with 19.15.3.103 NMAC when BR is the operator. If BR is not the operator it will comply with 19.15.17.11NMAC. BR includes Emergency Contact information on all signage.
- 3. BR has approval to use alternative fencing that provides better protection. BR constructs fencing around the BGT using 4 foot hog wire fencing topped with two strands of barbed wire, or with a pipe top rail. A six foot chain link fence topped with three strands of barbed wire will be use if the well location is within 1000 feet of permanent residence, school, hospital, institution or church. BR ensures that all gates associated with the fence are closed and locked when responsible personnel are not onsite.
- 4. BR will construct a screened, expanded metal covering, on the top of the BGT.
- 5. BR shall ensure that a below-grade tank is constructed of materials resistant to the below-grade tank's particular contents and resistant to damage from sunlight as shown on design drawing and specification sheet.
- 6. The BR below-grade tank system shall have a properly constructed foundation consisting of a level base free of rocks, debris, sharp edges or irregularities to prevent punctures, cracks or indentations of the liner or tank bottom as shown on design drawing.
- 7. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a belowgrade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 8. BR will construct and use a below-grade tank that does not have double walls. The below-grade tank's side walls will be open for visual inspection for leaks, the below-grade tank's bottom is elevated a minimum of six inches above the underlying ground surface and the below-grade tank is underlain with a geomembrane liner to divert leaked liquid to a location that can be visually inspected.

9. BR has equipped the below-grade tanks with the ability to detect high level in the tank and provide alarm notification and shutdown process streams into the tank. Once high level is detected RTU logic closes the inlet separator sales valve and does not permit vent valve to open. This shutdown of the sales valve and gagging of the vent valves prevents any hydrocarbon process streams from entering the pit tank once a high level is detected. Furthermore, an electronic page is sent to the BR MSO for that well site and to the designated contract "Water-Hauling" Company indicating a high level and that action must be taken to address this alarm. The environmental drain line from BR's compressor skid under normal operating conditions is in the open position. The environmental drain line is in place to capture any collected rain water or spilled lubricants from our compressor skids. The swab drain line is a manually operated drain and by normal operating procedures is in the closed position. The tank drain line is also a manually operated drain and during normal operations it is in the closed position.

......

- 10. The geomembrane liner consists of a 45-mil flexible LLDPE material manufactured by Raven Industries as J45BB. This product is a four layer reinforced laminated containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. The J45BB is reinforced with 1300 denier (minimum) tri-directional scrim reinforcement. It exceeds ASTMD3083 standard by 10%. J45BB has a warranty for 20 years from Raven Industries and is attached. It is typically used in Brine Pond, Oilfield Pit liner and other industrial applications. The manufacture specific sheet is attached and the design attached displays the proper installation of the liner.
- 11. The general specification for design and construction are attached in the BR document.



PROPERTIES TEST METHOD J30BB **J368E J45BE** Min. Roll Typical Roll Min. Roll Typical Roll Min. Roll Typical Roll Averages Averages Averages Averages Averages Averages Appearance Black/Black Black/Black Black/Black Thickness **ASTM D 5199** 27 mil 30 mil 32 mił 36 mil 40 mil 45 mil Weight Lbs Per MSF 126 lbs 140 lbs 151 lbs ASTM D 5261 168 lbs 189 lbs (oz/yd²) 210 lbs (18.14)(20.16)(21.74)(24.19)(27.21)(30.24)Construction **Extrusion laminated with encapsulated tri-directional scrim reinforcement Ply Adhesion **ASTM D 413** 16 lbs 20 lbs 19 lbs 24 lbs 25 lbs 31 lbs 88 lbf MD 1" Tensile Strength 110 lbf MD 90 lbf MD **ASTM D 7003** 113 lbf MD 110 lbf MD 138 lbf MD 63 lbf DD 79 lbf DD 70 lbf DD 87 lbf DD 84 lbf DD 105 lbf DD 1" Tensile Elongation @ 550 MD 750 MD 550 MD **ASTM D 7003** 750 MD Break % (Film Break) 550 MD 750 MD 550 DD 750 DD 550 DD 750 DD 550 DD 750 DD 1" Tensile Elongation @ 20 MD 33 MD 20 MD **ASTM D 7003** 30 MD 20 MD Peak % (Scrim Break) 36 MD 20 DD 33 DD 20 DD 31DD 20 DD 36 DD 75 lbf MD Tongue Tear Strength 97 lbf MD 75 lbf MD ASTM D 5884 104 lbf MD 100 lbf MD 117 lbf MD 75 lbf DD 90 lbf DD 75 lbf DD 92 lbf DD 100 lbf DD 118 lbf DD 180 lbf MD Grab Tensile 218 lbf MD ASTM D 7004 180 lbf MD 222 lbf MD 220 lbf MD 257 lbf MD 180 lbf DD 210 lbf DD 180 lbf DD 223 lbf DD 220 lbf DD 258 lbf DD 120 lbf MD Trapezoid Tear 146 lbf MD 130 lbf MD ASTM D 4533 189 lbf MD 160 lbf MD 193 lbf MD 120 lbf DD 141 lbf DD 130 lbf DD 172 lbf DD 160 lbf DD 191 lbf DD * Dimensional Stability ASTM D 1204 <1 < 0.5 <1 < 0.5 <1 < 0.5 Puncture Resistance **ASTM D 4833** 50 lbf 64 lbf 65 lbf 83 lbf 80 lbf 99 lbf Maximum Use Temperature 180° F 180° F 180° F 180° F 180° F 180° F Minimum Use Temperature -70° F

MD = Machine Direction

DD = Diagonal Directions

Note: Minimum Roll Averages are set to take into account product variability in addition to testing variability between laboratories.

-70° F

-70° F

*Dimensional Stability Maximum Value

**DURA-SKRIM J30BB, J36BB & J45BB are a four layer reinforced laminate containing no adhesives. The outer layers consist of a high strength polyethylene film manufactured using virgin grade resins and stabilizers for UV resistance in exposed applications. DURA-SKRIM J30BB, J36BB & J45BB are reinforced with a 1300 denier (minimum) tri-directional scrim reinforcement.

NORE RAVEN INDUSTRIES MAKES NO MARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no quarantee of patistrictory results from resultice upon contained information or recommendations and use aims all laberty for resulting loss or damage

RAVEN NDUSTRIES

PLANT LOCATION

-70° F

Sioux Falls, South Dakota

SALES OFFICE

-70° F

P.O. Box 5107 Sioux Falls, SD 57117-5107 (605) 335-0174 (605) 331-0333 FAX 800-635-3456

-70° F







RAVEN INDUSTRIES INC. EXPOSED GEOMEMBRANE LIMITED WARRANTY

Raven Industries Inc. warrants Dura-Skrim J30BB, J36BB, and J45BB to be free from manufacturing defects and to be able to withstand normal exposure to sunlight for a period of 20 years from the date of sale for normal use in approved applications in the U.S and Canada, excluding Hawaii. This warranty is effective for products sold and shipped from January 1, 2008 to December 31, 2008.

This Limited Warranty does not include damages or defects in the Raven geomembrane resulting from acts of God, casualty or catastrophe including but not limited to: earthquakes, floods, piercing hail, or tornadoes. The term "normal use" as used herein does not include, among other things improper handling during transportation, unloading, storage or installation, the exposure of Raven geomembranes to harmful chemicals, atypical atmospheric conditions, abuse of Raven geomembranes by machinery, equipment or people; improper site preparation or covering materials, excessive pressures or stresses from any source or improper application or installation. Raven geomembrane material warranty is intended for commercial use only and is not in effect for the consumer as defined in the Magnuson Moss Warranty or any similar federal, state, or local statues. The parties expressly agree that the sale hereunder is for commercial or industrial use only.

Should defects or premature loss of use within the scope of the above Limited Warranty occur, Raven Industries Inc. will, at its option, repair or replace the Raven geomembrane on a pro-rata basis at the then current price in such manner as to charge the Purchaser/User only for that portion of the warranted life which has elapsed since purchase of the material. Raven Industries Inc. will have the right to inspect and determine the cause of any alleged defect in the Raven geomembrane and to take appropriate steps to repair or replace the Raven geomembrane if a defect exists which is covered under this warranty. This Limited Warranty extends only to Raven's geomembrane, and does not extend to the installation service of third parties nor does it extend to materials furnished or installed by others in connection with the intended use of the Raven geomembranes.

Any claim for any alleged breach of this warranty must be made in writing, by certified mail, to the General Manager of Engineered Films Division of Raven Industries Inc. within ten (10) days of becoming aware of the alleged defect. Should the required notice not be given, the defect and all warranties are waived by the Purchaser, and Purchaser shall not have any rights under this warranty. Raven Industries Inc. shall not be obligated to perform repairs or replacements under this warranty unless and until the area to be repaired or replaced is clean, dry, and unencumbered. This includes, but is not limited to, the area made available for repair and/or replacement of Raven geomembrane to be free from all water, dirt, sludge, residuals and liquids of any kind. If after inspection it is determined that there is no claim under this Limited Warranty, Purchaser shall reimburse Raven Industries Inc. for its costs associated with the site inspection.

In the event the exclusive remedy provided herein fails in its essential purpose, and in that event only, the Purchaser shall be entitled to a return of the purchase price for so much of the material as Raven Industries Inc. determines to have violated the warranty provided herein. Raven Industries Inc. shall not be liable for direct, indirect, special, consequential or incidental damages resulting from a breach of this warranty including, but not limited to, damages for loss of production, lost profits, personal injury or property damage. Raven Industries Inc. shall not be obligated to reimburse Purchaser for any repairs, replacement, modifications or alterations made by Purchaser unless Raven Industries Inc. specifically authorized, in writing, said repairs, replacements, modifications or alteration in advance of them having been made. Raven Industry's liability under this warranty shall in no event exceed the replacement cost of the material sold to the Purchaser for the particular installation in which it failed.

Raven Industries Inc. neither assumes nor authorizes any person other than the undersigned of Raven Industries Inc. to assume for it any other or additional liability in connection with the Raven geomembrane made on the basis of the Limited Warranty. The Limited Warranty on the Raven geomembrane herein is given in lieu of all other possible material warranties, either expressed or implied, and by accepting delivery of the material; Purchaser waives all other possible warranties, except those specifically given. This Limited Warranty may only be modified by written document mutually executed by Owner and Raven Industries Inc.

Limited Warranty is extended to the purchaser/owner and is non-transferable and non-assignable; i.e., there are no third-party beneficiaries to this warranty.

Purchaser acknowledges by acceptance that the Limited Warranty given herein is accepted in preference to any and other possible materials warranties.

THIS LIMITED WARRANTY SHALL BE GOVERNED BY SOUTH DAKOTA LAW AND VENUE FOR ALL LEGAL PROCEEDINGS IN CONNECTION WITH THIS LIMITED WARRANTY SHALL BE IN MINNEHAHA COUNTY, SOUTH DAKOTA. RAVEN INDUSTRIES INC. MAKES NO WARRANTY OF ANY KIND OTHER THAN THAT GIVEN ABOVE AND HEREBY DISCLAIMS ALL WARRANTIES, BOTH EXPRESSED OR IMPLIED. OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THIS IS THE ONLY WARRANTY THAT APPLIES TO THE MATERIALS REFERRED TO HEREIN AND RAVEN INDUSTRIES INC. DISCLAIMS ANY LIABILITY FOR ANY WARRANTIES GIVEN BY ANY OTHER PERSON OR ENTITY, EITHER WRITTEN OR ORAL.

RAVEN INDUSTRIES' WARRANTY BECOMES AN OBLIGATION OF RAVEN INDUSTRIES INC. TO PERFORM UNDER THE WARRANTY ONLY UPON RECEIPT OF FINAL PAYMENT AND EXECUTION BY A DULY AUTHORIZED OFFICER OF RAVEN INDUSTRIES INC.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Maintenance and Operating Plan

In accordance with Rule 19.15.17 the following information describes the operation and maintenance of Below Grade Tank (BGT) on Burlington Resources Oil & Gas Company, LP (BR) locations. This is BR's standard procedure for all BGT. A separate plan will be submitted for any BGT which does not conform to this plan.

General Plan:

- BR will operate and maintain a BGT to contain liquids and solids and maintain the integrity of the liner, liner system and secondary containment system to prevent contamination of fresh water and protect public health and environment. BR will accomplish this by performing an inspection on a monthly basis, installing cathodic protection, and automatic overflow shutoff devices as seen on the design plan.
- 2. BR will not discharge into or store any hazardous waste in the BGT.
- 3. BR shall operate and install the below-grade tank to prevent the collection of surface water run-on. BR has built in shut off devices that do not allow a below-grade tank to overflow. BR constructs berms and corrugated retaining walls at least 6" above ground to keep from surface water run-on entering the below grade tank as shown on the design plan.
- 4. As per 19.17.15.12 Subsection D, Paragraph 3, BR will inspect the below-grade tank at least monthly reviewing several items which include 1) containment berms adequate and no oil present, 2) tanks had no visible leaks or sign of corrosion, 3) tank valves, flanges, and hatches had no visible leaks and 4) no evidence of significant spillage of produced liquids. In addition, BR's multi-skilled operators (MSOs) are required to visit each well location once per week. If detected on either inspection, BR shall remove any visible or measurable layer of oil from the fluid surface of a below-grade tank in an effort to prevent significant accumulation of oil overtime. The written record of the monthly inspections will include the items listed above and will be maintained for five years.
- 5. BR shall require and maintain a 10" adequate freeboard to prevent overtopping of the below-grade tank.
- 6. If the below grade tank develops a leak, or if any penetration of the pit liner or below grade tank, occurs below the liquid's surface, then BR shall remove all liquid above the damage or leak line within 48 hours. BR shall notify the appropriate district office. BR shall repair or replace the pit liner or below grade tank, within 48 hours of discovery. If the below grade tank or pit liner does not demonstrate integrity, BR shall promptly remove and install a below grade tank or pit liner that complies with Subsection I of 19.15.17.11 NMAC. BR shall notify the appropriate district office of a discovery of leaks less than 25 barrels as required pursuant to Subsection B of 19.15.3.116 NMAC shall be reported within twenty-four (24) hours of discovery of leaks greater than 25 barrels. In addition, immediate verbal notification pursuant to Subsection B, Paragraph (1), and Subparagraph (d) of 19.15.3.116 NMAC shall be reported to the division's Environmental Bureau Chief.

Burlington Resources Oil & Gas Company, LP San Juan Basin Below Grade Tank Closure Plan

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of Below Grade Tanks (BGTs) on Burlington Resources Oil & Gas Company, LP locations hereinafter known as BR locations. This is BR's standard procedure for all BGTs. A separate plan will be submitted for any BGT which does not conform to this plan.

General Requirements:

• .

- BR shall close a below-grade tank within the time periods provided in Subsection A of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I o f19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) permitted below-grade tanks within 60 days of cessation of the below-grade tank's operation., or c) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.
- 2. BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.
- 3. BR will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves. Documentation of how the below-grade tank was disposed of or recycled will be provided in the closure report.
- 4. If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless the equipment is required for some other purpose.
- 5. BR shall test the soils beneath the below-grade tank to determine whether a release has occurred. BR shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyze for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH division approves, does not exceed 100 mg/kg; and the chloride concentration, as determined by EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration, whichever is greater. BR shall notify the division of its results on form C-141.
- 6. If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

- 7. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site.
- Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name

- ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.
- 9. The surface owner shall be notified of BR's closing of the below-grade tank prior to closure as per the approved closure plan via certified mail, return receipt requested.
- 10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 11. BR shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federally jurisdicted lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. BR will repeat seeding or planting will be continued until successful vegetative growth occurs.
- 12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.
- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation
 - Re-vegetation application rates and seeding techniques
 - Photo documentation of the site reclamation
 - Confirmation Sampling Results
 - Proof of closure notice