Office Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II	OIL CONSERVATION DIVISION	30-007-20750
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.	7. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410		STATE FEE
District IV	Santa Fe, NM 87505	7. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	and the second section of the section of t	a Se
p	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOS	ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A /	
DIFFERENT RESERVOIR. USE "APPLIC	ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO AVAITON FOR PERMIT" (FORM C-10) FOR SUCH	ED VPR B
PROPOSALS.)		8 Well Number 146
1. Type of Well: Oil Well	Gas Well Other Coalbon Mathane	OGRID Number
2. Name of Operator	- · · · ·	GRID Number
	E & P COMPANY, L.P.	10. Do al warma on Wildoot
3. Address of Operator	100 DATON NA OFFIC	10. Pool name or Wildcat
P.O. BOX	190, RATON, NM 87740	
4. Well Location		
Unit Letter K: 21	67_ feet from the South line and 2335	_feet from theWestline
Section 25 Town		
o a line	11. Elevation (Show whether DR, RKB, RT, GR, et	
division of the state of the st	8,012' (GL)	
Pit or Below-grade Tank Application or		
	ter Distance from nearest fresh water well D	sistance from negrest surface water
Pit Liner Thickness: mil	Below-Grade Tank: Volumebbls;	Construction Material
12. Check A	ppropriate Box to Indicate Nature of Notice	e, Report or Other Data
NOTICE OF IN	FENTION TO: SU	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL WO	RK ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE D	RILLING OPNS.⊠ PAND A □
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEME	NT JOB
OTHER:		Amended 🛛
	eted operations. (Clearly state all pertinent details, a	
of starting any proposed wor	rk). SEE RULE 1103. For Multiple Completions: A	Attach wellbore diagram of proposed completion
or recompletion.		
	Il 11" surface hole to 334'. Run 10 jts. of 8 5/8",	
	pumped 100 sx Midcon II cement, 14 ppg, yield	1.66. Circulate 7 bbls of cement to surface.
WOC 8 hrs. Test surfa	ace 8 5/8" csg to 500 psi for 30 minutes.	
	334' - 2515'. Reached TD 2515' at 6:45 a.m.	
	well. Logger's TD at 2499'.	
	opf, J-55, and 8 jts 17 ppf, J-55 LT&C casing at 2428	
HES mixed and pumped	335 sks Midcon II cement. Circulated 27 bbls of	or cement to surface.
	bove is true and complete to the best of my knowled closed according to NMOCD guidelines [], a general permit [	
11.		□ or an (attached) afternative OCD-approved plan □.
SIGNATURE Shuly mit	TITLE Regulatory Ana	lyst DATE <u>03/07/2007</u>
Type or print name Shirley A. Mit		aso.com Telephone No. (505) 445-6785
For State Use Only	S man addiess. Sinieyimiceneriaetp	10.0p
	A NIATHIAT A	IINPRIIAAN .
APPROVED BY:	Yartin TITLE DISTRICTS	UPERVISUR DATE 2/3//0 >
Conditions of Approval (if any):		