Office <u>District I</u>	State of New Mexico	Form C-103
	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 30-007-20908
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5.\ Indicate\Type of Lease
District III	1220 South St. Francis Dr. 📋 🔾	V ISTATE FEE 🗵
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	2008 JUL 14	1
87505 SUNDRY NOT	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
DIFFERENT RESERVOIR. USE "APPLI PROPOSALS.)	CATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR A
1. Type of Well: Oil Well	Gas Well Other Coalbed Methane	8. Well Number 479
2. Name of Operator	, , , , , , , , , , , , , , , , , , ,	9. OGRID Number 180514
EL PA	ASO E & P COMPANY, L.P.	
3. Address of Operator	OV 100 D (TOY 1) OF 10	10. Pool name or Wildcat
	OX 190, RATON, NM 87740	Stubblefield Canyon – Vermejo Gas
4. Well Location		
Unit Letter <u>K</u> :	2015 feet from the South line and 1411	feet from theWest _ line
Section 28 Town		Colfax County
	11. Elevation (Show whether DR, RKB, RT, GR, etc.,	
Pit or Below-grade Tank Application []	7,931' (GL)	
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN	NTENTION TO: SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
TEMPORARILY ABANDON	=	
PULL OR ALTER CASING		
	_	_
OTHER.	☐ OTHER:	Completion 🖂
OTHER:		
13. Describe proposed or comp	pleted operations. (Clearly state all pertinent details, an	d give pertinent dates, including estimated date
13. Describe proposed or compof starting any proposed w		d give pertinent dates, including estimated date
13. Describe proposed or composed of starting any proposed wor recompletion.	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At	d give pertinent dates, including estimated date
13. Describe proposed or composed of starting any proposed wor recompletion.	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At	d give pertinent dates, including estimated date
 13. Describe proposed or composed of starting any proposed wor recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag 	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'.	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion
13. Describe proposed or composed of starting any proposed wor recompletion. 03/30/08 Weatherford ran Cement E Weatherford perf'd 1st stag HES frac'd 1st stage - Pur	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 1839'-1842', 1897'-1903' 36 Holes of 79,399 scf 70% quality nitrogen foam with 20# L	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion
13. Describe proposed or composed of starting any proposed wor recompletion. 03/30/08 Weatherford ran Cement E Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage -	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'-1903' 36 Holes nped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand.
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Pur Perf'd 3rd stage -	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 189 - 1839'-1842', 1897'-1903' 36 Holes apped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes apped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand.
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur Perf'd 3rd stage	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 189 - 1839'-1842', 1897'-1903' 36 Holes open 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes open 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes open 290,636 scf 70% quality nitrogen foam with 20# L	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur Perf'd 3rd stage	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 189 - 1839'-1842', 1897'-1903' 36 Holes apped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes apped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur Perf'd 3rd stage	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 189 - 1839'-1842', 1897'-1903' 36 Holes open 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes open 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes open 290,636 scf 70% quality nitrogen foam with 20# L	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Perf'd 3rd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur 04/22/08 RIH tubing, rods and pu	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'-1903' 36 Holes nped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes nped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes nped 290,636 scf 70% quality nitrogen foam with 20# L mp. Well is ready to be tested and put on production	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. In.
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Perf'd 3rd stage - Frac'd 3rd stage - Prac'd 3rd stage - Prac'd 3rd stage - Pur 04/22/08 RIH tubing, rods and pu	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 189 - 1839'-1842', 1897'-1903' 36 Holes open 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes open 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes open 290,636 scf 70% quality nitrogen foam with 20# L	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur Perf'd 3rd stage - Pur O4/22/08 RIH tubing, rods and pu	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'-1903' 36 Holes nped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes nped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes nped 290,636 scf 70% quality nitrogen foam with 20# L mp. Well is ready to be tested and put on production above is true and complete to the best of my knowledger closed according to NMOCD guidelines , a general permit	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Pur Perf'd	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 18e - 1839'-1842', 1897'- 1903' 36 Holes an organized for a mount of the following sections of the fol	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Frac'd 3rd stage - Frac'd 3rd stage - Pur Perf'd 3rd stage - Pur O4/22/08 RIH tubing, rods and pu	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. 18e - 1839'-1842', 1897'-1903' 36 Holes an organized from the second fro	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Pur Perf'd 3rd stage - Pur Stage - Pur Perf'd 3rd stage - Pur Perf'd 3rd stage - Pur Stage - Pur O4/22/08 RIH tubing, rods and pur I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Shirley A M	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'- 1903' 36 Holes inped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes inped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes inped 290,636 scf 70% quality nitrogen foam with 20# L 100 mp. Well is ready to be tested and put on production above is true and complete to the best of my knowledger closed according to NMOCD guidelines , a general permit . TITLE Regulatory A itchell E-mail address: shirley.mitchell@elpaso.com	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 s
13. Describe proposed or completion of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pur Perf'd 2nd stage - Frac'd 2nd stage - Pur Perf'd 3rd stage - Pur Perf'd	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'- 1903' 36 Holes inped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes inped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes inped 290,636 scf 70% quality nitrogen foam with 20# L 100 mp. Well is ready to be tested and put on production above is true and complete to the best of my knowledger closed according to NMOCD guidelines , a general permit . TITLE Regulatory A itchell E-mail address: shirley.mitchell@elpaso.com	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 s
of starting any proposed w or recompletion. 03/30/08 Weatherford ran Cement E 02/28/08 Weatherford perf'd 1st stag HES frac'd 1st stage - Pur Perf'd 2nd stage - Pur Perf'd 3rd stage - Pur Stage - Pur Perf'd 3rd stage - Pur Perf'd 3rd stage - Pur Stage - Pur O4/22/08 RIH tubing, rods and pur I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Shirley A M	pleted operations. (Clearly state all pertinent details, an ork). SEE RULE 1103. For Multiple Completions: At Bond Log. Estimated cement top at 36'. ge - 1839'-1842', 1897'- 1903' 36 Holes inped 79,399 scf 70% quality nitrogen foam with 20# L 1652'-1655', 1771'-1773', 1786'-1788' 28 Holes inped 133,599 scf 70% quality nitrogen foam with 20# L 653'-656', 685'-688', 720'-723' 28 Holes inped 290,636 scf 70% quality nitrogen foam with 20# L 100 mp. Well is ready to be tested and put on production above is true and complete to the best of my knowledger closed according to NMOCD guidelines , a general permit . TITLE Regulatory A itchell E-mail address: shirley.mitchell@elpaso.com	d give pertinent dates, including estimated date tach wellbore diagram of proposed completion inear gel with 7,894 lbs 20/40 sand. Linear gel with 12,581 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand. Linear gel with 17,327 lbs 20/40 sand.