	State of New N	1exico	Form C-103					
Office [*] <u>Dêstrict I</u>	Energy, Minerals and Natural Resources		May 27, 2004					
71625 N. French Dr., Hobbs, NM 88240		we say the same of	WELL API NO.					
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATIO	N DIVISION	30-007-20892 7. Indicate Type of Lease					
District III	1220 South St. Fi	ancis Dr. 🗔 🗸 🗏	STATE FEE					
District IV	Santa Ha NIM V/505							
1220 S. St. Francis Dr., Santa Fe, NM 87505	2004	DEC 24 PM 2						
	ICES AND REPORTS ON WEL		7. Lease Name or Unit Agreement Name					
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DEEPEN OR I	PLUG BACK TO A						
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			VPR A					
1. Type of Well: Oil Well	Gas Well Other Salt Wa	iter Disposal	8. Well Number 500					
2. Name of Operator	9. OGRID Number							
EL PAS	10 P. I. Will d							
3. Address of Operator	10. Pool name or Wildcat							
4. Well Location	(190, RATON, NM 87740							
	feet from the South lin	and 2540 foots	from the Fast line					
Section 30 Towns		ie and <u>2549</u> leet in NMPM						
Section 30 Towns								
0 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7,960' (GL)								
Pit or Below-grade Tank Application		, (32)						
Pit typeDepth to Grounds	vaterDistance from nearest fres	water well Dista	ance from nearest surface water					
Pit Liner Thickness: mi	Below-Grade Tank: Volume	bbls; Co	nstruction Material					
12 Check	Appropriate Box to Indicate	Nature of Notice	Report or Other Data					
12. Check	Appropriate Box to indicate	ivature of ivotice, i	Report of Other Data					
NOTICE OF I	ITENTION TO:	SUB	SEQUENT REPORT OF:					
PERFORM REMEDIAL WORK 🗌								
TEMPORARILY ABANDON	LLING OPNS. P AND A							
	MULTIPLE COMPL	CASING/CEMENT	7 IOB					
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	10B U					
_	MOLTIFLE COMPL							
OTHER:		OTHER:	RE-COMPLETION					
OTHER: 13. Describe proposed or com	oleted operations. (Clearly state a	OTHER:						
OTHER: 13. Describe proposed or com	oleted operations. (Clearly state a	OTHER:	RE-COMPLETION I give pertinent dates, including estimated da					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion.	pleted operations. (Clearly state a ork). SEE RULE 1103. For Mul	OTHER:	RE-COMPLETION I give pertinent dates, including estimated da					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502.	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multi-	OTHER:	RE-COMPLETION I give pertinent dates, including estimated da					
OTHER: 13. Describe proposed or come of starting any proposed we or recompletion. 12/04/2008 MIRU Animas 502. To RU superior Wireling	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multi-	OTHER: Il pertinent details, and iple Completions: Att	RE-COMPLETION I give pertinent dates, including estimated data and the second					
OTHER: 13. Describe proposed or come of starting any proposed we or recompletion. 12/04/2008 MIRU Animas 502. The RU superior Wireling Perf Stage 1 - (6427'-Perf Stage 2 - (5982'-Perf Stage 2 - (5	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple 1103 or Multiple 1103	OTHER: Il pertinent details, and iple Completions: Att 60', 6470'- 6500', 6515'- 5', 6010'- 6040', 6050'-	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added.					
OTHER: 13. Describe proposed or come of starting any proposed was or recompletion. 12/04/2008 MIRU Animas 502. The RU superior Wireling Perf Stage 1 - (6427'-Perf Stage 2 - (5982'-Perf Stage 3 - (5452'-Perf Stage 3 - (pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple	OTHER: Il pertinent details, and iple Completions: Att 60', 6470'- 6500', 6515'- 5', 6010'- 6040', 6050'-	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added.					
OTHER: 13. Describe proposed or com of starting any proposed wor recompletion. 12/04/2008 MIRU Animas 502. The superior Wireline Perf Stage 1 - (6427'-Perf Stage 2 - (5982'-Perf Stage 3 - (5452'-Perf Stage 3 - (5452'-P	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple	OTHER: Il pertinent details, and iple Completions: Att 60', 6470'- 6500', 6515'- 5', 6010'- 6040', 6050'-	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added.					
OTHER: 13. Describe proposed or com of starting any proposed wor recompletion. 12/04/2008 MIRU Animas 502. The superior Wireline Perf Stage 1 - (6427'-Perf Stage 2 - (5982'-Perf Stage 3 - (5452'-Perf Stage 3 - (5452'-P	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple	OTHER: Il pertinent details, and inple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added. 5580', 5590'- 5600' 400 Holes added.					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To 12/05/2008 RU superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- RIH with packer to 1 12/07/2008 RIH with packer to 1 12/09/2008 RU Halliburton. RU Halliburton. Tes Frac Glorieta Forma	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152'. Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with	OTHER: Il pertinent details, and inple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added. 5580', 5590'- 5600' 400 Holes added.					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To a superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- RIH with packer to 10 mirula	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152'. Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with a packer at 5900'.	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit 21 CP Linear gel.	RE-COMPLETION If give pertinent dates, including estimated dates, and wellbore diagram of proposed completions. - 6555' 400 Holes added. 6060' 200 Holes added. 5580', 5590'- 5600' 400 Holes added. h water.					
OTHER: 13. Describe proposed or com of starting any proposed wor recompletion. 12/04/2008 MIRU Animas 502. The superior Wireline Perf Stage 1 - (6427'-Perf Stage 2 - (5982'-Perf Stage 3 - (5452'-Perf Stage 3 - (5452'-P	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152". Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with a packer at 5900'. cid, flush with water. Frac Entrad line. Set WRBP at 5670'.	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To a superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152''. Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with a packer at 5900'. cid, flush with water. Frac Entrad line. Set WRBP at 5670'. cid and flush with water. Frac Dak	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To a superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 3 - (5452'- Perf	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152'. Wait on 3.5 pipe. Set packer at 6350'. It all lines to 5700 psi. Pump 15% It ion with 71,760 lbs 20/40 sand with a packer at 5900'. Cid, flush with water. Frac Entrad line. Set WRBP at 5670'. Cid and flush with water. Frac Dak 6140'. Clean hole to PBTD at 6700	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To a superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152''. Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with a packer at 5900'. cid, flush with water. Frac Entrad line. Set WRBP at 5670'. cid and flush with water. Frac Dak	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1° ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1° over perfs, set Arrow So	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To a superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage	pleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple (CO) with 4.5 Tubing. 6528') original Glorieta; 6430'- 646065') original Entrada; 5985'- 5995617') original Dakota; 5460'- 5480152'. Wait on 3.5 pipe. Set packer at 6350'. tall lines to 5700 psi. Pump 15% Ition with 71,760 lbs 20/40 sand with a packer at 5900'. cid, flush with water. Frac Entrad line. Set WRBP at 5670'. cid and flush with water. Frac Dak 6140'. Clean hole to PBTD at 6700, injection string. Landed at 38' a	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°- 1°,	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. T 12/05/2008 RU superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- RIH with packer to 1 12/07/2008 RIH with packer to 1 12/09/2008 RU Halliburton. Tes Frac Glorieta Forma 12/11/2008 Set RBP at 6160', set Pumped 15% HCL a 12/12/2008 MIRU Superior wire Pumped 15% HCL a 12/15/2008 Retrieve WRBPs at 12/20/2008 RIH 4 ½", 11.60 PPF 12/21/2008 MIT test to 1625 psi.	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the poleta o	OTHER: Il pertinent details, and iple Completions: Att 60', 6470'- 6500', 6515'. 5', 6010'- 6040', 6050'- 1', 5490'- 5520', 5540'- 5 ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1'. pove perfs, set Arrow Sot crew. Well ready for injection	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To 12/05/2008 RU superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the control of the con	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°. 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 5 ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1°, ove perfs, set Arrow Set crew. Well ready for injection best of my knowledge	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion 1. 6555' 400 Holes added. 1. 66555' 400 Holes added. 1. 65580', 5590'- 5600' 400 Holes added. 1. 6 sand with 21 CP Linear gel. 1. 6 sand with 21 CP Linear gel. 1. 6 and belief. I further certify that any pit or below					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To 12/05/2008 RU superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the control of the con	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°. 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 5 ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1°, ove perfs, set Arrow Set crew. Well ready for injection best of my knowledge	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. To 12/05/2008 RU superior Wireline Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the control of the con	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1° ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1° oove perfs, set Arrow Set crew. Well ready for injection best of my knowledges s □, a general permit □ s	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of proposed of proposed plan in the proposed p					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. The stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the state	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°. 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 5 ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1°, ove perfs, set Arrow Set crew. Well ready for injection best of my knowledge	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion 1-6555' 400 Holes added. 1-6555' 400 Holes added. 1-6550', 5590'- 5600' 400 Holes added. 1-6580', 5590'- 5600' 400 Holes added. 1-6580' 40					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. The stage 1 - (6427'-	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the state	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1° ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1° cove perfs, set Arrow Set crew. Well ready for injection best of my knowledge s □, a general permit □ Regulatory Analys hirley.mitchell @elpa	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. The stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 3 - (5452'- RIH with packer to 10 MIRU Halliburton. Test Frac Glorieta Forma 12/11/2008 RU Halliburton. Test Frac Glorieta Forma 12/11/2008 Set RBP at 6160', set Pumped 15% HCL at MIRU Superior wire Pumped 15% HCL at Retrieve WRBPs at 12/20/2008 RIH 4 ½", 11.60 PPF 12/21/2008 Installed wellhead. Signature of the stage of the	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the state	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- 1°, 5490°- 5520°, 5540°- 1° ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1° cove perfs, set Arrow Set crew. Well ready for injection best of my knowledge s □, a general permit □ Regulatory Analys hirley.mitchell @elpa	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					
OTHER: 13. Describe proposed or com of starting any proposed w or recompletion. 12/04/2008 MIRU Animas 502. The stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 2 - (5982'- Perf Stage 3 - (5452'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf Stage 1 - (6427'- Perf Stage 2 - (5982'- Perf Stage 2 - (5982'- Perf Stage 1 - (6427'- Perf	poleted operations. (Clearly state a ork). SEE RULE 1103. For Multiple of the state	OTHER: Il pertinent details, and iple Completions: Att 60°, 6470°- 6500°, 6515°- 5°, 6010°- 6040°, 6050°- 1°, 5490°- 5520°, 5540°- ICL acid and flush wit 21 CP Linear gel. a with 34,831 lbs 20/40 s ota with 83,750 lbs 20/4 1°. bove perfs, set Arrow Set crew. Well ready for injection best of my knowledges s □, a general permit □ Regulatory Analys	RE-COMPLETION If give pertinent dates, including estimated data are wellbore diagram of proposed completion of pr					

CURRENT WELLBORE DIAGRAM

LEASE: Vermejo Park Ranch	WELL:	A-500	FIELD:	Crow Canyon	API NO:	30-007-20892
LOC: 338' FSL & 2578' FEL	SEC:	31		31N / 21E	SPUD:	1/16/2008
BHL:	GL:	7966'	CTY/ST:	Colfax, NM	COMPL:	
CURRENT STATUS: Completion	KB:	7978'	DF:	7977'	PBTD:	6700'
			_		TD:	6750'

