

Submit To Appropriate District Office
Two Copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
July 17, 2008

1. WELL API NO.
30-007-20239
2. Type of Lease
☐ STATE ☒ FEE ☐ FED/INDIAN
3. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

4. Reason for filing:

- ☒ **COMPLETION REPORT** (Fill in boxes #1 through #31 for State and Fee wells only)
- ☒ **C-144 CLOSURE ATTACHMENT** (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)

7. Type of Completion:

☐ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☒ OTHER **RE-COMPLETION**

8. Name of Operator

EL PASO E & P COMPANY, L.P.

5. Lease Name or Unit Agreement Name
VPR B

6. Well Number:
35

10. Address of Operator

**PO BOX 190
RATON, NM 87740**

11. Pool name or Wildcat
Castle Rock Park - Vermejo Gas

12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	P	27	30N	18E		997	South	584	East	Colfax
BH:										

13. Date Spudded 03/20/2001	14. Date T.D. Reached 03/22/2001	15. Date Rig Released 03/22/2001	16. Date Completed (Ready to Produce) 08/01/2001	17. Elevations (DF and RKB, RT, GR, etc.) 8,274' GR
18. Total Measured Depth of Well 2793'	19. Plug Back Measured Depth 2793'	20. Was Directional Survey Made? No	21. Type Electric and Other Logs Run Array Induction, Comp Density, Cement Bond Log	

22. Producing Interval(s), of this completion - Top, Bottom, Name

**1117' - 2033' Raton Coals (New Perfs)
2468' - 2580' Original Perfs**

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb	316'	11"	100 sxs	None
5 1/2"	15.5 lb	2639'	7 7/8"	844 sxs	W/ Squeeze holes 2490' - 91', 2540' - 41', 2250' - 52', 730' - 731'

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2644'	

26. Perforation record (interval, size, and number)
2031' - 2033', 2036' - 2040', 1232' - 1237', 1117' - 1125' 84 holes Raton Coals (New Perfs)
2468' - 70', 2482' - 84', 2496' - 99', 2515' - 17', 2535' - 38', 2554' - 57', 2578' - 80' 68 holes Vermejo Coals (Original Perfs)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
1117' - 2033'	21# linear gel slick water and 110,518 16/30 sand
2468' - 2580'	125,000 lbs 16/30 sand

28. PRODUCTION

Date First Production 06/19/2001	Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) Pumping water up 2 7/8" tubing w/PC pump. Flowing gas up 5 1/2" casing.	Well Status (<i>Prod. or Shut-in</i>) PRODUCING
--	--	---

Date of Test 06/19/2001	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl	Gas - MCF 220	Water - Bbl. 40	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure 85 psi	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF 220	Water - Bbl. 40	Oil Gravity - API - (<i>Corr.</i>)	

29. Disposition of Gas (*Sold, used for fuel, vented, etc.*)

Sold, used for fuel.

30. Test Witnessed By

Mike Potter

31. List Attachments

32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.

33. If an on-site burial was used at the well, report the exact location of the on-site burial:

Latitude Longitude NAD 1927 1983

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature *Shirley Mitchell* Printed Name **Shirley Mitchell** Title **Regulatory Analyst** Date **05/05/2009**

E-mail Address **shirley.mitchell@elpaso.com**

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	T. Raton <u>529'</u>
T. Tubb	T. Delaware Sand	T. Morrison	T. Vermejo <u>2269'</u>
T. Drinkard	T. Bone Springs	T. Todilto	T. Trinidad <u>2549'</u>
T. Abo	T.	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology