

Submit 3 Copies To Appropriate District  
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.

30-037-~~2004~~ 20051

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Anna Katheryn

8. Well No.

1

9. Pool name or Wildcat  
Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
Prairie Sun, Inc.

3. Address of Operator  
10713 RR 620 N., Bldg F Suite 621, Austin Tx 78726

4. Well Location

Unit Letter I : 660 feet from the West line and 1980 feet from the South line

Section 19 Township 10N Range 27E NMPM Quay County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
4365' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE  
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND  
ABANDONMENT ☐

CASING TEST AND  
CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

10/06/02 thru 10/16/02

Drill 7 7/8" hole to 4288'. 8 5/8" csg collapsed and parted. Fish out 8 5/8" csg. Dress off top of 8 5/8" csg to 1908' to 32# csg. Run 43 jts 8 5/8" 32# J55 LT&C csg and tie together with Bowen csg patch. Perforate 8 5/8" csg at 1915 w/ 4 JSPF sqz holes.

Cement 8 5/8" csg with 865 sx Lite (65/35/6) + 1/2#/sx celloflake, 2#/gal Gilsonite, 5% salt (Yld --1.88 @ 12.8#/gal) Tail with 200 sx. Class "C" + 1% CaCl2. Did not circulate. Plug down at 11:00 hrs 10/15/02.

WOC for 18 hrs. Drill out with 7 7/8" bit at 10:00 hrs on 10/16/02

Test Casing and BOP to 2000 psi--OK.

Continue drilling 7 7/8" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gene Lee TITLE Agent DATE 10/23/02

Type or print name Gene Lee Telephone No. (505) 622-7355  
(This space for State use)

APPROVED BY K. E. Johnson TITLE DISTRICT SUPERVISOR DATE 12/4/02  
Conditions of approval, if any: