


\$

**Amoco Production Company** 

Petroleum Center Building 501 Airport Drive Farmington, New Mexico 87401 505-325-8841

S. D. Blossom District Superintendent

August 3, 1983



Oil Conservation Commission Box 2088 Santa Fe, NM 87501

File: DHS-358-986.510.1

Commingling Application for the Jicarilla Apache Tribal 151 No. 4, 1600' FWL x 820' FNL, Section 3, T26N, R5W, Rio Arriba County, New Mexico

Amoco Production Company requests approval to commingle production from the Undesignated Gallup and the Basin Dakota pools in the subject well. The commingling will utilize a production packer set between the two zones at 7432' and a sliding sleeve set at 7428' to produce up 2-3/8" tubing landed at 7514'.

The commingling of the Gallup and Dakota is necessary due to the size of the production casing. The  $4-\frac{1}{2}$ " casing is too small to land two standard size tubing strings. The proposed commingling will not adversely affect either zone for the following reasons:

- Neither zone will be damaged by the small amount of formation water which is produced. In 1982, the Dakota formation produced an average of 0.5 BWPD. The 52 hour flow test of the Gallup side produced only 1.4 BW for a rate of 0.6 BWPD. The water analyses performed on water samples obtained from the two zones indicate the waters produced will be compatible.
- 2. Neither zone has a history of sensitivity to liquid hydrocarbons and should not be damaged by condensate production.
- 3. Both zones have common ownership, so there will be no problems in allocating royalty or working interest payments.
- 4. The bottom hole pressure of the Gallup is 76 percent of the Basin Dakota.

In compliance with NMOCD Rule 303C, please find enclosed two copies of each of the following:

Page 2 August 3, 1983 File: DHS-358-986.510.1

Attachment No.

a.)

- 1. "Well Location and Dedication Plat"(NMOCD Form C-102).
- 2. Well location map showing location of all outside operated wells.
- 3. List of names and addresses of operators for all outside operated wells.
- 4. A complete well completion history (USGS Form 9-331, "Sundry Notices and Reports on Wells).
- 5. A complete engineering completion summary on both zones along with well test data on the Gallup.
- 6. Production deline curve for the Basin Dakota.
- 7. NMOCD Form C-116 showing latest Dakota production.
- 8. NMOCD Form C-116 showing 48 hour flow test of the Gallup from 4-19-83 to 4-21-83. We request an exception to be granted on the 30-day limit because the Gallup has been shut in since the flow test.
- 9. Actual bottom hole pressure taken on the Dakota.
- 10. Actual bottom hole pressure taken on the Gallup.
- 11. A copy of the gas analysis from the Dakota.
- 12. A copy of the gas analysis from the Gallup.
- 13. Water analysis of produced water from the Dakota.
- 14. Water analysis of produced water from the Gallup.
- 15. Formula for the allocation of production for each commingled zone.
- 16. A copy of the letter sent to all offset operators and the Minerals Management Services notifying them of our intent to commingle.

To allocate production to the individual Gallup and Dakota horizons we recommend the following:

- 1. Allocate 26.78 percent of the gas production to the Gallup horizon.
- 2. Allocate 73.22 percent of the gas production to the Dakota horizon.
- 3. Allocate 100 percent of the condensate production to the Dakota.

Page 3 August 3, 1983 File: DHS-358-986.510.1

We would like to obtain approval for this commingling application as soon as possible so we can start producing the Gallup formation.

S.D. Blocson Die

MJB/gw

Attachments

AM13

NEW LCO OIL CONSERVATION MISSION

WELL LOCATION AND ACERAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section

		Lease			Well No.	
duction Com	ipany	Jicarilla Apa	che Tribal	1 151	4	
Section	Township	Ronge -	County			
3	26 North	5 West	Rio	Arriba		
ation of Well:	•				<u></u>	
feer from the	North line and	1600 fe	set from the	West	line	
	Formation	Poci			Dedicated Avereage:	
· · · · · · · · · · · · · · · · · · ·	Dakota / Gallup '	Basin Dakota /	Undes.	Gallup	320 / 160	Acres
	Section 3 ation of Well: feet from the Producing	<u>3</u> <u>26 North</u> ation of Well: feer from the North line and Producing Formation	duction     Company     Jicarilla Apa       Section     Township     Ronge       3     26 North     5 West       ation of Well:     faer from the North     line and     1600       Producing Formation     Fooi	duction     Company     Jicarilla     Apache     Tribal       Section     Township     Ronge     County       3     26     North     5     West     Rio       ation of Welli     feer from the     North     ine and     1600     feer from the       Producing     Formation     Producing     Formation     Producing	duction     Company     Jicarilla     Apache     Tribal     151       Section     Township     Range     County       3     26 North     5 West     Rio Arriba       ation of Well:     feer from the     North     ine and     1600     feet from the     West       Producing Formation     Fooi     Fooi     Fooi     Fooi	duction     Company     Jicarilla Apache Tribal 151     4       Section     Township     Ronge     County       3     26 North     5 West     Rio Arriba       ation of Well:     feer from the     North     1600       Producing Formation     Foci     Dedicared Avereage:

1. Outline the acerage dedicated to the subject well by colored pencil or hachure marks on the plat below.

2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty),


3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

( ) Yes ( ) No If answer is "yes," type of consolidation.

If answer is "no," list the owners and tract descriptions which have actually consolidated. (Use reverse side of this form if necessary.)

--No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forcedpooling, or otherwise) or until a non standard unit, eliminating such interests, has been approved by the Commission.

CERTIFICATION I bereby certify that the information contained 820 boreis is true and complete to the knowladge and belief. DEC 01 1982 = చ Nome L. O. Speer, Jr. Position Area Superintendent OGICAL SURVEY Company AMOCO PRODUCTION COMPANY U. S. GEO FARMU Dote April 17, 1973 Gallup Sec J 3 simminition in the Bareby cartify that the well location shows a this plan was plotted from field notes of actu Edways mode by me or brader my seperition, a they the same is true and correct to the best of a knowledge, and belief. HEGY REGI Date Sur ered-APR 11.13, 1973 Registered Professional Engineer IN NAMES AND A DESCRIPTION OF VIVIUN and/or-Land Surveyor BANTA FE Certificate No. 2000 E. V. Echohawk LS Dakota



El Paso Exploration Company P.O. Box 4289 Farmington, NM 87499-4289

Union Texas Petroleum 14001 E. Iliff Ave. Suite 500 Aurora, Co. 80014

		:	
	Attachment 4	C	
	Form 9-331	C.	Form Approved.
	Dec. 1973		Budget Bureau No. 42R1424
RECEIVED	UNITED, STATES	5. LEASI	
JUL-27 1.8:	DEPARTMENT OF THE INTERIOR	Jicar	illa Apache Tribal 151
FARMINGTON	GEOLOGICAL SURVEY		DIAN, ALLOTTEE OR TRIBE NAME
DISTRICT			carilla Apache
DS 1 A	SUNDRY NOTICES AND REPORTS ON WEL		AGREEMENT NAME
DAS		13	
DE	{Do not use this form for proposals to drill or to deepen or plug back to a d reservoir. Use Form 9-331-C for such proposals.)		OR LEASE NAME
DF			illa Apache Tribal 151
AS R	$A_{t}^{1. \text{ oil}}$ well $\square$ well $\bigotimes$ other <b>Representation</b>	9. WELL	
17 MAL	2. NAME OF OPERATOR		
1	Among Production Company		OR WILDCAT NAME
1		╼╉╄╉╍╊╉┈╎	Dakota/Undes. Gallup
	501 Airport Drive, Farmingeran Mi 84.701		T., R., M., OR BLK. AND SURVEY OR
A for the former and the	4. LOCATION OF WELL (REPORT LOGATION SEE AND SANTA FE	Berlin UULU	NE/NW, Section 3, T26N, R5W
		10 000	ITY OD DADICUL 12 OTATE
	AT SURFACE: 820' FNL x 1600' FWL AT TOP PROD. INTERVAL: Same		ITY OR PARISH 13. STATE
	AT TOTAL DEPTH: Same	Rio An	riba New Mexico
		IA. APIN	20.000 00/00 ·
	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO REPORT, OR OTHER DATA		30-039-20605 TIONS (SHOW DF, KDB, AND WD) 6591' GL
	Reform, on other barr	STARS. ELEV	ATIONS (SHOW DF, KDB, AND WD)
	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT	2'2 1983 2'2 1983	6591' GL
• ·	TEST WATER SHUT-OFF	1083	
	FRACTURE TREAT	9.6 15 A	
	SHOOT OR ACIDIZE	CURVE	
	REPAIR WELL	GEOLOGICA (NOTOR	eport results of multiple completion or zone
	PULL OR ALTER CASING	rologion	hange on Form 9-330.)
	MULTIPLE COMPLETE	GEVINO MESE	
	CHANGE ZONES	Aller	
e.	ABANDON*		
	(omer <u>)</u>		
	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clear	rly state all pertine	ent details, and give pertinent dates
	including estimated date of starting any proposed work. If w	ell is directionally	drilled, give subsurface locations and
	measured and true vertical depths for all markers and zones p		
	This sundry is to amend our subsequent real	completion su	ndry of 3-18-83. Rigged up
	service unit on 12-17-82. Total depth of	the well is	7749' and plugback depth is
	7716'. Perforated interval 6992'-7000' w	ith 4 JSPF fo	r a total of 32 holes, .38"
	in diameter. Fraced the interval with 37.	,110 gals of	20# crosslinked gel containir
	2% KCL and 43,000# 10-20 mesh sand. Set a	production pa	cker at 7432' and landed tubi
	at 7518'. Opened sliding sleeve at 7428'.	<ul> <li>Released t</li> </ul>	he rig on 12-27-82. Flow
	tested Gallup from 1-29-83 to 2-3-83. Mov	ved in and ri	gged up service unit on
4	3-9-83. Perforated intervals 6584'-6594',	6646'-6662'	, 6676'-6700', 6724'-6744',
	6754'-6762', 6794'-6842', 6878'-6924' with	n 2 JSPF. Fr	aced from 6584'-6924' with
	70 quality foam. Frac pressured out when	1.0 ppg sand	hit perfs. Refraced same
	interval with 32,633 gals 20# gelled water	and 20,600#	20-40 mesh sand. Landed
	2-3/8" production tubing at 7514'. Release	sed rig on 4-	2-83. Sliding sleeve is now
	closed on the Gallup pending approval of a	commingling o	rder. Basin Dakota is back o
	production. Subsurface Safety Valve: Manu. and Type		
	18. I hereby certify that the foregoing is true and correct		· · · ·
	Criginal Signed By	in Supurpers	Tuly 10 1002
	SIGNED D.D. Lawson Bray TITLE Dist. Adn	ULII OUPVI DATE	<u> </u>
	(This space for Federal or	State office use)	
			rc
	APPROVED BY TITLE TITLE		
the state of the s			TREEPTED FOR RECORD
	an magazina and a same		
0 + 5 MM	S, Farmington		IIII AM JAAA
1 - J.C.B	Irnside, Denver	Reverse Side	JUL 25 1983
1 - Open			
-r (	ju sile - Klulece OPFRATO	_	FACINCTON
and the second	OPERATO	8	RY_DIO
· · · · ·			

#### ATTACHMENT NO. 5

- 5/8/73 Drilled 15" surface hole to 316'. Set 10-3/4" casing at 316'. Cement with 300 sx Class "A" cement with 2% CaCl<sub>2</sub>. Circulated cement.
- 5/15/73 Set 7-5/8" intermediate casing at 3558'. Cement with 640 sx 50-50 Pozmix with 6% gel and 2 pounds Tuf Plug per sack and tail-in with 100 sx Class "C" Neat. No cement circulated.
- 5/22/73 Set 4-1/2 casing at 7749' and cemented with 375 sacks 50-50 Class "C" Pozmix with 6% gel and 2 pounds Tuf Plug per sack and tail-in with 100 sacks Class "C" Neat. No cement circulated.
- 5/29/73 Spotted 7-1/2 HCL and perforated 7659-80' and 7630-44' with 1 SPF. Sand-water fraced with 47,460 gallons water, 15,000# 20-40 sand and 15,000# 10-20 sand. Dropped from 40 BPM to 36 BPM at 3700 psi. Finish injecting 10,000# 20-40 sand and 10,000# 10-20 sand. Breakdown pressure was 2000 psi. Treating pressures: Maximum 3800, minimum 3600, average 3700 psi. AIR 37 BPM. Set 4-1/2" bridge plug at 7620'and tested with 3800 psi for 15 minutes. Test 0K. Perforated 7584-96 and 7482-96' with 2 SPF.
- 5/30/73 Sand-water fraced interval 7596-7482' with 47,530 gallons water. Spearhead frac with 500 gallons 7-1/2% HCL. Sand-water frac with 10,000# 20-40 sand and 10,000# 10-20 sand. Dropped 24 balls and had no effect on pressure or injection rate. Completed frac with additional 15,000# 20-40 sand and 15,000# 10-20 sand. Maximum pressure 3800, minimum 3650, average 3750 psi. AIR 33 BPM.
- 5/31/73 Landed 2-3/8" production tubing at 7641'.

#### Gallup Recompletion

- 12/17/82 RUSU x KILL Dakota well.
- 12/19/82 Perforate interval 7000-6992' with 4 JSPF.
- 12/22/82 Sand-water frac Gallup with 37,110 gallons 20 pound gelled water and 43,000 pounds 10-20 mesh sand. Breakdown at 1090 psi. Maximum treating pressure 3560, average treating pressure 2160, minimum treating pressure 1900. Average injection rate - 30 BPM.
- 12/25/82 Set production packer at 7432'.
- 12/26/82 Landed tubing at 7518' with sliding sleeve at 7428'.
- 1/29/83 Flow test Gallup.

	<u>hrs</u>	MCF	<u>B0</u>	BW
1/29/83	24	23	0	0
1/30/83	24	22	0	0
1/31/83	24	22	0	0
2/01/83	24	22	0	0
2/02/83	24	22	0	0
2/03/83	24	16	0	0

- 3/09/83 Move in rig up service unit.
- 3/10/83 Set retrievable bridge plug at 6985' and test to 3500 psi. Perforate intervals 6794-6842', and 6878-6924' with 2 JSPF.
- 3/11/83 Breakdown formation at 1100 psi. Set retrievable bridge plug at 6786'. Pressure test to 3500 PSi. Perforate intervals 6584-6594", 6646-6662', 6676-6700', 6724-6744' and 6754-6762' with 2JSPF.
- 3/12/83 Retrieved bridge plug at 6786'.
- 3/13/83 Frac Gallup with 70 percent quality foam and 20-40 mesh sand. Frac pressured out when 1.0 ppg sand hit perfs.
- 3/15/83 Frac Gallup with 32,633 gallons 20 pounds gelled water and 20,600 pounds of 20-40 sand. Maximum treating pressure 3500 minimum treating pressure 1900 psi. Average treating rate was 30 BPM.
- 4/02/83 Land 2-3/8" production tubing at 7514 with sliding sleeve at 7428.

		Flow test Gallu	p	
Date	Hrs	MCF	BO	BW
4/19/83 4/20/83	24 24	65 45	0 0	1.4 0

Sliding sleeve is now closed on the Gallup horizon and the Basin Dakota is back on production.

AM13

				10	
	100	0000 	MCFD		
-	MAR				
	JUN.				Basi Jica
	DEC.				n Dak rílla
0	MAR.				kota Apacl
	SEP.				che
-	MAR.				Triba
36	JUN. SEP.				L1 15
	DEC.				l No
1077	MAR.				4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	SEP.				
0	MAR.				
<u>18</u>	JUN.				
1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -					
2					
	SEP.				
1070	MAR:				
1. A.	SEP:				
10	MAR				
18	JUN. Come of the second				
1 1 1	DEC.			经日本 巨铁 计可读自由目标时间间 法金属气	
282	JUN.				
	DEC.	recompleting Ga	- 1   1   2   2   2   2   2   2   2   2		
$\mathbb{C}$	MAR.				
11	SEP.				
	DEC.				

à

	ANN ANN ANN ANN ANN ANN ANN ANN ANN ANN		NIN NIN NIN NIN NIN NIN NIN NIN NIN NIN	DAY
	130 - 20 - 20 - 20 - 20 - 20 - 20 - 20 -	- DAYS	Werren 28 10 10 10 10	ELL NAME
	200 444 20 200	Ë	15-20-20-20-20-20-20-20-20-20-20-20-20-20-	В
•	Report to the second se	- 0 2	AAAAAAAAAAAA	JICARILLA APE C 3 26N 5W BASIN DAKOTA
	3162 3162 3162 3162 3162 3162 3162 3162	м О т	5309 5309 5308 5308 5308 5308 5308 5308 5308 5308	APACHE TRIBAL
· .	137 137 137 137 137 137 137 137 137 137	MCFD	187 187 188 188 188 188 188 188 188 188	BAL_151 #4 MCFD
	JAN FEB MAR APR JULY JULY NOV DEC		JAH FEB MAR JUNE JUNE SEPT OCT NOV	-
-	EPT IN ECT IN IN ECT IN	285 DAYS	JAH FEB MAR APR JUNE JUNE SEPT SEPT JDEC Lo	DAYS
		روز PAAR HO	Lun Relative Viv	DAYS
•	E D A	· · · ·	22 22 22 22 22 22 22 22 22 22 22 22 22	
	E0006	- но ВО - но	27 27 27 27 27 27 27 27 27 27 27 27 27 2	BC
	E 000	BO BW M	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	BC

1981

Attachment 6 con't

No well will be asrigned an allowable greater than the amount of oll produced on the official test. During gas-oil ratio test, each well shall be produced at a rate not exceeding the top unit allowable for the pool in which well is located by more than 25 percent. Operator is encouraged to take advantage of this 25 percent tolerance in order that well can be assigned increased allowables when authorized by the Division. Gas volumes must be reported in MCF measured at a pressure base of 15.025 psia and a temperature of 60° F. Specific gravity base will be 0.60. Report casing pressure in lieu of tubing pressure for any well producing through casing. Ma <sup>11</sup> original and one copy of this report to the district office of the New Mexico Oil Conservation Division in accordance with Ruie 301 and appropriate pool rules.	Attachment 7	Jicarilla Apache Tribal 151 4 C	LEASE NAME NO. U		Address 501 Airport Drive, Farmington, NM 8	Operator Amoco Production Company		STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT
the am to tak t a pre t a pre listrict		ω	s	Гос	87401			
ount of e advun e sure bs well proc		26N		LOCATION		Pcol Basín		
oll prod c not ex tage of 1 ase of 1 ducing th ducing the N		5W		z		ı Dakota		(
in the amount of oll produced on the official test. oduced at a rate not exceeding the top unit allowable for d to take advantage of this 25 percent tolerance in order t at a pressure base of 15.025 psia and a temperature of 60° at a pressure base of 15.026 psia and a temperature of 60° for any well producing through casing. district office of the New Mexico Oil Conservation Divisi		May Production	TEST	DATEOF		ta	GAS-OIL R	SANTA FE, NEW MEXICO 87501
1] test.  erance  erance		<u> </u>	STAT		TYPE TEST		RATIO	V ME:
in order ture of 6	•		SIZE		ιо (Х)		) TESTS	8 CICO 87
r the pool that well D <sup>o</sup> F. Spe sion in a			П	тво	 Sc		S	501
he pool in which well is at well can be assigned F. Specific gravity base on in accordance with	·		ALLOM-	DAILY	Scheduled XX	Con Rí		×
11 i a		96	TEST HOURS	CENGTH		County Rio Arriba		
I hereby certify is true and comp ledge and belief. District E July 1		6	WATER BBLS.	סי	Comp			
hereby cert ue and com e and belin pale H District July		61	GRAV.	ROD.	Completion	County		
y certify that the nd complete to the d belief. <i>(Signature</i> <i>(Signature</i> ) <i>(Title)</i> July 14, 1983		00	Bars	PROD. DURING				7 F
ity that the abov plete to the best f. (Signature) Engineer (Title) 14, 1983		1464	GAS M.C.F.	TEST	Spe			Form C-116 Revised 10-1-78
I hereby certify that the above information is true and complete to the best of my know- ledge and belief. Dele H Indernale District Engineer July 14, 1983		183,000	RATIO CU.FT/BBL	GAS - OIL	Special			78

\_ 1

Report casing pressure in lieu of tubing pressure for any well producing through casing. Mati original and one copy of this report to the district office of the New Mexico Oil Conservation Rule 301 and appropriate pool rules.	No well will be assigned an allowable greater than the amount of all produced on the official test. During gassoil ratio test, each well shall be produced at a rate not exceeding the top unit allowable for the pool in which well is located by more than 25 percent. Operator is encouraged to take advuntage of this 25 percent tolerance in order that well can be assigned increased allowables when authorized by the Division. Gas volumes must be reported in MCF measured at a pressure base of 15,025 psia and a temperature of 60° F. Specific gravity base will be 0.60.		<b>A</b> ttachment	8	Jicarilla Apache Tribal 151	ר ח זיטע זיע זיע		Address 501 Airport Drive, Farmington,	Operator Amoco Production Company		STATE OF NEW MEXICO	
bing pres report to	ole greate 11 shall l 15 encou e Divisi CF meas				4	2 0	WELL	on, NM			ICO ARTMEN	
the di	er than t be produ uraged t		 		C	с		ļ			-	
any wel strict of	he amou iced at o take i a press	· ·	 		<u>س</u>	S.	LOCA	87401	Pcol U1			
l produc fice of	int of ol a rate i advantag				26N	-	ATION		ndesi			
ing thro the New	l produc not exce se of thi				5W	ככ			ol Undesignated		ŝ	( 7
ugh casing. / Mexico Oil Con	ed on the officia reding the top ur is 25 percent tol )25 paia and a te				4-19-83 - 4- <b>2</b> 1-83	TEST	DATEOF		d Gallup	GAS-OIL R	P. O. BOX 2088 SANTA FE, NEW MEXICO 875	OF CONSERVATION DIVISION
servati	l test. nit allo crance					STA		TYPE TEST		RATIO	V M MX	
on Divisi	wable for t in order th ure of 60°					SIZE	CHOKE	1 0 17 X		TESTS	100 87	i U i K
sion in ac	r the pool i that well 0° F. Speci		 		-	PRESS.	TBG.	Sche		S	501	U C N
ion in accordance with	he pool in which well ta at well can be assigned F. Specific gravity base						DAILY	Scheduled	Cot			·
5				<u>, , , , , , , , , , , , , , , , , , , </u>	48	TEST	CEXCTH		County R:			
	I hereby certify is true and comp ledge and belief.				1.4	WATER BBLS.	ק	Compl	Rio Arriba			
District	eby ce and co and bel					GRAV.	PROD.	Completion				
(Sig	rtify tha omplete t lief.				0		ရ		County		For	
Lhoema (Signature) Engineer	t the abov the best				110	GAS M.C.F.	TEST	Spec			Form C-116 Revised 10-1-78	
ke	I hereby certify that the above information is true and complete to the best of my know- ledge and belief.					CU.FT/88L	GAS - CIL	Special X			78	

----

, July 14, 1983

	•	BOTTOM HOLE	PRESSURE DATA	į	•	
				-	- 10 <sup>-</sup>	
	WELL NAME &	NO. JIC/ ELD Daka	31-7		• ·	
	FI	ELD Daka	t.c.		•	
	•*				•	
	st <u>5-5-8</u>	3		•	• . • •	
Ce OI Te	st <u>J-J -</u>		مەربىيە بەرمەي بەرمەيمەر بەر بەر بەر بەر بەر بەر بەر بەر بەر ب	<u></u>		
	etion Data	. · · · ·				
		•	•			
Total	Depth			-	······	
Plugg	ed Back Depth	• •		••••••••••••••••••••••••••••••••••••••		
Produ	ction Casing		·	"-CSA	<u>F</u>	t.
10071	ŏ		······································	" Landed At	F	t.
	ng Nipple Dept					*******
Perio	rations				-	
	· · ·				•	
Mid-P	oint Perforati tion (Sub-Sea)	ons		· · · · · · · · · · · · · · · · · · ·	······	
Eleva	tion	GL;	والمحاور والمحاوي والمحاور وا	DF;	I	DB
Datum	(Sub-Sea)			·	······	
				-		
essure D	lata				e-	
	· · · · · · · · · · ·					
	in Tubing Drag	1/0	·. · ·		5 50	
Shut-	in Tubing Pres	ssure $760$ .				
Shut- Shut-	in Tubing Pres in Casing Pres	ssure <u>160</u> ssure <u>1040</u>				SIC SIC
Shut-	in Tubing Pres in Casing Pres e Pressure Dat	ssure 1040				SIC SIC
Shut-	in Casing Pres e Pressure Dat	ssure <u>1048</u>				
Shut- ottom Hol Type	in Casing Pres <u>e Pressure Dat</u> Instrument Use	ssure $1048$ and $AMERap$	× RP6-3			
Shut- ottom Hol Type Press	in Casing Pres <u>e Pressure Dat</u> Instrument Use sure Range of F	ssure $1048$ and $AMERap$ Element $6-7$	× RP6-3			
Shut- ottom Hol Type Press	in Casing Pres <u>e Pressure Dat</u> Instrument Use	ssure $1048$ and $AMERap$ Element $6-7$	× RP6-3			
Shut- <u> Sttom Hol</u> Type Press Date	in Casing Pres e Pressure Dat Instrument Use wre Range of F Element Caliby	ssure $1048$ and $AMERap$ Second $G-2$ rated	2 176-3 3000		P 5	SIC
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use sure Range of F Element Caliby Depth Stopped	ssure $1048$ ad $AMERep$ Element $6-3$ rated Extension	Pressure	- Gradient		31C
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres e Pressure Dat Instrument Use wre Range of F Element Caliby	ssure $1048$ and $AMERap$ Second $G-2$ rated	<u>Pressure</u> <u>757</u>		P 5	31C
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use sure Range of F Element Caliby Depth Stopped	ssure $1048$ ad $AMERep$ Element $6-3$ rated Extension	Pressure		P 5	31C
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	31C
Shut- <u>ttom Hol</u> Type Press Date <u>I</u>	in Casing Pres e Pressure Dat Instrument Use sure Range of F Element Caliby Depth Stopped Surface	ssure $1048$ $\frac{1048}{1048}$ $\frac{1048}{1000}$ $\frac{1048}$	<u>Pressure</u> <u>757</u>		P 5	SIC
Shut- <u>ttom Hol</u> Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	SIC
Shut- <u>ttom Hol</u> Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	SIC
Shut- <u>ttom Hol</u> Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	SIC
Shut- <u>ttom Hol</u> Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	31C
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	31C
Shut- ttom Hol Type Press Date <u>I</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u> <u>1099</u>		P 5	31C
Shut- <u>ettom Hol</u> Type Press Date <u>T</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u>		P 5	31C
Shut- <u>ettom Hol</u> Type Press Date <u>ree</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u> <u>1099</u>		P 5	31C
Shut- <u>ettom Hol</u> Type Press Date <u>T</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u> <u>1099</u>		P 5	31C
Shut- <u>ettom Hol</u> Type Press Date <u>ree</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u> <u>1099</u>		P 5	31 <b>C</b>
Shut- <u>ettom Hol</u> Type Press Date <u>ree</u>	in Casing Pres <u>e Pressure Dat</u> Instrument Use ure Range of F Element Calibr Depth Stopped <u>Surface</u> <u>6706</u>	ssure $1048$ Ea AMERap Blement G = 2 rated Extension 499 -652	<u>Pressure</u> <u>757</u> <u>991</u> <u>1099</u>		P 5	SIC

Attachment-10

BOTTOM HOLE PRESSURE DATA HELL NAME & NO. <u>Jie Apriche 151-4</u> FIELD <u>Gallup</u> Date of Test 4-28-83 Well Completion Data Total Depth Plugged Back Depth ... "·CSA Production Casing Ft. " Landed At \_\_\_\_\_ Ft. Tubing Seating Nipple Depth Perforations Mid-Point Perforations Elevation \_\_\_\_\_ GL; \_\_\_\_\_ DF; RDB Datum (Sub-Sea) Pressure Data 900 Shut-in Tubing Pressure PSIG Shut-in Casing Pressure 900 **PSIG** Fottom Hole Pressure Data Type Instrument Used amerada RPG-3 Element Pressure Range of Element 0- 3000 Date Element Calibrated Extension Depth Scopped Pressure -Gradient Temperature Tine Surface . 4.27 64-7 835 BA 550 835 Datun \_\_\_\_\_ BHP Remarks 

SOUTHERN UNION GAS COMPANY REPORT OF BTU TEST RESULTS

## AMOCO PROD CO AMOCO APACHE 151 4 (DAKota) 2991

NORTHWEST NEW MEXICO

4/20/82 5/13/81 DATE OF THIS TEST: DATE OF LAST TEST: TEST FREQUENCY: NOT SPECIFIED

RESULTS

TO:

REF:

3:	SPECIFIC GRAVIT BTU/CF @ 14.73/		0.9972 1167.2
		MOL %	G. P. M.
	CARBON DIOXIDE	0.709	0. 0000
	NITROGEN	0.142	0. 0000
	METHANE	86, 600	0, 0000
	ETHANE	8.010	2.1410
	PROPANE	2.385	0, 6560
	ISOBUTANE	0.485	0, 1580
	N-BUTANE	0.642	0, 2020
	ISOPENTANE	0.274	0.1000
	N-PENTANE	0.216	0.0780
	HEXANE +	0.558	0. 2460

TOTAL

0.558 100.021

3.5810

-----

( 70)

(677)

## CHEMICAL & GEOLOGICAL LABORATORIES

Attachment 12

P.O. Box 2794 Casper, Wyoming 82602

#### GAS ANALYSIS REPORT

Company	Amoco Production Co.	Date	2-11-83	Lab. No	A30051-2
Well No	Jicarilla Apache 151-4	Location			<u> </u>
Field	Otero Gallup	Formation	Gallup		
County	Rio Arriba	Depth	· · ·		
State	New Mexico	Sampling point	· · · · · · · · · · · · · · · · · · ·		
	<u>45 psig;</u> Sample pressure2psig;				RG # 3125
Remarks			· · ·		
	(2-1-83)				
					4

Component	Mole % or Valuna %	
Oxygen	0	
Nitrogen	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	
Carbon dioxide		
Hydrogen sulfide	• -	i.
Methane		Gallons
Ethane		per MCF
Propane		1.481
Iso-butane		0.294
N-butane.		0.585
lso-pentane		0.190
N-pentane	0.39	0.141
Hexanes & higher	0.20	0.092
	100.00	2,783
GPM of pentanes & higher fraction	0.	.423
Gross btu/cu. ft. @60° F. & 14.7 psia (dry basis)	······	1271
Specific gravity (calculated from analysis)		.733
Specific gravity (measured)	·····	736
Remarks:	•	

.

}

ENGINEER

		ANALYSIS # 3 Q	Ζ
DIRECT ANY QUESTIONS TO: CLAY TERRY DISTRICT ENGINEER 505-327-6222		THE WESTERN CO LABORATORY SER P.O. DRAWE FARMINGTON,	VICES R 360 N.M.
	ANALYSIS		
OPERATORAMOCO PRODUCTION	DATE SAMPLED	5-24-	-83
WELL JICARILLA APACHE 151 #	4 DATE RECEIVED	5-26-	-83
FIELD BASIN DAKOTA T R	SUBMITTED BY	MORRI	IS BELL
FORMATIONDAKOTA	WORKED BY	CLAY	TERRY
DEPTH	SAMPLE DESCRI	PTION <sup>DINGY</sup> , RUSTY	COLORED
COUNTLATO ARKIBA	· · · · · · · · · · · · · · · · · · ·	UTION. NO SUSPEN	IDED MATERIAL
STATE NEW MEXICO	NOTICABLE.		
	TERMINATIONS	· · · · · · · · · · · · · · · · · · ·	x
SPECIFIC GRAVITY 1.01 AT 60 °F	TOTAL DISSOLV	ED SOLIDS 15,5	519 ppm
	RESISTIVITY	0.41	F
pH7_0	(Ohm-meters)		$\frac{\Delta I - M}{(CALC)}$
CHEMICAL DE	TERMINATIONS		· · · · · · · · ·
IRON_Fe <sup>++</sup> 15 ppm / Fe <sup>±++</sup> -0- ppm	PHOSPHATE	<u>_</u>	
HYDROGEN SULFIDE -0-	SULFATE	1875	ppm
TOTAL HARDNESS 1200 PP	m BICARBONATE	647	ppm
CALCIUM240PF		7292	ррт
MAGNESIUM 146 PP	SODIUM & DOTASSIUM	5319	ppm
COMMENTS:			
			<u> </u>
·			
for Stiff type plot (in meq./1.)		n y, andarana Manana a a a a a a a a	
Na & K 50 40 30 20 10	0 10 20	30 40 50	C)
	· • <del>,   • • • • • • • • • • • • • • • • • • </del>	<del>╶╶╎╽╹╵╹╵╎╵╹╹╹╹╹╹╹╹╹</del>	100
	<b>└<del>┥</del>╎<mark>╞</mark>┼┽┼╎<u></u>┼┼┼┼┼┼</b>	<del>╅╋╎╋╋╋╋╞╗╋╋┥┥</del>	HCO,
Mg 3 + + + + + + + + + + + + + + + + + +	· • • • • • • • • • • • • • • • • • • •	<del>╻╻<mark>╎</mark>╻╻╻╻╻</del>	50.
			10
<del>╏╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹╹</del>		HITT MITTIN	ł

Analyst <u>Clay</u> TERRY



## EULLEELLULE LEETEEW CORDECECS



WATER TES	ST FOR INORGAN	IC CONTAMI	NATES		
PROJECT:	AMOCO PRODUCTIO	ON CO.	I.D. 1	Number: 4-049	
REPORT TO	): M. Bell	$\sim$	PROJE	CT NO.:	
	) BY: <u>M. Bell</u>		SAMPL	ED BY: M. Bell	
LOCATION	OF SAMPLE:	Jicarilla Apa	ache Tribal 151 N	10.4 - Wellhead Gallup	
DATE SAME	LED: 5/12/83	TE	STED BY: Nic	•	
DATE RECH	EIVED: 5/13/8:	3		·	
	DATE TESTED		PARAMETER	RESULT	
4-049-1	5/16/83	water	рН	6.95	
			Resistivity	0.33 ohm-meters	
			Hydroxide	none	
			Carbonate	none	
			Bicarbonate	108 mg/l as CaCO <sub>3</sub>	
			Total Dissolved Solids	21008 mg/1	
			Chloride	11600 mg/1	
			Sulfate	73 mg/1	
			Nitrate	3.8 mg/l as Nicrogen	
			Sodium	10800 _mg/1	
			Potassium	500 mg/1	
			Calcium	448 mg/lasCa	
COMMENTS:			Magnesium	600 mg/l as Mg	
		·	Total Hardness	3506 mg/l as CaCO <sub>3</sub>	_
COPIES TO:	AMOCO PRODUCTIO	ON CO.		> oglettope	
	501 Airport Dri	ive	TESI	YED BY:	
	Farmington, NM	87401			
Attn:	M. Bell		REVI	EWED BY: Stan Lueck, Sr. Cho	

Basin Dakota 1982	Aver	200 Dm 1					
Gallup Production	durin	ng foot	ction	~	150.4	MCFD	
	Lest			-	55.0	MCFD	
Basin Dakota	_	150 /				MCFD	Total
Gallup		$\frac{150.4}{205.4}$		73.22%	of total	product	ion
Carrob	-	<u>55</u> 205.4	=	26.78%	of total	producti	.on

# Formula for Allocation of Production

Sec. 1




S. D. Blossom District Superintendent

August 3, 1983

Amoco Production Company

Petroleum Center Building 501 Airport Drive Farmington, New Mexico 87401 505-325-8841



OIL CONSERVATION UNIDION Union Texas SANTA FE 14001 E. Iliff Ave. 80014 Aurora, CO

El Paso Natural Gas Company P.O. Box 990 Farmington, NM 87401

Minerals Management Services Drawer 600 87401 Farmington, NM

DHS-363-986.510.1 File:

Proposed Downhole Commingling of Jicarilla Apache Tribal 151 No. 4, Rio Arriba County, New Mexico

This is to advise you that the Farmington District Office of Amoco Production Company is requesting approval from the New Mexico Oil Conservation Division to downhole commingle production from the well below:

Jicarilla Apache Tribal 151 No. 4, Unit C, Section 3, T26N, R5W

This well has been completed in the Basin Dakota and Undesignated Gallup

Enclosed is a wellbore diagram and a map showing the location of offset

If you, as an offset operator, have no objections to the commingling of production from the Basin Dakota and Undesignated Gallup pools of the subject well, please sign the waiver below and send to:

New Mexico Oil Conservation Division Box 2088 87501 Sante Fe, NM


We would appreciate your sending one executed copy to the undersigned.

Very truly yours,

MJB/gw Enclosures Page 2 August 3, 1983 File: DHS-363-986.510.1

### Waiver

We hereby waive any objections to Amoco Production Company's application for commingling as set forth above.





S. D. Blossom

**District Superintendent** 

August 3, 1983

AUG 1 5 1983

SANTA FE

El Paso Natural Gas Company P.O. Box 990 Farmington, NM 87401

Union Texas 14001 E. Iliff Ave. Aurora, CO 80014

Minerals Management Services Drawer 600 Farmington, NM 87401

File: DHS-363-986.510.1

Proposed Downhole Commingling of Jicarilla Apache Tribal 151 No. 4, Rio Arriba County, New Mexico

This is to advise you that the Farmington District Office of Amoco Production Company is requesting approval from the New Mexico Oil Conservation Division to downhole commingle production from the well below:

Jicarilla Apache Tribal 151 No. 4, Unit C, Section 3, T26N, R5W

This well has been completed in the Basin Dakota and Undesignated Gallup pools.

Enclosed is a wellbore diagram and a map showing the location of offset wells.

If you, as an offset operator, have no objections to the commingling of production from the Basin Dakota and Undesignated Gallup pools of the subject well, please sign the waiver below and send to:

New Mexico Oil Conservation Division Box 2088 Sante Fe, NM 87501

We would appreciate your sending one executed copy to the undersigned.

Very truly yours,

S.D. Blossom

MJB/gw Enclosures

Amoco Production Company

Petroleum Center Building 501 Airport Drive Farmington, New Mexico 87401 505-325-8841

1983

AHG 4

EL PASO NATURAL GAS

Page 2 August 3, 1983 File: DHS-363-986.510.1

#### <u>Waiver</u>

We hereby waive any objections to Amoco Production Company's application for commingling as set forth above.

Co. location aso C Company <u>8-10-83</u> Date Bna

AM13