LOGGED IN 05/3

APPROPRE 1321741308

ABOVE THIS LINE FOR DIVISION USE ONLY

NEW MEXICO OIL CONSERVATION DIVISION

- Engineering Bureau -



		1220 South St. Francis Drive, Santa Fe, NM 87505			
		ADMINISTRATIVE APPLICATION CHECKLIST			
	cation Acronym [NSL-Non-Sta [DHC-Dow [PC-Po	ANDATORY FOR ALL ADMINISTRATIVE APPLICATIONS FOR EXCEPTIONS TO DIVISION RULES AND REGULATIONS WHICH REQUIRE PROCESSING AT THE DIVISION LEVEL IN SANTA FE s: ndard Location] [NSP-Non-Standard Proration Unit] [SD-Simultaneous Dedication] nhole Commingling] [CTB-Lease Commingling] [PLC-Pool/Lease Commingling] pol Commingling] [OLS - Off-Lease Storage] [OLM-Off-Lease Measurement] [WFX-Waterflood Expansion] [PMX-Pressure Maintenance Expansion] [SWD-Salt Water Disposal] [IPI-Injection Pressure Increase] lified Enhanced Oil Recovery Certification] [PPR-Positive Production Response]			
[1]	_	PPLICATION - Check Those Which Apply for [A]			
[1]	[A]	Location - Spacing Unit - Simultaneous Dedication NSL NSP SD			
	Check [B]	Cone Only for [B] or [C] Commingling - Storage - Measurement DHC CTB PLC PC OLS OLM Injection - Disposal - Pressure Increase - Enhanced Oil Recovery WFX PMX SWD PIPI EOR PPR			
	[C]	Injection - Disposal - Pressure Increase - Enhanced Oil Recovery ☐ WFX ☐ PMX ☐ SWD ☑ IPI ☐ EOR ☐ PPR			
	[D]	Other: Specify SWD - 526			
[2] NOTIFICATION REQUIRED TO: - Check Those Which Apply, of Does Not Apply [A] Working, Royalty or Overriding Royalty Interest Owners					
	[B]	Offset Operators, Leaseholders or Surface Owner			
	[C]	Application is One Which Requires Published Legal Notice			
	[D]	Notification and/or Concurrent Approval by BLM or SLO U.S. Bureau of Land Management - Commissioner of Public Lands, State Land Office			
	[E]	For all of the above, Proof of Notification or Publication is Attached, and/or,			
	[F]	☐ Waivers are Attached			
[3]		CURATE AND COMPLETE INFORMATION REQUIRED TO PROCESS THE TYPE ATION INDICATED ABOVE.			
	val is accurate a	TION: I hereby certify that the information submitted with this application for administrative and complete to the best of my knowledge. I also understand that no action will be taken on this quired information and notifications are submitted to the Division.			
	N ote:	Statement must be completed by an individual with managerial and/or supervisory eapacity.			
	or Type Name	Sp. Regulatory Alvisor 7/30/3 Title Date			
	USA Inc Tank 28	Sp. Regulatory Alvisor 7/30/3 Title Date 16696 Federal #3 SWD-526 Sp. Regulatory Alvisor 7/30/3 Date david_stauent@oxy.com e-mail Address 432-665-57/7			
30-025-31754					

To: New Mexico Oil Conservation Division

Attn: Phillip R. Goetze, P.G.

OXY USA Inc. (16696) formally requests an increase in maximum injection pressure to 1100 psi for the following approved SWD permit. The justification will be presented herein.

Well Name: Red Tank 28 Federal 3

API#: 30-025-31754

330 FNL 2310 FEL NWNE(B) Sec 28 T22S R32E

Administrative Order SWD-526 7/13/93

The SWD well is completed in the Bell Canyon and Cherry Canyon (4674-5748') with 2.875" composite lined tubing (2.25" ID) set at a depth of 4600'. See Figure 1 below:




Figure 1: Red Tank 28 Federal 3 Well Schematic.

On 7/9/2013 a planned step rate test was performed on the Red Tank 28 Federal 3 to identify the formation parting pressure, thus determining a maximum allowable injection pressure. The well was back flowed for 4hrs, then shut-in for an additional 12 hrs to ensure accurate testing results. The step-rate test was then conducted at the below rates utilizing treated water and a mobile pump truck. Pump rates were maintained for 15 minutes or until we achieved a stable injection pressure. Table 1 displays the injection rate for each step along with the corresponding surface treating pressure at the well head.

Rate [bbls/day]	Rate [bbls/min]	Cumulative Volume Pumped [bbls]	Tubing Head Pressure [psi]
432	0.30	5	994
576	0.40	11	1142
720	0.50	18	1195
864	0.60	27	1221
1008	0.70	38	1246
1152	0.80	50	1263
1296	0.90	63	1289
1440	1.00	78	1318
1800	1.25	97	1351
2160	1.50	119	1534
2520	1.75	146	1685
2880	2.00	176	2046
3600	2,50	213	2598
4320	3.00	258	3198
4608	3.20	290	3559

Table 1: Red Tank 28 Federal 3 Step Rate test data.

The formation parting pressure was determined to be 3201 psi during the step-rate test (See Figure 2.) The corresponding surface treating pressure when the formation parted was 1158 psi. The requested 1100 psi surface injection pressure represents an equivalent bottom-hole pressure well below the formation parting pressure. A conservative approach was taken in regards to injection rates in order to eliminate the possibility of fracture propagation into a non-disposal zone, thus the step rate test was terminated once we were able to determine that the formation parted.




Figure 2: Surface Treating Pressure & Calculated Bottom Hole Pressure versus injection rate.

Please advise if any additional data is required in order to make a ruling of the proposed increase in permitted injection pressure.

Best regards

Joseph M. Evans
Production Engineer
SE New Mexico Reservoir Management Team
OXY Permian Primary Development.
Office - 713-350-4640
Cell - 713-855-0624
joseph_evans@oxy.com

cc: NMOCD-Hobbs, BLM-Carlsbad

STATE OF NEW MEXICO



ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION



BRUCE KING GOVERNOR

ANITA LOCKWOOD CABINET SECRETARY

POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87504 (505) 827-5800

CORRECTED ADMINISTRATIVE ORDER SWD-526

APPLICATION OF POGO PRODUCING COMPANY FOR SALT WATER DISPOSAL, LEA COUNTY, NEW MEXICO.

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), Pogo Producing Company made application to the New Mexico Oil Conservation Division on June 21, 1993, for permission to complete for salt water disposal its Red Tank "28" Federal Well No. 3 located 330 feet from the North line and 2310 feet from the East line (Unit B) of Section 28, Township 22 South, Range 32 East, NMPM, Lea County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and
- (4) No objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED THAT:

The applicant herein, Pogo Producing Company is hereby authorized to complete its Red Tank "28" Federal Well No. 3 located 330 feet from the North line and 2310 feet from the East line (Unit B) of Section 28, Township 22 South, Range 32 East, NMPM, Lea County, New Mexico, in such manner as to permit the injection of salt water for disposal purposes into the Bell Canyon and Upper Cherry Canyon formations at approximately 4690 feet to 5800 through 2 7/8-inch plastic-lined tubing set in a packer located at approximately 4600 feet.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

The injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 938 psi.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Bell Canyon and Upper Cherry Canyon formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of disposal equipment and of the mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing, or packer in said well and shall ake such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER THAT, jurisdiction of this cause is hereby retained by the Division for the entry of such further order or orders as may be deemed necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of the operator to conduct operations in a manner which will ensure the protection of fresh water or in a manner inconsistent with the requirements set forth in this order, the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall submit monthly reports of the disposal operations in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

Corrected Administrative Order SWD-526 Pogo Producing Company July 22, 1993 Page 3

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

Approved at Santa Fe, New Mexico, on this 13th day of July, 1993.

WILLIAM LEMAY, Director

WJL/BES/amg

xc: Oil Conservation Division - Hobbs

US Bureau of Land Management - Carlsbad