540

PMAM 728358585

ABOVE THIS LINE FOR DIVISION USE ONLY

### NEW MEXICO OIL CONSERVATION DIVISION

- Engineering Bureau -

1220 South St. Francis Drive, Santa Fe, NM 87505



### ADMINISTRATIVE APPLICATION CHECKLIST THIS CHECKLIST IS MANDATORY FOR ALL ADMINISTRATIVE APPLICATIONS FOR EXCEPTIONS TO DIVISION RULES AND REGULATIONS WHICH REQUIRE PROCESSING AT THE DIVISION LEVEL IN SANTA FE **Application Acronyms:** [NSL-Non-Standard Location] [NSP-Non-Standard Proration Unit] [SD-Simultaneous Dedication] [DHC-Downhole Commingling] [CTB-Lease Commingling] [PLC-Pool/Lease Commingling] 5 [OLS - Off-Lease Storage] [OLM-Off-Lease Measurement] [PC-Pool Commingling] **IWFX-Waterflood Expansion** [PMX-Pressure Maintenance Expansion] [SWD-Salt Water Disposal] [IPI-Injection Pressure Increase] [PPR-Positive Production Response] [EOR-Qualified Enhanced Oll Recovery Certification] Abbev State SWD #1 TYPE OF APPLICATION - Check Those Which Apply for [A] [1] Location - Spacing Unit - Simultaneous Dedication 2290' FNL & 1200' FEL □ NSL □ NSP □ Sec 36 T10S R27E Check One Only for [B] or [C] Chaves County, NM. [B] Commingling - Storage - Measurement □ OLM 30-005-62556 ☐ CTB ☐ PLC ☐ PC ☐ OLS Injection - Disposal - Pressure Increase - Enhanced Oil Recovery [C] □ WFX □ PMX ☒ SWD □ IPI □ EOR □ PPR [D]Other: Specify **NOTIFICATION REQUIRED TO:** - Check Those Which Apply, or $\square$ Does Not Apply [2] Working, Royalty or Overriding Royalty Interest Owners [B] X Offset Operators, Leaseholders or Surface Owner Application is One Which Requires Published Legal Notice [C] [D]Notification and/or Concurrent Approval by BLM or SLO U.S. Bureau of Land Management - Commissioner of Public Lands, State Land Office [E]For all of the above, Proof of Notification or Publication is Attached, and/or, [F] Waivers are Attached SUBMIT ACCURATE AND COMPLETE INFORMATION REQUIRED TO PROCESS THE TYPE OF [3] APPLICATION INDICATED ABOVE. CERTIFICATION: I hereby certify that the information submitted with this application for administrative approval is accurate and complete to the best of my knowledge. I also understand that no action will be taken on this application until the required information and notifications are submitted to the Division. Note: Statement must be completed by an individual with managerial and/or supervisory capacity. Consulting Pet Engineer John Maxey September 14, 2017 Print or Type Name jcm@maxeyengineering.com

e-mail Address

STATE OF NEW MEXICO ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

### Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, New Mexico 87505

FORM C-108 Revised June 10, 2003

### APPLICATION FOR AUTHORIZATION TO INJECT

I.	PURPOSE: Secondary Recovery Pressure Maintenance X Disposal Storage Application qualifies for administrative approval? X Yes No
II.	OPERATOR: Hadaway Consulting and Engineering, LLC
	ADDRESS: PO Box 188, Canadian TX 79014
	CONTACT PARTY: John Maxey PHONE: (575) 623-0438
III.	WELL DATA: Complete the data required on the reverse side of this form for each well proposed for injection.  Additional sheets may be attached if necessary.
IV.	Is this an expansion of an existing project? Yes X No  If yes, give the Division order number authorizing the project:
V.	Attach a map that identifies all wells and leases within two miles of any proposed injection well with a one-half mile radius circle drawn around each proposed injection well. This circle identifies the well's area of review.
VI.	Attach a tabulation of data on all wells of public record within the area of review which penetrate the proposed injection zone. Such data shall include a description of each well's type, construction, date drilled, location, depth, record of completion, and a schematic of any plugged well illustrating all plugging detail.
VII.	Attach data on the proposed operation, including:
	<ol> <li>Proposed average and maximum daily rate and volume of fluids to be injected;</li> <li>Whether the system is open or closed;</li> <li>Proposed average and maximum injection pressure;</li> <li>Sources and an appropriate analysis of injection fluid and compatibility with the receiving formation if other than reinjected produced water; and,</li> <li>If injection is for disposal purposes into a zone not productive of oil or gas at or within one mile of the proposed well, attach a chemical analysis of the disposal zone formation water (may be measured or inferred from existing literature, studies, nearby wells, etc.).</li> </ol>
*VIII.	Attach appropriate geologic data on the injection zone including appropriate lithologic detail, geologic name, thickness, and depth. Give the geologic name, and depth to bottom of all underground sources of drinking water (aquifers containing waters with total dissolved solids concentrations of 10,000 mg/l or less) overlying the proposed injection zone as well as any such sources known to be immediately underlying the injection interval.
IX.	Describe the proposed stimulation program, if any.
*X.	Attach appropriate logging and test data on the well. (If well logs have been filed with the Division, they need not be resubmitted).
*XI.	Attach a chemical analysis of fresh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken.
XII.	Applicants for disposal wells must make an affirmative statement that they have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground sources of drinking water.
XIII.	Applicants must complete the "Proof of Notice" section on the reverse side of this form.
XIV.	Certification: I hereby certify that the information submitted with this application is true and correct to the best of my knowledge and belief.
	NAME: John C. Maxey TITLE: Consulting Petroleum Engineer
	SIGNATURE: DATE: September 14, 2017
*	E-MAIL ADDRESS: jcm@maxeyengineering.com  If the information required under Sections VI, VIII, X, and XI above has been previously submitted, it need not be resubmitted.  Please show the date and circumstances of the earlier submittal:

### III. WELL DATA

- A. The following well data must be submitted for each injection well covered by this application. The data must be both in tabular and schematic form and shall include:
  - (1) Lease name; Well No.; Location by Section, Township and Range; and footage location within the section.
  - (2) Each casing string used with its size, setting depth, sacks of cement used, hole size, top of cement, and how such top was determined.
  - (3) A description of the tubing to be used including its size, lining material, and setting depth.
  - (4) The name, model, and setting depth of the packer used or a description of any other seal system or assembly used.

Division District Offices have supplies of Well Data Sheets which may be used or which may be used as models for this purpose. Applicants for several identical wells may submit a "typical data sheet" rather than submitting the data for each well.

- B. The following must be submitted for each injection well covered by this application. All items must be addressed for the initial well. Responses for additional wells need be shown only when different. Information shown on schematics need not be repeated.
  - (1) The name of the injection formation and, if applicable, the field or pool name.
  - (2) The injection interval and whether it is perforated or open-hole.
  - (3) State if the well was drilled for injection or, if not, the original purpose of the well.
  - (4) Give the depths of any other perforated intervals and detail on the sacks of cement or bridge plugs used to seal off such perforations.
  - (5) Give the depth to and the name of the next higher and next lower oil or gas zone in the area of the well, if any.

### XIV. PROOF OF NOTICE

All applicants must furnish proof that a copy of the application has been furnished, by certified or registered mail, to the owner of the surface of the land on which the well is to be located and to each leasehold operator within one-half mile of the well location.

Where an application is subject to administrative approval, a proof of publication must be submitted. Such proof shall consist of a copy of the legal advertisement which was published in the county in which the well is located. The contents of such advertisement must include:

- (1) The name, address, phone number, and contact party for the applicant;
- (2) The intended purpose of the injection well; with the exact location of single wells or the Section, Township, and Range location of multiple wells;
- (3) The formation name and depth with expected maximum injection rates and pressures; and,
- (4) A notation that interested parties must file objections or requests for hearing with the Oil Conservation Division, 1220 South St. Francis Dr., Santa Fe, New Mexico 87505, within 15 days.

NO ACTION WILL BE TAKEN ON THE APPLICATION UNTIL PROPER PROOF OF NOTICE HAS BEEN SUBMITTED.


NOTICE: Surface owners or offset operators must file any objections or requests for hearing of administrative applications within 15 days from the date this application was mailed to them.

### INJECTION WELL DATA SHEET

OPERATOR:	Hadaway Consulting and Engineering, LL	_C		· · · · · · · · · · · · · · · · · · ·			
WELL NAME & NUM	MBER: Abbey State SWD #1	·		· · · · · · · · · · · · · · · · · · ·	·		
WELL LOCATION: _	2290' FNL & 1200' FEL FOOTAGE LOCATION	H UNIT LETTER	36 SECTION	10S TOWNSHIP	27E RANGE		
<u>WELI</u>	BORE SCHEMATIC	WELL CONSTRUCTION DATA Surface Casing					
	13 3/8" 54.5 ppf J55 csg @ 350'		17 1/2" 400 sx.	Casing Size: 13			
	8 5/8" 24 ppf J55 csg @ 1,553'	Top of Cement: _	Surface Intermedian		Circulation		
		Cemented with: _	12 1/4"  800 sx.  Surface	or	ft <sup>3</sup>		
		· ·	Production	1 Casing			
			7 7/8"				
		Top of Cement:	sx. Surface	Method Determined:			
	3 1/2" IPC tbg w/ packer set less than	Total Depth: Csg 7,300' - Well TD 7,305 - PBTD 7,220'					
	100' above the permited SWD interval.		Injection ed 6,790' feet				
	5 1/2" 15.5 ppf J55 csg @ 7,300' w/ the float collar set 2 its up at 7,220'.	<b>e</b>	(Perforated or Open H	ole; indicate which)			

Hi Way State #1 (P&A)
Surf 2417' FSL & 2245' FEL
Sec 36 T10S R27E
Chaves, NM
Sep 14, 2017

### **Current Wellbore**



10 sx cmt plug 30 - surface.

17 %" x 13 3/8" 54 ppf STC @ 338' cmt w/ 400 sx to surf.

35 sx cmt plug 350 - 250.

12 %" x 8 5/8" 24 ppf STC @ 1557' cmt w/ 650 sx to surf.

Cut and pulled 1586' of 5 %" casing. Set 50 sx cmt plug 1636-1448.

25 sx cmt plug 3500 - 3125.

Tops per OCD C105

Miss 6660' Siluro-Devonian 6798'

TOC 4273' (calc).

25 sx cmt plug 4500 - 4300.

CIBP set @ 5700' w/ 35' cmt on top.

Perforations 6,132 — 5,826

CIBP set @ 6238' w/ 35' cmt on top.

Perforations 6,334 -- 6,460

Well was originally drilled to a TD of 6881' then P&A in 7/1994 before being reentered in 10/2001. Upon reentry, 7 7/8" x 5 %" 15.5 & 17 ppf K55 @ 6616' cmt w/ 375 sx w/ TOC @ 4273' (calc).

35 sx cmt plug 6688 - 6588 after originally drilling dry hole.

### **INJECTION WELL DATA SHEET**

Γub	Γubing Size: 3 1/2"	Lining Material:	IPC
Туј	Type of Packer: Nickel plated Lo	k-Set or equivalent w/ profile and	on-off tool.
Pac	Packer Setting Depth: Within 100	0' of top of SWD interval.	
Oth	Other Type of Tubing/Casing Sea	al (if applicable): None	
		Additional Data	
1.	1. Is this a new well drilled for	injection? Yes	X No
	If no, for what purpose was t	he well originally drilled?This we	ell was originally drilled as a
	Devonian test and was F	P&A. No production casing was re	Jn.
2.	2. Name of the Injection Forma	ation: Fusselman	
3.	3. Name of Field or Pool (if app	plicable):	
4.		rated in any other zone(s)? List all st detail, i.e. sacks of cement or plug(s)	
5.	5. Give the name and depths of injection zone in this area:	Fany oil or gas zones underlying or o San Andres T/1,529' BGL	verlying the proposed
	,		
	<del></del>		

- I. Plan to reenter a 7,305' dry hole and convert to a water disposal well for the operator's proposed San Andres drilling program located in the area.
- II. Hadaway Consulting and Engineering, LLC (OGRID: 371985)
   P.O. Box 188, Canadian TX 79014
   Operator phone: (806) 323-8723
   Contact for Application: John Maxey (Maxey Engineering, LLC), (575) 623-0438
- III.A.1 Lease: State of New Mexico Land Office lease VC-0131 consisting of 320 acres in the E2 of section 36 T10S R27E, dated August 1, 2017. The well information: Abbey State SWD #1, (formerly: Hadley AFJ State #1, API# 30-005-62596) 2290' FNL & 1200' FEL of section 36 T10S R27E, Chaves County, NM. A C102 is attached as Exhibit "A".
- III.A.2 Surface construction is 17 ½" hole by 13 ¾" 54.5 ppf J55 casing set at 350' cemented with 400 sx of cement to surface.

Intermediate construction is 12 %" by 8 %" 24 ppf J55 casing set at 1,553' cemented with 800 sx of cement to surface.

Production construction will be 7 7/8" by 5 1/2" 15.5 ppf J55 casing set at 7,300' cemented with 900 sx of Class C cement plus additives to surface. (See attached injection well data sheets)

- III.A.3 Injection tubing will be 3 ½" 9.6 ppf J55 EUE IPC set within 100' of the top of the permitted injection interval with a packer. (See attached injection well data sheets)
- III.A.4 Packer will be a 5 1/2" nickel plated LokSet (or equivalent) packer with a stainless steel profile nipple and on-off tool. (See attached injection well data sheets)
- III.B.1 The disposal interval is Fusselman.

2.9

- III.B.2 The injection interval will be cased throughout, and will be perforated intermittently from 6,790' to 7,100'.
- III.B.3 This well was originally permitted and drilled as a Wildcat Devonian test. The proposed injection interval (reported as both Siluro-Devonian and

Montoy/Fusselman in the OCD file records) was drill stem tested and found to be wet. The DST test results are as follows:

RECEIVED

### YATES PETROLEUM CORPORATION

Hadley AFJ State #1, V-994 Unit H, 2290' FNL & 1200' FEL Sec. 36-T10S-R27E Chaves County, NM

APR 22'88

O. C. D.

### DRILL STEM TESTS:

DST #1 - MISRUN. (Communication around packer.)

DST #2 - 6800-6860' (60') MONTOYA/FUSSLEMAN: On 30 minute preflow had 3 oz in 5 mins; 5 oz in 15 mins; 6 oz in 20 mins (blow to bottom of bucket); 9 oz in 30 mins. SI 60 mins. Reopened with 7 oz; 9 oz in 10 mins; 10 oz in 20 mins; 12 oz in 30 mins; 13 oz in 40 mins; 15 oz in 50 mins; 15 oz in 60 mins. SI 120 mins. Opened 6:20 AM 4-6-88 (for 180" flow) - in 5 mins had weak blow; 2 oz in 20 mins, 4 oz in 20 mins; 7 oz in 30 mins; 8 oz in 35 mins. Did not have GTS. RECOVERY: 121' mud and 91' mud and water. Rw 0.08 at 60°, Cl 83000 ppm. SAMPLER: 0.40 scf gas, 300 cc oil and 1860 cc water, Rw 0.18 at 60°, Cl 28000 ppm at 120 psi. PRESSURES: IHP 3692; 1st IFP 80-369; ISIP 2718; 2nd IFP 376-581; FSIP 2718; 3rd IFP 600-1105; FHP 3648.

DST #3 - 6797-6838' (41') MONTOYA/FUSSLEMAN: TIMES: TO 45", SI 60", TO 60", SI 90", TO 180". SI. Opened tool with weak blow. Had 3 oz in bottom bucket in 40 mins, 5.5 oz in 45 mins. On 2nd open - 7 oz in bubble hose in 15 mins; 7.5 oz in 30 mins; 8 oz in 45 mins; 10 oz in 60 mins. On 3rd open - 7.5 oz in bubble hose in 20 mins; 10 oz in 60 mins; 10.5 oz 9n 80 mins; 12.5 oz in 120 mins, 14 oz in 180 mins. RECOVERY: 280' free gas, 187 gas and slightly oil cut mud, 93' drilling mud cut with formation water, 1486' formation water. SAMPLER .3 cfg, 360 cc oi, 2040 cc water at 110 psi. PRESSURES: (Bottom) IHP 3714; 1st IFP 27-341; ISIP 2704; 2nd IFP 370-484; ISIP 2704; 3rd IFP 494-865; FHP 3675.

- III.B.4 There will be no other perforated intervals.
- III.B.5 There is no known next lower oil or gas producing zones in the area of the well. The next higher zone would be San Andres oil production at 1,520'.
- IV. This is not an expansion of an existing project.
- V. Exhibit "B" identifies all wells and leases within a 2 mile radius of the proposed SWD well, and the ½ mile radius is the area of review for this application.
- VI. There is one well that penetrates the proposed injection interval within the Area of Review (AOR). A tabulation and schematic of the well is below. There are 2 other

wells in or very near the boundary of the AOR, however these wells are shallow and do not penetrate the proposed injection interval.

- VII.1 The proposed daily operating rate is 10,000 BWPD with a maximum of 20,000 BWPD.
- VII.2 This system will be open and closed taking both pipeline water and trucked water from the operator's anticipated producing San Andres wells in the area. This well is for a new drilling program and there are no producing wells yet. This permit for SWD and the permits for development drilling of the San Andres are being prepared concurrently.
- VII.3 The average daily surface operating pressure is anticipated to be on vacuum. The maximum surface pressure would be 0.2 psi/foot to the anticipated top of the injection (disposal) interval at 6,790', or 1,358 psi.
- VII.4 The source of the disposal fluid would be the operator's anticipated producing San Andres wells to be developed in the area. Per a Roswell Geological Symposium study of the Chisum San Andres (2 miles to the south), the San Andres has 55,261 ppm Cl and 35,8008 ppm Na.
- VII.5 Per a Roswell Geological Symposium study of the Chisum Devonian (2 miles to the south), the Devonian has 29,047 ppm Cl and 18,822 ppm Na.
- VIII. The Fusselman dolomite is a fine to coarsely crystalline, brown to light grey reservoir rock. Porosity development consists of small and large vugs and fractures. Lining the vugs are large crystals of dolomite rhombs developed through secondary crystallizations. The only source of drinking water in the area would be from the red beds from surface down to 350' BGL. Formation tops from the OCD form C105 are as follows:

San Andres	1520
Glorieta	2716
Yeso	2796
Abo	4980
Wolfcamp	5792
Miss	6651
Fusselman	6792

- IX. The well will be stimulated with acid if needed.
- X. Well logs previously submitted to the Division. A GR-CBL-VDL will be run on the well.
- XI. The wellsite is in a remote area and there were no obvious stock tanks or other indications of underground fresh water sources in a grid search of the area on Google Earth. There were no Points of Diversion within 1 mile of the proposed SWD on a location search of the State Engineers website.
- XII. Available geologic and engineering data were examined and no evidence of open faults or any other hydrologic connection between the disposal zone and any underground sources of drinking water were found.

XIII. A legal ad was published in the Roswell Daily Record, Chaves County New Mexico, with proof of publication attached (Exhibit "C"). A copy of this application has been mailed to the owner of the surface of the land on which the well is located (NM State Land Office), and all leasehold operators, leaseholders if no operator, and mineral owners if no leaseholder, per the attached USPS return receipt cards (Exhibit "D").

### **Data Sheet for Well Within Area of Review**

Operator: Elk Oil Company

Well Name: Hi Way State #1 (P&A) Location: 2,417' FSL & 2,245' FEL, Sec 36 T10S R27E

<u>GL Elevation (ft):</u> 3,698' <u>API #:</u> 30-005-63021

Spud Date: 6-30-1994 Reentry Comp Date: 9-18-2001

TD (ft): 6,881 PBTD (ft): 6,616

<u>Dry Hole P&A:</u> 7-24-1994 <u>Reentry P&A Date:</u> 4-5-2005

### **Wellbore Construction**

Hole OD (in)	Casing OD (in)	Weight (ppf)	<u>Grade</u>	Depth (ft)	Amt Cmt (sx)	TOC (ft from Surf)
17 1/2	13 3/8	54	Unknown	338	400	0
12 1⁄4	8 1/8	24	Unknown	1,557	650	0
7 1/s	5 1/2	15.5 & 17	K55	6,616	375	4,273 calc

### **Producing Interval and Details**


The well was original drilled to a TD of 6,881' and P&A as a dry hole. In August of 2001 the well was reentered and 5 ½" casing was run to 6,616'. An attempted completion was made through perforations 6,334 --- 6,460 (73 holes) and reported non-commercial. A second attempt was made through perforations 6,132 --- 5,826 (94 holes). The well was reported to be flowing gas and was subsequently shut in waiting on a pipeline. It appears the well was ultimately noncommercial as there is no production reported for this well, and the well was subsequently P&A in April of 2005.

### Comments

Schematic diagram attached.

Hi Way State #1 (P&A) Surf 2417' FSL & 2245' FEL Sec 36 T10S R27E Chaves, NM Sep 14, 2017

### **Current Wellbore**



10 sx cmt plug 30 - surface.

17 %" x 13 3/8" 54 ppf STC @ 338' cmt w/ 400 sx to surf. 35 sx cmt plug 350 - 250.

12 1/2" x 8 5/8" 24 ppf STC @ 1557' cmt w/ 650 sx to surf.

Cut and pulled 1586' of 5 %" casing. Set 50 sx cmt plug 1636 – 1448.

25 sx cmt plug 3500 - 3125.

Tops per OCD C105

Miss 6660' Siluro-Devonian 6798'

TOC 4273' (calc).

25 sx cmt plug 4500 - 4300.

CIBP set @ 5700' w/ 35' cmt on top.

Perforations 6,132 -- 5,826

CIBP set @ 6238' w/ 35' cmt on top.

Perforations 6,334 -- 6,460

Well was originally drilled to a TD of 6881' then P&A in 7/1994 before being reentered in 10/2001. Upon reentry, 7.7/8" x 5.5" 15.5 & 17 ppf K55 @ 6616' cmt w/ 375 sx w/ TOC @ 4273' (calc).

35 sx cmt plug 6688 - 6588 after originally drilling dry hole.

Exhibit "A"

District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 <u>District II</u> 811 S. First St., Artesia, NM 88210

Phone: (575) 748-1283 Fax: (575) 748-9720 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 Phone: (505) 334-6178 Fax: (505) 334-6170

1220 S. St. Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3460 Fax: (505) 476-3462

### State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office


☐ AMENDED REPORT

		W	ELL LC	CATIO	N AND ACR	EAGE DEDIC	ATION PLA	Т			
	API Number			<sup>2</sup> Pool Code			<sup>3</sup> Pool Nan	ne			
30-0	05-625	96									
<sup>4</sup> Property Code				Abbey State SWD					<sup>6</sup> Well Number 1		
<sup>7</sup> OGRID No. 371985			Ha	*Operator Name 'Elevation Hadaway Consulting & Engineering, LLC 3698.7'							
					" Surface I	ocation					
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/V	est line	County	
H	36	105	27E		2290	N	1200	E		Chaves	
			" Bo	ttom Hol	e Location If	Different From	Surface				
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/V	est line	County	
12 Dedicated Acres	<sup>13</sup> Joint or	Infill 14 Co	onsolidation	Code 15 Or	der No.						

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

				<del></del>
			<b>1</b>	"OPERATOR CERTIFICATION
[				I hereby certify that the information contained herein is true and complete
				to the best of my knowledge and belief, and that this organization either
<u>[</u>				owns a working interest or unleased mineral interest in the land including
				the proposed bottom hole location or has a right to drill this well at this
				location pursuant to a contract with an owner of such a mineral or working
ì			2290'	interest, or to a voluntary pooling agreement or a compulsory pooling
<u> </u>	,		2270	order heretofore entered by the division.
				ShuCMary 9/14/2017
				Signature Date
				John C Maxey
'				Printed Name
				icm@mayoyonginooring.com
<u> </u>	·		•	jcm@maxeyengineering.com
		· ·	1200'	E-mail Audress
				"SURVEYOR CERTIFICATION
i i				I hereby certify that the well location shown on this
]				plat was plotted from field notes of actual surveys
				made by me or under my supervision, and that the
			•	same is true and correct to the best of my belief.
				·
<b> </b>		<del></del>	<del></del>	Date of Survey
ĺ	· · ·			Signature and Seal of Professional Surveyor:
<b>,</b>			,	
			, , ,	
1			•	
ĺ				
ĺ				
<b>]</b>				Certificate Number

### Exhibit "B" Land Plat



### AFFIDAVIT OF PUBLICATION STATE OF NEW MEXICO

### I, Jenny Martinez Legals Clerk

Of the Roswell Daily Record, a daily newspaper published at Roswell, New Mexico do solemnly swear that the clipping hereto attached was published in the regular and entire issue of said paper and not in a supplement thereof for a period of:

One time with the issue dated

September 15th, 2017

Sworn and subscribed to before me

Clerk

this 15th day of September, 2017

Notary Public

My Commission expires
June 13, 2018

### Proposal...


### Publish September 15, 2017

Hadaway Engineering & Consulting, LLC, proposes to reenter the Hadey AFJ State #1 as a produced water disposal well. The well will be renamed the Abbity State SWD #1. The well is located 2290' FNL & 1200' FEL, Section 36 T108-R27E, Chaves County, New Mexico.

The maximum proposed rate of injection is 20,000 barrels of water per day and the maximum proposed injection pressure is 1,358 psi. Water will be disposed of into the Fusselman formation at an anticipated dapth of 8,790 to 7,100.

Contact for the application is Maxey Engineering, LLC, P.O. Box 1961, Roswell, New Mexico 88202, Attn: Mr. John Maxey, consulting Petroleum Engineer, Phone (575) 823-0438.

Interested parties must file objections or request a hearing with the New Mexico Oil Conservation Division, 1220 South St. Francis Drive, Santa Fe, New Mexico 87505 within 15 days.



■ Complete Items 1, 2, and 3.

Complete items 1, 2, and 3.

■ Complete items 1, 2, and 3.

34T Holding LLC

P.O. Box 11351 Midland, TX 79702

■ Complete batts 1, 2, and 3.

P.O. Box 11351 Midland, TX 79702

or on the front if space permits. Spool Holding LLC

7016 2710 0000 01906 4087

DK Boyd P.O. Box 11351 Midland, TX 79702

30706

70.16

3010

7076

CHEST HOUSE

0000


2770

7076

or on the front if space permits.

or on the front if snace namits. State of New Mexico P.O. Box 1148

Exhibit "D"



### **USPS Tracking® Results**

FAQs > (http://tag.usps.com/?erticleid=220900)

Track Another Package +

Tracking Number: 70162710000019164131 Delivered U.S. Postal Service" CERTIFIED MAIL® RECEIPT 0000 PATUS OF ITEM LOCATION n Individual HOUSTON, TX 77010 Chisos, Ltd. 28, 2017 in HOUSTON, TX 77010. 1331 Lamar St. Suite 1075 Houston, TX 77010 ional Facility NORTH HOUSTON TX DISTRIBUTION CENTER NORTH HOUSTON TX DISTRIBUTION CENTER Departed USPS Regional Facility COPPELL TX DISTRIBUTION CENTER SENDER: COMPLETE THIS SECTION clase items 1, 2, and 3. Print your name and address on the reverse so that we can return the card to you. Attach this card to the back of the mailplece, or on the front if space permits. SEP 26 2017 Attn: Sue Ann Craddock 670 Dona Ana Road, SW Deming, NM 88030 9590 9402 2868 7069 5990 78 2. Article Number (Transfer from service label) 7016 3010 0000 934816065 PS Form 3811, July 2015 PSN 7530-02-000-9053

### STATE LAND OFFICE DATA ACCESS

Home Select a different page......

### land details

\* Section: 36. \* Township: 10S. \* Range: 27E.

Example:

33

098

26E

Search Reset Printer Friendly Download

Instructions

Give Feedback

17 Records found.

No Links

Unit Letter	Lot	Tract	Qtr/Qtr	Surface Owner	Sub Surface Owner	Acreage	Lease Number	Lease Type	Соилту	Land Restriction	Land Remarks
Α			NE4NE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
В			NW4NE4	State	State			Grazing & Agriculture			
С			NE4NW4		State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
D			NW4NW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
Ε			SW4NW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
F			SE4NW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
G			SW4NE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves	·	
Н			SE4NE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
1			NE4SE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
J			NW4SE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		_
K			NE4SW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
L			NW4SW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
M			SW4SW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
N			SE4SW4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
0			SW4SE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
Р			SE4SE4	State	State	40.00	G0-2351-0000	Grazing & Agriculture	Chaves		
							R1-4908-0000	Right of Way	Chaves		



Date: October 10, 2017

John Maxey:

Delivered to the NM Oil Conservation Division

The following is in response to your October 10, 2017 request for delivery information on your Certified Mail™/RRE item number 9514800018587277000057. The delivery record shows that this item was delivered on October 6, 2017 at 10:56 am in SANTA FE, NM 87505. The scanned image of the recipient information is provided below.

Signature of Recipient:

Address of Recipient:

Thank you for selecting the Postal Service for your mailing needs.

If you require additional assistance, please contact your local Post Office or postal representative.

Sincerely, United States Postal Service



Date: October 10, 2017

John Maxey:

Delivered to the NM State Land Office

The following is in response to your October 10, 2017 request for delivery information on your Certified Mail™/RRE item number 9514800018587277000064. The delivery record shows that this item was delivered on October 6, 2017 at 7:35 am in SANTA FE, NM 87501. The scanned image of the recipient information is provided below.

Signature of Recipient:

ature of the same of the same

Address of Recipient:

very ress //48

Thank you for selecting the Postal Service for your mailing needs.

If you require additional assistance, please contact your local Post Office or postal representative.

Sincerely, United States Postal Service RECEIVED OCD

Maxey Engineering, LLC

P. O. Box 1361

2011 0CT -b P 1: 13 400 North Pennsylvania Avenue • Suite 230A Roswell, NM 88202-1361

> Office: (575) 623-0438 • Email: jcm@maxeyengineering.com www.maxeyengineering.com

> > October 4, 2017

David Catanach
Oil Conservation Division
New Mexico Dept of Energy
Minerals and Natural Resources
1220 South Saint Francis Drive
Santa Fe, NM 87505

Re:

Application of Hadaway Consulting & Engineering, LLC., for administrative approval of a Salt Water Disposal Well Permit located in unit H of Section 36, T10S R27E, Chaves County, New Mexico.

Dear Mr. Catanach

Hadaway Consulting & Engineering, LLC (OGRID No 371985) as operator for Newtex Partners, LLC., seeks administrative approval for a Salt Water Disposal Permit for the Abbey State SWD #1, to be reentered at a location 2290' FNL and 1200' FEL of Section 36, T10S R 27E, Chaves County, New Mexico. Enclosed is the complete administrative application.

Newtex owns 100% of the working interest in section 36 and has designated Hadaway as their operator. If you have any questions concerning the completed application please do not hesitate to contact me. Your attention to this matter is appreciated.

Sincerely,

Maxey Engineering, LLC

John C. Maxey

**Consulting Petroleum Engineer** 

### McMillan, Michael, EMNRD

From: John M <jcm@maxeyengineering.com>


**Sent:** Monday, October 23, 2017 10:47 AM

To: McMillan, Michael, EMNRD

Subject: Re: Hadaway Consulting and Engineering Abbey State SWD Well No. 1

Mike,

Bill Bahlburg called and said that you would like to see some kind of plug in the open hole over the Cambrian. What I was planning on doing for isolation is illustrated below which provides for good cementing velocities in open hole outside the casing annulus below the proposed injection interval, and leaves cement below the float collar. I was going to place the float 80' above the bottom of the casing rather than the typical 40'. Displacement is with a wiper plug that seats on the float and the cementers wash up on the plug leaving solid cement below the wiper (and some above). I could adjust the depth by leaving out a joint of casing, but having some kind of cased rat hole below the perforated interval is prudent, and best practice. I thought it easier to send you an illustration rather than explain over the phone. Let me know (call or email) if this will work and I'll send full schematic, or if the OCD would rather see something different.



Float Collar @ 7220'(PBTD)

5 ½" 15.5# J55 @ 7300'

John C. Maxey P.E.
Maxey Engineering, LLC
400 N. Pennsylvania, Suite 230A
P. O. Box 1361
Roswell, NM 88202-1361
Off: 575-623-0438

www.maxeyengineering.com

On 10/20/2017 10:28 AM, McMillan, Michael, EMNRD wrote:

Bill Bahlburg has not called about the cross-section Mike

From: McMillan, Michael, EMNRD

Sent: Wednesday, October 18, 2017 3:12 PM To: 'John M' <icm@maxeyengineering.com>

Subject: RE: Hadaway Consulting and Engineering Abbey State SWD Well No. 1

Thanks Mike

From: John M [mailto:jcm@maxeyengineering.com]

Sent: Wednesday, October 18, 2017 3:05 PM

To: McMillan, Michael, EMNRD < Michael. McMillan@state.nm.us >

Subject: Re: Hadaway Consulting and Engineering Abbey State SWD Well No. 1

Besides the one in the C108? I only found one P&A well in the AOR and that schematic is in the package (page 6) as the Hi Way State #1. I've reattached to this email.

Did you hear from the geologist Bill Bahlburg?

John C. Maxey P.E.
Maxey Engineering, LLC
400 N. Pennsylvania, Suite 230A
P. O. Box 1361
Roswell, NM 88202-1361
Off: 575-623-0438
www.maxeyengineering.com

On 10/18/2017 2:56 PM, McMillan, Michael, EMNRD wrote:

Include a wellbore diagram of the P&A well within the ½ Mile AOR.

Mike

From: John M [mailto:jcm@maxeyengineering.com]

Sent: Tuesday, October 17, 2017 4:05 PM

To: McMillan, Michael, EMNRD < Michael McMillan@state.nm.us>

Subject: Fwd: RE: RE: Hadaway Consulting and Engineering Abbey State SWD Well No. 1

Mike,

Attached is the Xsection and below are the geologist's comments. He makes the same point we all have discussed, we have thick, tight interval below our injection zone, and if there is Ellenburger present in the Katie Elder below the gamma kick, its 40' thick and tight. With 200' of tight rock below our injection interval it would be extremely difficult for fluids to breech without very significant amounts of hydraulic horsepower. We also would be running new casing, properly centralized, with a new primary cement job. This section of hole is in gauge and in good shape for primary cement.

Let me know if this helps,

John C. Maxey P.E. Maxey Engineering, LLC

400 N. P	ennsvlv	ania. Su	ite 230	A				
 P. O. Bo Roswell, Off: 575	x 1361 NM 88	202-1361						
 www.maxe			<u>m</u>					i :
								:: ::::::
Forv	warded Me	essage						:
Date:Tu	e, 17 Oct	2017 21:30	0:52 +0000	) · . · · · · · · · · ·		itate SWD \	Well No	.1
			ngineerin	loration.co g.com>	<u></u>			
			1					
				·				
John-						•		
want to ca neither do correlates Ellenburge	II the gam es anyone to the gar r thicknes	ma kick at else. You nma kick ii s to less th	7238 Eller could say in the Katie nan 45 ft.	nburger that gamn that gamn Elder at 7	at is fine. na kick at 673' whicl	ection 36. I I actually d 7238 in the n would lim	on't kno Abbey lit the	ow ar well
	te Re-entr	y. If the El				here it look		
Bill								;;
	a a a fraga ng ang ang ang ang ang ang ang ang a		erskin mar i 1905- <b>e</b> llik <b>arle</b> magnisiyek kirilin er (Ani's) erstekkel	g 1986 alin di di displanta proprieta genegalia ya ya kujishi ya wasa maka	nesskab in eggen skiller myrji i i i i rymmynu jefeli s sir ri skil	enament seis vona papas heimonovo ala	n Garlande (San San San San San San San San San San	Mount
 7	e www.av	ast com						



### New Mexico Office of the State Engineer Water Column/Average Depth to Water

(quarters are 1=NW 2=NE 3=SW 4=SE) (quarters are smallest to largest) (NAD83 UTM in meters)

No records found.

**PLSS Search:** 

Section(s): 25, 35-36

Township: 10S

Range: 27E

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

10/26/17 2:21 PM

WATER COLUMN/ AVERAGE DEPTH TO WATER



### New Mexico Office of the State Engineer Water Column/Average Depth to Water

(quarters are 1=NW 2=NE 3=SW 4=SE) (quarters are smallest to largest) (NAD83 UTM in meters)

No records found.

**PLSS Search:** 

Section(s): 31

Township: 10S

Range: 28E

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

10/26/17 2:21 PM

WATER COLUMN/ AVERAGE DEPTH TO WATER

C-10	B Review	v Checklist: R	eceived Add. Requ	ıest:	Reply Date:	Suspended:	[Ver 15]		
ORDER	TYPE: WF	X/PMX/SWD Nu	ımber: Ordei	Date:	Legacy Permit	s/Orders:			
Well No. 1 Well Name(s): Abbey State 5 W. SAPI: 30-0 0.5-6 2596 Spud Date: 3-17-1888 New or Old: (UIC Class II Primacy 03/07/1982) 2290FNL									
API: 30-0 05-6	2596	Spud Dat	3-17-1588	New or Old:	(UIC Class II	Primacy 03/07/1982)			
Footages / > 00 F	ことし	Lot	or Unit # Sec_5 6	T <sub>SD</sub> //	95 Rae マフ	County CATTUR	<u>5</u> _		
General Location: 7	umile	es EIR	US WY Pool:			Pool No :			
PLM 100K Map: P.//2	51.611	H4 Operator: C425	Pool:  Jaway  S4L+ing  Fincl Assur:	IN CENT	19 371485 Contac				
BLW TOOK Wap. 150		Operator. <u>Corr</u>		OGÚID	·Comai	St	-12017		
COMPLIANCE RULE 5.	9: Total Well	ls: <u> </u>	ve: Fincl Assur:	Compl.	Order?	5.9 OK? X Date:	16-20-7		
WELL FILE REVIEWED	Ourrent	Status:	4						
WELL DIAGRAMS: NEV	V: Proposed	or RE-ENTER:	Before Conv. After C	Conv. 🔘 l	ogs in Imaging:	<del>/</del>			
Planned Rehab Work to	Well:								
Well Construction	<u>Details</u>	Sizes (in) Borehole / Pipe	Setting Depths (ft)		Cement Sx or Cf	Cement Top and Deter	mination Method		
Plannedor Existin	g _Surface	175"/133/4"	350'	Stage Tool	400	Surfacel	Visyal		
Planned_or Existing	nterm/Prod		1553	And the second	800	SUPFICE	1 Uisyal		
Planned_or Existingl	nterm/Prod	77/8/55	7305		1265	SurFull			
Planned_or Existing	Prod/Liner				5-7°	*	•		
Planned_or Exis	tingLiner								
Plannedor Existing	OH / EERF	6790/7100	)	Inj Length	Comp	letion/Operation Det	ails:		
Injection Lithostratigrap	. 57	Depths (ft)	Injection or Confining Units	Tops	Drilled TD 730	5 PBTD 72	20		
Adjacent Unit: Litho. S	truc. Por.		<u>4</u> M 5	6660	NEW TD	_ NEW PBTD			
Confining Unit: Litho.	Struc. Por.		Dev	6792	NEW Open Hole	or NEW Perfs @			
Proposed Inj In	terval TOP:			(		in. Inter Coated?			
Proposed Inj Interva		· had bearing				epth <u>669</u> ft			
Confining Unit: Litho.					Min. Packer Depth	(100-ft linhit)	)		
Adjacent Unit: Litho. S		ınd Geologic In	formation	1	Proposed Max. Suri Admin. Inj. Press	face Press. 13 6 y ps			
POTASH: R-111-P			* * * * * * * * * * * * * * * * * * * *	0-14/0-		<del></del>	rπ)		
			WIPP () Noticed?_						
FRESH WATER: Ago	liter Pos	to tes	Max Depth	HYDRO	O AFFIRM STATEME	NT <u>By Qualified Perso</u>	<u>n</u> G		
		4			,				
		,	analysis Analysis	//					
'	, -	11	2-UK-Protectable Wate				- 1		
HC Potential: Produ	cing Interval	Promerly Pr	oducing?Method:	Logs(DST/E	&A/Other	_ 2-Mile Radius Pool Ma	ap 🔾		
AOR Wells: 1/2-M Radius Map? Well List? Total No. Wells Penetrating Interval: Horizontals?									
Penetrating Wells: No. Active Wells Num Repairs?on which well(s)?									
Penetrating Wells: No	. P&A Wells	Num Repairs?	on which well(s)?			Diagrams?	X		
NOTICE: Newspaper Date September Mineral Owner NWSLO Surface Owner NWSLO N. Date 5-Cpt 20, 2013  RULE 26.7(A): Identified Tracts?   Affected Persons: DV Bo 4 347 Hulding S Spoul 11 Identified Tracts?  N. Date 6-27-2017									
RULE 26.7(A): Identifi	ed Tracts?	Affected Per	sons: DV Boyd	347 H	iuldings, Sp	00/11 N. Date_G	-27-2017		
Order Conditions:	Issues:						_		
Add Order Cond:									