


# New Mexico Energy, Minerals and Natural Resources Department

**Bill Richardson**  
Governor

**Joanna Prukop**  
Cabinet Secretary  
**Reese Fullerton**  
Deputy Cabinet Secretary

**Mark Fesmire**  
Division Director  
Oil Conservation Division



**Administrative Order SWD-1124**  
**May 14, 2008**

APPLICATION OF J.F. MCADAMS FOR PRODUCED WATER DISPOSAL, LEA  
COUNTY, NEW MEXICO

## ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), J.F. McAdams (OGRID 11238) made application to the New Mexico Oil Conservation Division for permission to utilize for produced water disposal its Brooks Federal Well No. 3 (API No. 30-025-01711) located 660 feet from the South line and 1980 feet from the East line of Section 7, Township 20 South, Range 33 East, NMPM, Lea County, New Mexico.

### THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met;
- (4) No objections have been received within the waiting period prescribed by said rule; and
- (5) The operator is in compliance with the Division's Rule 40.

### IT IS THEREFORE ORDERED THAT:

J.F. McAdams is hereby authorized to utilize its Brooks Federal Well No. 3 (API No. 30-025-01711) located 660 feet from the South line and 1980 feet from the East line of Section 7, Township 20 South, Range 33 East, NMPM, Lea County, New Mexico, in such manner as to permit the injection of produced water for disposal purposes into the



Yates formation through an open hole interval from 2,910 feet to 3,025 feet and through plastic-lined tubing set with a packer located within 100 feet of the top of the injection interval.

Special Requirements:

The operator shall clean this well out to total depth and run a modern porosity log from total depth to the surface and provide a copy of that log to the Hobbs district office. The operator shall run an injection survey with both tracer and temperature logs within 6 months of commencing injection and every 5 years thereafter or more often as required by the Division. Copies of these logs shall be provided to the Hobbs district office. In order to prevent excessive localized pressuring of the Yates formation, this well is not permitted to dispose of waste-waters from wells not operated by the operator of this saltwater disposal well. The permit to inject into this well can be immediately revoked by the Division without notice if it is found that injected waters are not confined within the permitted injection depths or if sufficient evidence exists that the Capitan Reef or the Potash/Salt intervals are being invaded by waters being injected into this well.

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

After installing injection tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wellhead injection pressure on the well shall be limited to **no more than 582 psi**. In addition, the injection well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface injection pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the injection formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed.


The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall provide written notice of the date of commencement of injection to the Hobbs district office of the Division.

The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator received by the Division prior to the termination date, may grant an extension thereof for good cause shown.

  
MARK E. FESMIRE, P.E.  
Director

MEF/wvj

cc: Oil Conservation Division – Hobbs  
Bureau of Land Management - Carlsbad