

#### STATE OF NEW MEXICO

# ENERGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVISION

TONEY ANAYA GOVERNOR

October 29, 1986

POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87501 (505) 827-5800

APPLICATION OF BURK ROYALTY COMPANY TO EXPAND ITS WATERFLOOD PROJECT IN THE DOUBLE L QUEEN ASSOCIATED POOL IN CHAVES COUNTY, NEW MEXICO.

ORDER NO. WFX-563

## ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Order No. R-5164, Burk Royalty Company has made application to the Division on August 20, 1986, for permission to expand its Double L Queen Waterflood Project in the Double L Queen Associated Pool in Chaves County, New Mexico.

NOW, on this 27th day of October, 1986, the Division Director finds:

- 1. That application has been filed in due form.
- 2. That satisfactory information has been provided that all offset operators have been duly notified of the application.
- 3. That no objection has been received within the waiting period as prescribed by Rule 701B.
- 4. That the proposed injection well is eligible for conversion to water injection under the terms of Rule 701.
- 5. That the proposed expansion of the above referenced waterflood project will not cause waste nor impair correlative rights.
  - 6. That the application should be approved.

### IT IS THEREFORE ORDERED:

That the applicant, Burk Royalty Company, be and the same is hereby authorized to inject water into Queen formation through plastic-lined tubing set in a packer at approximately 1850 feet

in the following described well for purposes of secondary recovery to wit:

DOUBLE L QUEEN UNIT TRACT 18 WELL NO. 3 990' FNL and 1650' FWL of Section 25, Township 14 South, Range 29 East, NMPM, Chaves County, New Mexico

### IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That prior to commencing injection operations in the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of the casing.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 381 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Queen formation. That such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

That the operator shall notify the supervisor of the Division's Artesia District Office before injection is commenced through said well.

That the operator shall immediately notify the Supervisor of the Division's Artesia District Office of the failure of the tubing, casing, or packer in said well or the leakage of water from or around said well and shall take such steps as may be timely or necessary to correct such failure or leakage.

That the subject well shall be governed by all provisions of Division Order No. R-5164 and Rules 702, 703, 704, 705, and 706 not inconsistent herewith.

That the Division Director may rescind or suspend this injection authority if it becomes apparent that the injected water is not

being confined to the injection zone or it is endangering any fresh water aquifers.

DONE at Santa Fe, New Mexico, on the day and year hereinabove designated.

STATE OF NEW MEXICO

OIL CONSERVATION DIVISION

R. L. STAMETS,

Director

SEAL