October 27, 1987

New Mexico Oil Conservation Commission State Land Office Building P.O. Box 2088 Santa Fe, New Mexico 87501

Subject: Carson Unit Well No. 24-18

660' FSL, 1930' FWL

Section 18, T 25N, R 12W

Dear Sir:

Enclosed for your approval is our Application for Authorization to Inject for the above referenced well.

Very truly yours,

Maldrich L. Kuchera

President

Enclosures

EJB/das

UIL CUNSERVATION DIVISION POST OFFICE BOX 20HB STATE LAND OFFICE BUILDING BANTA FE, NEW MEXICO 97501

FORM C-108 Revised 7-1-81

APPLICATION FOR AUTHORIZATION TO INJECT

nii C	The state of the s
I.	Purpose: Secondary Recovery X Pressure Maintenance Disposal Storage Application qualifies for administrative approval? X yes no
11.	Operator: Hixon Development Company
	Address: P.O. Box 2810, Farmington, New Mexico 87499
	Contact party: Aldrich L. Kuchera Phone: (505)326-3325
III.	Well data: Complete the data required on the reverse side of this form for each well proposed for injection. Additional sheets may be attached if necessary.
IV.	Is this an expansion of an existing project? X yes no If yes, give the Division order number authorizing the project
٧.	Attach a map that identifies all wells and leases within two miles of any proposed injection well with a one-half mile radius circle drawn around each proposed injection well. This circle identifies the well's area of review.
* VI.	Attach a tabulation of data on all wells of public record within the area of review which penetrate the proposed injection zone. Such data shall include a description of each well's type, construction, date drilled, location, depth, record of completion, and a schematic of any plugged well illustrating all plugging detail.
VII.	Attach data on the proposed operation, including:
	 Proposed average and maximum daily rate and volume of fluids to be injected; Whether the system is open or closed; Proposed average and maximum injection pressure; Sources and an appropriate analysis of injection fluid and compatibility with the receiving formation if other than reinjected produced water; and If injection is for disposal purposes into a zone not productive of oil or gas at or within one mile of the proposed well, attach a chemical analysis of the disposal zone formation water (may be measured or inferred from existing literature, studies, nearby wells, etc.).
*VIII.	Attach appropriate geological data on the injection zone including appropriate lithologic detail, geological name, thickness, and depth. Give the geologic name, and depth to bottom of all underground sources of drinking water (aquifers containing waters with total dissolved solids concentrations of 10,000 mg/l or less) overlying the proposed injection zone as well as any such source known to be immediately underlying the injection interval.
IX.	Describe the proposed stimulation program, if any.
* X.	Attach appropriate logging and test data on the well. (If well logs have been filed with the Division they need not be resubmitted.)
* XI.	Attach a chemical analysis of fresh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken.
XII.	Applicants for disposal wells must make an affirmative statement that they have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water.
XIII.	Applicants must complete the "Proof of Notice" section on the reverse side of this form.
XIV.	Certification
	I hereby certify that the information submitted with this application is true and correct to the best of my knowledge and belief. Name: Aldrich L. Kuchera, Title Petroleum Engineer
	Signature: Weiltuslell Date: October 27, 1987
submi	e information required under Sections VI, VIII, X, and XI above has been previously tted, it need not be duplicated and resubmitted. Please show the date and circumstance e earlier submittal.

III. WELL DATA

- A. The following well data must be submitted for each injection well covered by this application. The data must be both in tabular and schematic form and shall include:
 - (1) Lease name; Well No.; location by Section. Township, and Range; and footage location within the section.
 - (2) Each casing string used with its size, setting depth, sacks of cement used, hole size, top of cement, and how such top was determined.
 - (3) A description of the tubing to be used including its size, lining material, and setting depth.
 - (4) The name, model, and setting depth of the packer used or a description of any other seal system or assembly used.

Division District offices have supplies of Well Data Sheets which may be used or which may be used as models for this purpose. Applicants for several identical wells may submit a "typical data sheet" rather than submitting the data for each well.

- B. The following must be submitted for each injection well covered by this application. All items must be addressed for the initial well. Responses for additional wells need be shown only when different. Information shown on schematics need not be repeated.
 - (1) The name of the injection formation and, if applicable, the field or pool name.
 - (2) The injection interval and whether it is perforated or open-hole.
 - (3) State if the well was drilled for injection or, if not, the original purpose of the well.
 - (4) Give the depths of any other perforated intervals and detail on the sacks of cement or bridge plugs used to seal off such perforations.
 - (5) Give the depth to and name of the next higher and next lower oil or gas zone in the area of the well, if any.

XIV. PROOF OF NOTICE

All applicants must furnish proof that a copy of the application has been furnished, by certified or registered mail, to the owner of the surface of the land on which the well is to be located and to each leasehold operator within one-half mile of the well location.

Where an application is subject to administrative approval, a proof of publication must be submitted. Such proof shall consist of a copy of the legal advertisement which was published in the county in which the well is located. The contents of such advertisement must include:

- (1) The name, address, phone number, and contact party for the applicant;
- (2) the intended purpose of the injection well; with the exact location of single wells or the section, township, and range location of multiple wells:
- (3) the formation name and depth with expected maximum injection rates and pressures; and
- (4) a notation that interested parties must file objections or requests for hearing with the Oil Conservation Division, P. D. Box 2088, Santa Fe, New Mexico 87501 within 15 days.

NO ACTION WILL BE TAKEN ON THE APPLICATION UNTIL PROPER PROOF OF NOTICE HAS BEEN SUBMITTED.

NOTICE: Surface owners or offset operators must file any objections or requests for hearing of administrative applications within 15 days from the date this application was mailed to them.

Hixon Development Company Application for Authorization to Inject Form C-108 Supplemental Information

Carson Unit Well No. 24-18 SE/4 SW/4, Section 18, T 25N, R 12W San Juan County, New Mexico

- I. Shown on Application.
- II. Shown on Application.
- III. Well data attached.
- IV. This well is located in Federal and State approved waterflood project operation since 1959.
- V. Area of review is shown on attached map.
- VI. Information for wells located in area of review are attached as follows:


Carson Unit Well No. 13-18
Carson Unit Well No. 14-18
Carson Unit Well No. 22-18
Carson Unit Well No. WI 23-18
Carson Unit Well No. WI 33-18
Carson Unit Well No. 34-18
Carson Unit Well No. 11-19
Carson Unit Well No. WI 21-19
Carson Unit Well No. 22-19
Carson Unit Well No. 31-19


- VII. 1. Proposed average injection rate is 600 BWPD, expected maximum injection rate is 1200 BWPD.
 - 2. The injection system will be closed.
 - 3. Average injection pressures are expected to be in the 850-975 psi range. Maximum injection pressure will be 975 psi.
 - 4. Refer to the attached water analysis report. Since the formation water to be encountered is primarily previously injected water, no problems are expected in mixing the two waters.

Application for Authorization to Inject Page 2

- 5. This well is part of an extensive waterflood project active in the Carson Unit since 1959. All produced water is reinjected into the oil productive Lower Gallup sand to maintain pressure. Injection into the Lower Gallup sand is for waterflooding, not disposal.
- VIII. The injection zone is the Lower Gallup sandstone. This zone is shown to be 68' in thickness with a top of 4861' KB as shown on SP log previously submitted. No known sources of underground drinking water exist in this area. Water well drilling in this area has shown the Ojo Alamo to be dry.
 - IX. The well will be acidized if required to maintain injection rate and pressure.
 - X. Logs were previously submitted.
 - XI. No known sources of drinking water exist in this area.
- XII. This well is part of the existing approved waterflood operation for the Carson Unit. It is not a disposal well.
- XIII. Proof of notification attached.
- XIV. Certification shown on Application.

Hixon Development Company Carson Unit Well No. 24-18 T25N-R12W





CENTRAL BISTI - CARSON UNIT AREA HIXON DEVELOPMENT COMPANY

san. I testing labo : ru, inc.

907 WEST APACHE . PO BOX 2079 . FARMINGTON, NEW MEXICO

PHONE

Date June 10, 1977

Report to	Hixon Development Compan	y
Requested by	A. Kuchera. Mgr.	Sampled by <u>Hixon Personnel</u>
³ roject	CBU #5	Location NW NW Sec. 6, T25N, R12W
Source of Material	Lower Gallup Produced Wa	ter
Lab No	24509 Water Analysis fo	r Petroleum Engineering
	TEST R	ESUL TS

WATER ANALYSIS FOR PETROLEUM ENGINEERING

<u>onstituent</u>		Constituents	•	
otal Solids H esistivity onductivity	2263 ppm 7.25 2.94 ohms/meter @70°F 3,400 micromhos/cm @ 70°F		Meg/L 29.3 2.3 0.5 neg. 0	ppm 674 45 6 3
omments		Anions		
ssentially thi ulfate solution	s is a 0.2% sodium n.	Chloride Bicarbonate Carbonate Hydroxide Sulfate	4.1 4.0 0 0 24.0	145 244 0 0 1150

Copies to Hixon Development Co. (3)

P.O. Box 2810

Farmington, New Mexico 87401

22006

Certified by:



Well Name: Carson Unit #24-18

Legal Description: 660' FSL, 1930' FWL

Sec. 18, T25N-R11W San Juan County, N.M.

Well Type: Water Injection Well

(waiting on approval)

Spud Date: 04/28/59

Surface Casing Hole Size: 12-1/4"
Surface Casing Size: 8-5/8"

Surface Casing Depth: 106'

Cementing Record: 100 sx.

Production Casing Hole Size: 7 - 7 / 8 "
Production Casing Size: 4 - 1 / 2 "
Production Casing Depth: 5007'

Cementing Record: 150 sx.

Perforations: 4861'-4889'

4894'-4902' 4934'-4941' 4946'-4960' 4963'-4976'

Plug-Back Depth: 5007'

Total Depth: 5010'

Hixon Development Company


Water Injection Schematic

Well Name: Carson Unit Well No. 24-18

Legal Location: 660'

660' FSL, 1930' FWL Section 18, T25N-R11W

San Juan County, New Mexico



Hixon Development Company, P.O. Box 2810, Farmington, New Mexico 87499, (505) 326-3325, whose agent is Aldrich L. Kuchera hereby notifies interested parties that the following well is to be converted to a water injection well. Maximum rate will be 1200 BWPD at less than 975 psi. Any request for information or objections should be filed with the Oil Conservation Division, State Land Office Building, PO Box 2088, Santa Fe, New Mexico 87501 within 15 days.

Carson Unit Well 24-18, SE/4 SW/4, Section 18, T25N, R12W

This Legal Notice will be published in the Farmington Daily Times on Thursday, October 29, 1987. The Affidavit of Publication will be forwarded to your office as soon as received.

Well Name:	Carson Unit #13-18	10 sk. surface marker
Legal Description:	1980' FSL, 750' FWL Sec. 18, T25N-R11W San Juan County, N.M.	25 sk. plug at base of surface casing (180'-94')
Well Type:	P & A	35 sk. plug at 380' (380'-258')
Spud Date:	01/11/60	
Surface Casing Hole Size: Surface Casing Size:	12-1/4 " 8-5/8"	50 sk. plug at csg. stub (1240'-1066')
Surface Casing Depth:	109'	Shot off 4-1/2"
canacc casing Depart.	100	casing at 1240'
Cementing Record:	100 sx.	
Production Casing Hole Size:	7-7/8*	
Production Casing Size:	4-1/2"	
Production Casing Depth:	5038'	<u>-</u>
•		
Cementing Record:	150 sx.	7-7/8" hole
Perforations:	4074' 4000'	
Penorations:	4874'-4890' 4892'-4898'	h 22 11
	4904'-4912'	in alexal
	4954'-4968'	
	4974'-4984'	10
Plug-Back Depth:	5038'	20 sk. plug over
Total Death	E0.401	and above perfs
Total Depth:	5040'	(5038'-4779')

Well Name:	Carson Unit #14-18	Abandonment marker
Legal Description:	660' FSL, 662.8' FWL Sec. 18, T25N-R11W San Juan County, N.M.	25 sk. plug at base of surface casing (100'-15')
Well Type:	P & A	35 sk. plug at 320' (380'-201')
Spud Date:	01/17/58	
		45 sk. plug at csg. stub
Surface Casing Hole Size:	12-1/4"	(1400'-1247')
Surface Casing Size:	8-5/8"	
Surface Casing Depth:	100.5'	Shot off 4-1/2"
		casing at 1400'
Cementing Record:	100 sx.	
		\
Production Casing Hole Size:	7-7/8"	\
Production Casing Size:	4-1/2"	// //
Production Casing Depth:	5023'	نہ ا
recommendating bepair	00-0	
Cementing Record:	150 sx.	7-7/8" hole —
Destaurties	40771 40041	
Perforations:	4877'-4904'	.
	4911'-4923'	· ()
	4951'-4957'	0, 1
	4962'-4976'	
	4980'-4997') \
Plug-Back Depth:	5020'	25 sk. plug over perforations
Total Depth:	5025'	(4941'-4626')
•		

Legal Description: 1980' FNL, 1980' FWL Sec. 18, T25N-R11W San Juan County, N.M. Well Type: P & A 35 sk. plug at 300' (300'-181') Spud Date: 01/19/60 Surface Casing Hole Size: 12-1/4" Surface Casing Size: 8-5/8" Surface Casing Depth: 109' Cementing Record: Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs Total Depth: 5025' 4899'-4647')	Well Name:	Carson Unit #22-18	10 sk. surface marker
Spud Date: 01/19/60 Surface Casing Hole Size: 12-1/4" (1360'-1207') Surface Casing Size: 8-5/8" Surface Casing Depth: 109' 30 sk. plug at csg. stub (1802'-1700') Cementing Record: 100 sx. Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Legal Description:	Sec. 18, T25N-R11W	of surface casing
Surface Casing Hole Size: 12-1/4" (1360'-1207') Surface Casing Size: 8-5/8" Surface Casing Depth: 109' 30 sk. plug at csg. stub (1802'-1700') Cementing Record: 100 sx. Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Well Type:	P & A	· · ·
Surface Casing Hole Size: 12-1/4" (1360'-1207') Surface Casing Size: 8-5/8" Surface Casing Depth: 109' 30 sk. plug at csg. stub (1802'-1700') Cementing Record: 100 sx. Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Spud Date:	01/19/60); 1)
Surface Casing Size: 8-5/8" Surface Casing Depth: 109' 30 sk. plug at csg. stub (1802'-1700') Cementing Record: 100 sx. Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs			
Cementing Record: 100 sx. Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs		· ·	(1360'-1207')
Cementing Record: 100 sx. Shot off 4-1/2" casing at 1802' Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Surface Casing Depth:	109'	
Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs			(1802'-1700')
Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Cementing Record:	100 sx.	Shot off 4 1/2"
Production Casing Hole Size: 7-7/8" Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs			
Production Casing Size: 4-1/2" Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Production Casing Hole Size:	7-7/8"	casing at 1992
Production Casing Depth: 5024' Cementing Record: 150 sx. 7-7/8" hole Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs			
Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Production Casing Depth:	5024'	() /
Perforations: 4881'-4891' 4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Competing Decords	450 Av	7 7/0" holo
4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Cementing Record:	150 SX.	7-7/6 Hole
4895'-4913' 4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs			
4940'-4944' 4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs	Perforations:	4881'-4891'	
4954'-4966' 4972'-4982' Plug-Back Depth: 5024' 20 sk. plug over and above perfs		4895'-4913'	\(\frac{1}{2}\)
Plug-Back Depth: 5024' 20 sk. plug over and above perfs		4940'-4944'	
Plug-Back Depth: 5024' 20 sk. plug over and above perfs		4954'-4966'	
and above perfs		4972'-4982'	$\langle 1 1 \rangle$
and above perfs	Dive Deals Deaths	50041	20 et plus ques
· · · · · · · · · · · · · · · · · · ·	гійд-васк Deptn:	5024	
	Total Depth:	5025'	·

Well Name: Carson Unit #23-18

Legal Description: 1980' FSL, 1888' FWL

Sec. 18, T25N-R11W San Juan County, N.M.

Well Type: Water Injection Well

Spud Date: 02/16/58

Surface Casing Hole Size: 12-1/4"
Surface Casing Size: 8-5/8"
Surface Casing Depth: 102'

Cementing Record: 100 sx.

Production Casing Hole Size: 7 - 7 / 8 "
Production Casing Size: 4 - 1 / 2 "
Production Casing Depth: 5006'

Cementing Record: 150 sx.

Perforations: 4875'-4891'

4901'-4913' 4944'-4951' 4965'-4970' 4974'-4984'

Plug-Back Depth: 5006'

Total Depth: 5010'

Well Name: Carson Unit #33-18

Legal Description: 1930' FSL, 1980' FEL

Sec. 18, T25N-R11W San Juan County, N.M.

Well Type: Water Injection Well

Spud Date: 05/06/59

Surface Casing Hole Size: 12-1/4"
Surface Casing Size: 8-5/8"
Surface Casing Depth: 109'

Cementing Record: 100 sx.

Production Casing Hole Size: 7-7/8"
Production Casing Size: 4-1/2"
Production Casing Depth: 5045'

Cementing Record: 150 sx.

Perforations: 4899'-4919'

4928'-4940' 4969'-4975' 4982'-4997' 5001'-5018'

Plug-Back Depth: 5045'

Total Depth: 5050'

Well Name:

Carson Unit #34-18

Legal Description:

660' FSL, 1980' FEL Sec. 18, T25N-R11W San Juan County, N.M.

Well Type:

Oil Well

Spud Date:

08/17/57

12-1/4"

Surface Casing Hole Size: Surface Casing Size: Surface Casing Depth:

8-5/8* 176

Cementing Record:

100 sx.

7-7/8" Production Casing Hole Size: 4-1/2" Production Casing Size: 5010

Production Casing Depth:

150 sx.

Cementing Record:

4869'-4886'

4900'-4908' 4952'-4958' 4971'-4978'

Plug-Back Depth:

4995'

Total Depth:

Perforations:

5014

Well Name: C	arson U	Jnit #11	-19
--------------	---------	----------	-----

Legal Description: 660' FNL, 662.8' FWL

Sec. 19, T25N-R11W

San Juan County, N.M.

P&A Well Type:

Spud Date: 06/09/59

12-1/4" Surface Casing Hole Size: Surface Casing Size: 8-5/8" Surface Casing Depth: 103

Cementing Record: 100 sx.

Production Casing Hole Size: 7-7/8* Production Casing Size: 4-1/2" **Production Casing Depth:** 5016'

Cementing Record: 150 sx.

Perforations: 4854'-4880'

> 4889'-4896' 4927'-4932' 4940'-4952' 4959'-4970'

Plug-Back Depth: 5016'

Total Depth: 5020' of surface casing (172'-86')

25 sk. plug at base -

10 sk. surface marker -2

35 sk. plug at 375'

(375'-253')

50 sk. plug at csg. stub.

(1225'-1051')

Shot off 4-1/2"

casing at 1225'



25 sk. plug over

and above perfs

(5016'-4693')

Well Name: Carson Unit #21-19

Legal Description: 660' FNL, 1980' FWL

Sec. 19, T25N-R11W San Juan County, N.M.

Well Type: Water Injection Well

Spud Date: 06/22/57

Surface Casing Hole Size: 12-1/4"
Surface Casing Size: 8-5/8"
Surface Casing Depth: 213'

Cementing Record: 130 sx.

Production Casing Hole Size: 7 - 7 / 8 "
Production Casing Size: 4 - 1 / 2 "
Production Casing Depth: 5022'

Cementing Record: 150 sx.

Perforations: 4866'-4892'

4900'-4908' 4939'-4944' 4951'-4962' 4969'-4978'

Plug-Back Depth: 5022'

Total Depth: 5026'

Well Name:	Carson Unit #22-19	10 sk. surface marker
Legal Description:	1980' FNL, 1980' FWL Sec. 19, T25N-R11W San Juan County, N.M.	25 sk. plug at base of surface casing (170'-84')
Well Type:	P & A	35 sk. plug at 400' 2 1 (400'-278')
Spud Date:	03/11/60	(1)
Surface Casing Hole Size: Surface Casing Size: Surface Casing Depth:	12-1/4" 8-5/8" 108'	50 sk. plug at csg. stub (694'-520') Shot off 4-1/2"
Cementing Re∞rd:	100 sx.	casing at 694'
		20 sk. plug across perfs (1300'-1041').
		Drilled out cmt. to 1300'.
		Perf.'d csg. at 1195'.
Production Casing Hole Size:	7-7/8"	Set retainer at 1145'
Production Casing Size:	4-1/2"	and pumped 75 sx.
Production Casing Depth:	5027	thru retainer.
Cementing Re∞rd:	150 sx.	Perf.'d csg. at 1325'. Set retainer at 1300' and pumped 125 sx.
Perforations:	4868'-4888'	thru retainer.
	4898'-4905'	
	4934'-4942'	
	4952'-4962'	$U = \{1, \dots, M\}$
	4968'-4980'	((
	January 1976 1218'-1224'	
	1234'-1244'	
Plus Book Books	5007	Set cmt. retainer
Plug-Back Depth:	5027	at 4782' and pumped
Total Depth:	5030	100 sx. cmt. thru cmt. retainer.

Well Name:	Carson Unit #31-19	10 sk. surface marker
Legal Description:	660' FNL, 1973.5' FEL Sec. 19, T25N-R11W San Juan County, N.M.	25 sk. plug at base of surface casing (130'-46')
Well Type:	P & A	35 sk. plug at 420' (420'-298')
Spud Date:	12/08/59	
Surface Casing Hole Size: Surface Casing Size:	12-1/4" 8-5/8"	50 sk. plug at csg. stub (1386'-1212')
Surface Casing Depth:	105'	Shot off 4-1/2" casing at 1386'
Cementing Record:	100 sx.	
Production Casing Hole Size:	7-7/8"	
Production Casing Size:	4-1/2"	/
Production Casing Depth:	5029'	
Cementing Record:	150 sx.	7-7/8" hole
Perforations:	4867'-4895' 4900'-4910' 4922'-4926' 4940'-4944' 4952'-4958' 4964'-4970' 4976'-4982'	ok d
Plug-Back Depth:	5029'	30 sk. plug above perforations
Total Depth:	5030'	(4919'-4531')

COMPAN

November 2, 1987

New Mexico Oil Conservation Commission State Land Office Building P.O. Box 2088 Santa Fe, N.M. 87501

Subject: Carson Unit Well No. 24-18

660' FSL, 1930' FWL Section 18, T 25N, R 12W San Juan County, New Mexico Affidavit of Publication

Dear Sir:

Enclosed herewith please find the original Affidavit of Publication on the above-referenced well. We forwarded the Application for Authorization to Inject to your office on October 27, 1987.

Thank you.

Very truly yours,

Earlene J. Bickford Administrative Manager

EJB/das

Enclosure

November 2, 1987

Mr. Frank Chavez N.M. Oil Conservation Commission 1000 Rio Brazos Road Aztec, New Mexico 87410

Subject: Carson Unit Well No. 24-18

660' FSL, 1930' FWL Section 18, T 25N, R 12W San Juan County, New Mexico Affidavit of Publication

Dear Mr. Chavez:

Enclosed herewith, for your information, please find a copy of the Affidavit of Publication on the above-referenced well. A copy of the Application for Authorization to Inject was forwarded to your office on October 27, 1987.

Thank you.

Very truly yours,

Earlene J. Bickford Administrative Manager

EJB/das

Enclosure

RECEIVED NOV 03 1987.

OIL CON. DIV.

AFFIDAVIT OF PUBLICATION

No. <u>10831</u>

STATE	OF	NEW	MEXICO,
County	of S	an Jua	ın:

Bo++v Shipp being duly
sworn, says: That he is the <u>Mational Ad anager</u> of
THE FARMINGTON DAILY TIMES, a daily newspaper of general circulation published in English at Farmington, said county and state, and that the
hereto attached loggl notice
was published in a regular and entire issue of the said FARMINGTON DAILY Times, a daily newspaper duly qualified for the purpose within the
meaning of Chapter 167 of the 1937 Session Laws of the State of New
Mexico for One consecutive (days) (weeks) on the same day as
follows:
First Publication Thursday, October 29, 1987
Second Publication
Third Publication
Fourth Publication
and that payment therefor in the amount of \$ 6.25
has been made. Betty Dlupp
Subscribed and sworn to before me this 29th day of 00tobor
NOTARY PUBLIC, SAN JUAN COUNTY, NEW MEXICO
My Commission expires: 4224 23, 1990

Copy of Publication

NOTICE

NOTICE
Hixon Development Company,
PO Box 2810, Farmington, New
Mexico 87499, (505) 326-3325
whose agent is Aldrich L. Kuchera
hereby notifies interested parties
that the following well is to be converted to a water injection well.
Maximum rate will be 1200 BWPD
at less than 975 psi. Any request Maximum rate will be 1200 BWPD at less than 975 psi. Any request for information or objections should be filed with the Oil Conservation Division. State Land Office Building, PO Box 2088, Santa Fe. New Mexico 87501 within 15 days. days.

Carson Unit Well 24-18, SE/4
SW/4, Section 18, T25N, R12W
Legal No. 20831 published in
the Farmington Daily Times, Farmington, New Mexico on Thursday,
October 29, 1987.

OIL CON DIV.

AFFIDAVIT OF PUBLICATION

No. 20831

STATE OF NEW MEXICO, County of San Juan:

Be++v Shipp being duly
sworn, says: That he is the <u>National Adamager</u> of
THE FARMINGTON DAILY TIMES, a daily newspaper of general circulation published in English at Farmington, said county and state, and that the
hereto attached legal notice
was published in a regular and entire issue of the said FARMINGTON DAILY TIMES, a daily newspaper duly qualified for the purpose within the
meaning of Chapter 167 of the 1937 Session Laws of the State of New
Mexico for One emiseculario (days) (weeks) on the same day as follows:
First Publication Thursday, October 29, 1987
Second Publication
Fourth Publication
has been made. Betty Olupp
Subscribed and sworn to before me this 29th day of 00tobor 1987.
NOTARÝ PUBLIC, SAN JUAN COUNTY, NEW MEXICO
My Commission expires: ANN 23, 1990

Copy of Publication

NOTICE

NOTICE
Hixon Development Company.
PO Box 2810, Farmington, New
Mexico 87499, (505) 326-3325
whose agent is Aldrich L. Kuchera
hereby notifies interested parties
that the following well is to be converted to a water injection well.
Maximum rate will be 1200 BWPD
at less than 975 psi. Any request
for information or objections
should be filed with the Oil Conservation Division. State Land Office Building, PO Box 2088, Santa
Fe, New Mexico 87501 within 15
days.

Fe, New Mexico 8/501 WHITIN 15 days. Carson Unit Well 24-18, SE/4 SW/4, Section 18, T25M, R12W Legal No. 20831 published in the Farmington Daily Times, Farm-ington, New Mexico on Thursday, October 29, 1987.



STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE

1000 PIO BRAZOS POAD AZTEC, NEW MEXICO 87410 (505) 334-6178

OIL CONSERVATION DIVISION BOX 2088 SANTA FE, NEW MEXICO 87501		
DATE 11-2-87		•
RE: Proposed MC Proposed DHC Proposed NSL Proposed SWD Proposed WFX Proposed PMX		·
Gentlemen:		
I have examined the application	on dated 10-28-87	
for the Hixon Development of Operator	Company Carson (Intille) #24-18 Lease and Well No.	<i>N-18-25N-12</i> Unit, S-T-R
and my recommendations are as	follows:	
Yours truly,		
Ja Busel	•	