STATE OF NEW MEXICO



# ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

**OIL CONSERVATION DIVISION** 

**ORDER SWD-487** 

POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87504 (505) 827-5800

BRUCE KING GOVERNOR

ANITA LOCKWOOD CABINET SECRETARY

### APPLICATION OF CIBOLA ENERGY CORPORATION

#### ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), Cibola Energy Corporation made application to the New Mexico Oil Conservation Division on August 9, 1992, for permission to complete for salt water disposal its Duncan Federal No. 4Y located 1650 feet from the North line and 324 feet from the West line (Unit E) of Section 18, Township 9 South, Range 28 East, NMPM, Chaves County, New Mexico.

### THE DIVISION DIRECTOR FINDS THAT:

(1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;

(2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;

(3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and

(4) No objections have been received within the waiting period prescribed by said rule.

## IT IS THEREFORE ORDERED THAT:

The applicant herein, Cibola Energy Corporation is hereby authorized to complete its Duncan Federal No. 4Y located 1650 feet from the North line and 324 feet from the West line (Unit E) of Section 18, Township 9 South, Range 28 East, NMPM, Chaves County, New Mexico, in such manner as to permit the injection of salt water for disposal purposes into the San Andres formation at approximately 2208 feet to 2260 through 2 3/8 inch plastic lined tubing set in a packer located at approximately 2108 feet.

Cibola Energy Corporation Administrative Order SWD-487 August 29, 1992 Page 2

#### **IT IS FURTHER ORDERED THAT:**

Prior to commencing injection operations into the well, the operator shall cement squeeze the Aceite Negra No. 4 to establish top of cement behind the production string of casing at approximately 1708 feet. Subsequently, a temperature survey will be run to verify the cement top and copies of such shall be furnished to the supervisor of the Artesia District Office.

Prior to commencing injection operations into the well, the operator shall complete deepening operations on the Louise Yates No. 1 and cement the production string of casing in a manner to establish a top of cement at approximately 1708 feet. Subsequently, a temperature survey or an acoustic survey will be run to verify the cement top and copies of such shall be furnished to supervisor of the Artesia District Office.

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

The injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 442 psi.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the San Andres formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment and of the mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Artesia district office of the Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage. Cibola Energy Corporation Administrative Order SWD-487 August 29, 1992 Page 3

<u>PROVIDED FURTHER THAT</u>, jurisdiction of this cause is hereby retained by the Division for the entry of such further order or orders as may be deemed necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of the operator to conduct operations in a manner which will ensure the protection of fresh water or in a manner inconsistent with the requirements set forth in this order, the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall submit monthly reports of the disposal operations in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

Approved at Santa Fe, New Mexico, on this 26th day of August, 1992.

J. LEMAY. Director

xc: OCD - Artesia BLM - Carlsbad