

**David H Arrington Oil & Gas
Green Eyed Squealy Worm #1
Sec 26-15S-34E
Lea County, New Mexico**

WORKOVER PROGNOSIS

WELL: Green Eyed Squealy Worm #1

LOCATION: 1974 FSL & 1129 FEL Section 26, T15S, R34E Lea County, NM

ELEVATION: GL: 4,055' KB: 4,075'

API #: 30-025-36013

PROPERTY NUMBER: 01250-001

OBJECTIVE: Re Establish Morrow Production

DIRECTIONS: From the center of Lovington, turn West on Hwy 83 and go to Lovington Inn, turn right (North) on 17th Street, go North to "T" @ Gum Street. Turn left (West) on Gum and go 7.2 miles to cattleguard. Turn right (North) @ cattleguard, go through locked gate - combination 6685, then go north about 1 mile to well.

OPERATOR: David H Arrington Oil & Gas, Inc. Office: (432) 682-6685
Midland, Texas 79701 Fax: (432) 682-4139

Engineer: Art Carrasco Home: (432) 683-3753
Mobile: (432) 559-0042

Wellsite Supervision: David Burgen Mobile: (432) 208-3170

Geology: Brian Ball Home: (432) 699-8037
Mobile: (432) 528-2393

CASING: **SURFACE:** 17 1/4" hole, 13 3/8" @ 498', Cmt'd w/ 515 sxs. TOC @ surf.
INTERMEDIATE: 11" 8 5/8" @ 6196'. Cmt'd with 1225/250 sx. TOC @ not circ.
PRODUCTION- 7 7/8" hole, 5 1/2" @ 13200'. Cmt'd with 415/250 sx TOC @ 9500'
TUBING HEAD: 11" 5,000# x 7 1/16" 5M w/ 2 - 2" outlets
TREE: Entire Tree above tag hanger is 5,000 psig rated

SEE ATTACHED WELLBORE DIAGRAMS FOR DETAILS

PROCEDURE

1. Rig up workover unit.
2. NU BOP's
3. Open wellhead and release any pressure.
4. Load hole and insure well is dead.
5. Release packer.
6. POH w/production tubing and packer.
7. GIH w/production tubing, tubing anchor, and downhole production equipment.
8. GIH w/rods and pump
9. Put well on production.
10. Rig down workover unit.

Existing

WELL NAME: Green Eyed Squatty Worm #1 FIELD: WC USER: 030568
 STATE: NM27 COUNTY: Lea LOCATION: 1975 FSL & 1129 FEL of 26-15S-34E
 API NO: 30-025-36013 SPUD DATE: 5/28/2000 FORMATION: Morrow
 TD: 13200' FBTD: 13100' ELEVATION: 4055' GL

PIPE RECORD								CEMENT & HOLE DATA				
CSG	OD	GRADE	THD	WT/FT	TOP	BTM	# JTS	BIT SIZE	DEPTH	SK	WT.	TOC
Surf	13.375"	K55	BTC	54.50#	0'	498		17.500"		515		Surf
Inter	8.625"	J55	LT&C	32.00#	0'	6.186		11.000"		1475		unk
Prod	5.500"		LT&C	17.00#	0'	13.200		7.875"		945		8500'
Tbg	2.375"	N80	EUE	4.700#	0'	12.911	403					

Remarks:
 Short Joint @ 12.600'

Downhole equipment

1 - 5 1/2" 3/8" CIBP 10K @ ± 13.050'
 2 - 2 3/8" N80 sub 10' top @ 13.006'
 7 - 2 3/8" Wireline Re-Entry Guide
 7 - 2 3/8" N80 sub 7'
 7 - 1.875" 7 XN profile nipple w/ 1.791" NOGO @ ?
 7 - 2 3/8" N80 sub 7'
 7 - 1.875" 7 profile nipple @ 7'
 7 - 2 3/8" N80 sub 7'
 1 - 5 1/2" 3/8" 10K Pkr @ 12.911'
 7 - 5 1/2" orliff tool w/ 1.875" 7 profile nipple @ ?
 7 - 2 3/8" N80 Tbg
 403 - its 2 3/8" N80 Tbg


CAPACITY	(wt)	(bbbl)	(ft/bbl)	(cf/ft)
Tubing	2.375	4.70	00367	258.65
Casing	5.500	17.00	02320	43.01

VOLUME BETWEEN	(bbbl)	(ft/bbl)	(cf/ft)
100'-C80	2.375	5.500	01780
180'-C80			

PERFORATION RECORD

DATE	TOP	BTM	ZONE	STATUS	SPF
4/15/2004	13084'	13100'	Morrow	Abandoned	2
4/15/2004	13055'	13059'	Morrow	Abandoned	2
4/15/2004	12893'	13004'	U Morrow	Active	6

LOGS:



GEOLOGIST: Bit Baker

TUBULAR GOODS PERFORMANCE

Material	Size	WT	Grade	Threads	ID (in)	Drift (in)	Collapse* (psi)	Burst* (psi)	Tensile* (lbs)
13.375	54.50	K55	BTC	12.615	12.459	1,130	2,730		
8.625	32.00	J55	LTC	7.921	7.796	2,530	3,930	417,000	
8.625	32.00	N80	LTC			3,050	5,710		
5.500	17.00	HCP	LTC	4.892	4.767				
5.500	17.00	WC80	LTC	4.892	4.767				
5.500	17.00	P110	LTC	4.892	4.767	7,480	10,640	445,000	
5.500	17.00	N80	LTC	4.892	4.767	6,280	7,740	348,000	
2.375	4.70	N80	EUE	1.995	1.901	11,780	11,200	104,340	

* Safety Factor Not Included

PREPARED BY: Art Carrasco

DATE: 8/24/2006

Updated:

OFFICE: 432.682.6685 ex.314

FAX: 432.682.4139