

Elevation: 3531' DF

17-1/2" Hole

602' - 13 3/8", H-40, 48# Casing
Cemented w/650 sxs. Circulated to Surf.

11" Hole

Perfs: 2370'-2720' Overall
2-3/8" Plastic lined tubing w/packer set @ 2300'

3949' - 8 5/8", J-55, 32# Casing.
Cemented w/1600 sxs. TOC @ 350'
by Temp Survey

Cement Plug: 100 sxs. 3906'-4000' (Tagged)

7-7/8" Hole

Cement Plug: 45 sxs. 6885'-7050' (Tagged)
4-1/2" Casing Cut & Pulled from 7000'

TOC @ 10025' by Temp Survey

C.I.B.P. @ 10550' w/35' Cement on Top

C.I.B.P. @ 11400' w/50' Cement on Top

Perfs 11421-29', 11438-42', 11446-56', 11465-67'

PBTD @ 11492'

11560' - 4 1/2", J-55 & N-80,
11.6# Casing
Cemented w/220 sxs

T.D. @ 11560'

Case No. 13451
June 16, 2005
EXHIBIT No. 5

Dadco, Inc.
Jones Federal B No. 3
660' FSL & 660' FEL
Sec. 23, T-19S, R-31E
Eddy County, N.M.

ATTACHMENT III