

**LCX Energy, LLC.**  
**DAILY DRILLING REPORT**

LCX EXHIBIT NO. 15

|                              |                            |                       |            |            |
|------------------------------|----------------------------|-----------------------|------------|------------|
| WELL: FED COM 1725 # 61      | DATE: NOV 17/05            | COST: _____           | DAY: _____ | CUM: _____ |
| RIG NAME: BIG DOG # 2        | SPUD DATE: October 7, 2005 | Drilling: _____       | 25,977     | 899,204    |
| DEPTH (MD): 8,030            | DAYS SINCE SPUD: 31        | Completion: _____     | NO. _____  | 13,678     |
| PROGRESS: 298'               |                            | Mud & DRILLING: _____ | 44,483     |            |
| PRES. OP. DRLG. @ 18-20 FPH. | SUPERVISOR: MIKE STEWARD   | CHEMIC/PIPE: _____    | \$85       | \$3,237    |

[illegible]

| MUD DATA   |           | HYDRAULICS    |       |
|------------|-----------|---------------|-------|
| TIME       | 6:00      |               |       |
| MUD TYPE   | C/B       |               |       |
| WEIGHT     | 8.9       |               |       |
| VIS (SEC)  | 30        |               |       |
| PV/YP      |           |               |       |
| GELS       | 1         | MUD MIXED     |       |
| WATER LOSS | 18        | SALT GEL      | 40    |
| CAKE       | 1         | STARCH        | 8     |
| TS/LGS %   |           | NUT PLUG      | 15    |
| HGS/SAND % |           | MICA          | 15    |
| O/W RATIO  | 100%      | SODA-ASH      | 2     |
| OIL %      |           | MF-55-/A SIDE | 5/    |
| LCM #      | 1#-2#     | C-202         | 12    |
| PH/ES      | 10        | 9390          | 5     |
| PM         | NA        | CAUSTIC       | 5     |
| PF/MF      | .6+.8     | ULTRA-LUB     | 5     |
| CL (PPM)   | 48,000    |               |       |
| CA (PPM)   | 2,110     | DRILL STRING  |       |
| SOLIDS %   | 1.00%     | Pick-up Wt    | 150K  |
| SAND %     | TR        | Rotating Wt   | 168K  |
| DEPTH      | 8,030     | Slack-off Wt  | 138K  |
| DATE       | 11/6/2005 | Torque        | 1 RND |

| BIT RECORD                    |         |       |  |
|-------------------------------|---------|-------|--|
| BIT # (#ofRR if re-run)       | 7       |       |  |
| SIZE                          | 7.875   |       |  |
| MFG.                          | SMITH   |       |  |
| TYPE                          | F37     |       |  |
| IADC CODE                     | 537     |       |  |
| SERIAL # (RR if re-run)       | PB 7148 |       |  |
| DEPTH IN                      | 6,538   |       |  |
| DEPTH OUT                     |         |       |  |
| JETS                          | 3 X13   |       |  |
| WOB (min   max)               | 18K     | 30K   |  |
| RPM (rot/motor or min(max)    | R-38    | M-107 |  |
| FOOTAGE (Daily   Cum)         | 298     | 1,492 |  |
| ROT. HOURS (Daily   Cum)      | 22.5    | 124.0 |  |
| ROP (Daily   Cum)             | 13.2    | 12.0  |  |
| Motor Circ. Hrs (Daily   Cum) | 1.0     | 5.0   |  |

| BIT GRADING |    |    |      |      |         |           |          |        |
|-------------|----|----|------|------|---------|-----------|----------|--------|
| Bit         | IN | O  | Dull | Loc. | Bearing | Gauge     | Other    | Reason |
| #           | 0  | BT | Ch.  |      | Seal    | (x/16ths) | Dull Ch. | Pulled |
| Remarks:    |    |    |      |      |         |           |          |        |

| BHA & DRILL STRING / CASING DETAIL |       |               |             |             |                |       |                                      |       |         | Last BHA Insp'n (Hrs):   |               |       |
|------------------------------------|-------|---------------|-------------|-------------|----------------|-------|--------------------------------------|-------|---------|--------------------------|---------------|-------|
| Description                        | Jts # | Length (feet) | OD (inches) | ID (inches) | Weight (lb/ft) | Grade | Connection<br>BOTM(Size & Thread)TOP |       |         | 10/27/05=6.5"DC=102. HRS |               |       |
| SURFACE CSG                        | 9     | 390           | 13.3/8      | 12.715      | 48             | H40   | ST&C                                 |       |         | BHA Buoy. Wt:<br>46,000  |               |       |
| INTERMEDIATE CSG                   | 30    | 1294          | 10.1        | 8.921       | 36             | J55   | LT&C                                 |       |         | Wt. Below Jars:<br>N/A   |               |       |
| POOD LONG STRING                   |       |               |             |             |                |       |                                      |       |         |                          |               |       |
| 1 X CROSS OVER                     |       |               |             |             |                |       |                                      |       |         |                          |               |       |
| POOD LONG STRING                   |       |               |             |             |                |       |                                      |       |         |                          |               |       |
| BIT                                | 1     | 17.875        |             |             | 99             |       |                                      |       | 4.5 REG |                          |               |       |
| 1X MRT 1.75%                       | 1     | 25.03         | 8           | 225         |                | 99    | DC                                   | 4.5XH | 4.5XH   |                          |               |       |
| 1XFLOAT SUB                        | 1     | 2.05          | 6.3/8       | 2.3/4       |                | 99    | DC                                   | 4.5XH | 4.5XH   | Previous Casing          |               |       |
| 1X SHOCK SUB                       | 1     | 10.08         | 8.5/16      | 2"          |                | 99    | DC                                   | 4.5XH | 4.5XH   | Size                     | 9.5/8         |       |
| 1XDTU STAB                         | 1     | 5.85          | 6"          | 225         | 2"             | 5     | 99                                   | DC    | 4.5XH   | 4.5XH                    | Depth         | 1,294 |
| 1X UBHO SUB                        | 1     | 2.58          | 8           | 225         | 2"             | 5     | 99                                   | DC    | 4.5XH   | 4.5XH                    | Weight        | 36    |
| 2XMON DC                           | 2     | 62.04         | 6"          | 225         | 2"             | 13/16 | 99                                   | DC    | 4.5XH   | 4.5XH                    | Grade         | J55   |
| 90X 4.5 16.80 E DP                 | 132   | 4208.29       | 4"          | 5           | 3/7/8          |       | 99                                   | DC    | 4.5XH   | 4.5XH                    | Gas Record    |       |
| 17X DRILL COLLARS                  | 17    | 524.03        | 6"          | 5           | 2."            | 225   | 99                                   | DC    | 4.5XH   | 4.5XH                    | BG gas units  | 100   |
|                                    |       |               |             |             |                |       |                                      |       |         |                          | Max gas units | 1,860 |
|                                    |       |               |             |             |                |       |                                      |       |         |                          | Max gas depth | 7,950 |
|                                    |       |               |             |             |                |       |                                      |       |         |                          | Conn. gas     |       |
| TOTAL BHA                          |       | 4,839.57      |             |             |                |       |                                      |       |         |                          | Trip gas-SURV |       |

|                           |                     |                 |
|---------------------------|---------------------|-----------------|
| <b>MUD PUMPS</b>          | <b>1</b>            | <b>1</b>        |
| <b>PUMP PRESSURE</b>      | <b>1200</b>         | <b>N/A</b>      |
| <b>SPM</b>                | <b>69</b>           |                 |
| <b>LINER SIZE</b>         | <b>7"</b>           |                 |
| <b>STROKE LENGTH</b>      | <b>9"</b>           |                 |
| <b>OUTPUT (gal/stk)</b>   | <b>4.3</b>          | <b>P-RATE</b>   |
| <b>OUTPUT (gpm)</b>       | <b>312</b>          | <b>-PUMP-SL</b> |
| <b>SPR &amp; PRESSURE</b> | <b>54 X 630 PSI</b> | <b>X 1400 F</b> |

| DEVIATION SURVEYS |       |       |     |      |        |       |      |
|-------------------|-------|-------|-----|------|--------|-------|------|
| MD                | TVD   | Incl. | Az. | DLS. | V.S.   | N-S   | E-W  |
| 7,722             | 4,902 | 89    | 181 | 2    | 3076.2 | -3076 | -1.9 |
| 7,786             | 4,904 | 88.2  | 180 | 1.3  | 3140.2 | -3140 | -8.6 |
| 7,849             | 4,905 | 89.7  | 180 | 2.5  | 3203.2 | -3203 | -8.6 |
| 7,913             | 4,905 | 89.6  | 180 | 0.3  | 32676  | -3267 | -8.3 |
|                   |       |       |     |      |        |       |      |
|                   |       |       |     |      |        |       |      |

|                      |                  |
|----------------------|------------------|
| Notes / Next 24 hrs: | DRLG. & BIT TRIP |
|----------------------|------------------|