

Iceman 26 W2AP Fed Com #1H Production Table

9/8/2016

Well Name	Well ID	Surface Location	Operator	Vert/Horiz	WFMP Comp Date	Production Time	Wolfcamp Production			Notes
							Cum Oil (MBO)	Cum Water (MBW)	Cum Gas (MMCF)	
Amoco 22 State #1	22E	1980 FNL & 660 FWL T23S - R27E, Sec. 22	Yates	V	6/2/1987	4.3 yrs	2	0	14	Upper & Lower WFMP Comingled
Walterscheid 23 #1	23M	1050 FSL & 660 FWL T23S - R27E, Sec. 23	Marbob	V	10/27/2006	8 months	1	6	1	WFMP Sd Compl.
Lost River Fee #1	23P	990 FSL & 990 FEL T23S - R27E, Sec. 23	RKI	V	12/11/2014	1.3 yrs	1	3	5	WFMP Sd & BSPG Comingled
Chaka State #3H	26NC	190 FSL & 1980 FWL T23S - R27E, Sec. 26	Concho	H	5/20/2015	1 yr	42	310	422	Lower WFMP Horiz.
Palo Duro BCO State #1	35I	1980 FSL & 660 FEL T23S - R27E, Sec. 35	Yates	V	1/12/2006	10.5 yrs	2	3	95	Lower WFMP Compl.

EXHIBIT

10

Mewbourne Oil Company

Eddy County, New Mexico

Iceman 26 W2AP Fed Com 1H

Sec 26, T23S, R27E

SL: 205' FNL & 330' FEL

BHL: 330' FSL & 330' FEL

Plan: Design #1

Standard Planning Report

31 October, 2014

EXHIBIT 11

Planning Report

Database: Hobbs
Company: Mewbourne Oil Company
Project: Eddy County, New Mexico
Site: Iceman 26 W2AP Fed Com 1H
Well: Sec 26, T23S, R27E
Wellbore: BHL: 330' FSL & 330' FEL
Design: Design #1

Local Co-ordinate Reference: Site Iceman 26 W2AP Fed Com 1H
TVD Reference: WELL @ 3156.0usft (Original Well Elev)
MD Reference: WELL @ 3156.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Project	Eddy County, New Mexico		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Iceman 26 W2AP Fed Com 1H			
Site Position:	Northing:	466,619.60 usft	Latitude:	32° 16' 57.811 N
From: Map	Easting:	555,727.60 usft	Longitude:	104° 9' 10.830 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16"	Grid Convergence: 0.10 °

Well	Sec 26, T23S, R27E			
Well Position	+N-S	0.0 usft	Northing:	466,619.60 usft
	+E-W	0.0 usft	Easting:	555,727.60 usft
Position Uncertainty	0.0 usft		Wellhead Elevation:	3,156.0 usft
			Ground Level:	3,136.0 usft

Wellbore	BHL: 330' FSL & 330' FEL				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
			(°)	(°)	(nT)
	IGRF200510	10/31/2014	7.44	60.09	48,305

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD)	+N-S	+E-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.0	0.0	0.0	177.94

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
9,333.0	0.00	0.00	9,333.0	0.0	0.0	0.00	0.00	0.00	0.00	
10,233.1	90.00	177.94	9,906.0	-572.6	20.6	10.00	10.00	0.00	177.94	
14,475.2	90.00	177.94	9,906.0	-4,812.0	173.4	0.00	0.00	0.00	0.00	BHL: 330 FSL & 330 I

Planning Report

Database: Hobbs
Company: Mewbourne Oil Company
Project: Eddy County, New Mexico
Site: Iceman 26 W2AP Fed Com 1H
Well: Sec 26, T23S, R27E
Wellbore: BHL: 330' FSL & 330' FEL
Design: Design #1

Local Co-ordinate Reference: Site Iceman 26 W2AP Fed Com 1H
TVD Reference: WELL @ 3156.0usft (Original Well Elev)
MD Reference: WELL @ 3156.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
SL: 205 FNL & 330 FEL									
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.00	0.00	2,700.0	0.0	0.0	0.0	0.00	0.00	0.00
2,800.0	0.00	0.00	2,800.0	0.0	0.0	0.0	0.00	0.00	0.00
2,900.0	0.00	0.00	2,900.0	0.0	0.0	0.0	0.00	0.00	0.00
3,000.0	0.00	0.00	3,000.0	0.0	0.0	0.0	0.00	0.00	0.00
3,100.0	0.00	0.00	3,100.0	0.0	0.0	0.0	0.00	0.00	0.00
3,200.0	0.00	0.00	3,200.0	0.0	0.0	0.0	0.00	0.00	0.00
3,300.0	0.00	0.00	3,300.0	0.0	0.0	0.0	0.00	0.00	0.00
3,400.0	0.00	0.00	3,400.0	0.0	0.0	0.0	0.00	0.00	0.00
3,500.0	0.00	0.00	3,500.0	0.0	0.0	0.0	0.00	0.00	0.00
3,600.0	0.00	0.00	3,600.0	0.0	0.0	0.0	0.00	0.00	0.00
3,700.0	0.00	0.00	3,700.0	0.0	0.0	0.0	0.00	0.00	0.00
3,800.0	0.00	0.00	3,800.0	0.0	0.0	0.0	0.00	0.00	0.00
3,900.0	0.00	0.00	3,900.0	0.0	0.0	0.0	0.00	0.00	0.00
4,000.0	0.00	0.00	4,000.0	0.0	0.0	0.0	0.00	0.00	0.00
4,100.0	0.00	0.00	4,100.0	0.0	0.0	0.0	0.00	0.00	0.00
4,200.0	0.00	0.00	4,200.0	0.0	0.0	0.0	0.00	0.00	0.00
4,300.0	0.00	0.00	4,300.0	0.0	0.0	0.0	0.00	0.00	0.00
4,400.0	0.00	0.00	4,400.0	0.0	0.0	0.0	0.00	0.00	0.00
4,500.0	0.00	0.00	4,500.0	0.0	0.0	0.0	0.00	0.00	0.00
4,600.0	0.00	0.00	4,600.0	0.0	0.0	0.0	0.00	0.00	0.00
4,700.0	0.00	0.00	4,700.0	0.0	0.0	0.0	0.00	0.00	0.00
4,800.0	0.00	0.00	4,800.0	0.0	0.0	0.0	0.00	0.00	0.00
4,900.0	0.00	0.00	4,900.0	0.0	0.0	0.0	0.00	0.00	0.00
5,000.0	0.00	0.00	5,000.0	0.0	0.0	0.0	0.00	0.00	0.00
5,100.0	0.00	0.00	5,100.0	0.0	0.0	0.0	0.00	0.00	0.00
5,200.0	0.00	0.00	5,200.0	0.0	0.0	0.0	0.00	0.00	0.00

Planning Report

Database: Hobbs
 Company: Mewbourne Oil Company
 Project: Eddy County, New Mexico
 Site: Iceman 26 W2AP Fed Com 1H
 Well: Sec 26, T23S, R27E
 Wellbore: BHL: 330' FSL & 330' FEL
 Design: Design #1

Local Co-ordinate Reference: Site Iceman 26 W2AP Fed Com 1H
 TVD Reference: WELL @ 3156.0usft (Original Well Elev)
 MD Reference: WELL @ 3156.0usft (Original Well Elev)
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,300.0	0.00	0.00	5,300.0	0.0	0.0	0.0	0.00	0.00	0.00
5,400.0	0.00	0.00	5,400.0	0.0	0.0	0.0	0.00	0.00	0.00
5,500.0	0.00	0.00	5,500.0	0.0	0.0	0.0	0.00	0.00	0.00
5,600.0	0.00	0.00	5,600.0	0.0	0.0	0.0	0.00	0.00	0.00
5,700.0	0.00	0.00	5,700.0	0.0	0.0	0.0	0.00	0.00	0.00
5,800.0	0.00	0.00	5,800.0	0.0	0.0	0.0	0.00	0.00	0.00
5,900.0	0.00	0.00	5,900.0	0.0	0.0	0.0	0.00	0.00	0.00
6,000.0	0.00	0.00	6,000.0	0.0	0.0	0.0	0.00	0.00	0.00
6,100.0	0.00	0.00	6,100.0	0.0	0.0	0.0	0.00	0.00	0.00
6,200.0	0.00	0.00	6,200.0	0.0	0.0	0.0	0.00	0.00	0.00
6,300.0	0.00	0.00	6,300.0	0.0	0.0	0.0	0.00	0.00	0.00
6,400.0	0.00	0.00	6,400.0	0.0	0.0	0.0	0.00	0.00	0.00
6,500.0	0.00	0.00	6,500.0	0.0	0.0	0.0	0.00	0.00	0.00
6,600.0	0.00	0.00	6,600.0	0.0	0.0	0.0	0.00	0.00	0.00
6,700.0	0.00	0.00	6,700.0	0.0	0.0	0.0	0.00	0.00	0.00
6,800.0	0.00	0.00	6,800.0	0.0	0.0	0.0	0.00	0.00	0.00
6,900.0	0.00	0.00	6,900.0	0.0	0.0	0.0	0.00	0.00	0.00
7,000.0	0.00	0.00	7,000.0	0.0	0.0	0.0	0.00	0.00	0.00
7,100.0	0.00	0.00	7,100.0	0.0	0.0	0.0	0.00	0.00	0.00
7,200.0	0.00	0.00	7,200.0	0.0	0.0	0.0	0.00	0.00	0.00
7,300.0	0.00	0.00	7,300.0	0.0	0.0	0.0	0.00	0.00	0.00
7,400.0	0.00	0.00	7,400.0	0.0	0.0	0.0	0.00	0.00	0.00
7,500.0	0.00	0.00	7,500.0	0.0	0.0	0.0	0.00	0.00	0.00
7,600.0	0.00	0.00	7,600.0	0.0	0.0	0.0	0.00	0.00	0.00
7,700.0	0.00	0.00	7,700.0	0.0	0.0	0.0	0.00	0.00	0.00
7,800.0	0.00	0.00	7,800.0	0.0	0.0	0.0	0.00	0.00	0.00
7,900.0	0.00	0.00	7,900.0	0.0	0.0	0.0	0.00	0.00	0.00
8,000.0	0.00	0.00	8,000.0	0.0	0.0	0.0	0.00	0.00	0.00
8,100.0	0.00	0.00	8,100.0	0.0	0.0	0.0	0.00	0.00	0.00
8,200.0	0.00	0.00	8,200.0	0.0	0.0	0.0	0.00	0.00	0.00
8,300.0	0.00	0.00	8,300.0	0.0	0.0	0.0	0.00	0.00	0.00
8,400.0	0.00	0.00	8,400.0	0.0	0.0	0.0	0.00	0.00	0.00
8,500.0	0.00	0.00	8,500.0	0.0	0.0	0.0	0.00	0.00	0.00
8,600.0	0.00	0.00	8,600.0	0.0	0.0	0.0	0.00	0.00	0.00
8,700.0	0.00	0.00	8,700.0	0.0	0.0	0.0	0.00	0.00	0.00
8,800.0	0.00	0.00	8,800.0	0.0	0.0	0.0	0.00	0.00	0.00
8,900.0	0.00	0.00	8,900.0	0.0	0.0	0.0	0.00	0.00	0.00
9,000.0	0.00	0.00	9,000.0	0.0	0.0	0.0	0.00	0.00	0.00
9,100.0	0.00	0.00	9,100.0	0.0	0.0	0.0	0.00	0.00	0.00
9,200.0	0.00	0.00	9,200.0	0.0	0.0	0.0	0.00	0.00	0.00
9,300.0	0.00	0.00	9,300.0	0.0	0.0	0.0	0.00	0.00	0.00
9,333.0	0.00	0.00	9,333.0	0.0	0.0	0.0	0.00	0.00	0.00
KOP @ 9333									
9,400.0	6.70	177.94	9,399.8	-3.9	0.1	3.9	10.00	10.00	0.00
9,500.0	16.70	177.94	9,497.6	-24.1	0.9	24.2	10.00	10.00	0.00
9,600.0	26.70	177.94	9,590.4	-61.0	2.2	61.1	10.00	10.00	0.00
9,700.0	36.70	177.94	9,675.4	-113.5	4.1	113.6	10.00	10.00	0.00
9,718.7	38.57	177.94	9,690.3	-124.9	4.5	125.0	10.00	10.00	0.00
Take Point: 330 FNL & 330 FEL									
9,800.0	46.70	177.94	9,750.0	-179.9	6.5	180.0	10.00	10.00	0.00
9,900.0	56.70	177.94	9,811.9	-258.2	9.3	258.4	10.00	10.00	0.00
10,000.0	66.70	177.94	9,859.3	-346.1	12.5	346.3	10.00	10.00	0.00
10,100.0	76.69	177.94	9,890.6	-440.8	15.9	441.1	10.00	10.00	0.00
10,200.0	86.69	177.94	9,905.0	-539.6	18.4	540.0	10.00	10.00	0.00

Planning Report

Database: Hobbs
Company: Mowbome Oil Company
Project: Eddy County, New Mexico
Site: Iccaman 26 W2AP Fed Com 1H
Well: Sec 26, T23S, R27E
Wellbore: BHL: 330' FSL & 330' FEL
Design: Design #1

Local Co-ordinate Reference: Site Iccaman 26 W2AP Fed Com 1H
TVD Reference: WELL @ 3156.0usft (Original Well Elev)
MD Reference: WELL @ 3156.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,233.0	90.00	177.94	9,906.0	-572.6	20.6	573.0	10.00	10.00	0.00
LP: 778 FNL & 330 FEL									
10,300.0	90.00	177.94	9,906.0	-639.5	23.0	639.9	0.00	0.00	0.00
10,400.0	90.00	177.94	9,906.0	-739.5	26.6	739.9	0.00	0.00	0.00
10,500.0	90.00	177.94	9,906.0	-839.4	30.2	839.9	0.00	0.00	0.00
10,600.0	90.00	177.94	9,906.0	-939.3	33.8	939.9	0.00	0.00	0.00
10,700.0	90.00	177.94	9,906.0	-1,039.3	37.4	1,039.9	0.00	0.00	0.00
10,800.0	90.00	177.94	9,906.0	-1,139.2	41.1	1,139.9	0.00	0.00	0.00
10,900.0	90.00	177.94	9,906.0	-1,239.1	44.7	1,239.9	0.00	0.00	0.00
11,000.0	90.00	177.94	9,906.0	-1,339.1	48.3	1,339.9	0.00	0.00	0.00
11,100.0	90.00	177.94	9,906.0	-1,439.0	51.9	1,439.9	0.00	0.00	0.00
11,200.0	90.00	177.94	9,906.0	-1,538.9	55.5	1,539.9	0.00	0.00	0.00
11,300.0	90.00	177.94	9,906.0	-1,638.9	59.1	1,639.9	0.00	0.00	0.00
11,400.0	90.00	177.94	9,906.0	-1,738.8	62.7	1,739.9	0.00	0.00	0.00
11,500.0	90.00	177.94	9,906.0	-1,838.7	66.3	1,839.9	0.00	0.00	0.00
11,600.0	90.00	177.94	9,906.0	-1,938.7	69.9	1,939.9	0.00	0.00	0.00
11,700.0	90.00	177.94	9,906.0	-2,038.6	73.5	2,039.9	0.00	0.00	0.00
11,800.0	90.00	177.94	9,906.0	-2,138.5	77.1	2,139.9	0.00	0.00	0.00
11,900.0	90.00	177.94	9,906.0	-2,238.5	80.7	2,239.9	0.00	0.00	0.00
12,000.0	90.00	177.94	9,906.0	-2,338.4	84.3	2,339.9	0.00	0.00	0.00
12,100.0	90.00	177.94	9,906.0	-2,438.4	87.9	2,439.9	0.00	0.00	0.00
12,200.0	90.00	177.94	9,906.0	-2,538.3	91.5	2,539.9	0.00	0.00	0.00
12,300.0	90.00	177.94	9,906.0	-2,638.2	95.1	2,639.9	0.00	0.00	0.00
12,400.0	90.00	177.94	9,906.0	-2,738.2	98.7	2,739.9	0.00	0.00	0.00
12,500.0	90.00	177.94	9,906.0	-2,838.1	102.3	2,839.9	0.00	0.00	0.00
12,600.0	90.00	177.94	9,906.0	-2,938.0	105.9	2,939.9	0.00	0.00	0.00
12,700.0	90.00	177.94	9,906.0	-3,038.0	109.5	3,039.9	0.00	0.00	0.00
12,800.0	90.00	177.94	9,906.0	-3,137.9	113.1	3,139.9	0.00	0.00	0.00
12,900.0	90.00	177.94	9,906.0	-3,237.8	116.7	3,239.9	0.00	0.00	0.00
13,000.0	90.00	177.94	9,906.0	-3,337.8	120.3	3,339.9	0.00	0.00	0.00
13,100.0	90.00	177.94	9,906.0	-3,437.7	123.9	3,439.9	0.00	0.00	0.00
13,200.0	90.00	177.94	9,906.0	-3,537.6	127.5	3,539.9	0.00	0.00	0.00
13,300.0	90.00	177.94	9,906.0	-3,637.6	131.1	3,639.9	0.00	0.00	0.00
13,400.0	90.00	177.94	9,906.0	-3,737.5	134.7	3,739.9	0.00	0.00	0.00
13,500.0	90.00	177.94	9,906.0	-3,837.4	138.3	3,839.9	0.00	0.00	0.00
13,600.0	90.00	177.94	9,906.0	-3,937.4	141.9	3,939.9	0.00	0.00	0.00
13,700.0	90.00	177.94	9,906.0	-4,037.3	145.5	4,039.9	0.00	0.00	0.00
13,800.0	90.00	177.94	9,906.0	-4,137.2	149.1	4,139.9	0.00	0.00	0.00
13,900.0	90.00	177.94	9,906.0	-4,237.2	152.7	4,239.9	0.00	0.00	0.00
14,000.0	90.00	177.94	9,906.0	-4,337.1	156.3	4,339.9	0.00	0.00	0.00
14,100.0	90.00	177.94	9,906.0	-4,437.1	159.9	4,439.9	0.00	0.00	0.00
14,200.0	90.00	177.94	9,906.0	-4,537.0	163.5	4,539.9	0.00	0.00	0.00
14,300.0	90.00	177.94	9,906.0	-4,636.9	167.1	4,639.9	0.00	0.00	0.00
14,400.0	90.00	177.94	9,906.0	-4,736.9	170.7	4,739.9	0.00	0.00	0.00
14,475.2	90.00	177.94	9,906.0	-4,812.0	173.4	4,815.1	0.00	0.00	0.00
BHL: 330 FSL & 330 FEL									

Planning Report

Database: Hobbs
Company: Mewbourne Oil Company
Project: Eddy County, New Mexico
Site: Iceman 26 W2AP Fed Com 1H
Well: Sec 26, T23S, R27E
Wellbore: BHL: 330' FSL & 330' FEL
Design: Design #1

Local Co-ordinate Reference:
TVD Reference:
MD Reference:
North Reference:
Survey Calculation Method:

Site Iceman 26 W2AP Fed Com 1H
WELL @ 3156.0usft (Original Well Elev)
WELL @ 3156.0usft (Original Well Elev)
Grid
Minimum Curvature

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
SL: 205 FNL & 330 FEL - plan hits target center - Point	0.00	0.00	0.0	0.0	0.0	466,619.60	555,727.60	32° 16' 57.811 N	104° 9' 10.830 W
KOP @ 9333 - plan hits target center - Point	0.00	0.00	9,333.0	0.0	0.0	466,619.60	555,727.60	32° 16' 57.811 N	104° 9' 10.830 W
Take Point: 330 FNL & 3 - plan misses target center by 6.7usft at 9718.8usft MD (9690.3 TVD, -124.9 N, 4.5 E) - Point	0.00	0.00	9,690.0	-125.0	11.2	466,494.60	555,738.80	32° 16' 56.574 N	104° 9' 10.702 W
LP: 778 FNL & 330 FEL - plan hits target center - Point	0.00	0.00	9,906.0	-572.6	20.6	466,047.00	555,748.20	32° 16' 52.144 N	104° 9' 10.602 W
BHL: 330 FSL & 330 FE - plan hits target center - Point	0.00	0.00	9,906.0	-4,812.0	173.4	461,807.60	555,901.00	32° 16' 10.187 N	104° 9' 8.905 W

