STATE OF NEW MEXICO



ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION 2040 S. PACHECO SANTA FE. NEW MEXICO 87505 (505) 827-7131

September 6, 1995

D. J. Simmons Company, Ltd.c/o On Site Technologies, Ltd.P. O. Box 2606Farmington, New Mexico 87499

Attention: Robert L. Crabb

Administrative Order DD-115

Dear Mr. Crabb:

Reference is made to your application on behalf of the operator D. J. Simmons Company, Ltd. dated July 31, 1995 for authorization to recomplete its existing L. V. Hamner "A" Well No. 1 (API No. 30-045-07939) by side tracking off of the vertical wellbore and directionally drill to a pre-determined bottom-hole location in order to further develop the Blanco-Mesaverde Pool underlying its existing 320-acre standard gas spacing and proration unit ("GPU") comprising the W/2 of Section 21, Township 29 North, Range 9 West, NMPM, San Juan County, New Mexico.

The Division Director Finds That:

- (1) The application has been duly filed under the provisions of Rule 111(D) and (E) of the General Rules and Regulations of the New Mexico Oil Conservation Division ("Division"), revised by Division Order No. R-10388, issued by the Oil Conservation Commission in Case 11,274 on June 13, 1995;
- (2) The L. V. Hamner "A" Well No. 1, located 590 feet from the South line and 1090 feet from the West line (Unit M) of said Section 21, was originally drilled and completed as an initial Blanco-Mesaverde well in 1954;
- (3) By Order No. R-8170, as amended, the Division promulgated the "General Rules For The Prorated Gas Pools of New Mexico/Special Rules and Regulations For The Blanco-Mesaverde Pool", which includes provisions for 320-acre gas spacing and proration units and well location requirements whereby the initial well drilled on a GPU shall be located be no closer than 790 feet to the outer boundary of the quarter section on which the well is located and not closer than 130 feet to any

quarter-quarter section line or subdivision inner boundary and the <u>infill</u> well drilled on an existing GPU shall be in the quarter section not containing a Mesaverde gas well and shall be located with respect to the restrictions as previously described;

- (4) The infill well for the subject GPU is the L. V. Hamner "A" Well No. 1-A (API No. 30-045-23389), located at a standard gas well location 1720 feet from the North line and 1760 feet from the West line (Unit F) of said Section 21.
- (5) The applicant/operator proposes to kick-off from vertical at a depth of approximately 3,550 feet in a northeasterly direction and drill in such a manner as to bottom back into the Blanco-Mesaverde Pool, with total horizontal displacement of said well to be approximately 600 feet;
- (6) The applicable drilling window or "producing area" for said wellbore should include that area within the SW/4 of said Section 21 that is no closer than 790 feet to the quarter section line; and,
- (7) It appearing the applicant has satisfied all of the appropriate requirements prescribed in said Rule 111.D and E, the subject application should be approved and the well should be governed by the provisions contained within this order and all other applicable provisions of Division General Rule 111.

IT IS THEREFORE ORDERED THAT:

(1) The operator, D. J. Simmons Company, Ltd., is hereby authorized to recomplete its existing L. V. Hamner "A" Well No. 1 (API No. 30-045-07939), located 590 feet from the South line and 1090 feet from the West line (Unit M) of Section 21, Township 29 North, Range 9 West, NMPM, San Juan County, New Mexico, by side tracking off of the vertical wellbore at a depth of approximately 3,550 feet in a northeasterly direction and drill in such a manner as to bottom back in the Blanco-Mesaverde Pool, within the SW/4 of said Section 21 such that the bottomhole location is no closer than 790 feet to the quarter section line;

PROVIDED HOWEVER THAT prior to commencing directional drilling operations in said wellbore, the applicant shall establish the location of the kick-off point by means of a directional survey acceptable to the Division.

<u>PROVIDED FURTHER THAT</u> during or upon completion of directional drilling operations, the applicant shall conduct an accurate wellbore survey from the kick-off point to total depth in order that the subsurface bottomhole location, as well as the wellbore's true depth and course, may be determined.

- (2) The applicant shall notify the supervisor of the Aztec district office of the Division of the date and time said wellbore surveys are to be conducted so that they may be witnessed. The applicant shall further provide a copy of said wellbore surveys to the Santa Fe and Aztec offices of the Division upon completion.
- (3) This well shall remain in the existing 320-acre standard gas spacing and proration unit comprising the W/2 of said Section 21.
- (4) The operator shall comply with all requirements and conditions set forth in Division General Rule 111.E(2) and any applicable requirements in 111.D and F and Order No. R-8170, as amended.
- (5) Form C-105 shall be filed in accordance with Division Rule 1105 and the operator shall indicate thereon true vertical depth in addition to measured depths.
- (6) Jurisdiction of this cause is retained for the entry of such further orders as the Division may deem necessary.

DONE at Santa Fe, New Mexico, on the day and year hereinabove designated.

STATE OF NEW MEXICO OIL CONSERVATION DIVISION

WILLIAM J. LEMAY

Director

SEAL

WJL/MES/kv

cc: Oil Conservation Division - Aztec

U. S. Bureau of Land Management - Farmington

File: Case 11,274 🗸