

BEFORE EXAMINER STOGNER  
OIL CONSERVATION DIVISION

---

EXHIBIT NO. 7

---

CASE NO. 11881

Wells in Area of Review  
Application for Authorization to Inject  
Southwest Royalties, Inc.

**Ammons Madera #4**

Location: 660' FSL & 1980' FWL  
Type: Oil

Sec 15, T26S, R33E  
Date Drilled: 10/96  
Total Depth: 5214'

Casing Record:

Size	Depth	Sacks Cement	
8 5/8"	300'	925	
5 1/2"	5214'	100	TOC @ 1145' CBL

Completion:

- 11/96 Perforated 5030-43'
- 11/96 Frac'ed well w/40,400# 16/30 sand. Put well on pump.

**Ammons Madera #3**

Location: 1980' FSL & 1980' FWL  
Type: Oil

Sec 15, T26S, R33E  
Date Drilled: 8/95  
Total Depth: 5221'

Casing Record:

Size	Depth	Sacks Cement	
8 5/8"	425'	300	
5 1/2"	5221'	370	TOC @ 3925' CBL

Completion:

- 8/95 Perf 5046-54'
- 10/95 Frac'ed well w/43,020# 16/30 sand. Put well on pump.

**Continental Fed #1**

Location: 1980' FNL & 1650' FWL  
Type: Oil

Sec 15, T26S, R33E  
Date Drilled: 5/72  
Total Depth: 5100'

Casing Record:

Size	Depth	Sacks Cement	
8 5/8"	375'	200	
4 1/2"	5100'	200	TOC @ 4240' CBL

Completion:

- 6/72 Perf 5003-13'
- 6/72 Frac'ed w/7500# sand.
- 7/95 Add perfs 5014-38'. Acidized w/2500 gal 7 1/2 % NEFE.