

COMPANY: E. G. WOODS WELL: SIMON NO. 1-A DC-1 FIELD: MALJAMAR LOCATION: LEA COUNTY: NEW MEXICO STATE:	COMPANY: E. G. WOODS		Well Location
	WELL: SIMON 1-A DC-1		
	FIELD: MALJAMAR		
	LOCATION: 660' FNL & 1980 FEL OF SEC. 29, T-17-S, R-32-E		
	COUNTY: LEA STATE: NEW MEXICO		
LOG ZERO GROUND LEVEL $\pm$ 2'		ELEV. 3970	
DRLG. ZERO GROUND LEVEL $\pm$ 2'		ELEV. 3970	
PERM. DATUM GROUND LEVEL		ELEV. 3968	

TYPE OF LOG	GAMMA RAY	NEUTRON/NEUTRON	
RUN NO.	1-OW	1-OW	
DATE (SAND LINE.)	11-19-58	11-19-58	
TOTAL DEPTH (DRILLER)	4020	4020	
EFFECTIVE DEPTH (DRILLER)	4020	4020	
TOP OF LOGGED INTERVAL	SURFACE	SURFACE	
BOTTOM OF LOGGED INTERVAL	3993	4005	
TYPE OF FLUID IN HOLE	OIL	OIL	
FLUID LEVEL	FULL	FULL	
MAXIMUM RECORDED TEMP.	-	-	BEFORE EXAMINER UTZ
SOURCE STRENGTH & TYPE	-	13.5	STATE CONSERVATION COMMISSION
SOURCE SPACING—IN.	-	13.5	EXHIBIT NO. 613
LENGTH OF MEAS. DEVICE—IN.	4	4	CASE NO. 1572
O.D. OF INSTRUMENT—IN.	3 5/8	3 5/8	
TIME CONSTANT—SECONDS	2.0-0.9	2.0-0.9	
LOGGING SPEED FT./MIN.	30-60	30-60	
STATISTICAL VARIATION—IN.	RECORDED	RECORDED	
SENSITIVITY REFERENCE	C-933	D368	
DETECTOR CLASS	SCINT	SCINT	
DETECTOR TYPE	D4G1	D6M1	
RECORDED BY	SCHLOTTERBACK		
WITNESSED BY	SHAW AND GRAY		

WELL RECORD					
RUN	BIT SIZE	CASING WT.—LB.	FROM WELL RECORD	FROM LOG	
1	11	8 5/8	SURFACE TO 2000	SURFACE TO 1992	
1	8 3/4	7	SURFACE TO 3511	SURFACE TO 3515	
1	6 1/4	OPEN HOLE	3511 TO 4020	3515 TO 4006	
			TO	TO	
			TO	TO	