



ACOUSTIC VELOCITY NEUTRON LOG

COMPANY <u>Belco Petroleum Corporation</u> WELL <u>Union Mead Com # 3</u> FIELD <u>Wildcat</u> County <u>Eddy</u> State <u>N.M.</u>	COMPANY <u>BELCO PETROLEUM CORPORATION</u>			
	WELL <u>UNION MEAD COM # 3</u>			
	FIELD <u>WILDCAT</u>			
	COUNTY <u>EDDY</u> STATE <u>NEW MEXICO</u>			
	Location <u>1980' FSL & 1980' FEL</u>		Other Services: <u>Guard Forxo</u>	
Sec. <u>5</u> Twp <u>22-S</u> Rge <u>27-E</u>				
Permanent Datum <u>Ground Level</u> Elev. <u>3159'</u>		Elev.: K.B. <u>3177'</u>		
Log Measured From <u>K. B. - 18</u> Ft. Above Perm. Datum		D.F. <u></u>		
Drilling Measured From <u>Kelly Bushing</u>		G.I. <u>3159'</u>		
Date	<u>1/27/73</u>	<u>2/22/73</u>		
Run by	<u>- One -</u>	<u>- Two -</u>		
Depth-Driller	<u>8,940</u>	<u>11,650</u>		
Depth-Welex	<u>8,943</u>	<u>11,639</u>		
Btm. Log Inter.	<u>8,870</u>	<u>11,624</u>		
Top Log Inter.	<u>Surface</u>	<u>8,370</u>		
Casing-Driller	<u>10-3/4" @ 1,819</u>	<u>7-7/8" @ 8,940</u>		<u>@</u>
Casing-Welex				
Bit Size	<u>9-1/2"</u>	<u>6-1/2"</u>		
Type Fluid in Hole	<u>Water</u>	<u>Water</u>		
Dens. Visc.	<u>1</u>	<u>1.31</u>	<u>1</u>	<u>1</u>
pH Fluid Loss	<u>1</u> ml	<u>8.5 13</u> ml	<u>1</u> ml	<u>1</u> ml
Source of Sample	<u>Pit</u>	<u>Pit</u>		
R _{max} @ Meas. Temp.	<u>.21 @ 58°F</u>	<u>.07 @ 80°F</u>	<u>@ °F</u>	<u>@ °F</u>
R _{min} @ Meas. Temp.	<u>.21 @ 58°F</u>	<u>.07 @ 80°F</u>	<u>@ °F</u>	<u>@ °F</u>
R _{avg} @ Meas. Temp.	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>
Source R _{min} R _{max}	<u>1</u>	<u>Measured</u>	<u>1</u>	<u>1</u>
R _{min} @ BHT	<u>.095 @ 135°F</u>	<u>.03 @ 183°F</u>	<u>@ °F</u>	<u>@ °F</u>
Time Since Circ.				
Max. Rec. Temp.	<u>135°F @ B.H.</u>	<u>183°F @ B.H.</u>	<u>°F @</u>	<u>°F @</u>
Equip Location	<u>612 1/2 lbs</u>	<u>612 1/2 lbs</u>	<u>1</u>	<u>1</u>
Recorded By	<u>Cam. Bell</u>	<u>AYLES</u>		
Witnessed By	<u>Mr. Boundy</u>	<u>& Mr. Henry</u>		

Fold Here

Remarks:

Service Ticket No.