

**PROPOSED JICARILLA "G" GALLUP-DAKOTA
COMMINGLED WELLBORE: 1656' FNL and 1979' FWL
SEC. 1-T26N-R5W**

**UNION TEXAS
PETROLEUM CORP.**

SURFACE CASING

Hole size: 13 3/4"
Casing: 10 3/4" 32.7# H-40
Casing set @ 300'
Top of Cement: Circulated to Surface

PRODUCTION CASING

Hole size: 7 7/8"
Casing: 5 1/2" 15.5# and 17# K-55
Casing set @ 7700'
Top of Cement: Circulated to Surface
in 3 Stages

(Estimated Jicarilla G well #1E
depths used for illustration)

BEFORE EXAMINER STAMETS
UTPC CONSERVATION DIVISION
UTPC 6
CASE NO. 8184 & 8185
Submitted by HERRINGTON
Hearing Date 5-9-84

Seating Nipple
Perf Sub
Mud Anchor

PERFORATIONS 7400'-8100'
Gallup: 7400'-8100'
Dakota: 8328'-8400'

PBTD 8410'
TD 8445'

GLE 7285'
KBE 7297'
KB 12'

**Rio Arriba County, New Mexico
Field: B.S. Mesa Gallup
and Basin Dakota Extension**