

**PROPOSED JICARILLA "F" MESAVERDE-GALLUP-DAKOTA
COMMINGLED WELLBORE: T26N-R4W
SECTIONS 27, 28, 33, 34**

**UNION TEXAS
PETROLEUM CORP.**

SURFACE CASING

Hole size: 13 3/4"
Casing: 10 3/4" 32.7# H-40
Casing set @ 300'
Top of Cement: Circulated to Surface

(Estimated Jicarilla F-8
depths used for illustration)

PRODUCTION CASING

Hole size: 7 7/8"
Casing: 5 1/2" 15.5# and 17# K-55
Casing set @ 7700'
Top of Cement: Circulated to Surface
in 3 Stages

BEFORE E.C. HERRINGTON
OIL CONSERVATION DIVISION
UTPC EXHIBIT NO. 6

CASE NO. 8186

Submitted by HERRINGTON

Hearing Date 5-9-84

Seating Nipple
Perf Sub
Mud Anchor

PERFORATIONS
Mesaverde: 5280'-5800'

PERFORATIONS
Gallup: 6950'-7750'
Dakota: 7960'-8020'

PBTD 8040'
TD 8080'

GLE 7058'
KBE 7070'
KB 12'

Rio Arriba County, New Mexico
Field: Blanco Mesaverde, Tapacito Gallup
Associated Extension, Wildhorse Gallup Gas, and Basin Dakota