Jason Kellahin W. Thomas Kellahin Karen Aubrey

KELLAHIN and KELLAHIN Attorneys at Law El Patio - 117 North Guadalupe Post Office Box 2265 Santa Fe, New Mexico 87504-2265

Telephone 982-4285 Area Code 505

February 18, 1985

RECEIVED

FED 1 - P

Mr. Richard L. Stamets
Oil Conservation Division
P. O. Box 2088
Santa Fe, New Mexico 87501

OIL CONSERVATION DIVISION

"Hand Delivered"

Re: Hicks Oil & Gas, Inc.

Salt Water Disposal Section 14,5 T28N, R13W, NMPM San Juan County, New Mexico (Cal = 8525)

Dear Mr. Stamets:

On behalf of Hicks Oil & Gas, Inc., please set the above referenced case on the docket now set for March 13, 1985.

Very truly yours

. Thomas Kellahin

WTK:ca Enc.

cc Mike Hicks
Hicks Oil & Gas, Inc.
P. O. Drawer 3307
Farmington, NM 87499

STATE OF NEW MEXICO DEPARTMENT OF ENERGY AND MINERALS OIL CONSERVATION DIVISION

IN THE MATTER OF THE APPLICATION OF HICKS OIL & GAS, INC., FOR SALT WATER DISPOSAL, SAN JUAN COUNTY, NEW MEXICO.

RECEIVED

EED 1

OIL CONSERVATION THAT A IN

APPLICATION

Cuse 8525

Comes now Hicks Oil & Gas, Inc., by and through its attorneys, Kellahin & Kellahin, and applies to the New Mexico Oil Conservation Division for authority to dispose of produced salt water into the Gallup Formation in the perforated interval from 5492 feet to 5824 feet in its SE Chacha Unit Well #37 located in Unit O of Section 15, T28N, R13W, NMPM, San Juan County, and in support thereof would show:

- 1. Applicant is the operator of its SE Chacha Unit Well #37 located in Unit O of Section 15, T28N, R13W, NMPM, San Juan County, New Mexico.
- 2. Applicant seeks to convert the subject well to a salt water disposal well in the Gallup Formation through perforations at 5492 feet to 5824 feet.
- 3. Applicant is preparing Division Form C-108 and will submit that application separate from this application.

Wherefore, Applicant requests that 4. this application be set for hearing and that after notice and hearing the application be granted.

Kellahin & Kellehin

W. Thomas Rellahin

P. O. Box 2265 Santa Fe, New Mexico 87501

(505) 982-4285

STATE OF NEW MEXICO ENERGY AND HINERALS DEPARTHENT

of the earlier submittal.

OIL CONSERVATION DIVISION POST DEFICE BOX 2088 STATE UNIC DEFICE BUILDING SINETA FE NEW MEANION TOUT

FORM C-108 Revised 7-1-81 Case 8525

I.	Purpose: Secondary Recovery Pressure Maintenance Disposal Storage Application qualifies for administrative approval? Ses Minu								
II.	Operator: Hicks Oil & Gas, Inc.								
	Address: P.O. Drawer 3307, Farmington, New Mexico 87499								
	Contact party: Mike Hicks Phone: 505/327-4902								
111.	Well data: Complete the data required on the reverse side of this form for each well proposed for injection. Additional sheets may be attached if necessary.								
IV.	Is this an expansion of an existing project? Tyes XXno If yes, give the Division order number authorizing the project								
٧.	Attach a map that identifies all wells and leases within two miles of any proposed injection vell with a one-half mile radius carcle drawn around each proposed injection well. This circle identifies the well's area of review.								
VI.	Attach a tabulation of data on all wells of public record within the area of review which penetrate the proposed injection zone. Such data shall include a description of each well's type, construction, date drilled, location, depth, record of completion, and a schematic of any plugged well illustrating all plugging detail.								
VII.	Attach data on the proposed operation, including:								
	 Proposed average and maximum daily rate and volume of fluids to be injected; Whether the system is open or closed; Proposed average and maximum injection pressure; Sources and an appropriate analysis of injection fluid and compatibility with the receiving formation if other than reinjected produced water; and If injection is for disposal purposes into a zone not productive of oil or gas at or within one mile of the proposed well, attach a chemical analysis of the disposal zone formation water (may be measured or inferred from existing literature, studies, nearby wells, etc.). 								
'I II.	Attach appropriate geological data on the injection zone including appropriate lithologic detail, geological name, thickness, and depth. Give the geologic name, and depth to bottom of all underground sources of drinking water (aquifers containing waters with total dissolved solids concentrations of 10,000 mg/l or less) overlying the proposed injection zone as well as any such source known to be immediately underlying the injection interval.								
IX.	Describe the proposed stimulation program, if any.								
х.	Attach appropriate logging and test data on the well. (If well logs have been filed with the Division they need not be resubmitted.)								
XI.	Attach a chemical analysis of frosh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken.								
XII.	Applicants for disposal wells must make an affirmative statement that they have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water.								
111.	Applicants must complete the "Proof of Notice" section on the reverse side of this form.								
xīv.	Certification								
	I hereby certify that the information submitted with this application is true and correct to the best of my knowledge and belief.								
	Name: Mike Hicks Title President								
	Signature: Mile Hicks Date: 1/17/85								

III. WELL DATA

- A. The following well data must be submitted for each injection well covered by this application. The data must be both in tabular and schematic form and shall include:
 - Lease name; Well No.: location by Section, Township, and Ranne: and Footage location within the section.
 - (2) Each coping string used with its size, setting depth, sacks of dement used, hole size, top of dement, and how such top was determined.
 - (3) A description of the tubing to be used including its size, lining material, and setting depth.
 - (4) The name, model, and setting depth of the packer used or a description of any other seal system or assembly used.

Division District offices have supplies of Well Data Sheets which may be used or which may be used as models for this purnose. Applicants for several identical wells may submit a "tyrical data sheet" rather than submitting the data for each well.

- 8. The following must be submitted for each injection well covered by this application. All items must be addressed for the initial well. Pesponses for additional wells need be shown only when different. Information shown on schematics need not be repeated.
 - (1) . The name of the injection formation and, if applicable, the field or pool name.
 - (2) The injection interval and whether it is perforated or open-hole.
 - (3) State if the well was drilled for injection or, if not, the original purpose of the well.
 - (4) Give the depths of any other perforated intervals and detail on the sacks of cement or bridge plugs used to seal off such perforations.
 - (5) Give the depth to and name of the next higher and next lower oil or gas zone in the area of the well, if any.

XIV. PROOF OF NOTICE


All applicants must furnish proof that a copy of the application has been furnished, by certified or registered mail, to the owner of the surface of the land on which the well is to be localed and to each leasenold operator within one-half mile of the well location.

here an application is subject to administrative approval, a proof of publication must be submitted. Such proof shall consist of a copy of the legal advertisement which was published in the county in which the well is located. The contents of such advertisement must include:

- (1) The name, address, phone number, and contact party for the applicant;
- (2) the interded purpose of the injection well; with the exact location of single wells or the section, township, and range location of multiple wells:
- (3) the formation name and depth with expected maximum injection rates and pressures; and
- (4) a notation that interested parties must file objections or requests for hearing with the Oil Conservation Division, P. O. Box 2088, Santa Fe, New Mexico 87501 within 15 days.

NO ACTION WILL BE TAKEN ON THE APPLICATION UNTIL PROPER PROOF OF NOTICE HAS BEEN SUBMITTED.

NOTICE: Surface owners or offset operators must file any objections or requests for hearing of administrative applications within 15 days from the date this application was mailed to them.



INJECTION WELL DATA SHEET

Hicks Cil & Gas, Inc.	S.E. Cha Cl	na Unit	
37 2100' FEL & 550' F			R13W RANGE
Schematic .	Surface Casing	Tabular Data	
	Size 8 5/8"-23	# Cemented wit	
8 / 8 · 23 / 6 517 ω/275 sx.	Intermediate Casino		
Tubing, Plastic control or Fiberglass		Cemented with	
	Hole size 7 7/ Total depth 594 Injection interval	8"	
- Stage Collar @ 4 Cemented W/100	; 520'	t to 5824' -hole, indicate which,	
Perforated 54 Re Drilled Perforated 570 Perforated 575 Squeezed w/5 Perforated 58	92-5502 08-12 3-63 0 sx cement		
5½-15.5#@5 1st Stage Cemer Tubing size 2 3/8" line	ited w/280 sx.	or Fiberglass	set in a
Baker Model "D" (brand and nodel) (or describe any other casing-tubing	g seal).		feet
 Name of the injection formation Name of field or Pool (if appli Is this a new well drilled for If no, for whit purpose was the 	injection? / 7 Yes	/X/ No	
4. Has the well over been perforat and give plugging detail (sucks	ed in any other zone(s of coment or bridge p	a)? List all such per hlug(s) used) NO	forated intervals
5. Give the depth to and name of a this area. Picture Cliff gamaparoximately 1500° below.		derlying oil or gas : 3700' above Dakota g	oncs (pools) in gas zone

Hicks Oil & Gas, Inc.

P. O. DRAWIER 3307 FARMINGTON, NM 87499 505-327-4902

APPLICATION FOR SALT WATER DISPOSAL S.E. CHA CHA UNIT WELL #37

VII

- l. Lease production currently averages 90 BWPD and this volume would be split between other injection wells. Also, we are planning to operate the injection well for commercial salt water disposal. At this time, it is estimated that we will be disposing of 100 bbls of water per day from wells off the lease. We do anticipate this volume to increase as the NMOCD revises it's rules concerning disposal of produced water in unlined pits. From injection records of wells in the field when the unit was actively water flooded it is estimated that 750 BWPD could be injected at 1000 psi.
- 2. The system will be an open system.
- 3. Average injection pressure 500 psi. Maximum injection pressure 1000 psi.
- 4. Sources of injected water.
 - 1. Produced water from the lease. Water analysis attatched.
 - 2. Produced water from San Juan Basin oil and gas wells. Typical water analysis attatched.
- Stimulation treatment will consist of 500-1000 gallons of 15% Iron Sequestering HCL acid. If necessary the well may be fractreated with approximately 30,000 gallons of gelled water and 30,000# of 20/40 sand.
- \overline{X} Well logs on file with NMOCD.
- XI No fresh water wells within one mile.

Hicks Oil & Gas. Inc.

P. O. DRAWER 3307 FARMINGTON, NM 87499 505-327-4902

XII Affirmative Statement

I, Mike Hicks, have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water.

Mike Hicks President

Hicks Oil & Gas, Inc.


TABULATION OF WELLS
WITHIN 1/2 MILE RADIUS
OF PROPOSED SALT WATER DISPOSAL WELL
S.E. CHA CHA UNIT WELL # 37

Robinson #3	GCU 113	S.E. Cha Cha 33	S.E. Cha Cha 32	S.E. Cha Cha 30	S,E, Cha Cha 29	S.E. Cha Cha 24	WELL
15-28-13	M-14-28-13	B-22-28-13	D-22-28-13	P-15-28-13	N-15-28-13	J-15-28-13	LOCATION
8 5/8 @330'	8 5/8 @210'	8 5/8 @202	8 5/8 @321	8 5/8 @324	8 5/8 @317	8 5/8 @328'	SURFACE CASING
225sx	200sx	160sx	225sx	225sx	225sx	225sx	CEMENT
surface	surface	Surface	surface	surface	surface	surface	T.O.C.
4½ @65 00' DV @19 5 4'	4½ @58 55'	4½ @5864	41/2 @6499	4½ @5859	4½ @5830*	5½ @5850"	PRODUCTION CASING
300sx	340sx	400sx 2 stage	500sx 2 stage	400sx 2 stage	400sx 2 stage sq.100sx	300sx 2 stage sq.100sx	CEMENT
Unknown	×	1670' 4620'	1500' 4920'	1600' 4500'	1610' 3518'	5200' 1600' 3407'	T.O.C.
Dakota 6332-6418	Gallup P&A 5712-5780	Gallup 5758-5770	Dakota P&A 6273-6377 Gallup 5670-5742	Gallup 5748-5824	Gallup 5751'	Gallup 5740-5758	PRODUCING
6500'	5865*	5865	65001	5860'	5830'	5852	TD

75/05/70% 1/11

Gallagos Canyon Unit Well #113 Unit M- Sec. 14, T28N, R13W

Well Schematic



CHA CHA GALLUP

Producing sandstone of the Cha Cha Gallup Oil Pool are the result of the transition of the regressive Carlile Seas, leaving the Gallup sandstones and the transgressive Niobrara Seas. The advancing seas caused truncation of the Gallup and deposition of new sands, silts and muds. The lower sands are cleaner and generally thought to be offshore bars deposited by currents parallel to the shore line. These basal Niobrara sandstones are oil bearing as are some of the cleaner Gallup sandstones.

The entire complex of upper Carlile-lower Niobrara sandstones has been known as "the Gallup" since the late nineteen fifties when production began along the Bisti-Hourseshoe Canyon trend.

Several of the basal Niobrara sandstones are present in the Cha Gallup Pool.

These sandstones have been described as follows:

Light-gray to gray-brown, fine to coarse grained quartz sandstone with minor chert, feldspar and rock fragments. Traces of glauconite and mica are present. Cement is primarily calcite with some secondary quartz. There is porosity present and oil staining is evident.

DRINKING WATER SOURCES

Considerable effort was made to obtain chemical analyses of the water bearing rocks in Township 28 North, Range 13 West, San Juan County, N.M. These efforts failed but analyses were observed of waters taken from sources outside the township which had similar ages and depositional histories.

The analyses showed the following:

- 1. There is no known source of potable* water immediately below the Cha Cha Gallup producing zones.
- 2. The only potable water aquifers found above the injection zones (Cha Cha Gallup) are:
 - a. the Cretaceous Kirtland (Farmington Sandstone) at depths of 630-815' in section 21. (This information obtained from Ed Welder, U.S.G.S., Albuquerque.

ROY L. PRITCHARD - PETROLEUM GEOLOGIST

Petroleum Club Pla:a Suite 103 • P.O. Box 2372 • Farmington, New Mexico 87499 • Telephone: (505) 325-2209

DRINKING WATER SOURCES cont.

b. the Ojo Alamo (Tertiary Period) has water with very low solids (350-850 mg/l). This is found to a depth of 350-450' in the area of interest.

*All references herein to potable or drinking water are based on dissolved solids of 10,000 mg/l or less as found in item VIII of Application for Authorization to Inject.