

Doyle Hartman

Yuronka Cooper

OPERATOR

LEASE

WELL NO.	FOOTAGE LOCATION	SECTION	TOWNSHIP	RANGE
1	660' FSL & 1980' FWL	8	24-S	37-E

SchematicTabular DataSurface CasingSize 8-5/8" " Cemented with 600 ex.TOC Circulated feet determined by \_\_\_\_\_Hole size 12"Intermediate Casing

Size \_\_\_\_\_ " Cemented with \_\_\_\_\_ ex.

TOC \_\_\_\_\_ feet determined by \_\_\_\_\_

Hole size \_\_\_\_\_

Long stringSize 4-1/2 " Cemented with 350 ex.TOC 2600 feet determined by CaliperHole size 7-7/8"Total depth 3700'Injection interval\_\_\_\_\_ feet to \_\_\_\_\_ feet  
(perforated or open-hole, indicate which)

Spudded 5-10-77 - John Yuronka.

Top of Anhydrite: 1158'.

Top of Yates: 2861'.

Perforate 3428'-3519' (gross) - 8 holes.

WO 9/77: Tracer showed communication from  
hole @ 3519' to water zone @ 3526'. Sqzd.  
w/50 sxs. Work unsuccessful.

Sold to Doyle Hartman 8-1-78.

Tubing size \_\_\_\_\_ lined with \_\_\_\_\_ (material) set in a

(brand and model)

packer at \_\_\_\_\_ feet.

(or describe any other casing-tubing seal).

Other Data

1. Name of the injection formation \_\_\_\_\_

2. Name of Field or Pool (if applicable) \_\_\_\_\_

3. Is this a new well drilled for injection? ☐ Yes ☐ No

If no, for what purpose was the well originally drilled? \_\_\_\_\_

4. Has the well ever been perforated in any other zone(s)? List all such perforated intervals and give plugging detail (sacks of cement or bridge plug(s) used) \_\_\_\_\_

5. Give the depth to and name of any overlying and/or underlying oil or gas zones (pools) in this area. \_\_\_\_\_

BEFORE EXAMINER SIGNATURE

WELL NO. 11

CASE NO. \_\_\_\_\_