

District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Rec'd 06/16/2020 - NMOC

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-005-64212
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator JALAPENO CORPORATION		6. State Oil & Gas Lease No. V0-9290
3. Address of Operator PO BOX 1608, ALBUQUERQUE, NM 87103		7. Lease Name or Unit Agreement Name Kobe 22
4. Well Location Unit Letter <u>E</u> : <u>2190</u> feet from the <u>NORTH</u> line and <u>280</u> feet from the <u>WEST</u> line Section <u>22</u> Township <u>9S</u> Range <u>27E</u> NMPM County <u>CHAVES</u>		8. Well Number #1Y
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 26307
10. Pool name or Wildcat WOLF LAKE; SAN ANDRES		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

THE KOBE #1Y WAS PLUGGED BY 3G WELL SERVICES BEGINNING ON JANUARY 16, 2020 AND COMPLETED ON JANUARY 28, 2020. A DETAILED PLUGGING REPORT IS ATTACHED.

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us

Spud Date: 10/7/14

Rig Release Date: 3/12/15

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE _____ TITLE Oil and Gas Associate DATE 6/16/2020

Type or print name Julie A Pascal E-mail address: jpascal@jalapenocorp.com PHONE: 505-242-2050

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 6/18/2020
Conditions of Approval (if any):

Plugging Report for Kobe 22 State 1Y

API: 30-005-64180

- | | |
|-----------|--|
| 1-16-2020 | Moved in, rigged up, laid down rods. |
| 1-17-2020 | Put on BOP, tallied tubing, made scraper run, set CIBP on tubing @ 1950' |
| 1-20-2020 | Went in hole and tagged CIBP @ 1954' GL, mixed and pumped 28 bbls of mud laden fluid. Pumped 25sx of class C cement. |
| 1-21-2020 | Went in hole and tagged @ 1710' pulled, pulled out of hole, perforated @ 950', potted 30sx class C cement @ 950', squeezed 4bbls into perforations, Perforated @ 469'. |
| 1-22-2020 | Went in and tagged @ 923', pumped another 15sx class C cement. |
| 1-24-2020 | Went in and tagged @ 768', removed BOP and pumped 125sx into perfs @ 469', circulated ½ bbl to steel pit. Will do cutoff on Monday. |
| 1-28-2020 | Did cutoff 5 ½ was full tagged surface plug @ 28' filled it up. Welded plate on wellhead and installed dry hole maker. |