Rec'd 06/11/2020 -NMOCD Submit 1 Copy To Appropriate District State of New Mexico Form C-103 Office Revised July 18, 2013 Energy, Minerals and Natural Resources District I - (575) 393-6161 WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II - (575) 748-1283 30-015-33922 OIL CONSERVATION DIVISION 811 S. First St., Artesia, NM 88210 5. Indicate Type of Lease 1220 South St. Francis Dr. District III - (505) 334-6178 STATE FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Grandi 22 DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 8. Well Number Gas Well X Other 1. Type of Well: Oil Well 2. Name of Operator 9. OGRID Number Devon Energy Production Company, LP 6137 3. Address of Operator 10. Pool name or Wildcat Carlsbad; Morrow South (Gas) 333 W. Sheridan Avenue, Oklahoma City, OK 73102 4. Well Location Unit Letter feet from the feet from the 660 North line and 1210 line **NMPM** Section Township 228 County Range 22 27E MM 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3094' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PANDA X PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. 06/05/20 Spot 25 sx class H cmt @ 9085' displace to 8885'. No required tag inside 5 1/2" csg. 2. 06/08/20 Spot 50 sx class C cmt @ 5850'. Tag TOC @ 5300' inside 5 1/2" csg. 3. 06/09/20 Perf @ 2350' sqz'd 165 sx class C cmt. Tag TOC @ 1732' inside 5 1/2" csg. Perf @ 476' break circulation, calculated 180 sx class C cmt to surface inside and behind 5 1/2" csg. RD P&A equipment, cut off WH, anchors, set dry hole marker, clean location. P&A complete. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us Rig Release Date: Spud Date: I hereby certify that the information above is true and complete to the best of my knowledge and belief.