OCD - REC'D 8/5/2020 Submit 1 Copy To Appropriate District State of New Mexico Form C-103 Office Revised July 18, 2013 Energy, Minerals and Natural Resources District I - (575) 393-6161 WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II - (575) 748-1283 30-015-46354 OIL CONSERVATION DIVISION 811 S. First St., Artesia, NM 88210 5. Indicate Type of Lease District III – (505) 334-6178 1220 South St. Francis Dr. STATE X FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM E0-5073-0007 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Lady Franklin 25 State DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well Other 123H 2. Name of Operator 9. OGRID Number 371449 Colgate Operating, LLC 3. Address of Operator 10. Pool name or Wildcat 300 North Marienfeld, Suite 1,000 - Midland, Tx 79701 Winchester; Bone Spring 4. Well Location 1381 feet from the South line and 265 feet from the West line Unit Letter: L Section: 25 Township: 19S Range: 28E **NMPM** County: Eddy 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3335 GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK □ REMEDIAL WORK ALTERING CASING □ PLUG AND ABANDON **TEMPORARILY ABANDON CHANGE PLANS** \boxtimes COMMENCE DRILLING OPNS.□ P AND A П MULTIPLE COMPL CASING/CEMENT JOB PULL OR ALTER CASING DOWNHOLE COMMINGLE **CLOSED-LOOP SYSTEM** \Box OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Based on Colgate Energy's experience in Section 25, will set surface casing at 325' instead of 950' as originally planned. Setting surface at 325' will isolate GW prior to drilling salt section. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE: TITLE: Operations Tech DATE: 8/3/2020 Type or print name Mikah Thomas E-mail address: <u>mthomas@colgateenergy.com</u> PHONE: 432-695-4272 For State Use Only John Garcia 8/18/2020 Petroleum Specialist APPROVED BY: **TITLE** DATE

Conditions of Approval (if any):