	To Appropriate I	District	T	State of New	w Mexico Re	ec'd 11/2	3/2020 - NM	OCD FO	orm C-103 august 1, 2011	
<u>District I</u> – (575) 1625 N. French I		Energy,	, Minerais and	Natural Resou	rces	WELL API NO		tugust 1, 2011		
District II – (575	, ,	OII O	ONGEDNAT	NICEDIA TIONI DIVICIONI			30-015-47059			
011 5. 1 list 5t., Altesia, 1414 60210					ONSERVATION DIVISION			5. Indicate Type of Lease		
1000 Pio Brazos Pd. Aztec. NM 97410					20 South St. Francis Dr.			STATE  FEE		
<u>District IV</u> – (505) 476-3460					a Fe, NM 87505		6. State Oil &	Gas Lease No.		
1220 S. St. France 87505	cis Dr., Santa Fe	, NM								
87303	SUNDR	Y NOTICE	ES AND RE	PORTS ON W	ELLS		7. Lease Name	or Unit Agreem	ent Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A							Rock Spur 27 W1CN State Com			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)										
1. Type of Well: Oil Well Gas Well Other							8. Well Number 1H			
Name of Operator     Mewbourne Oil Company							9. OGRID Number 14744			
3. Address of Operator							10. Pool name or Wildcat			
PO Box 5270, Hobbs, NM 88240							Purple Sage Wolfcamp (98220)			
4. Well Loca	tion									
Unit	LetterB_	:_	250_fee	et from the	North_line	and	360_feet from	theEast_	line	
Secti	ion	27	]	Township 2	4S Range	28E	NMPM	Count	ty Eddy	
				n (Show whethe	er DR, RKB, RT,	GR, etc.)			h = 110	
			2945' GL					_ ATV 810		
	10	N1 1 1	• , ,	D . T 1'			0.1			
	12. (	Ineck Ap	propriate	Box to Indica	ate Nature of I	Notice, F	Report or Oth	er Data		
	NOTICE	OF INTI	ENTION	TO:	f	SUBS	EQUENT R	EPORT OF:		
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WOR								ALTERING C	CASING	
TEMPORARILY ABANDON							P AND A			
PULL OR ALT	TER CASING	_	MULTIPLE (	COMPL	CASING/	CEMENT	JOB 🗆			
DOWNHOLE	COMMINGL	E 🗆								
OTHER:					OTHER:					
	ibe proposed	or complete	ed operation	Ennel	e all pertinent de	etails, and	give pertinent d	ates, including e	stimated date	
of star	ting any prop	osed work	). SEE RUI	LE 19.15.7.14 N	MAC. For Mul	tiple Com	pletions: Attach	wellbore diagra	am of	
									AIII OZ	
propo	sed completion					•		<b></b>		
	sed completion	on or recom	pletion.							
There was a mi	sed completion	on or recom	ipletion. of Approval	for the above v	well, according to	o Kurt Sim	mons. The con	ditions read "Ce	ment is	
There was a mirrequired to circ	sed completions is take in the Coulate on both	on or recom	pletion.  of Approval  d production	for the above v	well, according to ng", when they s	o Kurt Sim	umons. The con	ditions read "Ce	ment is	
There was a mirrequired to circ	sed completions is take in the Coulate on both	on or recom	pletion.  of Approval  d production	for the above v	well, according to	o Kurt Sim	umons. The con	ditions read "Ce	ment is	
There was a mirrequired to circ	sed completions is take in the Coulate on both ermediate str	Conditions of surface and ings of casi	of Approval d production ng" as detai	for the above versity of casis and the origin	well, according to ng", when they s	o Kurt Sim should read included	umons. The cond "Cement is recuired with this sundry	ditions read "Ce quired to circulat	ement is te on both	
There was a mirequired to circ surface and into	sed completions is take in the Coulate on both ermediate str	Conditions of surface and ings of casis	of Approval d production ng" as detai Casing Size 13 3/8"	for the above von strings of casiled in the origin  Casing Grade  H40	well, according to ng", when they s nal casing design	o Kurt Sim should read included	umons. The cond "Cement is rec with this sundry Setting Depth 425	ditions read "Ce quired to circular Sacks Cement 360	ement is te on both	
There was a mirequired to circ surface and into Casing Type Surface Intermediate	istake in the Culate on both ermediate str.  Fluid Type Spud Mud Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25	of Approval d production ng" as detai Casing Size 13 3/8" 9 5/8"	for the above von strings of casiled in the origin  Casing Grade  H40  J55	well, according to ng", when they s nal casing design Casing Weight 48 36	o Kurt Sim should read included	umons. The cond "Cement is reconsist this sundry  Setting Depth  425 2450	ditions read "Ce quired to circular Sacks Cement 360 530	ement is te on both  Top Cement  0	
There was a mirequired to circ surface and into a comparison of the comparison of th	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75	of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into Casing Type Surface Intermediate	istake in the Culate on both ermediate str.  Fluid Type Spud Mud Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25	of Approval d production ng" as detai Casing Size 13 3/8" 9 5/8"	for the above von strings of casiled in the origin  Casing Grade  H40  J55	well, according to ng", when they s nal casing design Casing Weight 48 36	o Kurt Simshould read included  Top MD  0	umons. The cond "Cement is reconsist this sundry  Setting Depth  425 2450	ditions read "Ce quired to circular Sacks Cement 360 530	ement is te on both  Top Cement  0	
There was a mirequired to circ surface and into a comparison of the comparison of th	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75	of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a comparison of the comparison of th	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75	of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a comparison of the comparison of th	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75	of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a surface and into a surface and into a surface and into a surface and intermediate a surface and intermediate a surface are a surface and into a surface and intermediate and into a surface and	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine OBM	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	of Approval d production ng" as detail  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above versions of casing of casing Grade  H40  J55  P110  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26 13.5	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a comparison of the comparison of th	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	of Approval d production ng" as detail  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26 13.5	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a surface and into a surface and into a surface and into a surface and intermediate a surface and intermediate a surface are a surface and into a surface and intermediate and into a surface and	istake in the Coulate on both ermediate structure of the Fluid Type Spud Mud Brine Cut Brine OBM	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	of Approval d production ng" as detail  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above versions of casing of casing Grade  H40  J55  P110  P110	well, according to ng", when they s nal casing design Casing Weight 48 36 26 13.5	o Kurt Simshould read included Top MD  0 0	mons. The cond "Cement is required with this sundry  Setting Depth  425  2450  9980	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into the surface and into the surface surfa	sed completic istake in the Coulate on both ermediate str.  Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decem	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	apletion. of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above version strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Relea	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5	o Kurt Simshould read included of the model	amons. The cond "Cement is recay with this sundry  Setting Depth  425 2450 9980 14694	ditions read "Ce quired to circular Sacks Cement 360 530 900	Top Cement  0 0 2250	
There was a mirequired to circ surface and into the surface and into the surface surfa	sed completic istake in the Coulate on both ermediate str.  Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decem	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	apletion. of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above version strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Relea	well, according to ng", when they s nal casing design Casing Weight 48 36 26 13.5	o Kurt Simshould read included of the model	amons. The cond "Cement is recay with this sundry  Setting Depth  425 2450 9980 14694	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into the surface and into the surface surfa	sed completic istake in the Coulate on both ermediate str.  Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decem	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	apletion. of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above version strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Relea	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5	o Kurt Simshould read included of the model	amons. The cond "Cement is recay with this sundry  Setting Depth  425 2450 9980 14694	ditions read "Ce quired to circular Sacks Cement 360 530 900	ement is te on both  Top Cement  0  2250	
There was a mirequired to circ surface and into a surface and into a surface Intermediate Production Liner  Spud Date:	sed completic istake in the Coulate on both ermediate str.  Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decem	Conditions of surface and ings of casis  Hole Size  17.5  12.25  8.75  6.125	apletion. of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above version strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Relea	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5	o Kurt Simshould read included of the model	smons. The cond "Cement is required this sundry  Setting Depth  425  2450  9980  14694  and belief.	ditions read "Ce quired to circular Sacks Cement 360 530 900	Top Cement  0  2250  9432	
There was a mirequired to circ surface and into a surface Intermediate Production Liner  Spud Date:  I hereby certify  SIGNATURE	sed completic istake in the Coulate on both crimediate structure.  Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decen	Conditions of surface and ings of casis  Hole Size 17.5 12.25 8.75 6.125  The conditions of casis and casi	apletion. of Approval d production ng" as detai  Casing Size 13 3/8" 9 5/8" 7" 4 1/2"	for the above very strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Releand complete to	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5  ase Date:  Engineer	Top MD  O  9432	Setting Depth 425 2450 9980 14694 and belief.	ditions read "Cequired to circulate".  Sacks Cement  360 530 900 210  ATE11/20/2	Top Cement  0  2250  9432	
There was a mirequired to circ surface and into a surface Intermediate Production Liner  Spud Date:  I hereby certify  SIGNATURE  Type or print in	Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decen	Conditions of surface and ings of casis and surface and ings of casis are surface and surface and surface and surface and surface and surface and surface are surface and surface are surface and surface and surface are surface and surface are surface and surface and surface are surface and surface and surface and surface are surface and surf	coppletion.  of Approval d production go as detaing Size  13 3/8"  9 5/8"  7"  4 1/2"	for the above very strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Releand complete to	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5  ase Date:	Top MD  O  9432	Setting Depth 425 2450 9980 14694 and belief.	ditions read "Ce quired to circular Sacks Cement 360 530 900 210	Top Cement  0  2250  9432	
There was a mirequired to circ surface and into a surface Intermediate Production Liner  Spud Date:  I hereby certify  SIGNATURE	Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decen	Conditions of surface and ings of casis and surface and ings of casis are surface and surface and surface and surface and surface and surface and surface are surface and surface are surface and surface and surface are surface and surface are surface and surface and surface are surface and surface and surface are surface and surf	coppletion.  of Approval d production go as detaing Size  13 3/8"  9 5/8"  7"  4 1/2"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Releated to TITLE  E-mail at	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5  ase Date:  the best of my king the best of my king the shall be shall	Top MD  O  9432	Setting Depth 425 2450 9980 14694 and belief.	ditions read "Cequired to circulate".  Sacks Cement  360 530 900 210  ATE11/20/2	Top Cement  0  2250  9432	
There was a mirequired to circ surface and into a surface Intermediate Production Liner  Spud Date:  I hereby certify  SIGNATURE  Type or print in	Fluid Type Spud Mud Brine Cut Brine OBM  Est. ~Decen	Conditions of surface and ings of casis  Hole Size 17.5 12.25 8.75 6.125  The conditions of casis and casi	coppletion.  of Approval d production go as detaing Size  13 3/8"  9 5/8"  7"  4 1/2"	for the above on strings of casiled in the origin  Casing Grade  H40  J55  P110  P110  Rig Releated to TITLE  E-mail at	well, according to ng", when they shal casing design  Casing Weight  48  36  26  13.5  ase Date:  Engineer	Top MD  O  9432	sumons. The cond "Cement is recovired this sundry  Setting Depth 425 2450 9980 14694  and belief.  Durne.com H	ditions read "Cequired to circulate".  Sacks Cement  360 530 900 210  ATE11/20/2	Top Cement  0 2250 9432	