

NEW MEXICO OIL CONSERVATION COMMISSION  
 JUL -5 1977  
 Santa Fe

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION  
 CONSERVATION COMM.

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		✓
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
 State  Fee

5. State Oil & Gas Lease No.  
 N/A

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL  GAS WELL  OTHER- Wildcat

7. Unit Agreement Name  
 None

2. Name of Operator  
 TransOcean Oil, Inc.

8. Form or Lease Name  
 State 2094

3. Address of Operator  
 1700 First City East Bldg., Houston, Texas 77002

9. Well No.  
 1

4. Location of Well  
 UNIT LETTER D 330' FEET FROM THE North LINE AND 330' FEET FROM THE West LINE, SECTION 2 TOWNSHIP 2N RANGE 14W NMPM.

10. Field and Pool, or Wildcat  
 Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)  
 7511'

12. County  
 Catron

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK   
 TEMPORARILY ABANDON   
 FULL OR ALTER CASING   
 OTHER   
 PLUG AND ABANDON   
 CHANGE PLANS

REMEDIATION WORK   
 COMMENCE DRILLING OPNS.   
 CASING TEST AND CEMENT JOBS   
 OTHER   
 ALTERING CASING   
 PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Received verbal permission June 30, 1977 from New Mexico Conservation Comm. (Carl Ulvog) in Santa Fe to P & A well.

- (1) Set cmt plug w/ 25 sx C1 "H" @ 5200-5125' (Yeso) (8.8# mud)
- Set cmt plug w/ 25 sx C1 "H" @ 4455-4380' (Glorietta) (8.8# mud)
- Set cmt plug w/ 25 sx C1 "H" @ 4130-4060' (San Andres) (8.8# mud)
- Set cmt plug w/ 25 sx C1 "H" @ 2805-2730' (Dakota) (8.8# mud)
- Set cmt plug w/ 25 sx C1 "H" @ 565-490' (1/2 in, 1/2 out surf csg) (8.8# mud)
- Set cmt plug w/ 10 sx @ surf w/ Dry Hole Marker.
- (2) A steel marker to be placed 4' above ground level.
- (3) Loc to be cleared of all junk and pits filled & loc to be leveled.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Nancy Hathaway  
 Nancy Hathaway

TITLE Drig Clerk

DATE 7/1/77

APPROVED BY Carl Ulvog

TITLE SENIOR PETROLEUM GEOLOGIST

DATE 7/6/77

CONDITIONS OF APPROVAL, IF ANY: