

WESTERN PETROLEUM
SERVICES
CEMENTING REPORT

DATE 11-2-84 DISTRICT Hobbs / El Paso F.R.# 723921
 OPERATOR MIDAS MINERAL CORP
 WELL NAME & NUMBER MIDAS #2
 LOCATION: SEC. _____ BLOCK OR TOWNSHIP _____ SURVEY OR RANGE _____
 COUNTY SAN MIGUEL STATE N. MEX
 STAGE NUMBER _____ TYPE JOB SLURRY

TBG/DP: Size	Weight	Disp	Conductor	Surface	Int.	Prod.	Liner
Perforated Interval			Size	<u>7 7/8</u>			
Pkr. Type	Set at		Weight	<u>29.70</u>			
Open Hole Size <u>10"</u>	Formation		Thread	<u>824</u>			
Stage Collar Type	Set at		Capacity	<u>24.5</u>			
Estimated Wash Out _____ %			Depth	<u>560</u>			

Sacks or Bbls.	Composition of Cement and Spacer	Gals/sk H2O	Weight Lb/Gal	Yield Ft 3	Pump Time Hours	TOTAL Cu. Ft.	TOTAL Bbls.
<u>15054</u>	<u>Ht 2% cement at 14# CEMENTAL</u>	<u>5.2</u>	<u>15.6</u>	<u>1.14</u>		<u>177</u>	<u>31</u>

Total Mix H2O 14 Bbls. Total Displacement 24.4 Bbls, Type 7 7/8" Total Products 55. Bbls

Time	Remarks	Rate	Pressure	
			Tubing	Casing
<u>630</u>	<u>BBLs AHEAD 25 BBLs</u>	<u>3.0</u>		<u>200</u>
<u>640</u>	<u>MIXING CEMENT</u>	<u>3.0</u>		<u>200</u>
<u>700</u>	<u>DISPLACING 24 BBLs</u>	<u>3.0</u>		<u>300</u>
<u>710</u>	<u>SHOT DOWN / CLOSE IN</u>	<u>-</u>		<u>250</u>

Break Down At _____ BPM At _____ PSI
 Squeezed To _____ PSI Running _____ Hesitation _____
 Reversed out _____ BBL Slurry at _____ PSI
 Customer considered service Satisfactory Unsatisfactory
 Customer Rep: RICHARD CYPRESS
 Max Pressure 1000 Differential Press. 250
 Bumped Plug Yes No Pressure to _____
 Cmt. Circ. to surface YES Sacks 3254
 Float Held 4 1/2 Yes _____ No _____
 Shut in with 250 PSI
 Service Supervisor SL MILLI