

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-059-20070

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER CO2

2. Name of Operator
Amoco Production Company

3. Address of Operator
PO Box 606, Clayton, NM 88415

4. Well Location
Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line
Section 35 Township 20N Range 34E NMPM Union County



7. Lease Name or Unit Agreement Name
BDCDGU-2034

8. Well No.
351

9. Pool name or Wildcat
Tubb

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4792' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- OTHER: Run Poly Liner
- PLUG AND ABANDON
- CHANGE PLANS

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING TEST AND CEMENT JOB
- OTHER:
- ALTERING CASING
- PLUG AND ABANDONMENT

MIRUSU
 RUN & SET 1.625" BLANKING PLG IN
 PROFILE
 BLEED TBG TO 0 PSI
 NUBOP
 RELEASE ON/OFF TOOL
 SWAB CSG DOWN, REC AS MUCH FLUID
 AS POSSIBLE
 LAYDOWN FG TBG
 RUN POLYBORE GAUGE RING
OPTION #1
 IF GAUGE RING GOES & LOOKS OK WHEN
 PULLED: RUN 10-3 1/8" DRILL COLLARS
 (COLLARS EQUIPPED WITH 2 7/8" PAC BOX
 ON TOP); RIG UP ROLLER REDUCTION

UNIT; RUN POLY LINER TO TOP OF PKR;
 FISH DRILL COLLARS FROM POLYLINER
 W/TBG FUSE ON WELLHEAD FLANGE;
 INSTALL SS B-1 ADAPTER & MASTER
 VALVE; INSTALL METER RUN; RU
 LUBRICATOR & FISH BLANKING PLUG;
 RETURN WELL TO PRODUCTION;
 RD MOSU
OPTION #2
 IF GAUGE RING DOES NOT MAKE IT TO
 PKR DEPTH OR COMES OUT WITH SIGNS
 OF CSG DAMAGE, RERUN 3 1/2" FG
 PRODUCTION TBG; LATCH ON TO PKR;
 FISH BLANKING PLUG; PRESS TEST CSG
 & PKR TO 500 PSI; RETURN WELL TO
 PRODUCTION; RD MOSU

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Billy E. Prichard TITLE Field Foreman DATE 11/2/96
 TYPE OR PRINT NAME Billy E Prichard TELEPHONE NO. 374-3053

(This space for State Use)

APPROVED BY Rg E Johnson TITLE **DISTRICT SUPERVISOR** DATE 11-21-96
 CONDITIONS OF APPROVAL, IF ANY: