

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL API NO. 30-007-20109
5. Indicate Type of Lease STATE [] FEE [X]
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: OIL WELL [] GAS WELL [] OTHER Coal Methane
2. Name of Operator Pennzoil Exploration and Production Company
3. Address of Operator P.O. Box 2967, Houston, TX 77252
4. Well Location Unit Letter H : 1651 Feet From The North Line and 671 Feet From The East Line
Section 16 Township 30 N Range 17 E NMPM Colfax County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 9139 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [X] PLUG AND ABANDONMENT []
CASING TEST AND CEMENT JOB [X]
OTHER: Drilling completed [X]

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
2/8/91 Drill 17 1/2" hole to 23'. Set 23' of 13 3/7" conductor.
2/9/91 Drill 12 1/4" hole to 255'. Drill 11" hole to 310'. Set and cement 11 jts. (308') 8 5/8", 24 lb., K-55, ST&C casing w/220 sks class G @ 15.6 ppg. cement to surface.
2/10/91 Test BOP and casing to 600 psi for 30 minutes. No pressure drop.
2/12/91 Drill 7 7/8" hole to 1809' with air hammer.
2/13/91 Drill 7 7/8" hole to 2149' with air. Mud up.
2/18/91 Drill 7 7/8" hole with mud to 2745'.
2/19/91 Core 2745' to 2773' and 2773' to 2794'.
2/20/91 Drill 7 7/8" hole to 2876' with mud. Log.
2/21/91 Set and cement 91 jts (2861') 5 1/2, 17.0 lb., K-55, LT&C casing with 550 sks silicalite @ 11.5 ppg. Bump plug. Cement to surface. Rig released. Wait on completion of tool

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 3/05/91
TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO. 376-2817

(This space for State Use)
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 3-8-91
CONDITIONS OF APPROVAL, IF ANY: